

**THE DYNKIN DIAGRAMS PACKAGE**  
**VERSION 3.141 592 653 589 793 238 462**

BEN MCKAY

Table 1: The Dynkin diagrams of the reduced simple root systems  
 [3] pp. 265–290, plates I–IX

$A_n$		<code>\dynkin A{}</code>
$B_n$		<code>\dynkin B{}</code>
$C_n$		<code>\dynkin C{}</code>
$D_n$		<code>\dynkin D{}</code>
$E_6$		<code>\dynkin E6</code>
$E_7$		<code>\dynkin E7</code>
$E_8$		<code>\dynkin E8</code>
$F_4$		<code>\dynkin F4</code>
$G_2$		<code>\dynkin G2</code>

---

*Date:* 4 December 2024.

Thanks to Jeffrey Adams, Paul Aspinwall, Mikhail Borovoi, Fran Burstall, Michiel Van Couwenberghe, Xu Gao, Skip Garibaldi, Enrico Gregorio, Mamuka Jibladze, Tasho Kaletha, Jordan Lambert, Sriotchilism O'Zaic, Gopal Prasad, Anthony Pulido, Andres Sambarino, Paul Schwahn, Felix Weinstein, Niels Wen and Gordon Williams.

## CONTENTS

1. Quick introduction, 3
  2. Interaction with *TikZ*, 4
  3. Set options globally, 5
  4. Disconnected Dynkin diagrams, 5
  5. Coxeter diagrams, 6
  6. Satake diagrams, 8
  7. How to fold, 10
  8. Labels for the roots, 13
  9. Label expansion, 15
  10. Label subscripts, 16
  11. Height and depth of labels, 18
  12. Text style for the labels, 18
  13. Bracing roots, 19
  14. Label placement, 20
  15. Style, 25
  16. Suppress or reverse arrows, 27
  17. Backwards and upside down, 27
  18. Drawing on top of a Dynkin diagram, 28
  19. Mark lists, 29
  20. Indefinite edges, 30
  21. Root ordering, 33
  22. Parabolic subgroups, 34
  23. Extended Dynkin diagrams, 36
  24. Affine twisted and untwisted Dynkin diagrams, 37
  25. Extended Coxeter diagrams, 39
  26. Witt symbols, 40
  27. Kac style, 41
  28. Ceref style, 42
  29. More on folded Dynkin diagrams, 44
  30. Typesetting mathematical names of Dynkin diagrams, 50
  31. Connecting Dynkin diagrams, 50
  32. Other examples, 53
  33. Example: the complex simple Lie algebras, 63
  34. An example of Mikhail Borovoi, 66
  35. Syntax, 68
  36. Options, 68
- References, 73

## 1. QUICK INTRODUCTION

Load the Dynkin diagram package (see options below)

```
\documentclass{amsart}
\usepackage{dynkin-diagrams}
\begin{document}
The Dynkin diagram of  $(B_3)$  is \dynkin B3.
\end{document}
```


Invoke it

The Dynkin diagram of  $(B_3)$  is \dynkin B3.

The Dynkin diagram of  $B_3$  is .

Indefinite rank Dynkin diagrams


```
\dynkin B{}
```



Inside a TikZ statement

The Dynkin diagram of  $(B_3)$  is  

```
\tikz \dynkin B3;
```

The Dynkin diagram of  $B_3$  is .

Inside a Dynkin diagram environment

The Dynkin diagram of  $(B_3)$  is  

```
\begin{dynkinDiagram}B3
\draw[very thick,red] (root 1) to [out=-45, in=-135] (root 3);
\end{dynkinDiagram}
```

The Dynkin diagram of  $B_3$  is .

## 2. INTERACTION WITH TIKZ

Inside a `TikZ` environment, default behaviour is to draw from the origin, so you can draw around the diagram:

Inside a `TikZ` environment

```
\begin{tikzpicture}
\draw (0,0) -- (.5,1) -- (1,0);
\dynkin[edge length=1cm]G2
\end{tikzpicture}
```



But it looks bad in the middle of text:

Inside a `TikZ` environment

```
The Dynkin diagram of \(\B_3\) is
\begin{tikzpicture}[baseline]
\dynkin B3
\draw[very thick,red] (root 1) to [out=-45, in=-135] (root 3);
\end{tikzpicture}
```

The Dynkin diagram of  $B_3$  is 

A vertical shift realigns the diagram to ambient text:

Inside a `TikZ` environment

```
The Dynkin diagram of \(\B_3\) is
\begin{tikzpicture}[baseline]
\dynkin[vertical shift] B3
\draw[very thick,red] (root 1) to [out=-45, in=-135] (root 3);
\end{tikzpicture}
```

The Dynkin diagram of  $B_3$  is 

## 3. SET OPTIONS GLOBALLY

Most options set globally ...

```
\pgfkeys{/Dynkin diagram,
  edge length=.5cm,
  fold radius=.5cm,
  indefinite edge/.style={
    draw=black,
    fill=white,
    thin,
    densely dashed}}
```

You can also pass options to the package in `\usepackage`. *Danger*: spaces in option names are replaced with hyphens: `edge length=1cm` is `edge-length=1cm` as a global option; moreover you should drop the extension `/.style` on any option with spaces in its name (but not otherwise). For example,

...or pass global options to the package


```
\usepackage[
  ordering=Kac,
  edge/.style=blue,
  indefinite-edge={draw=green,fill=white,densely dashed},
  indefinite-edge-ratio=5,
  mark=o,
  root-radius=.06cm]
{dynkin-diagrams}
```

## 4. DISCONNECTED DYNKIN DIAGRAMS

Disconnected Dynkin diagrams that represent a product of simple Lie groups (or a sum of Lie algebras, or a product of Coxeter systems, ...) have a different syntax (to ensure back compatibility):


Command

The Dynkin diagram of  $(B_3 \times A_2)$  is `\dynkins{B3|A2}`.

The Dynkin diagram of  $B_3 \times A_2$  is .

Environment

The Dynkin diagram of  $(B_3 \times A_2)$  is  
`\begin{DynkinDiagrams}{B3|A2}\end{DynkinDiagrams}`

The Dynkin diagram of  $B_3 \times A_2$  is .

Each factor can have its own options.

#### Environment

```
The Dynkin diagram of  $(B_3 \times A_2)$  is
\[
\begin{DynkinDiagrams}
{[name=Bob]B3|[name=Alice]A2}
\draw[very thick,blue] (Bob root 1)
to [out=-45, in=-135] (Alice root 2);
\end{DynkinDiagrams}
\]
```

The Dynkin diagram of  $B_3 \times A_2$  is



They are spaced out by the length of one edge between successive diagrams; change this with `separator length`.

Table 2: The Dynkin diagrams of the rank 2 root systems

$A_1 \times A_1$	$\bullet \bullet$	<code>\dynkins {A1 A1}</code>
$A_2$	$\bullet \text{---} \bullet$	<code>\dynkin A2</code>
$B_2$	$\bullet \rightleftarrows \bullet$	<code>\dynkin B2</code>
$C_2$	$\bullet \rightleftarrows \bullet$	<code>\dynkin C2</code>
$D_2$	$\bullet \text{---} \bullet$	<code>\dynkin D2</code>
$G_2$	$\bullet \rightleftarrows \bullet$	<code>\dynkin G2</code>

## 5. COXETER DIAGRAMS

#### Coxeter diagram option

```
\dynkin[Coxeter]F4
```
















#### gonality option for $G_2$ and $I_n$ Coxeter diagrams

```
\(G_2=\dynkin[Coxeter,gonality=n]G2\), \
\ (I_n=\dynkin[Coxeter,gonality=n]I{\})
```

$G_2 = \overset{n}{\bullet} \text{---} \bullet$ ,  $I_n = \bullet \text{---} \overset{n}{\bullet}$

Table 3: The Coxeter diagrams of the simple reflection groups

$A_n$		<code>\dynkin [Coxeter] A{}</code>
$B_n$		<code>\dynkin [Coxeter] B{}</code>
$C_n$		<code>\dynkin [Coxeter] C{}</code>
$D_n$		<code>\dynkin [Coxeter] D{}</code>
$E_6$		<code>\dynkin [Coxeter] E6</code>
$E_7$		<code>\dynkin [Coxeter] E7</code>
$E_8$		<code>\dynkin [Coxeter] E8</code>
$F_4$		<code>\dynkin [Coxeter] F4</code>
$G_2$		<code>\dynkin [Coxeter,gonality=n] G2</code>
$H_2$		<code>\dynkin [Coxeter] H2</code>
$H_3$		<code>\dynkin [Coxeter] H3</code>
$H_4$		<code>\dynkin [Coxeter] H4</code>
$I_n$		<code>\dynkin [Coxeter,gonality=n] I{}</code>

Some people prefer Coxeter diagrams to have these labels appear on the bottom of the diagram, so say `Coxeter above=false`, most likely as a global option.

Table 4: The Coxeter diagrams of the simple reflection groups

$A_n$		<code>\dynkin [Coxeter] A{}</code>
$B_n$		<code>\dynkin [Coxeter] B{}</code>
$C_n$		<code>\dynkin [Coxeter] C{}</code>
$D_n$		<code>\dynkin [Coxeter] D{}</code>
$E_6$		<code>\dynkin [Coxeter] E6</code>
$E_7$		<code>\dynkin [Coxeter] E7</code>
$E_8$		<code>\dynkin [Coxeter] E8</code>
$F_4$		<code>\dynkin [Coxeter] F4</code>
$G_2$		<code>\dynkin [Coxeter,gonality=n] G2</code>
$H_2$		<code>\dynkin [Coxeter] H2</code>
$H_3$		<code>\dynkin [Coxeter] H3</code>
$H_4$		<code>\dynkin [Coxeter] H4</code>
$I_n$		<code>\dynkin [Coxeter,gonality=n] I{}</code>

## 6. SATAKE DIAGRAMS

Satake diagrams use the standard name instead of a rank

`\(A_{IIIb}=\dynkin A{IIIb}\)`

$$A_{IIIb} = \begin{array}{c} \circ - \circ - \circ - \circ \\ \circ - \circ - \circ - \circ \end{array} \begin{array}{c} \circ \\ \circ \end{array}$$

We use a solid gray bar to denote the folding of a Dynkin diagram, rather than the usual double arrow, since the diagrams turn out simpler and easier to read.







Table 5: The Satake diagrams of the real simple Lie algebras [13] p. 532–534

$A_I$		<code>\dynkin AI</code>
$A_{II}$		<code>\dynkin A{II}</code>
$A_{IIIa}$		<code>\dynkin A{IIIa}</code>
$A_{IIIb}$		<code>\dynkin A{IIIb}</code>
$A_{IV}$		<code>\dynkin A{IV}</code>
$B_I$		<code>\dynkin BI</code>
$B_{II}$		<code>\dynkin B{II}</code>
$C_I$		<code>\dynkin CI</code>
$C_{IIa}$		<code>\dynkin C{IIa}</code>
$C_{IIb}$		<code>\dynkin C{IIb}</code>
$D_{Ia}$		<code>\dynkin D{Ia}</code>
$D_{Ib}$		<code>\dynkin D{Ib}</code>
$D_{Ic}$		<code>\dynkin D{Ic}</code>
$D_{II}$		<code>\dynkin D{II}</code>
$D_{IIIa}$		<code>\dynkin D{IIIa}</code>
$D_{IIIb}$		<code>\dynkin D{IIIb}</code>
$E_I$		<code>\dynkin EI</code>
$E_{II}$		<code>\dynkin E{II}</code>
$E_{III}$		<code>\dynkin E{III}</code>
$E_{IV}$		<code>\dynkin E{IV}</code>
$E_V$		<code>\dynkin EV</code>
$E_{VI}$		<code>\dynkin E{VI}</code>
$E_{VII}$		<code>\dynkin E{VII}</code>
$E_{VIII}$		<code>\dynkin E{VIII}</code>

continued ...


Table 5: ... continued

$E_{IX}$		<code>\dynkin E{IX}</code>
$F_I$		<code>\dynkin FI</code>
$F_{II}$		<code>\dynkin F{II}</code>
$G_I$		<code>\dynkin GI</code>

## 7. HOW TO FOLD


If you don't like the solid gray "folding bar", most people use arrows. Here is  $E_{II}$

```
\dynkin[edge length=.75cm,
  labels*={1,...,6},
  involutions={16;35}]E6
```




The double arrows for  $A_{IIIa}$  are big

```
\dynkin[edge length=.75cm,
  involutions={1{10};29;38;47;56}]{A}{oo.o**.**.oo}
```




We can add labels

```
\dynkin[edge length=.75cm,
  involutions={
    1<below>[\sigma]{10};
    2<below>[\sigma]9;
    3<below>[\sigma]8;
    4<below>[\sigma]7;
    5<below>[\sigma]6}
]{A}{oo.o**.**o.oo}
```




Style options

```
\dynkin[edge length=.75cm,
  involution/.style={blue!50,stealth-stealth,thick},
  involutions={1{10};29;38;47;56}
]{A}{oo.o**.**o.oo}
```




Arrow angles

```
\dynkin[edge length=.75cm,
  involutions={[[in=-120,out=-60,relative]1{10};29;38;47;56}
]{A}{oo.o**.**o.oo}
```




## Arrow angles

```
\dynkin[involutions={16;60;01}]E[1]{6}
\dynkin[involutions={out=-80,in=-100,relative}16;60;01]E[1]{6}
```




If you don't like the solid gray "folding bar", most people use arrows ...

```
\tikzset{/Dynkin diagram/fold style/.style={stealth-stealth,thick,
shorten <=1mm,shorten >=1mm,}}
\dynkin[ply=3,edge length=.75cm]D4
\begin{dynkinDiagram}[ply=4]D[1]%
{****.*****.*****}
\dynkinFold 1{13}
\dynkinFold[bend right=90] 0{14}
\end{dynkinDiagram}
```



... but you could try springs pulling roots together


```
\tikzset{/Dynkin diagram/fold style/.style=
{decorate,decoration={name=coil,aspect=0.5,
segment length=1mm,amplitude=.6mm}}}
\dynkin[ply=3,edge length=.75cm]D4
\begin{dynkinDiagram}[ply=4]D[1]%
{****.*****.*****}
\dynkinFold 1{13}
\dynkinFold[bend right=90]0{14}
\end{dynkinDiagram}
```



## 8. LABELS FOR THE ROOTS


Make a list of labels for the roots. Optionally, you can add label directions to say where to put each label relative to its root.

```
\dynkin[labels={m\cosh\theta,1,2,3,,n-2,n-1,n,n+1},
label directions={,,left,,,right,,},
scale=1.8,
extended] D{*ooo...oooo}
```




Make a macro to assign labels to roots

```
\dynkin[label,label macro/.code={\alpha_{\drlap{#1}}},edge
length=.75cm]D5
```




Labelling several roots

```
\dynkin[labels={,2,...,5,,7},label
macro/.code={\alpha_{\drlap{#1}}}]A7
```




The foreach notation I

```
\dynkin[labels={1,3,...,7}]A9
```




## The foreach notation II

```
\dynkin[labels={,\alpha_2,\alpha_...\alpha_7}]A7
```



## The foreach notation III

```
\dynkin[label macro/.code={\beta_{\drlap{#1}}},labels={,2,...,7}]A7
```



## Label the roots individually by root number

```
\dynkin[label]B3
```




## Access root labels via TikZ

```
\begin{dynkinDiagram}B3
\node[below,/Dynkin diagram/text style] at (root 2)
{\(\alpha_{\drlap{2}}\)};
\end{dynkinDiagram}
```



## The labels have default locations, mostly below roots

```
\dynkin[labels={1,2,3}]E8
```




## The starred form flips labels to alternate locations, mostly above roots

```
\dynkin[labels*={1,2,3}]E8
```



## Labelling several roots and alternates

```
\dynkin[label macro/.code={\alpha_{\drlap{#1}}},
label macro*/.code={\gamma_{\drlap{#1}}},
labels={,2,...,5,,7},
labels*={1,3,4,5,6}]A7
```



## 9. LABEL EXPANSION


## Best not to have too much expansion

```
\dynkin[labels={\mathbb{K}}] A1
```




## Sometimes we don't have enough expansion

```
\def\rs{1,2,3,2,2,1}
\dynkin[labels=\rs,ordering=Carter]{E}{6}
```



## Ask for more expansion

```
\def\rs{1,2,3,2,2,1}
\dynkin[expand labels=\rs,ordering=Carter]{E}{6}
```




Many options to the package admit an `expand` in front of them to get more expansion.

## 10. LABEL SUBSCRIPTS

Note the slight improvement that `\drlap` makes: the labels are centered on the middle of the letter  $\alpha$ , ignoring the space taken up by the subscripts, using the `mathtools` command `\mathrlap`, but only for labels which are *not* placed to the left or right of a root.

Label subscript spacing

```
\dynkin[label,label macro/.code={\alpha_{#1}},
  edge length=.75cm]D{15}
\par\noindent{}%
\dynkin[label,label macro/.code={\alpha_{\drlap{#1}}},
  edge length=.75cm]D{15}
```






## Label subscript spacing

```

\dynkin[label,label macro/.code={\alpha_{#1}},
edge length=.75cm]E8
\dynkin[label,label macro/.code={\alpha_{#1}},backwards,
edge length=.75cm]E8
\par\noindent{}%
\dynkin[label,label macro/.code={\alpha_{\mathrlap{#1}}},
edge length=.75cm]E8
\dynkin[label,label macro/.code={\alpha_{\mathrlap{#1}}},backwards,
edge length=.75cm]E8
\par\noindent{}%
\dynkin[label,label macro/.code={\alpha_{\drlap{#1}}},
edge length=.75cm]E8
\dynkin[label,label macro/.code={\alpha_{\drlap{#1}}},backwards,
edge length=.75cm]E8

```




## 11. HEIGHT AND DEPTH OF LABELS

Labels are set with default maximum height the height of the character  $b$ , and default maximum depth the depth of the character  $g$ . To change these, set `label height` and `label depth`:

Change height and depth of characters

```
\dynkin[labels={a,b,c,d},label height=d,label depth=d]F4
\dynkin[labels*={a,b,c,d},label height=d,label depth=d]F4
\dynkin[label macro/.code={\alpha_{\drlap{#1}}},
  label macro*/.code={\gamma_{\drlap{#1}}},
  label height=${\alpha_1},
  label depth=${\alpha_1},
  labels={,2,...,5,,7},
  labels*={1,3,4,5,6}]A7
\dynkin[labels={A,B,C,D},label height=$A$,label depth=$A$]F4
\dynkin[labels={a^1,b^2,c^3,d^4},label height=$X^X$]F4
```



## 12. TEXT STYLE FOR THE LABELS


Use a text style: big and blue

```
\begin{dynkinDiagram}[text style/.style={scale=1.2,blue},
  edge length=1cm,
  labels={1,2,n-1,n},
  label macro/.code={\alpha_{\drlap{#1}}}]A{}
\end{dynkinDiagram}
```



Use a text style; font selection is in the label macro


```
\begin{dynkinDiagram}[text style/.style={scale=1.2,blue},
  edge length=1cm,
  labels={1,2,n-1,n},
  label macro/.code={\mathbb{A}_{\drlap{#1}}}A{}
\end{dynkinDiagram}
```



### 13. BRACING ROOTS


Bracing roots

```
\begin{dynkinDiagram}A{*.x*.}
  \dynkinBrace[p]12
  \dynkinBrace[q]45
\end{dynkinDiagram}
```



Bracing roots, and a starred form

```
\begin{dynkinDiagram}A{10}
  \dynkinBrace[\text{Roots 2 to 9}]29
  \dynkinBrace*[\text{Roots 3 to 8}]38
\end{dynkinDiagram}
```




## Bracing roots

```

\newcommand\circleRoot[1]{
\draw[fill=white] (root #1) circle (3pt);
\fill[black] (root #1) circle (1.5pt);}
\begin{dynkinDiagram}A{**.***.***.***.***.***}
\foreach\r in {4,7,10,13} {\circleRoot \r}
\dynkinBrace[y-1]13
\dynkinBrace[z-1]56
\dynkinBrace[t-1]{11}{12}
\dynkinBrace[x-1]{14}{16}
\end{dynkinDiagram}


```



## 14. LABEL PLACEMENT


Take a  $D_8$ :

```
\dynkin[label,edge length=.75cm]D8
```




If you want to fold this diagram,

```
\dynkin[fold right,label,edge length=.75cm]D8
```



you will be glad that the 6 sits where it does, under and to the left. If you don't want to fold, you might prefer instead to put the 6 on the right side.


```
\dynkin[label,edge length=.75cm,label directions={,,,right,,}]D8
```



The default locations are overridden by the label directions. For extended diagrams, this list starts at 0-offset.


```
\dynkin[label,
  label directions={above,,,,},
  involutions={[out=-60,in=-120,relative]16;60;01}
]E[1]{6}
```

Table 6: Dynkin diagrams from Euler products [20]




continued ...

Table 6: ... continued



continued ...

Table 6: ... continued



```

\tikzset{/Dynkin diagram,ordering=Dynkin,label macro/.code={\alpha_{\drlap{#1}}}}
\newcounter{EPNo}
\setcounter{EPNo}{0}
\NewDocumentCommand\EP{smmmm}{
  \stepcounter{EPNo}\roman{EPNo}. &
  \def\eL{.6cm}
  \IfStrEqCase{#2}{
    D{
      \gdef\eL{1cm}
      \tikzset{/Dynkin diagram/label directions={,,right,,}}
      E{\gdef\eL{.75cm}}
      F{\gdef\eL{.35cm}}
      G{\gdef\eL{.35cm}}
    }
  }
  \IfBooleanTF{#1}{
    \dynkin[edge length=\eL,backwards,labels*={#4},labels={#5}]{#2}{#3}
  }{
}

```

```

\dynkin[edge length=\eL,labels*={#4},labels={#5}]{#2}{#3}
\tikzset{/Dynkin diagram/label directions={}}
\}
\renewcommand*\do[1]{\EP#1}%
\begin{longtable}{MM}
\caption{Dynkin diagrams from Euler products \cite{Langlands:1967}}\
\endfirsthead
\caption{\dots continued}\
\endhead
\multicolumn{2}{c}{\dots continued \dots}\
\endfoot
\endlastfoot
\docsvlist{
A{***.**}{1,1,1,1,1}{1,2,n-1,n},
A{***.**}{1,1,1,1,1}{1,2,n-1,n},
A{**.*.**}{1,1,1,1,1,1}{1,2,m-1,,m,n},
B{**.*.**}{2,2,2,2,1}{1,2,n-1,n},
*B{***.**}{2,2,2,2,1}{n,n-1,2,1,},
C{**.*.**}{1,1,1,1,2}{1,2,n-1,},
*C{***.**}{1,1,1,1,2}{n,n-1,2,1,},
D{**.*.**}{1,1,1,1,1,1}{1,2,n-2,n-1,n},
D{**.*.**}{1,1,1,1,1,1}{1,2,n-2,n-1,n},
E6{1,1,1,1,1,1}{1,...,5},
*E7{1,1,1,1,1,1,1}{6,...,1},
E7{1,1,1,1,1,1,1}{1,...,6},
*E8{1,1,1,1,1,1,1,1}{7,...,1},
E8{1,1,1,1,1,1,1,1}{1,...,7},
G2{1,3}{1},
G2{1,3}{1},
B{**.*.**}{2,2,2,2,1}{1,2,n-1,n},
F4{1,1,2,2}{3,2,1},
C3{1,1,2}{2,1},
C{**.*.**}{1,1,1,1,2}{1,n-2,n-1,n},
*B3{2,2,1}{1,2},
F4{1,1,2,2}{1,2,3},
D{**.*.**}{1,1,1,1,1,1}{1,2,n-2,n-2,n,n},
E6{1,1,1,1,1,1}{1,2,3,4,,5},
E6{1,1,1,1,1,1}{1,2,3,5,,4},
*E7{1,1,1,1,1,1,1}{5,...,1,6},
*E7{1,1,1,1,1,1,1,1}{6,4,3,2,1,5},
*E8{1,1,1,1,1,1,1,1}{6,...,1,7},
*E8{1,1,1,1,1,1,1,1}{7,5,4,3,2,1,6},
*E7{1,1,1,1,1,1,1,1}{5,...,1,,6},
*E7{1,1,1,1,1,1,1,1}{1,...,5,,6},
*E8{1,1,1,1,1,1,1,1}{6,...,1,,7}}
\end{longtable}

```



## 15. STYLE


## Colours

```
\dynkin[extended,
  o/.append style={fill=orange},
  */.style=blue!50!red,
  edge length=.75cm,
  edge/.style={blue!50,thick},
  arrow width=2mm,
  arrow style={red,width=2mm,line width=1pt}]F4
```



Popular arrow shapes. These mess with nonwhite backgrounds, but are prettier than the default shape.

```
\begin{tcolorbox}[colback=white,colframe=white]
\begin{tabular}{rcc}
default&\dynkin G2 & &\dynkin F4\\
Bourbaki&\dynkin[Bourbaki arrow]G2& &\dynkin[Bourbaki arrow]F4\\
bird&\dynkin[bird arrow]G2 & &\dynkin[bird arrow]F4
\end{tabular}
\end{tcolorbox}
```



Use `\tikzset{/Dynkin diagram,Bourbaki arrow}` to force all arrows to have Bourbaki style throughout your document.


## Other arrow shapes

```
\dynkin[edge length=.5cm,
  arrow width=2mm,
  arrow shape/.style={-Stealth[blue,width=2mm]}]F4
\dynkin[edge length=1cm,
  arrow shape/.style={-Bourbaki[length=7pt]}]F4
```




## Edge lengths

The Dynkin diagram of  $(A_3)$  is `\dynkin[edge length=1.2]A3`

The Dynkin diagram of  $A_3$  is 

## Root marks

`\dynkin E8`  
`\dynkin[mark=*]E8`  
`\dynkin[mark=o]E8`  
`\dynkin[mark=O]E8`  
`\dynkin[mark=t]E8`  
`\dynkin[mark=x]E8`  
`\dynkin[mark=X]E8`




At the moment, you can only use:

- \* • solid dot
- o ○ hollow circle
- O ⊙ double hollow circle
- t ⊗ tensor root
- x × crossed root
- X × thickly crossed root

## Mark styles

The parabolic subgroup  $(E_{8,124})$  is  
`\dynkin[parabolic=124,x/.style={brown,very thick}]E8`

The parabolic subgroup  $E_{8,124}$  is 

## Sizes of root marks


$(A_{3,3})$  with big root marks is `\dynkin[root radius=.08cm,parabolic=3]A3`

$A_{3,3}$  with big root marks is 

## 16. SUPPRESS OR REVERSE ARROWS

Some diagrams have double or triple edges

```
\dynkin F4
\dynkin G2
```




Suppress arrows

```
\dynkin[arrows=false]F4
\dynkin[arrows=false]G2
```



Reverse arrows


```
\dynkin[reverse arrows]F4
\dynkin[reverse arrows]G2
```



## 17. BACKWARDS AND UPSIDE DOWN

Default

```
\dynkin E8
\dynkin F4
\dynkin G2
```




Backwards

```
\dynkin[backwards]E8
\dynkin[backwards]F4
\dynkin[backwards]G2
```



## Reverse arrows

```
\dynkin[reverse arrows]F4
\dynkin[reverse arrows]G2
```




## Backwards, reverse arrows

```
\dynkin[backwards,reverse arrows]F4
\dynkin[backwards,reverse arrows]G2
```



## Backwards versus upside down

```
\dynkin[label]E8
\dynkin[label,backwards]E8
\dynkin[label,upside down]E8
\dynkin[label,backwards,upside down]E8
```



## 18. DRAWING ON TOP OF A DYNKIN DIAGRAM


## TikZ can access the roots themselves

```
\begin{dynkinDiagram}A4
  \fill[white,draw=black] (root 2) circle (.15cm);
  \fill[white,draw=black] (root 2) circle (.1cm);
  \draw[black] (root 2) circle (.05cm);
\end{dynkinDiagram}
```




Draw curves between the roots

```
\begin{dynkinDiagram}[label]E8
  \draw[very thick, black!50,-latex]
    (root 3.south) to [out=-45, in=-135] (root 6.south);
\end{dynkinDiagram}
```



Change marks

```
\begin{dynkinDiagram}[mark=o,label]E8
  \dynkinRootMark{*}5
  \dynkinRootMark{*}8
\end{dynkinDiagram}
```



## 19. MARK LISTS

The package allows a list of root marks instead of a rank:

A mark list

```
\dynkin E{oo**ttxx}
```



The mark list `oo**ttxx` has one mark for each root: `o`, `o`, `*`, `*`, `t`, `x`, `x`, `x`. Roots are listed in the current default ordering. (Careful: in an affine root system, a mark list will *not* contain a mark for root zero.)

If you need to repeat a mark, you can give a *single digit* positive integer to indicate how many times to repeat it.

A mark list with repetitions

```
\dynkin A{x4o3t4}
```




Table 7: Classical Lie superalgebras [10]. We need a slightly larger root radius parameter to distinguish the tensor product symbols from the solid dots.

		<code>\tikzset{/Dynkin diagram,root radius=.07cm}</code>
$A_{mn}$		<code>\dynkin A{o3.oto.oo}</code>
$B_{mn}$		<code>\dynkin B{o3.oto.oo}</code>
$B_{0n}$		<code>\dynkin B{o3.o3.o*}</code>
$C_n$		<code>\dynkin C{too.oto.oo}</code>
$D_{mn}$		<code>\dynkin D{o3.oto.o4}</code>
$D_{21\alpha}$		<code>\dynkin A{oto}</code>
$F_4$		<code>\dynkin F{ooot}</code>
$G_3$		<code>\dynkin [extended,affine mark=t, reverse arrows]G2</code>

Table 8: Classical Lie superalgebras [10]. Here we see the problem with using the default root radius parameter, which is too small for tensor product symbols.

$A_{mn}$		<code>\dynkin A{o3.oto.oo}</code>
$B_{mn}$		<code>\dynkin B{o3.oto.oo}</code>
$B_{0n}$		<code>\dynkin B{o3.o3.o*}</code>
$C_n$		<code>\dynkin C{too.oto.oo}</code>
$D_{mn}$		<code>\dynkin D{o3.oto.o4}</code>
$D_{21\alpha}$		<code>\dynkin A{oto}</code>
$F_4$		<code>\dynkin F{ooot}</code>
$G_3$		<code>\dynkin [extended,affine mark=t, reverse arrows]G2</code>

## 20. INDEFINITE EDGES

An *indefinite edge* is a dashed edge between two roots,  $\bullet\text{---}\bullet$  indicating that an indefinite number of roots have been omitted from the Dynkin diagram. In between any two entries in a mark list, place a period to indicate an indefinite edge:

Indefinite edges


```
\dynkin D{o.o*.*.t.to.t}
```

---

In certain diagrams, roots may have an edge between them even though they are not subsequent in the ordering. For such rare situations, there is an option:


#### Indefinite edge option

```
\dynkin[make indefinite edge={3-5},label]D5
```




#### Give a list of edges to become indefinite

```
\dynkin[make indefinite edge/.list={1-2,3-5},label]D5
```



#### Indefinite edge style

```
\dynkin[indefinite edge/.style={
  draw=black,fill=white,thin,densely dashed},
  edge length=1cm,
  make indefinite edge={3-5}]D5
```



#### The ratio of the lengths of indefinite edges to those of other edges

```
\dynkin[edge length = .5cm,
  indefinite edge ratio=3,
  make indefinite edge={3-5}]D5
```


























Table 9: Springer's table of indices [28], pp. 320-321, with one form of  $E_7$  corrected

$A_n$		
$A_n$		
$B_n$		
$C_n$		
$D_n$		
$E_6$		<code>\dynkin E{*oooo*}</code>
$E_6$		<code>\dynkin E{o*o*oo}</code>
$E_6$		<code>\dynkin E{o*oooo}</code>
$E_6$		<code>\dynkin E{**ooo*}</code>
$E_7$		<code>\dynkin E{*oooooo}</code>
$E_7$		<code>\dynkin E{oooooo*o}</code>
$E_7$		<code>\dynkin E{oooooo*}</code>
$E_7$		<code>\dynkin E{*oooo*o}</code>
$E_7$		<code>\dynkin E{*oooo**}</code>
$E_7$		<code>\dynkin E{*o**o*o}</code>
$E_8$		<code>\dynkin E{*ooooooo}</code>
$E_8$		<code>\dynkin E{ooooooo*}</code>
$E_8$		<code>\dynkin E{*oooooo*}</code>
$E_8$		<code>\dynkin E{oooooo**}</code>
$E_8$		<code>\dynkin E{*oooo***}</code>
$F_4$		<code>\dynkin F{ooo*}</code>
$D_4$		<code>\dynkin D{o*oo}</code>



21. ROOT ORDERING

Root ordering

```

\dynkin[label,ordering=Adams]E6
\dynkin[label,ordering=Bourbaki]E6
\dynkin[label,ordering=Carter]E6
\dynkin[label,ordering=Dynkin]E6
\dynkin[label,ordering=Kac]E6
    
```

Default is Bourbaki. Sources are Adams [1] p. 11, pp. 56–57, Bourbaki [3] pp. 265–290 plates I–IX, Carter [5] pp. 540–609, Dynkin [8] (reprinted, translated into English, in Dynkin [9] p. 180), Kac [17] p. 53.

	Adams	Bourbaki	Carter	Dynkin	Kac
$E_6$					
$E_7$					
$E_8$					
$F_4$					
$G_2$					

The marks are set down in order according to the current root ordering:

```

\dynkin[label]E{*otxX0t*}
\dynkin[label,ordering=Carter]E{*otxX0t*}
\dynkin[label,ordering=Kac]E{*otxX0t*}
    
```

## Convert between orderings

```
\newcount\r
\dynkinOrder E8.Carter::6->Bourbaki.{\r}
In \(\E_8\), root 6 in Carter's ordering is root \the\r{} in
    Bourbaki's ordering.
```

In  $E_8$ , root 6 in Carter's ordering is root 2 in Bourbaki's ordering.

## 22. PARABOLIC SUBGROUPS

Each set of roots is assigned a number, with each binary digit zero or one to say whether the corresponding root is crossed or not:

The flag variety of pointed lines in projective 3-space is associated to the Dynkin diagram `\dynkin[parabolic=3]A3`.

The flag variety of pointed lines in projective 3-space is associated to the Dynkin diagram  $\times \rightarrow \bullet$ .

## Commutative diagrams: anchor nodes to center

```
\begin{tikzcd}[row sep=0em,column sep=1em,cramped,
cells={nodes={anchor=center}}]
& \dynkin{G}{xx} \arrow{dr} \arrow{dl} & \\
& \dynkin{G}{*x} \arrow{dr} & \\
& \dynkin{G}{x*} \arrow{dl} & \\
& \dynkin{G}{**} & \\
\end{tikzcd}
```




Table 11: The Hermitian symmetric spaces

$A_n$		Grassmannian of $k$ -planes in $\mathbb{C}^{n+1}$
$B_n$		$(2n - 1)$ -dimensional quadric hypersurface
$C_n$		space of Lagrangian $n$ -planes in $\mathbb{C}^{2n}$
$D_n$		$(2n - 2)$ -dimensional quadric hypersurface
$D_n$		component of maximal null subspaces of $\mathbb{C}^{2n}$
$D_n$		the other component
$E_6$		complexified octave projective plane
$E_6$		its dual plane
$E_7$		the space of null octave 3-planes in octave 6-space


```

\NewDocumentCommand\HSS{mommm}
{#1&\IfNoValueTF{#2}{\dynkin{#3}{#4}}{\dynkin[parabolic=#2]{#3}{#4}}&#5\\}
\RenewDocumentCommand\do{m}{\HSS #1}
\renewcommand*{\arraystretch}{1.5}
\begin{longtable}
{>\columncolor[gray]{.9}>$1<$>\columncolor[gray]{.9}>$1<$>\columncolor[gray]{.9}}1}
\caption{The Hermitian symmetric spaces}\endhead\endfoot\endlastfoot
\docsvlist{%
{{A_n}A{**.*x**.*}}{Grassmannian of $k$-planes in $\mathbb{C}^{n+1}$}},
{{B_n}[1]B}{$(2n-1)$-dimensional quadric hypersurface}},
{{C_n}[16]C}{space of Lagrangian $n$-planes in $\mathbb{C}^{2n}$}},
{{D_n}[1]D}{$(2n-2)$-dimensional quadric hypersurface}},
{{D_n}[32]D}{component of maximal null subspaces of $\mathbb{C}^{2n}$}},
{{D_n}[16]D}{the other component}},
{{E_6}[1]E6}{complexified octave projective plane}},
{{E_6}[32]E6}{its dual plane}},
{{E_7}[64]E7}{the space of null octave 3-planes in octave 6-space}}
\end{longtable}

```

## 23. EXTENDED DYNKIN DIAGRAMS

Extended Dynkin diagrams

`\dynkin [extended] A7`

The extended Dynkin diagrams are also described in the notation of Kac [17] p. 55 as affine untwisted Dynkin diagrams: we extend `\dynkin A7` to become `\dynkin A[1]7`:

Extended Dynkin diagrams



`\dynkin A[1]7`

Table 12: The Dynkin diagrams of the extended simple root systems

$A_1^1$		<code>\dynkin [extended] A1</code>
$A_n^1$		<code>\dynkin [extended] A{}</code>
$B_n^1$		<code>\dynkin [extended] B{}</code>
$C_n^1$		<code>\dynkin [extended] C{}</code>
$D_n^1$		<code>\dynkin [extended] D{}</code>
$E_6^1$		<code>\dynkin [extended] E6</code>
$E_7^1$		<code>\dynkin [extended] E7</code>
$E_8^1$		<code>\dynkin [extended] E8</code>
$F_4^1$		<code>\dynkin [extended] F4</code>
$G_2^1$		<code>\dynkin [extended] G2</code>

Directed edges

```
\dynkin[edge length=.75cm,
edge/.style={-stealth[sep=2pt]},
labels={1,2,\ell-1,\ell},
labels*={0}]A[1]{}
```



24. AFFINE TWISTED AND UNTWISTED DYNKIN DIAGRAMS

The affine Dynkin diagrams are described in the notation of Kac [17] p. 55:

Affine Dynkin diagrams

```
\(A^{(1)}_7=\dynkin A[1]7, \
E^{(2)}_6=\dynkin E[2]6, \
D^{(3)}_4=\dynkin D[3]4\)
```




Table 13: The affine Dynkin diagrams

$A_1^1$		<code>\dynkin A[1]1</code>
$A_n^1$		<code>\dynkin A[1]{}</code>
$B_n^1$		<code>\dynkin B[1]{}</code>
$C_n^1$		<code>\dynkin C[1]{}</code>
$D_n^1$		<code>\dynkin D[1]{}</code>
$E_6^1$		<code>\dynkin E[1]6</code>
$E_7^1$		<code>\dynkin E[1]7</code>
$E_8^1$		<code>\dynkin E[1]8</code>
$F_4^1$		<code>\dynkin F[1]4</code>
$G_2^1$		<code>\dynkin G[1]2</code>
$A_2^2$		<code>\dynkin A[2]2</code>

continued ...

Table 13: ... continued






$A_{ev}^2$		<code>\dynkin A[2]{even}</code>
$A_{od}^2$		<code>\dynkin A[2]{odd}</code>
$D_n^2$		<code>\dynkin D[2]{}</code>
$E_6^2$		<code>\dynkin E[2]6</code>
$D_4^3$		<code>\dynkin D[3]4</code>

Table 14: Some more affine Dynkin diagrams




















$A_4^2$		<code>\dynkin A[2]4</code>
$A_5^2$		<code>\dynkin A[2]5</code>
$A_6^2$		<code>\dynkin A[2]6</code>
$A_7^2$		<code>\dynkin A[2]7</code>
$A_8^2$		<code>\dynkin A[2]8</code>
$D_3^2$		<code>\dynkin D[2]3</code>
$D_4^2$		<code>\dynkin D[2]4</code>
$D_5^2$		<code>\dynkin D[2]5</code>
$D_6^2$		<code>\dynkin D[2]6</code>
$D_7^2$		<code>\dynkin D[2]7</code>
$D_8^2$		<code>\dynkin D[2]8</code>
$D_4^3$		<code>\dynkin D[3]4</code>
$E_6^2$		<code>\dynkin E[2]6</code>

Table 15: Some more Kac–Moody Dynkin diagrams, only allowed in Kac ordering

$E_6$		<code>\dynkin [ordering=Kac,label]E6</code>
$E_7$		<code>\dynkin [ordering=Kac,label]E7</code>
$E_8$		<code>\dynkin [ordering=Kac,label]E8</code>

continued ...

Table 15: ... continued

$E_9$		<code>\dynkin [ordering=Kac,label]E9</code>
$E_{10}$		<code>\dynkin [ordering=Kac,label]E{10}</code>
$E_{11}$		<code>\dynkin [ordering=Kac,label]E{11}</code>

25. EXTENDED COXETER DIAGRAMS

Extended and Coxeter options together

`\dynkin [extended,Coxeter]F4`

















Table 16: The extended (affine) Coxeter diagrams

$A_n$		<code>\dynkin [extended,Coxeter]A{}</code>
$B_n$		<code>\dynkin [extended,Coxeter]B{}</code>
$C_n$		<code>\dynkin [extended,Coxeter]C{}</code>
$D_n$		<code>\dynkin [extended,Coxeter]D{}</code>
$E_6$		<code>\dynkin [extended,Coxeter]E6</code>
$E_7$		<code>\dynkin [extended,Coxeter]E7</code>
$E_8$		<code>\dynkin [extended,Coxeter]E8</code>
$F_4$		<code>\dynkin [extended,Coxeter]F4</code>
$G_2$		<code>\dynkin [extended,Coxeter]G2</code>
$H_2$		<code>\dynkin [extended,Coxeter]H2</code>
$H_3$		<code>\dynkin [extended,Coxeter]H3</code>
$H_4$		<code>\dynkin [extended,Coxeter]H4</code>
$I_1$		<code>\dynkin [extended,Coxeter]I1</code>


## 26. WITT SYMBOLS

The *Witt symbol* [16, 21, 30] is a different notation for the various series:

Witt symbol	Cartan symbol	
$P_{n+1}$	$A_n$	
$S_{n+1}$	$B_n$	
$R_{n+1}$	$C_n$	
$Q_{n+1}$	$D_n$	
$T_{n+1}$	$E_n$	$n = 6, 7, 8$
$U_5$	$F_4$	
$V_3$	$G_2$	
$W_2$	$I_1$	

Witt symbols

`\dynkin[extended]P7, \dynkin[extended]Q7, \dynkin[extended]T7`





27. KAC STYLE

We include a style called `Kac` which tries to imitate the style of [17].

```

Kac style
\dynkin[Kac]F4
-----
o---o => o---o
    
```

Table 17: The Dynkin diagrams of the simple root systems in Kac style

$A_n$		<code>\dynkin A{}</code>
$B_n$		<code>\dynkin B{}</code>
$C_n$		<code>\dynkin C{}</code>
$D_n$		<code>\dynkin D{}</code>
$E_6$		<code>\dynkin E6</code>
$E_7$		<code>\dynkin E7</code>
$E_8$		<code>\dynkin E8</code>
$F_4$		<code>\dynkin F4</code>
$G_2$		<code>\dynkin G2</code>

Table 18: The Dynkin diagrams of the extended simple root systems in Kac style

$A_1^1$		<code>\dynkin [extended]A1</code>
$A_n^1$		<code>\dynkin [extended]A{}</code>
$B_n^1$		<code>\dynkin [extended]B{}</code>
$C_n^1$		<code>\dynkin [extended]C{}</code>

continued ...

Table 18: ... continued

$D_n^1$		<code>\dynkin [extended]D{}</code>
$E_6^1$		<code>\dynkin [extended]E6</code>
$E_7^1$		<code>\dynkin [extended]E7</code>
$E_8^1$		<code>\dynkin [extended]E8</code>
$F_4^1$	$\circ - \circ - \circ \Rightarrow \circ - \circ$	<code>\dynkin [extended]F4</code>
$G_2^1$	$\circ - \circ \Rightarrow \circ$	<code>\dynkin [extended]G2</code>

Table 19: The Dynkin diagrams of the twisted simple root systems in Kac style

$A_2^2$	$\circ \Leftarrow \circ$	<code>\dynkin [extended]A[2]2</code>
$A_{ev}^2$	$\circ \Leftarrow \circ - \circ - \circ - \dots - \circ - \circ \Leftarrow \circ$	<code>\dynkin [extended]A[2]{even}</code>
$A_{od}^2$		<code>\dynkin [extended]A[2]{odd}</code>
$D_n^2$	$\circ \Leftarrow \circ - \circ - \circ - \dots - \circ - \circ \Rightarrow \circ$	<code>\dynkin [extended]D[2]{}</code>
$E_6^2$	$\circ - \circ - \circ \Leftarrow \circ - \circ$	<code>\dynkin [extended]E[2]6</code>
$D_4^3$	$\circ - \circ \Leftarrow \circ$	<code>\dynkin [extended]D[3]4</code>

## 28. CEREF STYLE

We include a style called `ceref` which paints oblong root markers with shadows. The word “ceref” is an old form of the word “serif”.

Ceref style

`\dynkin[ceref]F4`




Table 20: The Dynkin diagrams of the simple root systems in ceref style

$A_n$		<code>\dynkin A{}</code>
$B_n$		<code>\dynkin B{}</code>
$C_n$		<code>\dynkin C{}</code>
$D_n$		<code>\dynkin D{}</code>
$E_6$		<code>\dynkin E6</code>
$E_7$		<code>\dynkin E7</code>
$E_8$		<code>\dynkin E8</code>
$F_4$		<code>\dynkin F4</code>
$G_2$		<code>\dynkin G2</code>

Table 21: The Dynkin diagrams of the extended simple root systems in ceref style

$A_1^1$		<code>\dynkin [extended]A1</code>
$A_n^1$		<code>\dynkin [extended]A{}</code>
$B_n^1$		<code>\dynkin [extended]B{}</code>
$C_n^1$		<code>\dynkin [extended]C{}</code>
$D_n^1$		<code>\dynkin [extended]D{}</code>
$E_6^1$		<code>\dynkin [extended]E6</code>
$E_7^1$		<code>\dynkin [extended]E7</code>
$E_8^1$		<code>\dynkin [extended]E8</code>
$F_4^1$		<code>\dynkin [extended]F4</code>
$G_2^1$		<code>\dynkin [extended]G2</code>

Table 22: The Dynkin diagrams of the twisted simple root systems in ceref style


$A_2^2$		<code>\dynkin [extended] A [2] 2</code>
$A_{ev}^2$		<code>\dynkin [extended] A [2] {even}</code>
$A_{od}^2$		<code>\dynkin [extended] A [2] {odd}</code>
$D_n^2$		<code>\dynkin [extended] D [2] {}</code>
$E_6^2$		<code>\dynkin [extended] E [2] 6</code>
$D_4^3$		<code>\dynkin [extended] D [3] 4</code>

### 29. MORE ON FOLDED DYNKIN DIAGRAMS

The Dynkin diagrams package has limited support for folding Dynkin diagrams.


#### Folding

`\dynkin[fold]A{13}`




#### Big fold radius

`\dynkin[fold, fold radius=1cm]A{13}`



#### Small fold radius


`\dynkin[fold, fold radius=.2cm]A{13}`



Some Dynkin diagrams have multiple foldings, which we attempt to distinguish (not entirely successfully) by their *ply*: the maximum number of roots folded together. Most diagrams can only allow a 2-ply folding, so `fold` is a synonym for `ply=2`.

## 3-ply

```
\dynkin[ply=3]D4
\dynkin[ply=3,fold right]D4
\dynkin[ply=3]D[1]4
```



## 4-ply

```
\dynkin[ply=4]D[1]4
```



The  $D_\ell^{(1)}$  diagrams can be folded on their left end and separately on their right end:

## Left, right and both

```
\dynkin D[1]{ } \
\dynkin[fold left]D[1]{ } \
\dynkin[fold right]D[1]{ } \
\dynkin[fold]D[1]{ }
```



We have to be careful about the 4-ply foldings of  $D_{2\ell}^{(1)}$ , for which we can have two different patterns, so by default, the package only draws as much as it can without distinguishing the two:

Default  $D_{2\ell}^{(1)}$  and the two ways to finish it

```

\dynkin[ply=4]D[1]{****.*****.*****} \
\begin{dynkinDiagram}[ply=4]{D}[1]{****.*****.*****}
  \dynkinFold[bend right=90]1{13}
  \dynkinFold[bend right=90]0{14}
\end{dynkinDiagram} \
\begin{dynkinDiagram}[ply=4]{D}[1]{****.*****.*****}
  \dynkinFold01
  \dynkinFold1{13}
  \dynkinFold{13}{14}
\end{dynkinDiagram}

```

Table 23: Some foldings of Dynkin diagrams. For these diagrams, we want to compare a folding diagram with the diagram that results when we fold it, so it looks best to set `fold radius` and `edge length` to equal lengths.

$A_3$		<code>\dynkin [fold]A[0]3</code>
$C_2$		<code>\dynkin C[0]2</code>
$A_{2\ell-1}$		<code>\dynkin [fold]A{**.*****.**}</code>
$C_\ell$		<code>\dynkin C{}</code>
$B_3$		<code>\dynkin [fold]B[0]3</code>
$G_2$		<code>\dynkin [reverse arrows]G[0]2</code>
$D_4$		<code>\dynkin [ply=3, fold right]D4</code>
$G_2$		<code>\dynkin G2</code>

continued ...

Table 23: ...continued

$D_{\ell+1}$		<code>\dynkin [fold]D{}</code>
$B_{\ell}$		<code>\dynkin B{}</code>
$E_6$		<code>\dynkin [fold]E[0]6</code>
$F_4$		<code>\dynkin [reverse arrows]F[0]4</code>
$A_3^1$		<code>\dynkin [ply=4]A[1]3</code>
$A_1^1$		<code>\dynkin A[1]1</code>
$A_{2\ell-1}^1$		<code>\dynkin [fold]A[1]{**.*.....**}</code>
$C_{\ell}^1$		<code>\dynkin C[1]{}</code>
$B_3^1$		<code>\dynkin [ply=3]B[1]3</code>
$A_2^2$		<code>\dynkin A[2]2</code>
$B_3^1$		<code>\dynkin [ply=2]B[1]3</code>
$G_2^1$		<code>\dynkin G[1]2</code>
$B_{\ell}^1$		<code>\dynkin [fold]B[1]{}</code>
$D_{\ell}^2$		<code>\dynkin D[2]{}</code>
$D_4^1$		<code>\dynkin [ply=3]D[1]4</code>
$B_3^1$		<code>\dynkin B[1]3</code>
$D_4^1$		<code>\dynkin [ply=3]D[1]4</code>
$G_2^1$		<code>\dynkin G[1]2</code>
$D_{\ell+1}^1$		<code>\dynkin [fold]D[1]{}</code>
$D_{\ell}^2$		<code>\dynkin D[2]{}</code>
$D_{\ell+1}^1$		<code>\dynkin [fold right]D[1]{}</code>
$B_{\ell}^1$		<code>\dynkin B[1]{}</code>

















continued ...

Table 23: ...continued

$D_{2\ell}^1$		<pre>\begin{dynkinDiagram}[ply=4]D[1]% {****.*****.*****} \dynkinFold01 \dynkinFold1{13} \dynkinFold{13}{14} \end{dynkinDiagram}</pre>
$A_{\text{odd}}^2$		<pre>\dynkin A[2]{odd}</pre>
$D_{2\ell}^1$		<pre>\begin{dynkinDiagram}[ply=4]{D}[1]% {****.*****.*****} \dynkinFold[bend right=90]1{13} \dynkinFold[bend right=90]0{14} \end{dynkinDiagram}</pre>
$A_{\text{even}}^2$		<pre>\dynkin A[2]{even}</pre>
$E_6^1$		<pre>\dynkin [fold]E[1]6</pre>
$F_4^1$		<pre>\dynkin [reverse arrows]F[1]4</pre>
$E_6^1$		<pre>\dynkin [ply=3]E[1]6</pre>
$D_4^3$		<pre>\dynkin D[3]4</pre>
$E_7^1$		<pre>\dynkin [fold]E[1]7</pre>
$E_6^2$		<pre>\dynkin E[2]6</pre>
$F_4^1$		<pre>\dynkin [fold]F[1]4</pre>
$G_2^1$		<pre>\dynkin G[1]2</pre>
$A_{\text{odd}}^2$		<pre>\dynkin [odd,fold]A[2]{****.***}</pre>
$A_{\text{even}}^2$		<pre>\dynkin A[2]{even}</pre>
$D_3^2$		<pre>\dynkin [fold]D[2]3</pre>
$A_2^2$		<pre>\dynkin A[2]2</pre>



Table 24: Frobenius fixed point subgroups of finite simple groups of Lie type [4] p. 15

$A_{\ell \geq 1}$		<code>\dynkin A{}</code>
${}^2A_{\ell \geq 2}$		<code>\dynkin [fold]A{}</code>
$B_{\ell \geq 2}$		<code>\dynkin B{}</code>
${}^2B_2$		<code>\dynkin [fold]B2</code>
$C_{\ell \geq 3}$		<code>\dynkin C{}</code>
$D_{\ell \geq 4}$		<code>\dynkin D{}</code>
${}^2D_{\ell \geq 4}$		<code>\dynkin [fold]D{}</code>
${}^3D_4$		<code>\dynkin [ply=3]D4</code>
$E_6$		<code>\dynkin E6</code>
${}^2E_6$		<code>\dynkin [fold]E6</code>
$E_7$		<code>\dynkin E7</code>
$E_8$		<code>\dynkin E8</code>
$F_4$		<code>\dynkin F4</code>
${}^2F_4$		<code>\dynkin [fold]F4</code>
$G_2$		<code>\dynkin G2</code>
${}^2G_2$		<code>\dynkin [fold]G2</code>

## 30. TYPESETTING MATHEMATICAL NAMES OF DYNKIN DIAGRAMS

The `\dynkinName` command, with the same syntax as `\dynkin`, typesets a default name of your diagram in L<sup>A</sup>T<sub>E</sub>X. It is perhaps only useful when automatically generating a large collection of Dynkin diagrams in a computer program.

Name of a diagram

```
\dynkinName[label,extended]B7
\dynkinName A[2]{even}
\dynkinName[Coxeter]B7
\dynkinName[label,extended]B{}
\dynkinName D[3]4
```

---


$B_7^1$   $A_{ev}^2$   $B_7$   $B_n^1$   $D_4^3$

## 31. CONNECTING DYNKIN DIAGRAMS

We can make some sophisticated folded diagrams by drawing multiple diagrams, each with a name:

Name a diagram

```
\dynkin[name=Bob]D6
```



We can then connect the two with folding edges:

Connect diagrams

```
\begin{dynkinDiagram}[name=upper]A3
  \node (current) at ($(upper root 1)+(0,-.3cm)$) {};
  \dynkin[at=(current),name=lower]A3
  \begin{pgfonlayer}{Dynkin behind}
    \foreach \i in {1,...,3}%
    {%
      \draw[/Dynkin diagram/fold style]
        ($(upper root \i)$)
        -- ($(lower root \i)$);%
    }%
  \end{pgfonlayer}
\end{dynkinDiagram}
```



## The nonsplit Freudenthal–Tits magic square

```

\newcommand\clrK{\rowcolor{BurntOrange!80}}
\newcommand\clrL{\rowcolor{SeaGreen}}
\newcommand\clrH{\rowcolor{RoyalBlue!50}}
\newcommand\clrO{\rowcolor{OrangeRed!70}}
\newcommand\clrOO{\cellcolor{Red}}
\NewDocumentCommand\hd{om}{
\cellcolor{gray!30}$\IfNoValueF{#1}{\mathbb{#1}\setminus}\mathbb{#2}$}
\tikzset{/Dynkin diagram/fold style/.style={blue!22,ultra thick}}
\begin{tcolorbox}[colback=white,colframe=white]
\begin{tabular}{|c|c|c|c|c|}\hline
\hd[A]{B}&\hd{K}&\hd{L}&\hd{H}&\hd{O}\ \ \ \hline
\clrK\hd{K}&\ \ dynkin A1 & \ \ dynkin A{*o} & \ \ dynkin C{o*o} & \ \ dynkin
F{*ooo} \ \ \hline
\clrL\hd{L}&\ \ dynkin A{**} & & & 
\begin{dynkinDiagram}[name=upper]A2
\node (current) at ($(upper root 1)+(0,-.35cm)$) {};
\dynkin[at=(current),name=lower]A2
\begin{pgfonlayer}{Dynkin behind}
\foreach \i in {1,2}{%
\draw[/Dynkin diagram/fold style] ($(upper root \i)$) -- ($(lower
root \i)$);}
\end{pgfonlayer}
\end{dynkinDiagram}&
\ \ dynkin A{*ooo*} & 
\ \ dynkin E{*oooo*} \ \ \hline
\clrH\hd{H} & & 
\ \ dynkin C{***} & & 
\ \ dynkin [fold] A{****} & 
\ \ dynkin D{*oo*o*} & 
\ \ dynkin E{*oooo**}\ \ \hline
\clrO\hd{O} & & 
\ \ dynkin F{****} & & 
\ \ dynkin [o/.style = {
solid,
draw=black,
fill=black}] E{II} & 
\ \ dynkin [backwards] E{***oo*o} & 
\clrOO \ \ dynkin E{*oooo**}\ \ \hline
\end{tabular}
\end{tcolorbox}

```


A \ B	$\mathbb{K}$	$\mathbb{L}$	$\mathbb{H}$	$\mathbb{O}$
$\mathbb{K}$				
$\mathbb{L}$				
$\mathbb{H}$				
$\mathbb{O}$				

The following diagrams arise in the Satake diagrams of the pseudo-Riemannian symmetric spaces [2].

```

\pgfkeys{/Dynkin diagram,edge length=.5cm,fold radius=.5cm}
\begin{tikzpicture}
  \dynkin[name=1]A{IIIb}
  \node (a) at (-.3,-.4){};
  \dynkin[name=2,at=(a)]A{IIIb}
  \begin{pgfonlayer}{Dynkin behind}
    \foreach \i in {1,...,7}{
      \draw[/Dynkin diagram/fold style]
        ($(\i root \i)$) -- ($(\i+1 root \i)$);}
  \end{pgfonlayer}
\end{tikzpicture}

```



```

\pgfkeys{/Dynkin diagram,
  edge length=.75cm,
  edge/.style={draw=example-color,double=black,very thick}}
\begin{tikzpicture}
  \foreach \d in {1,...,4}{
    \node (current) at ($(\d*.05,\d*.3)$){};
    \dynkin[name=\d,at=(current)]D{oooo}
  }
  \begin{pgfonlayer}{Dynkin behind}
    \newcommand\df[2]{
      \draw[/Dynkin diagram/fold style]
        ($(\#1 root \i)$) -- ($(\#2 root \i)$);}
  \end{pgfonlayer}

```


```

\foreach \i in
{1,...,6}{\df{1}{2}\df{2}{3}\df{3}{4}}
\end{pgfonlayer}
\end{tikzpicture}


```

32. OTHER EXAMPLES

${}^1D_4$  4-ply tied straight:



${}^1D_4$  4-ply tied bending:



```

\tikzset{/Dynkin diagram,
edge length=1cm,
fold radius=1cm,

```

```

label,
label*=true,
label macro/.code={\alpha_{#1}},
label macro*/.code={\beta_{#1}}}
\({}^1 D_4\) 4-ply tied straight:
\begin{dynkinDiagram}[ply=4]D[1]%
{****.*****.****}
\dynkinFold 01
\dynkinFold 1{13}
\dynkinFold{13}{14}
\end{dynkinDiagram}
\({}^1 D_4\) 4-ply tied bending:
\begin{dynkinDiagram}[ply=4,label]D[1]%
{****.*****.****}
\dynkinFold1{13}
\dynkinFold[bend right=65]0{14}
\end{dynkinDiagram}

```

Below we draw the Vogan diagrams of some affine Lie superalgebras [25, 24].

$\mathfrak{sl}(2m|2n)^{(2)}$

```
\begin{dynkinDiagram}[ply=2,label]{B}[1]{oo.oto.oo}
\dynkinLabelRoot*71
\end{dynkinDiagram}
```

---


```
\dynkin[label]B[1]{oo.oto.oo}
```

---


```
\dynkin[ply=2,label]B[1]{oo.Oto.Oo}
```

---


`\dynkin[label]B[1]{oo.0to.0o}`




`\dynkin[label]D[1]{oo.oto.ooo}`



`\dynkin[label]D[1]{o0.ot0.ooo}`




`\dynkin[label,fold]D[1]{oo.oto.ooo}`




$\mathfrak{sl}(2m+1|2n)^2$

`\dynkin[label]B[1]{oo.oto.oo}`




`\dynkin[label]B[1]{o0.oto.o0}`








`\dynkin[ply=2,label,double fold]B[1]{oo.0t0.oo}`




$sl(2|2n)^{(2)}$

`\dynkin[ply=2,label,double edges]D[1]{oo.oto.ooo}`




`\dynkin[ply=2,label,double fold left]D[1]{oo.oto.ooo}`




$osp(2m|2n)^{(2)}$

`\dynkin[label,label macro/.code={1}]D[2]{o.oto.oo}`




`\dynkin[label,label macro/.code={1}]D[2]{o.0to.0o}`




$\mathfrak{osp}(2|2n)^{(2)}$ 


```
\dynkin[label,label macro/.code=\lablIt{#1},
  affine mark=*]
D[2]{o.o.o.o*}
```




```
\dynkin[label,label macro/.code=\lablIt{#1},
  affine mark=*]
D[2]{o.o.0.o*}
```


 $\mathfrak{sl}(1|2n+1)^4$ 

```
\dynkin[label,label macro/.code={1}]D[2]{o.o.o.o*}
```



```
\dynkin[label,label macro/.code={1}]D[2]{o.o.0.o*}
```




$A^1$

```

\begin{tikzpicture}
  \dynkin[name=upper]A{oo.t.oo}
  \node (Dynkin current) at (upper root 1){};
  \dynkinSouth
  \dynkin[at=(Dynkin
current),name=lower]A{oo.t.oo}
  \begin{pgfonlayer}{Dynkin behind}
  \foreach \i in {1,...,5}{
    \draw[/Dynkin diagram/fold style]
      ($(\upper root \i)$) --
      ($(\lower root \i)$);
  }
  \end{pgfonlayer}
\end{tikzpicture}


```



```

\dynkin[fold]A[1]{oo.t.oooo.t.oo}


```



```

\dynkin[fold,affine mark=t]A[1]{oo.o.ootoo.o.oo}


```









```

\dynkin[affine mark=t]A[1]{o*.t.*o}

```



$B^1$ `\dynkin[affine mark=*]A[2]{o.oto.o*}``\dynkin[affine mark=*]A[2]{o.oto.o*}``\dynkin[affine mark=*]A[2]{o.ooo.oo}``\dynkin[odd]A[2]{oo.*to.*o}``\dynkin[odd, fold]A[2]{oo.oto.oo}``\dynkin[odd, fold]A[2]{o*.oto.o*}`

$D^1$

`\dynkin D{otoo}`



`\dynkin D{ot*o}`




`\dynkin[fold]D{otoo}`




$C^1$

`\dynkin[double edges,fold,affine  
mark=t,odd]A[2]{to.o*}`




`\dynkin[double edges,fold,affine  
mark=t,odd]A[2]{t*.oo}`




$F^1$ 


```
\begin{dynkinDiagram}A{oto*}%
  \dynkinQuadrupleEdge 12%
  \dynkinTripleEdge 43%
\end{dynkinDiagram}%
```




```
\begin{dynkinDiagram}A{*too}%
  \dynkinQuadrupleEdge 12%
  \dynkinTripleEdge 43%
\end{dynkinDiagram}%
```

 $G^1$ 



```
\begin{dynkinDiagram}A{ot*oo}%
  \dynkinQuadrupleEdge 12%
  \dynkinDefiniteDoubleEdge 43%
\end{dynkinDiagram}%
```



```
\begin{dynkinDiagram}A{oto*o}%
  \dynkinQuadrupleEdge 12%
  \dynkinDefiniteDoubleEdge 43%
\end{dynkinDiagram}%
```












```

\begin{dynkinDiagram}A{*too*}%
  \dynkinQuadrupleEdge 12%
  \dynkinDefiniteDoubleEdge 43%
\end{dynkinDiagram}%
-----

-----
\begin{dynkinDiagram}A{*too*}%
  \dynkinQuadrupleEdge 12%
  \dynkinDefiniteDoubleEdge 43%
\end{dynkinDiagram}%
-----


```

33. EXAMPLE: THE COMPLEX SIMPLE LIE ALGEBRAS

$\mathfrak{g}$	Diagram	Weights	Roots	Simple roots
$A_n$		$\frac{1}{n+1}\mathbb{Z}^{n+1} / \langle \sum e_j \rangle$	$e_i - e_j$	$e_i - e_{i+1}$
$B_n$		$\frac{1}{2}\mathbb{Z}^n$	$\pm e_i, \pm e_i \pm e_j, i \neq j$	$e_i - e_{i+1}, e_n$
$C_n$		$\mathbb{Z}^n$	$\pm 2e_i, \pm e_i \pm e_j, i \neq j$	$e_i - e_{i+1}, 2e_n$
$D_n$		$\frac{1}{2}\mathbb{Z}^n$	$\pm e_i \pm e_j, i \neq j$	$e_i - e_{i+1}, \quad i \leq n-1$ $e_{n-1} + e_n$
$E_8$		$\frac{1}{2}\mathbb{Z}^8$	$\pm 2e_i \pm 2e_j, \quad i \neq j,$ $\sum_i (-1)^{m_i} e_i, \quad \sum m_i \text{ even}$	$2e_1 - 2e_2,$ $2e_2 - 2e_3,$ $2e_3 - 2e_4,$ $2e_4 - 2e_5,$ $2e_5 - 2e_6,$ $2e_6 + 2e_7,$ $-\sum e_j,$ $2e_6 - 2e_7$
$E_7$		$\frac{1}{2}\mathbb{Z}^8 / \langle e_1 - e_2 \rangle$	quotient of $E_8$	quotient of $E_8$
$E_6$		$\frac{1}{3}\mathbb{Z}^8 / \langle e_1 - e_2, e_2 - e_3 \rangle$	quotient of $E_8$	quotient of $E_8$
$F_4$		$\mathbb{Z}^4$	$\pm 2e_i,$ $\pm 2e_i \pm 2e_j, \quad i \neq j,$ $\pm e_1 \pm e_2 \pm e_3 \pm e_4$	$2e_2 - 2e_3,$ $2e_3 - 2e_4,$ $2e_4,$ $e_1 - e_2 - e_3 - e_4$

$\mathfrak{g}$	Diagram	Weights	Roots	Simple roots
$G_2$		$\mathbb{Z}^3 / \langle \sum e_j \rangle$	$\pm(1, -1, 0),$ $\pm(-1, 0, 1),$ $\pm(0, -1, 1),$ $\pm(2, -1, -1),$ $\pm(1, -2, 1),$ $\pm(-1, -1, 2)$	$(-1, 0, 1),$ $(2, -1, -1)$

```

\NewDocumentEnvironment{bunch}{}{
  \renewcommand*{\arraystretch}{1}
  \begin{array}{@{}ll@{}}
    \\\ \midrule
  }{
    \\\ \midrule\end{array}}
\small
\NewDocumentCommand\nt{mm}{
  \newcolumnntype{#1}{>\columncolor[gray]{.9}>{\$}m{#2cm}<{\$}}
\nt{G}{.3}\nt{J}{2.1}\nt{K}{3}\nt{R}{3.7}\nt{S}{3}
\NewDocumentCommand\LieG{}{\mathfrak{g}}
\NewDocumentCommand\W{om}{
  \ensuremath{
    \mathbb{Z}^{\#2}
    \IfValueT{#1}{/\left<#1\right>}}
\renewcommand*{\arraystretch}{1.5}
\NewDocumentCommand\quo{}{\text{quotient of } E_8}
\begin{longtable}{@{}GJKRS@{}}
\LieG&
  \text{Diagram}&
  \text{Weights}&
  \text{Roots}&
  \text{Simple roots}\\
\midrule\endfirsthead
\LieG&
  \text{Diagram}&
  \text{Weights}&
  \text{Roots}&
  \text{Simple roots}\\
\midrule\endhead
A_n&
  \dynkin A{}&
  \frac{1}{n+1}\W[\sum e_j]{n+1}&
  e_i-e_j&
  e_i-e_{i+1}\\
B_n&
  \dynkin B{}&
  \frac{1}{2}\W n&
  \pm e_i, \pm e_i \pm e_j, i \ne j&
  e_i-e_{i+1}, e_n\\
C_n&
  \dynkin C{}&

```



```

\W n&
\pm 2 e_i, \pm e_i \pm e_j, i\ne j&
e_i-e_{i+1}, 2e_n\\
D_n&
\dynkin D{}&
\frac{12}{W n&
\pm e_i \pm e_j, i\ne j &
\begin{bunch}
e_i-e_{i+1},&i\le n-1\\
e_{n-1}+e_n
\end{bunch}\\
E_8&
\dynkin E8&
\frac{12}{W 8&
\begin{bunch}
\pm 2e_i\pm 2e_j,&i\ne j,\\
\sum_i(-1)^{m_i}e_i,&\sum m_i \text{ even}
\end{bunch}&
\begin{bunch}
2e_1-2e_2,\\
2e_2-2e_3,\\
2e_3-2e_4,\\
2e_4-2e_5,\\
2e_5-2e_6,\\
2e_6+2e_7,\\
-\sum e_j,\\2e_6-2e_7
\end{bunch}\\
E_7&
\dynkin E7&
\frac{12}{W[e_1-e_2]8&
\quo&
\quo\\
E_6&
\dynkin E6&
\frac{13}{W[e_1-e_2,e_2-e_3]8&
\quo&
\quo\\
F_4&
\dynkin F4&
\W4&
\begin{bunch}
\pm 2e_i,\\
\pm 2e_i \pm 2e_j, \quad i \ne j,\\
\pm e_1 \pm e_2 \pm e_3 \pm e_4
\end{bunch}&
\begin{bunch}
2e_2-2e_3,\\
2e_3-2e_4,\\
2e_4,\\
e_1-e_2-e_3-e_4
\end{bunch}\\
G_2&
\dynkin G2&


```

```

\W[\sum e_j]3&
\begin{bunch}
  \pm(1,-1,0),\ \
  \pm(-1,0,1),\ \
  \pm(0,-1,1),\ \
  \pm(2,-1,-1),\ \
  \pm(1,-2,1),\ \
  \pm(-1,-1,2)
\end{bunch}
&
\begin{bunch}
  (-1,0,1),\ \
  (2,-1,-1)
\end{bunch}
\end{longtable}

```

## 34. AN EXAMPLE OF MIKHAIL BOROVoi




```

\tikzset{
  big arrow/.style={
    -Stealth,
    line cap=round,
    line width=1mm,
    shorten <=1mm,
    shorten >=1mm}}
\newcommand\catholic[2]{
  \draw[big arrow,green!25!white] (root #1) to (root #2);}
\newcommand\protestant[2]{
  \begin{scope}[transparency group, opacity=.25]
    \draw[big arrow,orange] (root #1) to (root #2);
  \end{scope}}
\begin{dynkinDiagram}[%
  edge length=1.2cm,
  indefinite edge/.style={
    thick,
    loosely dotted},
  labels*={0,1,2,3,\ell-3,\ell-2,\ell-1,\ell}]
D[1]{}
\catholic 06\catholic 17
\protestant 70\protestant 61
\end{dynkinDiagram}

```

There are many undocumented features, which are not usually very useful; here is a taste, from [14] p. 61.



```

\begin{center}
\makeatletter
\newcommand{\extraNode}[6]%
{%
\dynkinPlaceRootRelativeTo{#1}{#2}{#3}{#4}{#5}
\dynkinDefiniteSingleEdge{#1}{#2}
\dynkinRootMark{o}{#1}
\advance\dynkin@nodes by 1
\dynkinLabelRoot{#1}{#6}
}%
\newcommand{\extraDotNode}[6]%
{%
\dynkinPlaceRootRelativeTo{#1}{#2}{#3}{#4}{#5}
\dynkinIndefiniteSingleEdge{#1}{#2}
\dynkinRootMark{o}{#1}
\advance\dynkin@nodes by 1
\dynkinLabelRoot{#1}{#6}
}%
\makeatother
\tikzset{/Dynkin diagram,mark=o,edge length=.5cm}
\begin{tabular}{>{\columncolor[gray]{.9}}c}
\dynkin A{}
\\ \midrule
\begin{dynkinDiagram}A{ooo.o}
\dynkinLabelRoot{1}{\varepsilon_1}
\dynkinLabelRoot{2}{\varepsilon_2}
\dynkinLabelRoot{3}{\varepsilon_3}
\dynkinLabelRoot{4}{\varepsilon_p}
\dynkin[at=(root 4),arrows=false]B2
\dynkin[at=(root 2),labels={\eta_q,\eta_{q-1},\eta_2,\eta_1}]A{oo.oo}
\end{dynkinDiagram}
\\ \midrule
\dynkin[arrows=false] G{2}
\\ \midrule
\begin{dynkinDiagram}[%
labels={\varepsilon_{p-1},\psi,\zeta_{r-1},\eta_{q-1}},
mark=o,edge length=.75cm]D4
\extraDotNode{5}{3}{northeast}{right}{left}{\zeta_2}
\extraDotNode{6}{4}{southeast}{right}{left}{\eta_2}
\extraDotNode{7}{1}{west}{below}{above}{\varepsilon_2}
\extraNode{8}{5}{northeast}{right}{left}{\zeta_1}

```

```

\extraNode{9}{6}{southeast}{right}{left}{\eta_1}
\extraNode{10}{7}{west}{below}{above}{\varepsilon_1}
\end{dynkinDiagram}
\end{tabular}
\end{center}

```

### 35. SYNTAX

The syntax is `\dynkin[<options>]{<letter>}[<twisted rank>]{<rank>}` where `<letter>` is A, B, C, D, E, F or G, the family of root system for the Dynkin diagram, `<twisted rank>` is 0, 1, 2, 3 (default is 0) representing:

- 0 finite root system
- 1 affine extended root system, i.e. of type <sup>(1)</sup>
- 2 affine twisted root system of type <sup>(2)</sup>
- 3 affine twisted root system of type <sup>(3)</sup>

and `<rank>` is

- (1) an integer representing the rank or
- (2) blank to represent an indefinite rank or
- (3) the name of a Satake diagram as in section 6.

The environment syntax is `\begin{dynkinDiagram}` followed by the same parameters as `\dynkin`, then various Dynkin diagram and *TikZ* commands, and then `\end{dynkinDiagram}`.

### 36. OPTIONS

```

*/.style = TikZ style data,
default : solid,draw=black,fill=black
style for roots like •
o/.style = TikZ style data,
default : solid,draw=black,fill=white
style for roots like ◦
O/.style = TikZ style data,
default : solid,draw=black,fill=white
style for roots like ⊙
t/.style = TikZ style data,
default : solid,draw=black,fill=black
style for roots like ⊗
x/.style = TikZ style data,
default : solid,draw=black,line cap=round
style for roots like ×
X/.style = TikZ style data,
default : solid,draw=black,thick,line cap=round
style for roots like ✕
affine mark = o,O,t,x,X,*,
default : *
default root mark for root zero in an affine Dynkin diagram
arrow shape/.style = TikZ style data,
default : -{Computer Modern Rightarrow[black]}
continued ...

```

Table 26: ...continued

shape of arrow heads for most Dynkin diagrams that have arrows

**arrow style** = TikZ style data,  
**default** : black  
 set to override the default style for the arrows in nonsimply laced Dynkin diagrams, including length, width, line width and color

**arrow width** = length,  
**default** : 1.5(root radius)  
 if you change arrow style or shape, use **arrow width** to say how wide your arrows will be

**arrows** = true or false,  
**default** : true  
 whether to draw the arrows that arise along the edges

**backwards** = true or false,  
**default** : false  
 whether to reverse right to left

**bird arrow** = true or false,  
**default** : false  
 whether to use bird style arrows in  $G_2, F_4$ .

**Bourbaki arrow** = true or false,  
**default** : false  
 whether to use Bourbaki style arrows in  $G_2, F_4$ .

**ceref** = true or false,  
**default** : false  
 whether to draw roots in a “ceref” style

**Coxeter** = true or false,  
**default** : false  
 whether to draw a Coxeter diagram, rather than a Dynkin diagram

**double edges** = TikZ style data,  
**default** : not set  
 set to override the **fold** style when folding roots together in a Dynkin diagram, so that the foldings are indicated with double edges (like those of an  $F_4$  Dynkin diagram without arrows)

**double fold** = TikZ style data,  
**default** : not set  
 set to override the **fold** style when folding roots together in a Dynkin diagram, so that the foldings are indicated with double edges (like those of an  $F_4$  Dynkin diagram without arrows), but filled in solidly

**double left** = TikZ style data,  
**default** : not set  
 set to override the **fold** style when folding roots together at the left side of a Dynkin diagram, so that the foldings are indicated with double edges (like those of an  $F_4$  Dynkin diagram without arrows)

**double fold left** = TikZ style data,  
**default** : not set

continued ...

Table 26: ...continued

set to override the `fold` style when folding roots together at the left side of a Dynkin diagram, so that the foldings are indicated with double edges (like those of an  $F_4$  Dynkin diagram without arrows), but filled in solidly

`double right = TikZ style data,`  
 default : not set  
 set to override the `fold` style when folding roots together at the right side of a Dynkin diagram, so that the foldings are indicated with double edges (like those of an  $F_4$  Dynkin diagram without arrows)

`double fold right = TikZ style data,`  
 default : not set  
 set to override the `fold` style when folding roots together at the right side of a Dynkin diagram, so that the foldings are indicated with double edges (like those of an  $F_4$  Dynkin diagram without arrows), but filled in solidly

`edge label/.style = TikZ style data,`  
 default : `text height=0,text depth=0,label distance=-2pt`  
 style of edge labels in the Dynkin diagram, as found, for example, on some Coxeter diagrams

`edge length = length,`  
 default : `.35cm`  
 distance between nodes in the Dynkin diagram

`edge/.style = TikZ style data,`  
 default : `solid,draw=black,fill=white,thin`  
 style of edges in the Dynkin diagram

`extended = true or false,`  
 default : `false`  
 Is this an extended Dynkin diagram?

`fold = true or false,`  
 default : `true`  
 whether, when drawing Dynkin diagrams, to draw them 2-ply

`fold left = true or false,`  
 default : `true`  
 whether to fold the roots on the left side of a Dynkin diagram

`fold radius = length,`  
 default : `.3cm`  
 the radius of circular arcs used in curved edges of folded Dynkin diagrams

`fold right = true or false,`  
 default : `true`  
 whether to fold the roots on the right side of a Dynkin diagram

`fold left style/.style = TikZ style data,`  
 default :  
 style to override the `fold` style when folding roots together on the left half of a Dynkin diagram

continued ...

Table 26: ...continued

**fold right style/.style** = TikZ style data,  
**default** :  
 style to override the **fold** style when folding roots together on the right half of a Dynkin diagram

**fold style/.style** = TikZ style data,  
**default** : **solid,draw=black!40,fill=none,line width=radius**  
 when drawing folded diagrams, style for the fold indicators

**gonality** = math,  
**default** : 0  
 the gonality of a  $G$  or  $I$  Coxeter diagram

**horizontal shift** = length,  
**default** : 0  
 the gonality of a  $G$  or  $I$  Coxeter diagram

**indefinite edge ratio** = float,  
**default** : 1.6  
 ratio of indefinite edge lengths to other edge lengths

**indefinite edge/.style** = TikZ style data,  
**default** : **solid,draw=black,fill=white,thin,densely dotted**  
 style of the dotted or dashed middle third of each indefinite edge

**involution/.style** = TikZ style data,  
**default** : **latex-latex,black**  
 style of involution arrows

**involutions** = semicolon separated list of pairs,  
**default** :  
 involution double arrows to draw

**Kac** = true or false,  
**default** : false  
 whether to draw in the style of [17]

**Kac arrows** = true or false,  
**default** : false  
 whether to draw arrows in the style of [17]

**label** = true or false,  
**default** : false  
 whether to label the roots according to the current labelling scheme

**label\*** = true or false,  
**default** : false  
 whether to label the roots at alternative label locations according to the current labelling scheme

**label depth** = 1-parameter  $\TeX$  macro,  
**default** : **g**  
 the current maximal depth of text labels for the roots, set by giving mathematics text of that depth

**label directions** = comma separated list,  
**default** :  
 list of directions to place root labels: above, below, right, left, below right, and so on.

continued ...

Table 26: ...continued

**label\* directions** = comma separated list,  
 default : list of directions to place alternate root labels: above, below, right, left, below right, and so on.

**label height** =  $\langle$ 1-parameter  $\TeX$  macro $\rangle$ ,  
 default : b  
 the current maximal height of text labels for the roots, set by giving mathematics text of that height

**label macro** = 1-parameter  $\TeX$  macro,  
 default : #1  
 the current labelling scheme for roots

**label macro\*** =  $\langle$ 1-parameter  $\TeX$  macro $\rangle$ ,  
 default : #1  
 the current labelling scheme for alternate roots

**make indefinite edge** =  $\langle$ edge pair  $i$ - $j$  or list of such $\rangle$ ,  
 default : {}  
 edge pair or list of edge pairs to treat as having indefinitely many roots on them

**mark** =  $\langle$ o,0,t,x,X,\* $\rangle$ ,  
 default : \*  
 default root mark

**name** =  $\langle$ string $\rangle$ ,  
 default : anonymous  
 A name for the Dynkin diagram, with `anonymous` treated as a blank; see section 31

**ordering** =  $\langle$ Adams, Bourbaki, Carter, Dynkin, Kac $\rangle$ ,  
 default : Bourbaki  
 which ordering of the roots to use in exceptional root systems as in section 21

**parabolic** =  $\langle$ integer $\rangle$ ,  
 default : 0  
 A parabolic subgroup with specified integer, where the integer is computed as  $n = \sum 2^{i-1} a_i$ ,  $a_i = 0$  or 1, to say that root  $i$  is crossed, i.e. a noncompact root

**ply** =  $\langle$ 0,1,2,3,4 $\rangle$ ,  
 default : 0  
 how many roots get folded together, at most

**reverse arrows** = true or false,  
 default : true  
 whether to reverse the direction of the arrows that arise along the edges

**root radius** =  $\langle$ number $\rangle$ cm,  
 default : .05cm  
 size of the dots and of the crosses in the Dynkin diagram

**separator length** = length,  
 default : .35cm

continued ...



Table 26: ...continued

distance between successive components of a disconnected Dynkin diagram

`text style = TikZ style data,`  
`default : scale=.7`  
 Style for any labels on the roots

`upside down = true or false,`  
`default : false`  
 whether to reverse up to down

`vertical shift = <length>,`  
`default : .5ex`  
 amount to shift up the Dynkin diagram, from the origin of TikZ coordinates.

All other options are passed to TikZ. To force addition expansion, you can add the word `expand` in front of

`affine mark`  
`arrow color`  
`arrow style`  
`arrow width`  
`at`  
`edge length`  
`fold radius`  
`gonality`  
`involutions`  
`label directions`  
`label* directions`  
`labels`  
`labels*`  
`mark`  
`name`  
`ordering`  
`parabolic`  
`ply`  
`root radius`  
`separator length`  
`twisted series`  
`vertical shift`

## REFERENCES

1. J. F. Adams, *Lectures on exceptional Lie groups*, Chicago Lectures in Mathematics, University of Chicago Press, Chicago, IL, 1996, With a foreword by J. Peter May, Edited by Zafer Mahmud and Mamoru Mimura. MR 1428422
2. Kurando Baba, *Satake diagrams and restricted root systems of semisimple pseudo-Riemannian symmetric spaces*, Tokyo J. Math. **32** (2009), no. 1, 127–158. MR 2541161
3. Nicolas Bourbaki, *Lie groups and Lie algebras. Chapters 4–6*, Elements of Mathematics (Berlin), Springer-Verlag, Berlin, 2002, Translated from the 1968 French original by Andrew Pressley. MR 1890629

4. R. W. Carter, *On the representation theory of the finite groups of Lie type over an algebraically closed field of characteristic 0* [MR1170353 (93j:20034)], Algebra, IX, Encyclopaedia Math. Sci., vol. 77, Springer, Berlin, 1995, pp. 1–120, 235–239. MR 1392478
5. ———, *Lie algebras of finite and affine type*, Cambridge Studies in Advanced Mathematics, vol. 96, Cambridge University Press, Cambridge, 2005. MR 2188930
6. Meng-Kiat Chuah, *Cartan automorphisms and Vogan superdiagrams*, Math. Z. **273** (2013), no. 3-4, 793–800. MR 3030677
7. Cristina Draper Fontanals and Valerio Guido, *On the real forms of the exceptional Lie algebra  $\mathfrak{e}_6$  and their Satake diagrams*, Non-associative and non-commutative algebra and operator theory, Springer Proc. Math. Stat., vol. 160, Springer, Cham, 2016, pp. 211–226. MR 3613831
8. E. B. Dynkin, *Semisimple subalgebras of semisimple Lie algebras*, Mat. Sbornik N.S. **30(72)** (1952), 349–462 (3 plates), Reprinted in English translation in [9]. MR 0047629
9. ———, *Selected papers of E. B. Dynkin with commentary*, American Mathematical Society, Providence, RI; International Press, Cambridge, MA, 2000, Edited by A. A. Yushkevich, G. M. Seitz and A. L. Onishchik. MR 1757976
10. L. Frappat, A. Sciarrino, and P. Sorba, *Structure of basic Lie superalgebras and of their affine extensions*, Comm. Math. Phys. **121** (1989), no. 3, 457–500. MR 990776
11. William Fulton and Joe Harris, *Representation theory*, Graduate Texts in Mathematics, vol. 129, Springer-Verlag, New York, 1991, A first course, Readings in Mathematics. MR 1153249
12. L. C. Grove and C. T. Benson, *Finite reflection groups*, second ed., Graduate Texts in Mathematics, vol. 99, Springer-Verlag, New York, 1985. MR 777684
13. Sigurdur Helgason, *Differential geometry, Lie groups, and symmetric spaces*, Graduate Studies in Mathematics, vol. 34, American Mathematical Society, Providence, RI, 2001, Corrected reprint of the 1978 original. MR 1834454
14. James E. Humphreys, *Introduction to Lie algebras and representation theory*, Graduate Texts in Mathematics, vol. 9, Springer-Verlag, New York-Berlin, 1978, Second printing, revised. MR 499562
15. ———, *Reflection groups and Coxeter groups*, Cambridge Studies in Advanced Mathematics, vol. 29, Cambridge University Press, Cambridge, 1990. MR 1066460
16. N. W. Johnson, J. G. Ratcliffe, R. Kellerhals, and S. T. Tschantz, *The size of a hyperbolic Coxeter simplex*, Transform. Groups **4** (1999), no. 4, 329–353. MR 1726696
17. Victor G. Kac, *Infinite-dimensional Lie algebras*, third ed., Cambridge University Press, Cambridge, 1990. MR 1104219
18. S. Pratik Khastgir and Ryu Sasaki, *Non-canonical folding of Dynkin diagrams and reduction of affine Toda theories*, Progr. Theoret. Phys. **95** (1996), no. 3, 503–518. MR 1388245
19. Anthony W. Knap, *Lie groups beyond an introduction*, second ed., Progress in Mathematics, vol. 140, Birkhäuser Boston, Inc., Boston, MA, 2002. MR 1920389
20. Robert P. Langlands, *Euler products*, Yale University Press, New Haven, Conn.-London, 1971, A James K. Whittemore Lecture in Mathematics given at Yale University, 1967, Yale Mathematical Monographs, 1. MR 0419366
21. Peter McMullen and Egon Schulte, *Abstract regular polytopes*, Encyclopedia of Mathematics and its Applications, vol. 92, Cambridge University Press, Cambridge, 2002. MR 1965665
22. A. L. Onishchik and È. B. Vinberg, *Lie groups and algebraic groups*, Springer Series in Soviet Mathematics, Springer-Verlag, Berlin, 1990, Translated from the Russian and with a preface by D. A. Leites. MR 91g:22001
23. A. L. Onishchik and È. B. Vinberg, *Lie groups and algebraic groups*, Springer Series in Soviet Mathematics, Springer-Verlag, Berlin, 1990, Translated from the Russian and with a preface by D. A. Leites. MR 1064110
24. B. Ransingh, *Vogan diagrams of affine twisted Lie superalgebras*, ArXiv e-prints (2013), 1–9.
25. Biswajit Ransingh, *Vogan diagrams of untwisted affine Kac-Moody superalgebras*, Asian-Eur. J. Math. **6** (2013), no. 4, 1350062, 10. MR 3149279
26. V. Regelskis and B. Vlaar, *Reflection matrices, coideal subalgebras and generalized Satake diagrams of affine type*, ArXiv e-prints (2016), 1–118.
27. Ichirō Satake, *Algebraic structures of symmetric domains*, Kanō Memorial Lectures, vol. 4, Iwanami Shoten, Tokyo; Princeton University Press, Princeton, N.J., 1980. MR 591460
28. T. A. Springer, *Linear algebraic groups*, second ed., Modern Birkhäuser Classics, Birkhäuser Boston, Inc., Boston, MA, 2009. MR 2458469

29. È. B. Vinberg (ed.), *Lie groups and Lie algebras, III*, Encyclopaedia of Mathematical Sciences, vol. 41, Springer-Verlag, Berlin, 1994, Structure of Lie groups and Lie algebras, A translation of it Current problems in mathematics. Fundamental directions. Vol. 41 (Russian), Akad. Nauk SSSR, Vsesoyuz. Inst. Nauchn. i Tekhn. Inform., Moscow, 1990 [MR1056485 (91b:22001)], Translation by V. Minachin [V. V. Minakhin], Translation edited by A. L. Onishchik and È. B. Vinberg. MR 1349140
30. Ernst Witt, *Spiegelungsgruppen und Aufzählung halbeinfacher Liescher Ringe*, Abh. Math. Sem. Hansischen Univ. **14** (1941), 289–322. MR 5099
31. Jean-Bernard Zuber, *Generalized Dynkin diagrams and root systems and their folding*, Topological field theory, primitive forms and related topics (Kyoto, 1996), Progr. Math., vol. 160, Birkhäuser Boston, Boston, MA, 1998, pp. 453–493. MR 1653035

SCHOOL OF MATHEMATICAL SCIENCES, UNIVERSITY COLLEGE CORK, CORK, IRELAND

*Email address:* b.mckay@ucc.ie