

# The latex-lab-mathtools code\*

L<sup>A</sup>T<sub>E</sub>X Project

v0.80a 2024-09-18

Abstract

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>The Implementation</b>	<b>1</b>
	2.1 File declaration . . . . .	1
	2.2 Tagpdf support . . . . .	1
	2.3 \shortintertext . . . . .	2
	<b>Index</b>	<b>4</b>

## 1 Introduction

This file implements adaptations to the mathtools package needed for the tagging project.

## 2 The Implementation

1 `<@@=math>`

2 `<*kernel>`

### 2.1 File declaration

3 `\ProvidesFile{latex-lab-mathtools.ltx}`

4 `[2024-07-13 v0.1a mathtools adaptations]`

### 2.2 Tagpdf support

To make the code independent from tagging being loaded and active we load the tagpdf-base package:

5 `\RequirePackage{tagpdf-base}`

---

\*

## 2.3 \shortintertext

Similar to the `\intertext` command from `amsmath`, `\shortintertext` errors with active tagging as it is processed twice which leads to duplicated structures. The fix is similar but is complicated as `mathtools` defines two version (and an additional `\intertext` version) and package options to switch between the variants.

At first we redefine all the internal commands

```

6 \ExplSyntaxOn
7 \tl_new:N\l__math_mathtools_init_tl
8 \AddToHook{package/mathtools/after}
9 {%
10   \cs_if_eq:NNTF\intertext@ \MT_intertext:
11     {
12       \tl_set:Nn \l__math_mathtools_init_tl {\MT_orig_intertext_false:}
13     }
14     {
15       \tl_set:Nn \l__math_mathtools_init_tl {\MT_orig_intertext_true:}
16     }
17   \cs_if_eq:NNTF\shortintertext@ \MT_shortintertext:n
18     {
19       \tl_put_right:Nn \l__math_mathtools_init_tl
20         {\MT_orig_shortintertext_false:}
21     }
22     {
23       \tl_put_right:Nn \l__math_mathtools_init_tl
24         {\MT_orig_shortintertext_true:}
25     }
26   \def\MT_intertext: {%
27     \def\intertext##1{%
28       \ifmode\else\\\@empty\fi
29       \noalign{%
30         \penalty\postdisplaypenalty\vskip-\belowdisplayskip
31         \vskip-\lineskiplimit % CCS
32         \vskip\normallineskiplimit % CCS
33         \vskip\l_MT_above_intertext_sep
34         \vbox{%

```

Stop tagging when measuring:

```

35     \ifmeasuring@\tag_suspend:n{\measuring}\fi
36     \normalbaselines
37     \ifdim
38       \ifdim\@totalleftmargin=\z@
39         \linewidth
40       \else
41         -\maxdimen
42       \fi
43     =\columnwidth
44     \else \parshape\@ne \@totalleftmargin \linewidth
45     \fi

```

End the previous mc:

```

46     \tag_mc_end_push:

```

We are already in a par so we change now to Span:

```

47     \tagpdfsetup{para/tag=Span}

```

```

48         \noindent\ignorespaces##1\par
Restart the MC
49         \tag_mc_begin_pop:n{}}%
50         \penalty\predisplaypenalty\vskip\abovedisplayskip%
51         \vskip-\lineskiplimit      % CCS
52         \vskip\normallineskiplimit % CCS
53         \vskip\l_MT_below_intertext_sep
54     }%
55 }%
56 \MH_let:NwN \shortintertext \shortintertext@
57 }

\def\MT_orig_shortintertext:n #1{%
58     \ifvmode\else\\\@empty\fi
59     \noalign{%
60         \penalty\postdisplaypenalty\vskip\abovedisplayshortskip
61         \vbox{%
62             \ifmeasuring@\tag_suspend:n{\measuring}\fi
63             \normalbaselines
64             \MH_if_dim:w
65             \MH_if_dim:w \@totalleftmargin=\z@
66             \linewidth
67             \MH_else:
68                 -\maxdimen
69             \MH_fi:
70                 =\columnwidth
71             \MH_else:
72                 \parshape\@ne \@totalleftmargin \linewidth
73             \MH_fi:
74             \tag_mc_end_push:
75             \tagpdfsetup{para/tag=Span}
76             \tagpdfparaOn
77             \noindent\ignorespaces#1\par
78             \tag_mc_begin_pop:n{}}
79         \penalty\predisplaypenalty\vskip\abovedisplayshortskip%
80     }%
81 }
82 }
83
84 \def\MT_shortintertext:n #1{%
85     \ifvmode\else\\\@empty\fi
86     \noalign{%
87         \penalty\postdisplaypenalty\vskip\abovedisplayshortskip
88         \vskip-\lineskiplimit
89         \vskip\normallineskiplimit
90         \vskip\l_MT_above_shortintertext_sep
91         \vbox{%
92             \ifmeasuring@\tag_suspend:n{\measuring}\fi
93             \normalbaselines
94             \MH_if_dim:w
95             \MH_if_dim:w \@totalleftmargin=\z@
96             \linewidth
97             \MH_else:
98                 -\maxdimen
99             \MH_fi:

```

```

100         =\columnwidth
101     \MH_else:
102         \parshape\@ne \@totalleftmargin \linewidth
103     \MH_fi:
104     \tag_mc_end_push:
105     \tagpdfsetup{para/tag=P}

```

Why is it needed to enable paratagging??

```

106     \tagpdfpara0n
107     \noindent\ignorespaces#1\par
108     \tag_mc_begin_pop:n{}}%
109     \penalty\predisplaypenalty\vskip\abovedisplayshortskip%
110     \vskip-\lineskiplimit
111     \vskip\normallineskiplimit
112     \vskip\l_MT_below_shortintertext_sep
113 }%
114 }
115

```

end hook

```

116 \l_math_mathtools_init_tl
117 }
118 \ExplSyntaxOff
119 </kernel>

```

## Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

	<b>Symbols</b>	<code>\ExplSyntaxOn</code> . . . . . 6
<code>\</code> . . . . .	28, 59, 85	
	<b>A</b>	<b>F</b>
<code>\abovedisplayshortskip</code> . . . . .	61, 80, 87, 109	<code>\fi</code> . . . . . 28, 35, 42, 45, 59, 63, 85, 92
<code>\abovedisplayskip</code> . . . . .	50	
<code>\AddToHook</code> . . . . .	8	<b>I</b>
	<b>B</b>	<code>\ifdim</code> . . . . . 37, 38
<code>\belowdisplayskip</code> . . . . .	30	<code>\ifvmode</code> . . . . . 28, 59, 85
	<b>C</b>	<code>\ignorespaces</code> . . . . . 48, 78, 107
<code>\columnwidth</code> . . . . .	43, 71, 100	<code>\intertext</code> . . . . . 2, 27
cs commands:		<b>L</b>
<code>\cs_if_eq:NNTF</code> . . . . .	10, 17	<code>\lineskiplimit</code> . . . . . 31, 51, 88, 110
	<b>D</b>	<code>\linewidth</code> . . . . . 39, 44, 67, 73, 96, 102
<code>\def</code> . . . . .	26, 27, 58, 84	
	<b>E</b>	<b>M</b>
<code>\else</code> . . . . .	28, 40, 44, 59, 85	<code>\maxdimen</code> . . . . . 41, 69, 98
<code>\ExplSyntaxOff</code> . . . . .	118	<code>\measuring</code> . . . . . 35, 63, 92
		MH commands:
		<code>\MH_else:</code> . . . . . 68, 72, 97, 101
		<code>\MH_fi:</code> . . . . . 70, 74, 99, 103
		<code>\MH_if_dim:w</code> . . . . . 65, 66, 94, 95

<code>\MH_let:NwN</code> .....	56	<b>S</b>	
MT commands:		<code>\shortintertext</code> .....	2, 56
<code>\l_MT_above_intertext_sep</code> .....	33	<b>T</b>	
<code>\l_MT_above_shortintertext_sep</code> ..	90	tag commands:	
<code>\l_MT_below_intertext_sep</code> .....	53	<code>\tag_mc_begin_pop:n</code> .....	49, 79, 108
<code>\l_MT_below_shortintertext_sep</code> .	112	<code>\tag_mc_end_push:</code> .....	46, 75, 104
<code>\MT_intertext:</code> .....	10, 26	<code>\tag_suspend:n</code> .....	35, 63, 92
<code>\MT_orig_intertext_false:</code> .....	12	<code>\tagpdfparaOn</code> .....	77, 106
<code>\MT_orig_intertext_true:</code> .....	15	<code>\tagpdfsetup</code> .....	47, 76, 105
<code>\MT_orig_shortintertext:n</code> .....	58	TeX and L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> commands:	
<code>\MT_orig_shortintertext_false:</code> ..	20	<code>\@empty</code> .....	28, 59, 85
<code>\MT_orig_shortintertext_true:</code> ...	24	<code>\@ne</code> .....	44, 73, 102
<code>\MT_shortintertext:n</code> .....	17, 84	<code>\@totalleftmargin</code> 38, 44, 66, 73, 95, 102	
<b>N</b>		<code>\ifmeasuring@</code> .....	35, 63, 92
<code>\noalign</code> .....	29, 60, 86	<code>\intertext@</code> .....	10
<code>\noindent</code> .....	48, 78, 107	<code>\shortintertext@</code> .....	17, 56
<code>\normalbaselines</code> .....	36, 64, 93	<code>\z@</code> .....	38, 66, 95
<code>\normallineskiplimit</code> ....	32, 52, 89, 111	tl commands:	
<b>P</b>		<code>\tl_new:N</code> .....	7
<code>\par</code> .....	48, 78, 107	<code>\tl_put_right:Nn</code> .....	19, 23
<code>\parshape</code> .....	44, 73, 102	<code>\tl_set:Nn</code> .....	12, 15
<code>\penalty</code> .....	30, 50, 61, 80, 87, 109	tl internal commands:	
<code>\postdisplaypenalty</code> .....	30, 61, 87	<code>\l_math_mathtools_init_tl</code> .....	
<code>\predisplaypenalty</code> .....	50, 80, 109	.....	7, 12, 15, 19, 23, 116
<code>\ProvidesFile</code> .....	3	<b>V</b>	
<b>R</b>		<code>\vbox</code> .....	34, 62, 91
<code>\RequirePackage</code> .....	5	<code>\vskip</code> ...	30, 31, 32, 33, 50, 51, 52, 53, 61, 80, 87, 88, 89, 90, 109, 110, 111, 112