

Documented Code For tracklang v1.6.5

Nicola L.C. Talbot

Dickimaw Books

<http://www.dickimaw-books.com/>

2025-03-04

Contents

1 Introduction	1
2 Main Package Code	2
3 L^AT_EX Code (tracklang.sty)	2
4 Generic Code (tracklang.tex)	8
4.1 Internal Lists	22
4.2 Known Languages	24
4.3 Mappings	28
4.4 Tracking Languages and Dialects	37
4.5 Predefined Root Languages	56
4.6 Predefined Dialects	70
4.7 Dialect Option Synonyms	80
4.8 Conditionals and Loops	84
4.9 Resources	124
5 Regions Generic Code (tracklang-region-codes.tex)	136
6 ISO 15924 Scripts L^AT_EX Package (tracklang-scripts.sty)	143
7 ISO 15924 Scripts Generic Code (tracklang-scripts.tex)	144

1 Introduction

This is the documented code for the tracklang package. See tracklang-manual.pdf for the main user guide.

2 Main Package Code

3 L^AT_EX Code (tracklang.sty)

To ensure maximum portability this file only uses L^AT_EX kernel commands, rather than using more convenient commands provided by packages such as etoolbox.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{tracklang}[2025/03/04 v1.6.5 (NLCT) Track Languages]
```

```
\@tracklang@declareoption Set up package options.
```

```
\providecommand*{\@tracklang@declareoption}[1]{%
  \DeclareOption{#1}{\TrackPredefinedDialect{#1}}%
}
```

Load generic code:

```
\input{tracklang}
```

There are no other options as this package will typically be loaded using `\RequirePackage` by a package. Explicitly adding an option at that point might create a package option clash. The declared package options are all the possible language names that might be passed as a document class option. (Also, adding any non-language options here will interfere with `\@tracklang@declaredoptions`.)

```
\let\@tracklang@declaredoptions\@declaredoptions
```

Version 1.6.3: however, it's useful to pick up `verbose` passed in the document class and this shouldn't conflict with any language label.

```
\DeclareOption{verbose}{\TrackLangShowVerbosetrue}
\DeclareOption{noverbose}{\TrackLangShowVerbosefalse}
```

```
\DeclareOption{warn}{\TrackLangShowWarningstrue}
\DeclareOption{nowarn}{\TrackLangShowWarningsfalse}
```

```
\ProcessOptions
```

Unset `\@tracklang@declareoption`:

```
\let\@tracklang@declareoption\@gobble
```

In the event that the language hasn't been supplied through the package options (or through the class options, which the package options should process provided the document class has used the standard option declarations) we need to check if any of the known language packages have been loaded. This is a bit risky as it relies on the packages not changing their internal language macros. It would be easier if all the language packages could provide a reliable user interface to determine which languages (and variants) have been loaded.

```
\@tracklang@prelangpkgcheck@hook In the event that any of the language packages choose to load this package
and use tracklang.tex's commands to identify the tracked languages and regions,
then they can first define \@tracklang@prelangpkgcheck@hook to do \endinput
which will skip the checks.
```

```
\csname @tracklang@prelangpkgcheck@hook\endcsname
```

```
\ifx\@tracklang@languages\@empty
```

First test if `\LocaleForEach` is defined.

```
\ifx\LocaleForEach\undefined
  \@tracklang@verbose{\string\LocaleForEach\space not defined
    (checking for other packages)}%
```

If `babel` has been loaded, the languages are stored in `\bbl@loaded`, so check if this command has been defined, and if it has add those languages.

```
\@ifundefined{bbl@loaded}%
  {%
```

If translator has been loaded, the languages are stored in `\trans@languages`

```
\@ifundefined{trans@languages}
  {%
```

Has `ngerman` been loaded?

```
\@ifpackageloaded{ngerman}%
  {%
    \@tracklang@add@ngerman
  }%
  {%
```

Has `german` been loaded?

```
\@ifpackageloaded{german}%
  {%
    \@tracklang@add@german
  }%
  {%
```

Has `polyglossia` been loaded?

```
\@ifpackageloaded{polyglossia}
  {%
```

`polyglossia` now provides `\xpg@bcp@loaded`, which contains a comma-separated list of language tags, so use that if it exists.

```
\@ifundefined{xpg@bcp@loaded}%
  {%
```

Older versions: `polyglossia` sets `\langle lang \rangle@loaded` for each loaded language, so check this for all known languages. I don't know how to consistently check for variants. (Conditionals such as `\if@british@locale` are set immediately with `\setotherlanguage` but are deferred to the start of the document with `\setmainlanguage`, which is too late for `tracklang`.) Script names seem to be stored in `\xpg:scripttag@⟨language⟩` but again this doesn't seem to be set for the main language until the start of the document. New versions of `polyglossia` store the list of loaded languages in `\xpg@loaded`, so check if this is defined.

```
\@ifundefined{xpg@loaded}%
  {%
```

`\xpg@loaded` isn't defined, so iterate over known options and check if the language has been loaded.

```

\PackageInfo{tracklang}{polyglossia loaded but
\string\xpg@loaded\space not defined. Will attempt
to track known languages.}%
\@for\this@language:=\@tracklang@declaredoptions\do{%
  \ifundefined{\this@language @loaded}%
  {%
    {\@nameuse{\@tracklang@add@\this@language}}%
  }%
}%
}%
{%
\@for\this@language:=\xpg@loaded\do{%
  \ifundefined{\@tracklang@add@\this@language}%
  {%
    \PackageWarning{tracklang}%
      {Adding unknown polyglossia language ‘\this@language’}%

    \AddTrackedLanguage{\this@language}%
  }%
  {\@nameuse{\@tracklang@add@\this@language}}%
}%
}%
}%
{%
\@for\this@language:=\xpg@bcp@loaded\do{%

```

These are language tags, which is more convenient.

```

\expandafter\TrackLanguageTag{\this@language}%
}%
}%

```

The `\xpg@bcp@loaded` list doesn't seem to include the main language until the start of the document environment but `\mainbabelname` is defined after `\setmainlanguage`. I'm not sure if `\mainbabelname` was provided in the same version of polyglossia as `\xpg@bcp@loaded` or a different one, so have a separate conditional.

```

\ifundefined{mainbabelname}{}%
{%
  \let\@org@tracklang@add@latex\@tracklang@add@latex
  \def\@tracklang@add@latex{%
    \PackageWarning{tracklang}%
      {Can't detect polyglossia main language. It may
      not have been set yet}%
  }%
  \ifundefined{\@tracklang@add@\mainbabelname}%
  {%
    \PackageWarning{tracklang}%
      {Adding unknown polyglossia main babel name ‘\mainbabelname’}%
    \expandafter\AddTrackedLanguage{\mainbabelname}%
  }%
}

```

```

    }%
    {%
        \nameuse{@tracklang@add@mainbabelname}%
    }%
    \let@tracklang@add@latex\org@tracklang@add@latex
} %
} %
{ %

```

None of the known packages have been loaded, so do nothing in case another package wants to load this one before setting up the language options. However, if at this point babel has been loaded, then it's an older version that hasn't defined \bbl@loaded so check for this.

```

    \@ifpackageloaded{babel}
    {%
        \PackageInfo{tracklang}{babel loaded but
        \string\bbl@loaded\space not defined. Will attempt
        to track known languages.}%
        \@for\this@language:=\@tracklang@declaredoptions\do{%
            \ifundefined{captions\this@language}%
            {}%
            {\@nameuse{@tracklang@add@\this@language}}%
        }%
    }%
    {}%
} %
} %
} %
} %
} %
{ %

```

Add from translator. If translator has been loaded, the language names are stored in \trans@languages but these are labels used by translator, so some mapping is required.

```

\let@tracklang@add@Acadian@tracklang@add@acadian
\let@tracklang@add@French@tracklang@add@french
\let@tracklang@add@Afrikaans@tracklang@add@afrikaans
\let@tracklang@add@Dutch@tracklang@add@dutch
\let@tracklang@add@AmericanEnglish@tracklang@add@american
\let@tracklang@add@Austrian@tracklang@add@austrian
\@namedef{@tracklang@add@Austrian1997}{@tracklang@add@naustrian}%
\let@tracklang@add@Bahasa@tracklang@add@bahasa
\let@tracklang@add@Basque@tracklang@add@basque
\let@tracklang@add@Brazilian@tracklang@add@brazil
\let@tracklang@add@Portuguese@tracklang@add@portuguese
\let@tracklang@add@Breton@tracklang@add@breton
\let@tracklang@add@BritishEnglish@tracklang@add@british
\let@tracklang@add@Bulgarian@tracklang@add@bulgarian
\let@tracklang@add@Canadian@tracklang@add@canadian
\let@tracklang@add@Canadien@tracklang@add@canadien

```

```

\let\@tracklang@add@Catalan\@tracklang@add@catalan
\let\@tracklang@add@Croatian\@tracklang@add@croatian
\let\@tracklang@add@Czech\@tracklang@add@czech
\let\@tracklang@add@Danish\@tracklang@add@danish
\let\@tracklang@add@Dutch\@tracklang@add@dutch
\let\@tracklang@add@English\@tracklang@add@english
\let\@tracklang@add@Esperanto\@tracklang@add@esperanto
\let\@tracklang@add@Estonian\@tracklang@add@estonian
\let\@tracklang@add@Finnish\@tracklang@add@finnish
\let\@tracklang@add@French\@tracklang@add@french
\let\@tracklang@add@Galician\@tracklang@add@galician
\let\@tracklang@add@German\@tracklang@add@german
\@namedef{@tracklang@add@German1997}{\@tracklang@add@ngerman}%
\let\@tracklang@add@Greek\@tracklang@add@greek
\let\@tracklang@add@Polutoniko\@tracklang@add@polutoniko
\let\@tracklang@add@Hebrew\@tracklang@add@hebrew
\let\@tracklang@add@Hungarian\@tracklang@add@hungarian
\let\@tracklang@add@Icelandic\@tracklang@add@icelandic
\let\@tracklang@add@Irish\@tracklang@add@irish
\let\@tracklang@add@Italian\@tracklang@add@italian
\let\@tracklang@add@Latin\@tracklang@add@latin
\let\@tracklang@add@LowerSorbian\@tracklang@add@lowersorbian
\let\@tracklang@add@Magyar\@tracklang@add@magyar
\let\@tracklang@add@Nynorsk\@tracklang@add@nynorsk
\let\@tracklang@add@Norsk\@tracklang@add@norsk
\let\@tracklang@add@Polish\@tracklang@add@polish
\let\@tracklang@add@Portuguese\@tracklang@add@portuguese
\let\@tracklang@add@Romanian\@tracklang@add@romanian
\let\@tracklang@add@Russian\@tracklang@add@russian
\let\@tracklang@add@Scottish\@tracklang@add@scottish
\let\@tracklang@add@Serbian\@tracklang@add@serbian
\let\@tracklang@add@Slovak\@tracklang@add@slovak
\let\@tracklang@add@Slovene\@tracklang@add@slovene
\let\@tracklang@add@Spanish\@tracklang@add@spanish
\let\@tracklang@add@Swedish\@tracklang@add@swedish
\let\@tracklang@add@Turkish\@tracklang@add@turkish
\let\@tracklang@add@Ukrainian\@tracklang@add@ukrainian
\let\@tracklang@add@UpperSorbian\@tracklang@add@uppersorbian
\let\@tracklang@add@Welsh\@tracklang@add@welsh

```

Now iterate through the declared languages:

```

\@for\this@language:=\trans@languages\do{%
  \ifundefined{@tracklang@add@\this@language}{}%
  {\@nameuse{@tracklang@add@\this@language}}%
}%
}%
{%

```

Add from babel

```

\@for\this@language:=\bbl@loaded\do{%

```

```

\ifundefined{@tracklang@add@\this@language}%
{%
  \PackageWarning{tracklang}%
    {Adding unknown babel language ‘\this@language’}%

  \AddTrackedLanguage{\this@language}%
}%
{\@nameuse{@tracklang@add@\this@language}}%
}%

```

If babel has been loaded with serbian, then the script needs to be set to Latn.
(The Cyrillic script is provided with serbianc.)

```

\ifx\captionsserbian\undefined
\else
  \SetTrackedDialectScript{serbian}{Latn}%
\fi
}%
\else
  \@tracklang@verbose{\string\LocaleForEach\space defined}%

```

\LocaleForEach is defined, so use that:

```

\LocaleForEach
{%
  \@tracklang@verbose{Checking babel locale ‘#1’}%
  \@tracklang@ifundef{@tracklang@add@#1}%
  {
    \getlocaleproperty\tracklang@propresult{#1}{identification/tag.bcp47}%
    \expandafter\TrackLanguageTag\expandafter{\tracklang@propresult}%
  }

```

If babel label doesn't match tracklang's dialect label, add mapping:

```

\edef\@tracklang@tmp{#1}%
\ifx\TrackLangLastTrackedDialect\@tracklang@tmp
\else
  \@tracklang@info
    {Adding mapping ‘\TrackLangLastTrackedDialect’ -> ‘#1’}%
  \expandafter\SetTrackedDialectLabelMap\expandafter
    {\TrackLangLastTrackedDialect}{#1}%
\fi
}%
{%
  \@nameuse{@tracklang@add@#1}%
}%
}%

```

```

\ifx\@tracklang@languages\@empty
  \@tracklang@pkgwarn{tracklang}{no dialect information picked up
with \string\LocaleForEach}%
\fi
\fi

```

End of check for language packages

```
\fi
```

4 Generic Code (tracklang.tex)

Does the category code of @ need changing?

```
\@tracklang@restore@at
```

```
\ifnum\catcode'\@=11\relax
  \def\@tracklang@restore@at{}%
\else
  \expandafter\edef\csname @tracklang@restore@at\endcsname{%
    \noexpand\catcode'\noexpand\@=\number\catcode'\@\relax
  }%
  \catcode'\@=11\relax
\fi
```

First check if this file has already been loaded:

```
\ifx\@tracklang@languages\undefined
\else
  \@tracklang@restore@at
  \expandafter\endinput
\fi
```

Version info.

```
\expandafter\def\csname ver@tracklang.tex\endcsname{%
  2025/03/04 v1.6.5 (NLCT) Track Languages Generic Code}
```

Define a long command for determining the existence of a control sequence by its name. (`\relax` is considered undefined.)

```
\@tracklang@ifundef
```

```
\long\def\@tracklang@ifundef#1#2#3{%
  \ifcsname#1\endcsname
    \expandafter\ifx\csname #1\endcsname\relax
      #2%
    \else
      #3%
    \fi
  \else
    \expandafter\ifx\csname #1\endcsname\relax
      #2%
    \else
      #3%
    \fi
  \fi
}
```

`\ifcsname` is an eTeX primitive. Need to check if it's defined.

```
\ifx\ifcsname\undefined
```

Not using eTeX.

```
\long\def\@tracklang@ifundef#1#2#3{%
  \expandafter\ifx\csname #1\endcsname\relax
    #2%
```



```

    \else
      #3%
    \fi
  }

```

Can't have an else part here as T_EX won't recognise `\ifcsize` and we'll have an unmatched end brace.

```
\fi
```

The shell escape stuff needs the Plain T_EX version of `\input`. This is `\@@input` if we're using L^AT_EX.

```
\@tracklang@input
```

```

\ifx\@@input\undefined
  \let\@tracklang@input\input
  \def\@tracklang@inputfile#1{\input #1\relax}
\else
  \let\@tracklang@input\@@input
  \def\@tracklang@inputfile#1{\input{#1}}
\fi

```

Provide some commands in case the L^AT_EX kernel hasn't been loaded.

```
\@tracklang@nnil
```

```

\ifx\@nnil\undefined
  \def\@tracklang@nnil{\@nil}
\else
  \let\@tracklang@nnil\@nnil
\fi

```

```
\@tracklang@for
```

```

\ifx\@for\undefined
  \long\def\@tracklang@for#1:=#2\do#3{%
    \expandafter\def\expandafter\@fortmp\expandafter{#2}%
    \ifx\@fortmp\empty
      \else
        \expandafter
          \@tracklang@forloop #2,\@nil,\@nil\@@ #1{#3}%
        \fi
      }
  \long\def\@tracklang@forloop#1,#2,#3\@@ #4#5{%
    \def #4{#1}%
    \ifx#4\@tracklang@nnil
      \else
        #5%
        \def #4{#2}%
        \ifx#4\@tracklang@nnil
          \else
            #5%
            \@tracklang@iforloop #3\@@ #4{#5}%
          \fi
        \fi
      \fi
    }

```

```

    \fi
  \fi
}
\long\def\@tracklang@iforloop#1,#2\@@ #3#4{%
  \def#3{#1}%
  \ifx#3\@tracklang@nnil
    \expandafter
    \@tracklang@fornoop
  \else
    #4\relax
    \expandafter\@tracklang@iforloop
  \fi
  #2\@@ #3{#4}%
}
\long\def\@tracklang@fornoop#1\@@ #2#3{}
\else
  \let\@tracklang@for\@for
\fi

```

\@tracklang@namedef

```

\ifx\@namedef\undefined
  \def\@tracklang@namedef#1{\expandafter\def\csname#1\endcsname}
\else
  \let\@tracklang@namedef\@namedef
\fi

```

\@tracklang@enamedef

```

\def\@tracklang@enamedef#1{\expandafter\edef\csname#1\endcsname}

```

\@tracklang@nameuse

```

\def\@tracklang@nameuse#1{%
  \@tracklang@ifundef{#1}{\csname#1\endcsname}%
}

```

```

\@tracklang@ifcseqcsname{<cs>}{<csname>}{<true>}{<false>}

```

\@tracklang@ifcseqcsname

Compares two commands, the first is reference as a control sequence the second is referenced as a control sequence name. Condition is false if the second isn't defined (no check for the existence of the first).

```

\def\@tracklang@ifcseqcsname#1#2#3#4{%
  \@tracklang@ifundef{#2}{#4}%
  {%
    \expandafter\ifx\expandafter#1\csname#2\endcsname
    #3%
  \else
    #4%
  \fi
}

```

```

    }%
  }

\@tracklang@sanitize
\ifx\@onelevel@sanitize\undefined
  \def\@tracklang@sanitize#1{%
    \edef#1{\expandafter\@tracklang@strip@prefix\meaning#1}%
  }
  \def\@tracklang@strip@prefix#1>{}
\else
  \let\@tracklang@sanitize\@onelevel@sanitize
\fi

\@tracklang@firstoftwo
\long\def\@tracklang@firstoftwo#1#2{#1}

\@tracklang@secondoftwo
\long\def\@tracklang@secondoftwo#1#2{#2}

\@tracklang@err
\ifx\PackageError\undefined
  \def\@tracklang@err#1#2{%
    \errhelp{#2}%
    \errmessage{tracklang: #1}}
\else
  \def\@tracklang@err#1#2{\PackageError{tracklang}{#1}{#2}}
\fi

\ifTrackLangShowWarnings Allow user to switch warnings on or off.
  \newif\ifTrackLangShowWarnings
  \TrackLangShowWarningstrue

\@tracklang@pkgwarn Provided for related packages such as texosquery.
\ifx\PackageWarning\undefined
  \def\@tracklang@pkgwarn#1#2{%
    \ifTrackLangShowWarnings
      {%
        \newlinechar='^^J
        \def\MessageBreak{^^J}%
        \message{^^J#1 Warning: #2 on line \the\inputlineno.^^J}%
      }%
    \fi
  }
\else
  \def\@tracklang@pkgwarn#1#2{%
    \ifTrackLangShowWarnings
      \PackageWarning{#1}{#2}%
    \fi
  }
\fi

```

```

\@tracklang@warn
    \def\@tracklang@warn#1{\@tracklang@pkgwarn{tracklang}{#1}}%

\ifTrackLangShowInfo Allow user to switch information messages on or off.
    \newif\ifTrackLangShowInfo
    \TrackLangShowInfofalse

\@tracklang@info
    \ifx\PackageInfo\undefined
        \def\@tracklang@info#1{%
            \ifTrackLangShowInfo
                {%
                    \newlinechar='\^^J
                    \def\MessageBreak{^^J}%
                    \message{^^Jtracklang Info: #1 on line \the\inputlineno.^^J}%
                }%
            \fi
        }%
    \else
        \def\@tracklang@info#1{%
            \ifTrackLangShowInfo
                \PackageInfo{tracklang}{#1}%
            \fi
        }%
    \fi

\ifTrackLangShowVerbose Allow user to switch verbose (debugging) information messages on or off. Note
that verbose information will be off regardless of this switch if the info switch
is off.
    \newif\ifTrackLangShowVerbose
    \TrackLangShowVerbosefalse

\@tracklang@verbose
    \def\@tracklang@verbose#1{%
        \ifTrackLangShowVerbose
            \@tracklang@info{#1}%
        \fi
    }%

\@tracklang@IfFileExists
    \ifx\IfFileExists\undefined
        \long\def\@tracklang@IfFileExists#1#2#3{%
            \openin0=#1 %
            \ifeof0\relax
                \def\@tracklang@tmp{#3}%
            \else
                \closein0\relax
                \edef\@filef@und{#1 }%
                \def\@tracklang@tmp{#2}%
            \fi
        }%
    \fi

```

```

    \fi
    \@tracklang@tmp
  }

  \else
    \let\@tracklang@IfFileExists\IfFileExists
  \fi

```

`\TrackLangEncodingName` Provide a default encoding name to avoid repeated tests to determine whether or not `\inputencodingname` has been defined.

```

\ifx\inputencodingname\undefined
  \def\TrackLangEncodingName{utf8}
\else
  \def\TrackLangEncodingName{\inputencodingname}
\fi

```

Provide a way to query the environment variables `LC_ALL` or `LANG` to determine the region and language. The result is stored in `\TrackLangEnv` if it can be obtained. If it can't be obtained, `\TrackLangEnv` is set to empty. Also define `\TrackLangQueryOtherEnv{<name>}` to query `LC_ALL`, `<name>`, `LANG`. For example

```

%\TrackLangQueryOtherEnv{LC\_MONETARY}
%

```

Note that there's not much that can be done from within `TEX` for the C or POSIX locale or a locale starting with a slash, so provide a check for them.

`\@tracklang@checklocale`

```

\def\@tracklang@checklocale{%
  \ifx\TrackLangEnv\empty
  \else
    \ifx\TrackLangEnv\@tracklang@locale@posix
      \def\TrackLangEnv{}%
    \else
      \ifx\TrackLangEnv\@tracklang@locale@c
        \def\TrackLangEnv{}%
      \else
        \expandafter\@tracklang@checklocale
          \TrackLangEnv\empty\relax
      \fi
    \fi
  \fi
}

```

`\@tracklang@checklocale` Check for leading slash.

```

\def\@tracklang@checklocale#1#2\relax{%
  \ifx#1/\relax
    \def\TrackLangEnv{}%
  \fi
}

```

`\@tracklang@locale@posix`

```
\def\@tracklang@locale@posix{POSIX}
```

`\@tracklang@locale@c`

```
\def\@tracklang@locale@c{C}
```

```
\ifx\directlua\undefined
```

We can't use Lua, so we'll have to use the shell escape if it's enabled. First determine if the shell escape is available.

`\@tracklang@tryshellescape` No shell escape.

```
\def\@tracklang@tryshellescape#1{%
```

```
\def\TrackLangQueryEnv{%
```

```
\@tracklang@warn{\string\TrackLangQueryEnv\space  
non-operational as shell escape has been disabled}%
```

```
\def\TrackLangEnv{}%
```

```
}%
```

```
\def\TrackLangQueryOtherEnv##1{%
```

```
\@tracklang@warn{\string\TrackLangQueryOtherEnv{##1}\space  
non-operational as shell escape has been disabled}%
```

```
\def\TrackLangEnv{}%
```

```
}%
```

```
}%
```

```
\ifx\pdfshellescape\undefined
```

```
\ifx\shellescape\undefined
```

Can't determine if the shell escape has been enabled.

```
\def\@tracklang@tryshellescape#1{%
```

```
\def\TrackLangQueryEnv{%
```

```
\@tracklang@warn{\string\TrackLangQueryEnv\space  
non-operational as can't determine if the  
shell escape has been enabled. (Consider using  
eTeX or pdfTeX.)}%
```

```
\def\TrackLangEnv{}%
```

```
}%
```

```
\def\TrackLangQueryOtherEnv##1{%
```

```
\@tracklang@warn{\string\TrackLangQueryOtherEnv{##1}\space  
non-operational as can't determine if the  
shell escape has been enabled. (Consider using  
eTeX or pdfTeX.)}%
```

```
\def\TrackLangEnv{}%
```

```
}%
```

```
}%
```

```
\else
```

`\shellescape` is defined. Check no one's been messing around with it and set it to `\relax`.

```
\ifx\shellescape\relax
```

```
\else
```

```

        \ifnum\shellescape=0\relax
        \else
        \def\@tracklang@tryshellescape#1{#1}%
        \fi
    \fi
\fi
\else

```

\pdfshellescape is defined. Check no one's been messing around with it and set it to \relax. (Default no-op already set.)

```
\ifx\pdfshellescape\relax
```

\pdfshellescape has been set to \relax. Is it possible that \shellescape is available?

```

    \ifx\shellescape\undefined
    \else
    \ifx\shellescape\relax
    \else

```

\shellescape is available.

```

        \ifnum\shellescape=0\relax
        \else
        \def\@tracklang@tryshellescape#1{#1}%
        \fi
    \fi
\fi
\else
    \ifnum\pdfshellescape=0\relax
    \else
        \def\@tracklang@tryshellescape#1{#1}%
        \fi
    \fi
\fi

```

Try the shell escape:

```

\@tracklang@tryshellescape
{%
```

\TrackLangQueryEnv

```

\def\TrackLangQueryEnv{%
  \begingroup\endlinechar=-1\relax
  \everyeof{\noexpand}%
  \edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%
    \@tracklang@input|"kpsewhich --var-value LC_ALL" }}\@tracklang@x
  \@tracklang@checklocale
  \ifx\TrackLangEnv\empty
    \begingroup\endlinechar=-1\relax
    \everyeof{\noexpand}%
    \edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%
      \@tracklang@input|"kpsewhich --var-value LANG" }}\@tracklang@x

```

Not sure if a path is likely to occur with `kpsewhich` but check for it just in case.

```
\@tracklang@checklocale
\ifx\TrackLangEnv\empty
```

Try `texosquery` if available.

```
\ifx\TeXOSQueryLocale\undefined
\@tracklang@warn{Locale environment variables
unavailable (tried LC\string_ALL and LANG)}%
\else
\@tracklang@info{Using texosquery to find locale}%
\TeXOSQueryLocale\TrackLangEnv
\ifx\TrackLangEnv\empty
\@tracklang@warn{Locale can't be found
(tried querying LC\string_ALL and LANG variables and
tried using texosquery)}%
\fi
\fi
\fi
\fi
}%
```

`\TrackLangQueryOtherEnv`

```
\def\TrackLangQueryOtherEnv#1{%
\begingroup\endlinechar=-1\relax
\everyeof{\noexpand}%
\edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%
\@tracklang@input|"kpsewhich --var-value LC_ALL" }}\@tracklang@x
\@tracklang@checklocale
\ifx\TrackLangEnv\empty
\begingroup\endlinechar=-1\relax
\everyeof{\noexpand}%
\edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%
\@tracklang@input|"kpsewhich --var-value #1" }}\@tracklang@x
\@tracklang@checklocale
\ifx\TrackLangEnv\empty
\begingroup\endlinechar=-1\relax
\everyeof{\noexpand}%
\edef\@tracklang@x{\endgroup\def\noexpand\TrackLangEnv{%
\@tracklang@input|"kpsewhich --var-value LANG" }}\@tracklang@x
\@tracklang@checklocale
\ifx\TrackLangEnv\empty
```

Try `texosquery` if available.

```
\ifx\TeXOSQueryLocale\undefined
\@tracklang@warn{Locale environment variables unavailable
(tried LC\string_ALL, #1 and LANG)}%
\else
\@tracklang@info{Using texosquery to find locale}%
\TeXOSQueryLocale\TrackLangEnv
\ifx\TrackLangEnv\empty
```



```

        \@tracklang@warn{Locale can't be found
        (tried querying LC\string_ALL, #1 and LANG variables and
        tried using texosquery)}%
    \fi
\fi
\fi
\fi
\fi
}%
}%
\else
\directlua is defined, so we can query it through Lua:

```

```
\TrackLangQueryEnv
```

```

\def\TrackLangQueryEnv{%
\edef\TrackLangEnv{\directlua{
  l = os.getenv("LC_ALL")
  if l == nil or l == "" or l == "C" or l == "POSIX"
    or string.find(l, "^/") then
    l = os.getenv("LANG")
    if l == nil or l == "" or l == "C" or l == "POSIX"
      or string.find(l, "^/") then
      l=os.setlocale(nil)
      if l == nil or l == "C" or l == "POSIX"
        or string.find(l, "^/") then
        l = ""
      end
    end
  end
  tex.print(l)}}%
\ifx\TrackLangEnv\empty

```

Try texosquery if available.

```

\ifx\TeXOSQueryLocale\undefined
\@tracklang@warn{Locale can't be found through Lua
(tried querying LC\string_ALL and LANG variables and
os.setlocale(nil))}%
\else
\TeXOSQueryLocale\TrackLangEnv
\ifx\TrackLangEnv\empty
\@tracklang@warn{Locale can't be found through Lua
(tried querying LC\string_ALL and LANG variables and
os.setlocale(nil) and tried using texosquery)}%
\fi
\fi
\fi
}

```

```
\TrackLangQueryOtherEnv
```

```

\def\TrackLangQueryOtherEnv#1{%
\edef\TrackLangEnv{\directlua{
  l = os.getenv("LC_ALL")
  if l == nil or l == "" or l == "C" or l == "POSIX"
    or string.find(l, "~/") then
    l = os.getenv("#1")
    if l == nil or l == "" or l == "C" or l == "POSIX"
      or string.find(l, "~/") then
      l = os.getenv("LANG")
      if l == nil or l == "" or l == "C" or l == "POSIX"
        or string.find(l, "~/") then
        l=os.setlocale(nil)
        if l == nil or l == "C" or l == "POSIX"
          or string.find(l, "~/") then
          l = ""
        end
      end
    end
  end
  tex.print(l)}}%
\ifx\TrackLangEnv\empty

```

Try texosquery if available.

```

\ifx\TeXOSQueryLocale\undefined
\@tracklang@warn{Locale can't be found through Lua
(tried querying LC\string_ALL, #1 and LANG variables and
os.setlocale(nil))}%
\else
\TeXOSQueryLocale\TrackLangEnv
\ifx\TrackLangEnv\empty
\@tracklang@warn{Locale can't be found through Lua
(tried querying LC\string_ALL, #1 and LANG variables and
os.setlocale(nil) and tried using texosquery)}%
\fi
\fi
\fi
}
\fi

```

Allowed formats for the localisation environment variables are

<iso-lang> [*[_<iso-territory>]*] [*[\langle encoding \rangle]*] [*[\@<modifier \rangle]*]

(where the square brackets above indicate an optional component not that there are literal square brackets.) This is a bit fiddly, so it needs to be broken up into manageable chunks.

`\TrackLangParseFromEnv` Parse `\TrackLangEnv`, if it has been set, and set `\TrackLangEnvLang`, `\TrackLangEnvTerritory` and `\TrackLangEnvCodeSet`. If the information is unavailable, the relevant

commands will be set to empty. Use `\TrackLangFromEnv` to query, parse and set.

```

\def\TrackLangParseFromEnv{%
  \ifx\TrackLangEnv\undefined
    \@tracklang@warn{\string\TrackLangParseFromEnv\space
      non-operational as \string\TrackLangEnv\space hasn't been
      defined}%
    \def\TrackLangEnvLang{}%
    \def\TrackLangEnvTerritory{}%
    \def\TrackLangEnvCodeSet{}%
    \def\TrackLangEnvModifier{}%
  \else
    \ifx\TrackLangEnv\empty
      \@tracklang@warn{\string\TrackLangParseFromEnv\space
        non-operational as \string\TrackLangEnv\space is empty}%
      \def\TrackLangEnvLang{}%
      \def\TrackLangEnvTerritory{}%
      \def\TrackLangEnvCodeSet{}%
      \def\TrackLangEnvModifier{}%
    \else
      \@tracklang@parse@locale{\TrackLangEnv}%
      \let\TrackLangEnvLang\@TrackLangEnvLang
      \let\TrackLangEnvTerritory\@TrackLangEnvTerritory
      \let\TrackLangEnvCodeSet\@TrackLangEnvCodeSet
      \let\TrackLangEnvModifier\@TrackLangEnvModifier
    \fi
  \fi
}

```

`\@tracklang@parse@locale` Parse localisation format.

```
\def\@tracklang@parse@locale#1{%
```

Initialise.

```

  \def\@TrackLangEnvLang{}%
  \def\@TrackLangEnvSubLang{}%
  \def\@TrackLangEnvFirstSubLang{}%
  \def\@TrackLangEnvTerritory{}%
  \def\@TrackLangEnvCodeSet{}%
  \def\@TrackLangEnvVariant{}%
  \def\@TrackLangEnvModifier{}%
  \def\@TrackLangEnvScript{}%
  \def\@TrackLangEnvAdditional{}%

```

Just in case argument is empty or `\relax`.

```

  \expandafter\ifx\expandafter\relax#1\relax
  \else

```

Parse codeset and modifier first.

```

  \expandafter\@tracklang@parse@env
  #1..\relax\@tracklang@end@parse@env\@tracklang@result

```

Parse language and territory.

```
\ifx\@tracklang@result\empty
\else
\expandafter\@tracklang@split@underscoreorhyp\expandafter
{\@tracklang@result}%
\let\@TrackLangEnvLang\@tracklang@split@pre
\let\@TrackLangEnvTerritory\@tracklang@split@post
\fi
\fi
}
```

`\@tracklang@split@underscoreorhyp` Split on either an underscore or a hyphen and store the results in `\@tracklang@split@pre` and `\@tracklang@split@post`

```
\def\@tracklang@split@underscoreorhyp#1{%
```

First try to split on an underscore.

```
\@tracklang@split@underscore{#1}%
```

If the post part was empty, try to split on hyphen instead.

```
\ifx\@tracklang@split@post\empty
\@tracklang@split@hyphen{#1}%
```

If the post part was empty, maybe the underscore has had its category code changed to 12.

```
\ifx\@tracklang@split@post\empty
\@tracklang@split@otherunderscore{#1}%
\fi
\fi
}
```

`\@tracklang@split@underscore` Split on an underscore and store the results in `\@tracklang@split@pre` and `\@tracklang@split@post`. First make sure that the underscore has its normal subscript category code.

```
{
\catcode'\_8\relax
\gdef\@tracklang@split@underscore#1{%
\@@tracklang@split@underscore#1__\relax\@tracklang@end@split@underscore
}
\gdef\@@tracklang@split@underscore#1_#2_#3\@tracklang@end@split@underscore{%
\def\@tracklang@split@pre{#1}%
\ifx\relax#3\relax
\def\@tracklang@split@post{#2}%
\else
\@tracklang@split@underscore@remainder#2_#3%
\fi
}
\gdef\@tracklang@split@underscore@remainder#1__\relax{%
\def\@tracklang@split@post{#1}%
}
}
```

`\tracklang@split@otherunderscore` As above but where underscore has catcode 12.

```
{
  \catcode'\_12\relax
  \gdef\@tracklang@split@otherunderscore#1{%
    \@tracklang@split@otherunderscore#1__\relax\@tracklang@end@split@underscore
  }
  \gdef\@tracklang@split@otherunderscore#1_#2_#3\@tracklang@end@split@underscore{%
    \def\@tracklang@split@pre{#1}%
    \ifx\relax#3\relax
      \def\@tracklang@split@post{#2}%
    \else
      \@tracklang@split@otherunderscore@remainder#2_#3%
    \fi
  }
  \gdef\@tracklang@split@otherunderscore@remainder#1__\relax{%
    \def\@tracklang@split@post{#1}%
  }
}
```

`\@tracklang@split@hyphen` Split on a hyphen and store the results in `\@tracklang@split@pre` and `\@tracklang@split@post`

```
{
  \catcode'\-12\relax
  \gdef\@tracklang@split@hyphen#1{%
    \@tracklang@split@hyphen#1--\relax\@tracklang@end@split@hyphen
  }
  \gdef\@tracklang@split@hyphen#1-#2-#3\@tracklang@end@split@hyphen{%
    \def\@tracklang@split@pre{#1}%
    \ifx\relax#3\relax
      \def\@tracklang@split@post{#2}%
    \else
      \@tracklang@split@hyphen@remainder#2-#3%
    \fi
  }
  \gdef\@tracklang@split@hyphen@remainder#1--\relax{%
    \def\@tracklang@split@post{#1}%
  }
}
```

`\@tracklang@parseenv` Parse for the codeset. The first argument will be the language and (optionally) the territory. So the final argument is the control sequence to use to store the first argument, which can then be split.

```
\gdef\@tracklang@parseenv#1.#2.#3\@tracklang@end@parseenv#4{%
  \def\@TrackLangEnvCodeSet{#2}%
  \def#4{#1}%
  \ifx\@TrackLangEnvCodeSet\empty
    \tracklangparsemod#4%
  \else
    \tracklangparsemod\@TrackLangEnvCodeSet
  \fi
}
```

```

\fi
}

```

`\tracklangparsemod` Extract the modifier from the code set. The `@` is rather awkward as we need to change its category code as it's likely to be set to 12 within `\TrackLangEnv`. So change the category code of `@` to 12, but this means we can't use it in the command name, so although these are private internal commands they don't look like internal commands.)

```

{\catcode'\@=12\relax
 \gdef\tracklangparsemod#1{
  \expandafter\tracklangparseenvatmod#1@\relax\tracklangendparseenvatmod
  \let#1\tracklangtmp
 }%
 \gdef\tracklangparseenvatmod#1@#2@#3\tracklangendparseenvatmod{%
  \def\tracklangtmp{#1}%

```

Need to use `\csname` here as can't use internal commands.

```

 \expandafter\def\csname @TrackLangEnvModifier\endcsname{#2}%

```

Sanitize in case it contains any special characters.

```

 \csname @tracklang@sanitize\expandafter\endcsname
 \csname @TrackLangEnvModifier\endcsname
 }
}

```

4.1 Internal Lists

`\@tracklang@languages` Provide a list to keep track of all the languages.

```

\def\@tracklang@languages{}

```

`\@tracklang@dialects` Provide a list to keep track of all the dialects. Here the “dialect” isn't necessarily an actual dialect but may be a root language or a synonym. It will usually correspond to the language name as specified by the user in the package option.

```

\def\@tracklang@dialects{}

```

`\@tracklang@regions` Provide a list to keep track of all the regions.

```

\def\@tracklang@regions{}

```

```

\@tracklang@ifinlist{<item>}{<list>}{<true
part>}{<false part>}

```

`\@tracklang@ifinlist`

Checks if `<item>` is in `<list>`. (Performs a one-level expansion on `<list>` but no expansion on `<item>`.)

```

\def\@tracklang@ifinlist#1#2#3#4{%
 \def\@tracklang@doifinlist##1,#1,##2\end@tracklang@doifinlist{%
  \def\@before{##1}%
  \def\@after{##2}%

```

```

    }%
    \expandafter\@tracklang@doifinlist\expandafter,#2,#1,\@nil
    \end@tracklang@doifinlist
    \ifx\@after\@tracklang@nnil
not found
    #4%
    \else
found
    #3%
    \fi
}

```

```
\@tracklang@add{\<item>}{\<list cs>}
```

\@tracklang@add

Adds an item to the list given by $\langle list\ cs \rangle$. Does nothing if $\langle item \rangle$ is empty or is already in the list. The $\langle item \rangle$ is fully expanded before being added.

```

\def\@tracklang@add#1#2{%
First find out if the item is empty.
    \edef\@tracklang@element{#1}%
    \ifx\@tracklang@element\empty
Item is empty, so do nothing.
    \else
    \expandafter\@tracklang@ifinlist\expandafter{\@tracklang@element}#2%
    {%
Already in list, so do nothing.
    }%
    {%
Not in list, so add.
    \ifx\empty#2\relax
    \let#2\@tracklang@element
    \else
    \edef#2{#2,\@tracklang@element}%
    \fi
    }%
    \fi
}

```

```
\AddTrackedDialect{\<dialect name>}{\<language name>}
```

\AddTrackedDialect

Add a dialect. (v1.3 switched from unexpanded to expanded def. All labels should be expandable.)

```

\def\AddTrackedDialect#1#2{%
\@tracklang@add{#1}{\@tracklang@dialects}%
\@tracklang@add{#2}{\@tracklang@languages}%

```

Add region to list if available.

```
\@tracklang@enamedef{@tracklang@fromdialect@#1}{#2}%  
\@tracklang@ifundef{@tracklang@todialect@#2}%  
{\@tracklang@enamedef{@tracklang@todialect@#2}{#1}}%  
{%  
  \def\@tracklang@lang{#1}%  
  \expandafter\@tracklang@add\expandafter\@tracklang@lang  
    \csname @tracklang@todialect@#2\endcsname  
}%
```

Provide a convenient way of referencing the last dialect to be tracked.

```
\edef\TrackLangLastTrackedDialect{#1}%  
}
```

`\AddTrackedLanguage`

```
\AddTrackedLanguage{<language name>}
```

Add a dialect.

```
\def\AddTrackedLanguage#1{%  
  \AddTrackedDialect{#1}{#1}%  
}
```

`\AddTrackedRegion`

```
\AddTrackedRegion{<country code>}{<dialect>}
```

Add to tracked region list.

```
\def\AddTrackedRegion#1#2{%  
  \AddTrackedIsoLanguage{3166-1}{#1}{#2}%  
  \@tracklang@add{#1}{\@tracklang@regions}%  
}
```

4.2 Known Languages

`\@tracklang@known@langs` List of known (root) languages (that may or may not be tracked).

```
\def\@tracklang@known@langs{}
```

`\TrackLangNewLanguage`

```
\TrackLangNewLanguage{<language name>}{<639-1  
code>}{<639-2 (T)>}{<639-2 (B)>}{<639-3>}{<3166-1>}{<default  
script>}
```

Identifies a new language that may be tracked. The code arguments may be empty if not available. (v1.3 switched from unexpanded to expanded def. All labels should be expandable.) Most root languages don't have an associated country code as they're spoken in multiple regions. The *<default script>* is the default script identified with the ISO 15924 alpha script code. To reduce overheads, only define 639-3 if there's no 639-1 or 639-2 code.


```

\def\TrackLangNewLanguage#1#2#3#4#5#6#7{%
  \@tracklang@add{#1}{\@tracklang@known@langs}%
  \edef\@tracklang@tmp{#2}%
  \ifx\@tracklang@tmp\empty
  \else
    \@tracklang@enamedef{\@tracklang@knownisolang@#2}{#1}%
    \@tracklang@enamedef{\@tracklang@knowniso@639@1@#1}{#2}%
  \fi
  \edef\@tracklang@tmp{#3}%
  \ifx\@tracklang@tmp\empty
  \else
    \@tracklang@enamedef{\@tracklang@knownisolang@#3}{#1}%
    \@tracklang@enamedef{\@tracklang@knowniso@639@2@#1}{#3}%
  \fi
  \edef\@tracklang@tmp{#4}%
  \ifx\@tracklang@tmp\empty
  \else
    \@tracklang@enamedef{\@tracklang@knowniso@639@2B@#1}{#4}%
  \fi
  \edef\@tracklang@tmp{#5}%
  \ifx\@tracklang@tmp\empty
  \else
    \@tracklang@enamedef{\@tracklang@knownisolang@#5}{#1}%
    \@tracklang@enamedef{\@tracklang@knowniso@639@3@#1}{#5}%
  \fi
  \edef\@tracklang@tmp{#6}%
  \ifx\@tracklang@tmp\empty
  \else
    \@tracklang@enamedef{\@tracklang@knowniso@3166@#1}{#6}%
  \fi
  \edef\@tracklang@tmp{#7}%
  \ifx\@tracklang@tmp\empty
  \else
    \@tracklang@enamedef{\@tracklang@knowniso@script@#1}{#7}%
  \fi
}

```

\TrackLangIfKnownLang{<language>}{<true>}{<false>}

\TrackLangIfKnownLang

Tests if <language> is known (but not necessarily tracked).

```

\def\TrackLangIfKnownLang#1#2#3{%
  \expandafter\@tracklang@ifinlist\expandafter{#1}{\@tracklang@known@langs}%
  {#2}%
  {#3}%
}

```

`\TrackLangIfKnownIsoTwoLetterLang`

```
\TrackLangIfKnownIsoTwoLetterLang{language}{true}  
{false}
```

Checks if the given language has an ISO 639-1 language code (but is not necessarily tracked).

```
\def\TrackLangIfKnownIsoTwoLetterLang#1#2#3{%  
  \@tracklang@ifundef{@tracklang@knowniso@639@1@#1}%  
  {#3}%  
  {#2}%  
}
```

`\TrackLangGetKnownIsoTwoLetterLang`

```
\TrackLangGetKnownIsoTwoLetterLang{language}
```

Gets the ISO 639-1 language code for the given language.

```
\def\TrackLangGetKnownIsoTwoLetterLang#1{%  
  \@tracklang@nameuse{@tracklang@knowniso@639@1@#1}%  
}
```

`\TrackLangIfKnownIsoThreeLetterLang`

```
\TrackLangIfKnownIsoThreeLetterLang{language}{true}  
{false}
```

Checks if the given language has an ISO 639-2 language code (but is not necessarily tracked).

```
\def\TrackLangIfKnownIsoThreeLetterLang#1#2#3{%  
  \@tracklang@ifundef{@tracklang@knowniso@639@2@#1}%  
  {#3}%  
  {#2}%  
}
```

`\TrackLangGetKnownIsoThreeLetterLang`

```
\TrackLangGetKnownIsoThreeLetterLang{language}
```

Gets the ISO 639-2 language code.

```
\def\TrackLangGetKnownIsoThreeLetterLang#1{%  
  \@tracklang@nameuse{@tracklang@knowniso@639@2@#1}%  
}
```

`\TrackLangIfKnownIsoThreeLetterLangB`

```
\TrackLangIfKnownIsoThreeLetterLangB{language}{true}  
{false}
```

Checks if the given language has an ISO 639-2 (B) language code (but is not necessarily tracked).

```

\def\TrackLangIfKnownIsoThreeLetterLangB#1#2#3{%
  \@tracklang@ifundef{@tracklang@knowniso@639@2B@#1}%
  {#3}%
  {#2}%
}

```

`\TrackLangGetKnownIsoThreeLetterLangB{<language>}`

`\TrackLangGetKnownIsoThreeLetterLangB`

Gets the ISO 639-2 (B) language code.

```

\def\TrackLangGetKnownIsoThreeLetterLangB#1{%
  \@tracklang@nameuse{@tracklang@knowniso@639@2B@#1}%
}

```

`\TrackLangIfKnownLangFromIso{<ISO code>}{<true>}{<false>}`

`\TrackLangIfKnownLangFromIso`

Checks if the given ISO language code (639-1 or 639-2 or 639-3) is recognised (but not necessarily tracked).

```

\def\TrackLangIfKnownLangFromIso#1#2#3{%
  \@tracklang@ifundef{@tracklang@knownisolang@#1}%
  {#3}%
  {#2}%
}

```

`\TrackLangGetKnownLangFromIso{<ISO code>}`

`\TrackLangGetKnownLangFromIso`

Gets the root language label from the given ISO code (639-1 or 639-2).

```

\def\TrackLangGetKnownLangFromIso#1{%
  \@tracklang@nameuse{@tracklang@knownisolang@#1}%
}

```

`\TrackLangIfHasKnownCountry{<language>}{<true>}{<false>}`

`\TrackLangIfHasKnownCountry`

Checks if the given language has an ISO 3166-1 country code (but is not necessarily tracked).

```

\def\TrackLangIfHasKnownCountry#1#2#3{%
  \@tracklang@ifundef{@tracklang@knowniso@3166@#1}%
  {#3}%
  {#2}%
}

```

`\TrackLangGetKnownCountry{<language>}`

`\TrackLangGetKnownCountry`

Fetches the ISO 3166-1 country code for the given language.

```
\def\TrackLangGetKnownCountry#1{%  
  \@tracklang@nameuse{@tracklang@knowniso@3166@#1}%  
}
```

```
\TrackLangGetDefaultScript{<language>}
```

\TrackLangGetDefaultScript

Gets the default script for the given root language label.

```
\def\TrackLangGetDefaultScript#1{%  
  \@tracklang@nameuse{@tracklang@knowniso@script@#1}%  
}
```

```
\TrackLangIfHasDefaultScript{<language>}{<true>}{<false>}
```

\TrackLangIfHasDefaultScript

If there's a default script for <language>, do <true> otherwise do <false>.

```
\def\TrackLangIfHasDefaultScript#1#2#3{%  
  \@tracklang@ifundef{@tracklang@knowniso@script@#1}{#3}{#2}%  
}
```

4.3 Mappings

```
\AddTrackedIsoLanguage{<code type>}{<code>}{<language>}
```

\AddTrackedIsoLanguage

Adds a mapping between the given ISO code and language name. There may be multiple mappings from an ISO code to a language name, but only one mapping from a language name to an ISO code. (v1.3 switched from unexpanded to expanded def. All labels should be expandable.)

```
\def\AddTrackedIsoLanguage#1#2#3{%  
  \@tracklang@namedef{@tracklang@#1@isofromlang@#3}{#2}%  
  \@tracklang@ifundef{@tracklang@#1@isotolang@#2}%  
  {\@tracklang@namedef{@tracklang@#1@isotolang@#2}{#3}}%  
  {%  
    \def\@tracklang@lang{#3}%  
    \expandafter\@tracklang@add\expandafter\@tracklang@lang  
    \csname @tracklang@#1@isotolang@#2\endcsname  
  }%  
}
```

```
\TrackedLanguageFromIsoCode{<code type>}{<code>}
```

\TrackedLanguageFromIsoCode

Fetches the language label (or labels) associated with the given code.

```
\def\TrackedLanguageFromIsoCode#1#2{%  
  \@tracklang@nameuse{@tracklang@#1@isotolang@#2}%  
}
```

}

`\TrackedIsoCodeFromLanguage{<code type>}{<language>}`

`\TrackedIsoCodeFromLanguage`

Fetches the code associated with the given language or dialect.

```
\def\TrackedIsoCodeFromLanguage#1#2{%
  \@tracklang@nameuse{@tracklang@#1isofromlang@#2}%
}
```

`\TrackedLanguageFromDialect{<dialect>}`

`\TrackedLanguageFromDialect`

Fetches the language name from the given dialect.

```
\def\TrackedLanguageFromDialect#1{%
  \@tracklang@nameuse{@tracklang@fromdialect@#1}%
}
```

`\TrackedDialectsFromLanguage{<root language label>}`

`\TrackedDialectsFromLanguage`

Fetches the tracked dialects whose language is given by *<root language label>*.

```
\def\TrackedDialectsFromLanguage#1{%
  \@tracklang@nameuse{@tracklang@todialect@#1}%
}
```

`\TwoLetterIsoCountryCode`

```
\def\TwoLetterIsoCountryCode{3166-1}
```

`\TwoLetterIsoLanguageCode`

```
\def\TwoLetterIsoLanguageCode{639-1}
```

`\ThreeLetterIsoLanguageCode`

```
\def\ThreeLetterIsoLanguageCode{639-2}
```

`\ThreeLetterExtIsoLanguageCode`

```
\def\ThreeLetterExtIsoLanguageCode{639-3}
```

`\SetTrackedDialectModifier{<dialect>}{<value>}`

`\SetTrackedDialectModifier`

Set the modifier for *<dialect>*. (For example, old or new.) Arguments are expanded.

```
\def\SetTrackedDialectModifier#1#2{%
  \@tracklang@namedef{@tracklang@modifier@#1}{#2}%
}
```

```
\GetTrackedDialectModifier{<dialect>}
```

\GetTrackedDialectModifier

Get the modifier for <dialect>.

```
\def\GetTrackedDialectModifier#1{%  
  \@tracklang@nameuse{@tracklang@modifier@#1}%  
}
```

```
\IfHasTrackedDialectModifier{<dialect>}{<true>}{<false>}
```

\IfHasTrackedDialectModifier

If there's a modifier for <dialect>, do <true> otherwise do <false>.

```
\def\IfHasTrackedDialectModifier#1#2#3{%  
  \@tracklang@ifundef{@tracklang@modifier@#1}{#3}{#2}%  
}
```

```
\SetTrackedDialectScript{<dialect>}{<value>}
```

\SetTrackedDialectScript

Set the script for <dialect>. (For example, Latn or Cyril.) Arguments are expanded.

```
\def\SetTrackedDialectScript#1#2{%  
  \@tracklang@namedef{@tracklang@script@#1}{#2}%  
}
```

```
\GetTrackedDialectScript{<dialect>}
```

\GetTrackedDialectScript

Get the script for <dialect>.

```
\def\GetTrackedDialectScript#1{%  
  \@tracklang@nameuse{@tracklang@script@#1}%  
}
```

```
\IfHasTrackedDialectScript{<dialect>}{<true>}{<false>}
```

\IfHasTrackedDialectScript

If there's a script for <dialect>, do <true> otherwise do <false>.

```
\def\IfHasTrackedDialectScript#1#2#3{%  
  \@tracklang@ifundef{@tracklang@script@#1}{#3}{#2}%  
}
```

```
\IfTrackedDialectIsScriptCs{<dialect>}{<cs>}{<true>}{<false>}
```

\IfTrackedDialectIsScriptCs

If the given tracked dialect has an associated script and that script code matches the replacement text for the control sequence $\langle cs \rangle$ then do $\langle true \rangle$ otherwise to $\langle false \rangle$. If the tracked dialect doesn't have an associated script then the default script for the root language is tested. The use of a control sequence allows $\backslash ifx$ for the test, which means that this command can expand. The supplementary package `tracklang-script` provides control sequences for known ISO 15924 codes.

```

\def\IfTrackedDialectIsScriptCs#1#2#3#4{%
  \IfHasTrackedDialectScript{#1}%
  {%
    \expandafter\ifx\expandafter#2\csname @tracklang@script@#1\endcsname
    #3%
  \else
    #4%
  \fi
}%
{%
  \TrackLangIfHasDefaultScript{\TrackedLanguageFromDialect{#1}}%
  {%
    \expandafter\ifx\expandafter
      #2\csname @tracklang@knowniso@script@\TrackedLanguageFromDialect{#1}\endcsname
      #3%
    \else
      #4%
    \fi
  }%
  {#4}%
}%
}

```

```
\SetTrackedDialectVariant{<dialect>}{<value>}
```

$\backslash SetTrackedDialectVariant$

Set the modifier for $\langle dialect \rangle$. (For example, old or new.) Arguments are expanded.

```

\def\SetTrackedDialectVariant#1#2{%
  \@tracklang@enamedef{@tracklang@variant@#1}{#2}%
}

```

```
\GetTrackedDialectVariant{<dialect>}
```

$\backslash GetTrackedDialectVariant$

Get the modifier for $\langle dialect \rangle$.

```

\def\GetTrackedDialectVariant#1{%
  \@tracklang@nameuse{@tracklang@variant@#1}%
}

```

<code>\IfHasTrackedDialectVariant</code>	<code>\IfHasTrackedDialectVariant{<dialect>}{<true>}{<false>}</code>
	<p>If there's a modifier for <i><dialect></i>, do <i><true></i> otherwise do <i><false></i>.</p> <pre> \def\IfHasTrackedDialectVariant#1#2#3{% \@tracklang@ifundef{@tracklang@variant@#1}{#3}{#2}% } </pre>
<code>\SetTrackedDialectSubLang</code>	<code>\SetTrackedDialectSubLang{<dialect>}{<value>}</code>
	<p>Set the sublang for <i><dialect></i>. Arguments are expanded.</p> <pre> \def\SetTrackedDialectSubLang#1#2{% \@tracklang@enamedef{@tracklang@sublang@#1}{#2}% } </pre>
<code>\GetTrackedDialectSubLang</code>	<code>\GetTrackedDialectSubLang{<dialect>}</code>
	<p>Get the sublang for <i><dialect></i>.</p> <pre> \def\GetTrackedDialectSubLang#1{% \@tracklang@nameuse{@tracklang@sublang@#1}% } </pre>
<code>\IfHasTrackedDialectSubLang</code>	<code>\IfHasTrackedDialectSubLang{<dialect>}{<true>}{<false>}</code>
	<p>If there's a sublang for <i><dialect></i>, do <i><true></i> otherwise do <i><false></i>.</p> <pre> \def\IfHasTrackedDialectSubLang#1#2#3{% \@tracklang@ifundef{@tracklang@sublang@#1}{#3}{#2}% } </pre>
<code>\SetTrackedDialectAdditional</code>	<code>\SetTrackedDialectAdditional{<dialect>}{<value>}</code>
	<p>Set the extra for <i><dialect></i>. Arguments are expanded.</p> <pre> \def\SetTrackedDialectAdditional#1#2{% \@tracklang@enamedef{@tracklang@extra@#1}{#2}% } </pre>
<code>\GetTrackedDialectAdditional</code>	<code>\GetTrackedDialectAdditional{<dialect>}</code>
	<p>Get the extra for <i><dialect></i>.</p> <pre> \def\GetTrackedDialectAdditional#1{% \@tracklang@nameuse{@tracklang@extra@#1}% } </pre>

HasTrackedDialectAdditional

`\IfHasTrackedDialectAdditional{<dialect>}{<true>}{<false>}`

If there's extra info for <dialect>, do <true> otherwise do <false>.

```
\def\IfHasTrackedDialectAdditional#1#2#3{%
  \@tracklang@ifundef{@tracklang@extra@#1}{#3}{#2}%
}
```

\GetTrackedLanguageTag

`\GetTrackedLanguageTag{<dialect>}`

Get the language tag for <dialect>.

```
\def\GetTrackedLanguageTag#1{%
  \IfTrackedLanguageHasIsoCode{639-1}{\TrackedLanguageFromDialect{#1}}%
  {\TrackedIsoCodeFromLanguage{639-1}{\TrackedLanguageFromDialect{#1}}}%
  {%
    \IfTrackedLanguageHasIsoCode{639-2}{\TrackedLanguageFromDialect{#1}}%
    {\TrackedIsoCodeFromLanguage{639-2}{\TrackedLanguageFromDialect{#1}}}%
    {%
      \IfTrackedLanguageHasIsoCode{639-3}{\TrackedLanguageFromDialect{#1}}%
      {\TrackedIsoCodeFromLanguage{639-3}{\TrackedLanguageFromDialect{#1}}}%
      {und}% undefined
    }%
  }%
  \@tracklang@ifundef{@tracklang@sublang@#1}%
  {}%
  {-\csname @tracklang@sublang@#1\endcsname}%
  \@tracklang@ifundef{@tracklang@script@#1}%
  {}%
  {-\csname @tracklang@script@#1\endcsname}%
  \IfTrackedLanguageHasIsoCode{3166-1}{#1}%
  {-\TrackedIsoCodeFromLanguage{3166-1}{#1}}%
  {}%
  \@tracklang@ifundef{@tracklang@variant@#1}%
  {}%
  {-\csname @tracklang@variant@#1\endcsname}%
  \@tracklang@ifundef{@tracklang@extra@#1}%
  {}%
  {-\csname @tracklang@extra@#1\endcsname}%
}
```

\SetCurrentTrackedDialect

`\SetCurrentTrackedDialect{<dialect>}`

Provided for use by language hooks to establish the current tracked dialect. This command doesn't change \languagenname or hyphenation patterns etc. It just provides convenient commands that can be accessed. The argument may

be a tracklang dialect label or the language hook label from which a tracklang dialect label can be obtained or the root language label.

```
\def\SetCurrentTrackedDialect#1{%
  \edef\CurrentTrackedDialect{#1}%
  \@tracklang@verbose{Setting current tracked dialect '\CurrentTrackedDialect'}%
  \IfTrackedDialect{\CurrentTrackedDialect}%
  {%
    {%
      \@tracklang@verbose{Not a recognised tracklang label}%
```

Has a mapping from this dialect to a tracklang dialect been supplied?

```
\IfHookHasMappingFromTrackedDialect{\CurrentTrackedDialect}%
{%
  \IfTrackedDialect{\GetTrackedDialectFromMapping\CurrentTrackedDialect}%
  {%
    \edef\CurrentTrackedDialect{\GetTrackedDialectFromMapping
      {\CurrentTrackedDialect}}%
    \@tracklang@verbose{Mapping found to tracklang label '\CurrentTrackedDialect'}%
  }%
  {%
```

Has the root language name been supplied?

```
\IfTrackedLanguage{#1}%
{%
  \@tracklang@verbose{Supplied label is a root language.
    Finding last tracked dialect for language '#1'}%
```

Get the last dialect to be tracked with this language.

```
\edef\@tracklang@dialects{\TrackedDialectsFromLanguage{#1}}%
\@tracklang@for\@tracklang@dialect:=\@tracklang@dialects\do{%
  \let\CurrentTrackedDialect\@tracklang@dialect
}%
}%
{%
  \@tracklang@verbose{No tracklang dialect found for label '#1'}%
}%
}%
{%
  \@tracklang@verbose{No mapping found}%
```

Has the root language name been supplied?

```
\IfTrackedLanguage{#1}%
{%
  \@tracklang@verbose{Supplied label is a root language.
    Finding last tracked dialect for language '#1'}%
```

Get the last dialect to be tracked with this language.

```
\edef\@tracklang@dialects{\TrackedDialectsFromLanguage{#1}}%
\@tracklang@for\@tracklang@dialect:=\@tracklang@dialects\do{%
  \let\CurrentTrackedDialect\@tracklang@dialect
```

```

    }%
  }%
  {%
    \@tracklang@verbose{No tracklang dialect found for label '#1'}%
  }%
}%
}%
\IfTrackedDialect{\CurrentTrackedDialect}%
{%
  \edef\CurrentTrackedLanguage{%
    \TrackedLanguageFromDialect{\CurrentTrackedDialect}}%
  \edef\CurrentTrackedDialectModifier{%
    \GetTrackedDialectModifier{\CurrentTrackedDialect}}%
  \edef\CurrentTrackedDialectVariant{%
    \GetTrackedDialectVariant{\CurrentTrackedDialect}}%
}

Get the default script if not set.
\IfHasTrackedDialectScript{\CurrentTrackedDialect}%
{%
  \edef\CurrentTrackedDialectScript{%
    \GetTrackedDialectScript{\CurrentTrackedDialect}}%
}%
{%
  \edef\CurrentTrackedDialectScript{%
    \TrackLangGetDefaultScript\CurrentTrackedLanguage}%
}%
\edef\CurrentTrackedDialectSubLang{%
  \GetTrackedDialectSubLang{\CurrentTrackedDialect}}%
\edef\CurrentTrackedDialectAdditional{%
  \GetTrackedDialectAdditional{\CurrentTrackedDialect}}%
\edef\CurrentTrackedLanguageTag{%
  \GetTrackedLanguageTag{\CurrentTrackedDialect}}%
}

Region code.
\IfTrackedLanguageHasIsoCode{3166-1}{\CurrentTrackedDialect}%
{%
  \edef\CurrentTrackedRegion{%
    \TrackedIsoCodeFromLanguage{3166-1}{\CurrentTrackedDialect}}%
}%
{\def\CurrentTrackedRegion{}}%

Language code.
\IfTrackedLanguageHasIsoCode{639-1}{\CurrentTrackedLanguage}%
{%
  \edef\CurrentTrackedIsoCode{%
    \TrackedIsoCodeFromLanguage{639-1}{\CurrentTrackedLanguage}}%
}%
{%
  \IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
  {%
    \edef\CurrentTrackedIsoCode{%

```

```

        \TrackedIsoCodeFromLanguage{639-2}{\CurrentTrackedLanguage}}%
    }%
    {%
        \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
        {%
            \edef\CurrentTrackedIsoCode{%
                \TrackedIsoCodeFromLanguage{639-3}{\CurrentTrackedLanguage}}%
            }%
            {%
                \def\CurrentTrackedIsoCode{}%
            }%
        }%
    }%
}
\@tracklang@verbose{Current tracked dialect: '\CurrentTrackedDialect'.\MessageBreak
Language: '\CurrentTrackedLanguage'.\MessageBreak
ISO code: '\CurrentTrackedIsoCode'.\MessageBreak
Sub-lang: '\CurrentTrackedDialectSubLang'.\MessageBreak
Modifier: '\CurrentTrackedDialectModifier'.\MessageBreak
Variant: '\CurrentTrackedDialectVariant'.\MessageBreak
Script: '\CurrentTrackedDialectScript'.\MessageBreak
Region: '\CurrentTrackedRegion'.\MessageBreak
Additional: '\CurrentTrackedDialectAdditional'.\MessageBreak
Tag: '\CurrentTrackedLanguageTag'.
}%
}%
{%
    \@tracklang@warn{Unknown dialect label '#1' passed to
        \string\SetCurrentTrackedDialect}%
    \edef\CurrentTrackedLanguage{\language}%
    \def\CurrentTrackedDialectModifier{}%
    \def\CurrentTrackedDialectVariant{}%
    \def\CurrentTrackedDialectScript{}%
    \def\CurrentTrackedDialectSubLang{}%
    \def\CurrentTrackedDialectAdditional{}%
    \def\CurrentTrackedIsoCode{}%
    \def\CurrentTrackedRegion{}%
    \def\CurrentTrackedLanguageTag{\und}%
}%
}

```

`\AddTrackedLanguageIsoCodes{<language>}`

`\AddTrackedLanguageIsoCodes`

Adds the 639-1, 639-2 and 639-3 ISO codes for the given language, which must have previously been declared using `\TrackLangNewLanguage`.

```

\def\AddTrackedLanguageIsoCodes#1{%
    \@tracklang@ifundef{\@tracklang@knowniso@639@1@#1}%
    {}%
    {}%
}

```

```

\AddTrackedIsoLanguage\TwoLetterIsoLanguageCode
  {\csname @tracklang@knowniso@639@1@#1\endcsname}{#1}%
}%
\@tracklang@ifundef{@tracklang@knowniso@639@2@#1}%
{}%
{%
\AddTrackedIsoLanguage\ThreeLetterIsoLanguageCode
  {\csname @tracklang@knowniso@639@2@#1\endcsname}{#1}%
Does it have a different 639-2 (B) code?
\@tracklang@ifundef{@tracklang@knowniso@639@2B@#1}%
{}%
{%
\AddTrackedIsoLanguage{\ThreeLetterIsoLanguageCode-T}%
  {\csname @tracklang@knowniso@639@2@#1\endcsname}{#1}%
\AddTrackedIsoLanguage{\ThreeLetterIsoLanguageCode-B}%
  {\csname @tracklang@knowniso@639@2B@#1\endcsname}{#1}%
}%
}%
\@tracklang@ifundef{@tracklang@knowniso@639@3@#1}%
{}%
{%
\AddTrackedIsoLanguage\ThreeLetterExtIsoLanguageCode
  {\csname @tracklang@knowniso@639@3@#1\endcsname}{#1}%
}%
}

```

`\AddTrackedCountryIsoCode` As above but adds the 3166-1 country code if provided. Most root languages don't have an associated country code as they're spoken in multiple regions. Some of those that do have an associated region code may also be spoken as a minority language elsewhere, so this is separate from the previous command. If a regionless setting is required, use `\TrackLocale` instead of `\TrackPredefinedDialect`.

```

\def\AddTrackedCountryIsoCode#1{%
\@tracklang@ifundef{@tracklang@knowniso@3166@#1}%
{}%
{%
\expandafter \expandafter \expandafter
\AddTrackedRegion
\expandafter \expandafter \expandafter
  {\csname @tracklang@knowniso@3166@#1\endcsname}{#1}%
}%
}

```

4.4 Tracking Languages and Dialects

The commands here are provided to indicate that a language or dialect is active (tracked) in the document.

```
\TrackPredefinedDialect{<dialect label>}
```

\TrackPredefinedDialect

Track a predefined language or dialect.

```
\def\TrackPredefinedDialect#1{%
  \@tracklang@ifundef{@tracklang@add@#1}%
  {%
    \@tracklang@err{Dialect or language ‘#1’ is not predefined}{}%
  }%
  {\@tracklang@nameuse{@tracklang@add@#1}}%
}
```

\@tracklang@hassecondchar Check if second argument is present (non-empty and not \relax).

```
\def\@tracklang@hassecondchar#1#2\@end@tracklang@hassecondchar#3#4{%
  \ifx\relax#2\relax
    #4%
  \else
    #3%
  \fi
}
```

\@tracklang@hasthirdchar Check if third argument is present (non-empty and not \relax).

```
\def\@tracklang@hasthirdchar#1#2#3\@end@tracklang@hasthirdchar#4#5{%
  \ifx\relax#3\relax
    #5%
  \else
    #4%
  \fi
}
```

\@tracklang@hasfourthchar Check if fourth argument is present (non-empty and not \relax).

```
\def\@tracklang@hasfourthchar#1#2#3#4\@end@tracklang@hasfourthchar#5#6{%
  \ifx\relax#4\relax
    #6%
  \else
    #5%
  \fi
}
```

\@tracklang@hasfifthchar Check if fifth argument is present (non-empty and not \relax).

```
\def\@tracklang@hasfifthchar#1#2#3#4#5\@end@tracklang@hasfifthchar#6#7{%
  \ifx\relax#5\relax
    #7%
  \else
    #6%
  \fi
}
```

\@tracklang@hasninthchar Check if ninth argument is present (non-empty and not \relax).

```

\def\@tracklang@hasninthchar#1#2#3#4#5#6#7#8#9\@end@tracklang@hasninthchar{%
  \ifx\relax#9\relax
    \expandafter\@tracklang@secondoftwo
  \else
    \expandafter\@tracklang@firstoftwo
  \fi
}

```

\@tracklang@ifalpha Check if argument a, ..., z or A, ..., Z.

```

\def\@tracklang@ifalpha#1#2#3{%
  \ifx\relax#1\relax
    First argument empty or \relax.
    #3%
  \else
    \ifnum\lccode'#1<'a\relax
      #3%
    \else
      \ifnum\lccode'#1>'z\relax
        #3%
      \else
        Is alpha.
        #2%
      \fi
    \fi
  \fi
}

```

\@tracklang@ifdigit Check if argument is digit (0,...,9).

```

\def\@tracklang@ifdigit#1#2#3{%
  \ifx\relax#1\relax
    First argument empty or \relax.
    #3%
  \else
    \ifnum'#1<'0\relax
      #3%
    \else
      \ifnum'#1>'9\relax
        #3%
      \else
        Is digit.
        #2%
      \fi
    \fi
  \fi
}

```

`\@tracklang@ifalldigits` Check if the argument only consists of digits (no sign).

```
\def\@tracklang@ifalldigits#1{%
\expandafter\ifx\relax#1\relax
\expandafter\@tracklang@secondoftwo
\else
\expandafter\@@tracklang@ifalldigits#1\@tracklang@nnil
\fi
}
```

`\@@tracklang@ifalldigits`

```
\def\@@tracklang@ifalldigits#1{%
\ifx#1\@tracklang@nnil
\def\@tracklang@next{\expandafter\@tracklang@firstoftwo}%
\else
\@tracklang@ifdigit{#1}%
{%
\let\@tracklang@next\@@tracklang@ifalldigits
}%
{%
\def\@tracklang@next##1\@tracklang@nnil{%
\expandafter\@tracklang@secondoftwo}%
}%
\fi
\@tracklang@next
}
```

`\@tracklang@ifalphanumeric` Check if argument is an alphanumeric (0,...,9) or (a,...,z) or (A,...,Z).

```
\def\@tracklang@ifalphanumeric#1#2#3{%
\@tracklang@ifalpha{#1}%
{#2}%
{%
\@tracklang@ifdigit{#1}{#2}{#3}%
}%
}
```

`\TrackLangIfAlphaNumericChar{<tag>}{<true>}{<false>}`

`\TrackLangIfAlphaNumericChar`

Check if the argument is a single alphanumeric character.

```
\def\TrackLangIfAlphaNumericChar#1#2#3{%
\expandafter\ifx\expandafter\relax#1\relax
```

Tag empty or `\relax`.

```
#3%
\else
\expandafter\@tracklang@hassecondchar#1\relax\relax
\@end@tracklang@hassecondchar
{#3}%
{\expandafter\@tracklang@ifalphanumeric#1{#2}{#3}}%
```



```
\fi
}
```

```
\TrackLangIfLanguageTag{<tag>}{<true>}{<false>}
```

\TrackLangIfLanguageTag

Check if the argument is a language tag (two or three letter lower case).

```
\def\TrackLangIfLanguageTag#1#2#3{%
\expandafter\@tracklang@hasthirdchar#1\relax\relax\relax
\@end@tracklang@hasthirdchar
{%
```

Has 3 or more characters.

```
\expandafter\@tracklang@hasfourthchar#1\relax\@end@tracklang@hasfourthchar
{#3}%
{%
```

Has 3 characters. Are they all lower case?

```
\expandafter\@tracklang@iflanguage@iii@tag#1{#2}{#3}%
}%
}%
{%
```

Has less than 3 characters.

```
\expandafter\@tracklang@hassecondchar#1\relax\relax
\@end@tracklang@hassecondchar
{%
```

Has two characters. Are they both lower case?

```
\expandafter\@tracklang@iflanguage@ii@tag#1{#2}{#3}%
}%
{#3}%
}%
}
```

@tracklang@iflanguage@ii@tag

```
\def\@tracklang@iflanguage@ii@tag#1#2#3#4{%
\ifnum\lccode'#1=#1\relax
\ifnum\lccode'#2=#2\relax
#3%
\else
#4%
\fi
\else
#4%
\fi
}
```

@tracklang@iflanguage@iii@tag

```
\def\@tracklang@iflanguage@iii@tag#1#2#3#4#5{%
```

```

\ifnum\lccode'#1='#1\relax
  \ifnum\lccode'#2='#2\relax
    \ifnum\lccode'#3='#3\relax
      #4%
    \else
      #5%
    \fi
  \else
    #5%
  \fi
\else
  #5%
\fi
}

```

```
\TrackLangIfRegionTag{<tag>}{<true>}{<false>}
```

\TrackLangIfRegionTag

Check if the argument is a region tag (two letter upper case or three digit numeric).

```

\def\TrackLangIfRegionTag#1#2#3{%
  \expandafter\@tracklang@hasthirdchar#1\relax\relax\relax
  \@end@tracklang@hasthirdchar
  {%

```

Has 3 or more characters. Is it a three digit numeric code?

```

  \expandafter\@tracklang@hasfourthchar#1\relax\@end@tracklang@hasfourthchar
  {%

```

Has 4 or more characters.

```

    #3%
  }%
  {%

```

Has 3 characters. Are they all digits?

```

    \@tracklang@ifalldigits{#1}{#2}{#3}%
  }%
}%
{%

```

Has less than 3 characters.

```

  \expandafter\@tracklang@hassecondchar#1\relax\relax
  \@end@tracklang@hassecondchar
  {%

```

Has two characters. Are they both upper case?

```

  \expandafter\@tracklang@ifregion@ii@tag#1{#2}{#3}%
  }%
  {#3}%
}%
}

```

`\@tracklang@ifregion@ii@tag`

```
\def\@tracklang@ifregion@ii@tag#1#2#3#4{%
  \ifnum\uccode'#1='#1\relax
    \ifnum\uccode'#2='#2\relax
      #3%
    \else
      #4%
    \fi
  \else
    #4%
  \fi
}
```

`@tracklang@ifregion@iii@tag`

```
\def\@tracklang@ifregion@iii@tag#1#2#3#4#5{%
  \ifnum\uccode'#1='#1\relax
    \ifnum\uccode'#2='#2\relax
      \ifnum\uccode'#3='#3\relax
        #4%
      \else
        #5%
      \fi
    \else
      #5%
    \fi
  \else
    #5%
  \fi
}
```

`\TrackLangIfScriptTag{<tag>}{<true>}{<false>}`

`\TrackLangIfScriptTag`

Check if the argument is a script tag (four letter title case).

```
\def\TrackLangIfScriptTag#1#2#3{%
  \expandafter\@tracklang@hasfifthchar#1\relax\relax\relax\relax\relax
  \@end@tracklang@hasfifthchar
  {#3}%
  {%
```

Has less than 5 characters.

```
\expandafter\@tracklang@hasfourthchar#1\relax\relax\relax\relax
\@end@tracklang@hasfourthchar
{%
```

Has four characters. Are they title case? (First letter upper case, others lower case.)

```
\expandafter\@tracklang@ifscripttag#1{#2}{#3}%
}%
```

```

    {#3}%
  }%
}

```

`\@tracklang@ifscripttag`

```

\def\@tracklang@ifscripttag#1#2#3#4#5#6{%
  \ifnum\uccode'#1=#1\relax
    \ifnum\lccode'#2=#2\relax
      \ifnum\lccode'#3=#3\relax
        \ifnum\lccode'#4=#4\relax
          #5%
        \else
          #6%
        \fi
      \else
        #6%
      \fi
    \else
      #6%
    \fi
  \else
    #6%
  \fi
}

```

`\TrackLangIfVariantTag{<tag>}{<true>}{<false>}`

`\TrackLangIfVariantTag`

Check if the argument is a variant tag.

```

\def\TrackLangIfVariantTag#1#2#3{%
  \expandafter\@tracklang@hasfifthchar#1\relax\relax\relax\relax\relax
  \end@tracklang@hasfifthchar
  {%

```

Has at least 5 characters. Does it have a maximum of 8?

```

  \expandafter\@tracklang@hasninthchar#1\relax\relax\relax\relax\relax
  \relax\relax\relax\relax
  \end@tracklang@hasninthchar
  {#3}%
  {#2}%
  }%
  {%

```

Less than 5 characters.

```

  \expandafter\@tracklang@hasfourthchar#1\relax\relax\relax\relax
  \end@tracklang@hasfourthchar
  {%

```

Has 4 characters.

```

  \expandafter\@tracklang@ifvariant@iv@tag#1{#2}{#3}%

```

```

    }%
    {#3}%
  }%
}

```

`\@tracklang@ifvariant@iv@tag` four character variant starting with a digit.

```

\def\@tracklang@ifvariant@iv@tag#1#2#3#4#5#6{%
  \@tracklang@ifdigit{#1}%
  {#5}
  {#6}%
}

```

`\@tracklang@parse@extlang` `\@TrackLangEnvSubLang`, `\@tracklang@split@pre` and `\tracklang@split@post` should be initialised before use. This assumes the tag is well formed.

```

\def\@tracklang@parse@extlang{%
  \TrackLangIfLanguageTag{\@tracklang@split@pre}
  {%
    \ifx\@TrackLangEnvSubLang\empty
      \let\@TrackLangEnvSubLang\@tracklang@split@pre
      \let\@TrackLangEnvFirstSubLang\@TrackLangEnvSubLang
    \else
      \edef\@TrackLangEnvSubLang{\@TrackLangEnvSubLang-\@tracklang@split@pre}%
    \fi
  }

```

Split again if there's more.

```

\ifx\@tracklang@split@post\empty
\else
  \expandafter\@tracklang@split@underscoreorhyp\expandafter
  {\@tracklang@split@post}%
  \ifx\@tracklang@split@pre\empty
  \else
    \@tracklang@parse@extlang
  \fi
\fi
}%
{ }%
}

```

`\@tracklang@parse@variant` `\@TrackLangEnvVariant`, `\@tracklang@split@pre` and `\tracklang@split@post` should be initialised before use.

```

\def\@tracklang@parse@variant{%
  \TrackLangIfVariantTag{\@tracklang@split@pre}
  {%
    \ifx\@TrackLangEnvVariant\empty
      \let\@TrackLangEnvVariant\@tracklang@split@pre
    \else
      \edef\@TrackLangEnvVariant{\@TrackLangEnvVariant
        -\@tracklang@split@pre}%
    \fi
  }

```

Split again if there's more.

```
\ifx\@tracklang@split@post\empty
\else
\expandafter\@tracklang@split@underscoreorhyp\expandafter
{\@tracklang@split@post}%
\ifx\@tracklang@split@pre\empty
\else
\@tracklang@parse@variant
\fi
\fi
}%
}%
}
```

`\TrackLanguageTag{<tag>}`

`\TrackLanguageTag`

Parse RFC 5646 language tag (assumes regular and well-formed). See also <https://tools.ietf.org/html/rfc5646>. Ensure `<tag>` is fully-expanded. Warn if argument is empty.

```
\def\TrackLanguageTag#1{%
\edef\@tracklang@tag{#1}%
\ifx\@tracklang@tag\empty
\@tracklang@warn{Empty tag in \string\TrackLanguageTag}%
\else
\expandafter\@TrackLanguageTag\expandafter{\@tracklang@tag}%
\fi
}
```

`\@TrackLanguageTag` Argument must be expanded.

```
\def\@TrackLanguageTag#1{%
\@tracklang@ifundef{\@tracklang@add@#1}%
{%
```

Parse language tag.

```
\@tracklang@parselangtag{#1}%
```

Track this information.

```
\@tracklang@track@locale
}%
{%
```

Predefined tag.

```
\@tracklang@nameuse{\@tracklang@add@#1}%
}%
}
```

```
\TrackIfKnownLanguage{<tag>}{<success code>}{<fail code>}
```

\TrackIfKnownLanguage

Like \TrackLanguageTag but does <fail code> if the tag doesn't contain a valid language code. If successful, does <success code> after tracking the language.

```
\def\TrackIfKnownLanguage#1#2#3{%
  \edef\@tracklang@tag{#1}%
  \ifx\@tracklang@tag\empty
    #3%
  \else
    \expandafter\@TrackIfKnownLanguage\expandafter{\@tracklang@tag}{#2}{#3}%
  \fi
}
```

\@TrackIfKnownLanguage Argument must be expanded.

```
\def\@TrackIfKnownLanguage#1#2#3{%
```

First check if it's predefined.

```
\@tracklang@ifundef{\@tracklang@add@#1}%
{%
```

Parse language tag.

```
\@tracklang@parselangtag{#1}%
```

Track this information if \@TrackLangEnvLang is a known ISO language code.

```
\TrackLangIfKnownLangFromIso{\@TrackLangEnvLang}%
{\@tracklang@track@locale#2}{#3}%
}%
{%
```

Predefined tag.

```
\@tracklang@nameuse{\@tracklang@add@#1}%
#2%
}%
}
```

\@tracklang@parse@langtag

```
\def\@tracklang@parselangtag#1{%
```

Initialise.

```
\def\@TrackLangEnvLang{}%
\def\@TrackLangEnvSubLang{}%
\def\@TrackLangEnvFirstSubLang{}%
\def\@TrackLangEnvTerritory{}%
\def\@TrackLangEnvCodeSet{}%
\def\@TrackLangEnvVariant{}%
\def\@TrackLangEnvModifier{}%
\def\@TrackLangEnvScript{}%
\def\@TrackLangEnvAdditional{}%
```

First split to determine language code.

```
\@tracklang@split@underscoreorhyp{#1}%
```

Save the result.

```
\let\@TrackLangEnvLang\@tracklang@split@pre
```

Is there anything else?

```
\ifx\@tracklang@split@post\empty
```

That's it.

```
\else
```

Split again.

```
\expandafter\@tracklang@split@underscoreorhyp\expandafter  
{\@tracklang@split@post}%
```

Is this an extension to the language tag?

```
\@tracklang@parse@extlang
```

Does this fit the format for a script?

```
\TrackLangIfScriptTag{\@tracklang@split@pre}%  
{%
```

Found script.

```
\let\@TrackLangEnvScript\@tracklang@split@pre
```

Split again if there's more.

```
\ifx\@tracklang@split@post\empty
```

```
\else
```

```
\expandafter\@tracklang@split@underscoreorhyp\expandafter  
{\@tracklang@split@post}%
```

```
\fi
```

```
}%
```

```
{}%
```

Does this fit the format for a region?

```
\TrackLangIfRegionTag{\@tracklang@split@pre}%  
{%
```

Found region. Is it a 2 letter alpha or a 3 digit numeric code?

```
\expandafter\@tracklang@hasthirdchar\@tracklang@split@pre  
\relax\relax\relax  
\@end@tracklang@hasthirdchar  
{%
```

Is three digit numeric code. We need the mappings. Has `tracklang-region-codes.tex` been loaded?

```
\ifx\TrackLangIfKnownNumericRegion\undefined  
\@tracklang@inputfile{tracklang-region-codes.tex}%  
\fi  
\TrackLangIfKnownNumericRegion{\@tracklang@split@pre}%  
{%  
\edef\@TrackLangEnvTerritory{%  
\TrackLangNumericToAlphaIIRegion{\@tracklang@split@pre}%  
}%  
}%
```



```

    {%
      \let\@TrackLangEnvTerritory\@tracklang@split@pre
      \@tracklang@warn{Unrecognised numeric region code
        '\@tracklang@split@pre'}%
    }%
  }%
  {%

```

Is two letter alpha code.

```

    \let\@TrackLangEnvTerritory\@tracklang@split@pre
  }%
  \expandafter\@tracklang@split@underscoreorhyps\expandafter
    {\@tracklang@split@post}%
  }%
  {}%

```

Parse for variant.

```

    \@tracklang@parse@variant

```

Anything left can go in additional.

```

    \let\@TrackLangEnvAdditional\@tracklang@split@post
  \fi
  }%

```

input@extra@region@filelist

```

\def\@tracklang@extra@region@filelist{}

```

TrackLangAddExtraRegionFile Add a file name to the list of extra region code files that should be input by tracklang-regions-codes.tex

```

\def\TrackLangAddExtraRegionFile#1{%
  \ifx\TrackLangRegionMap\undefined
  \else
    tracklang-region-codes.tex has already been loaded so input the file now.
    \@tracklang@inputfile{#1}%
  \fi
  \@tracklang@add{#1}{\@tracklang@extra@region@filelist}%
}

```

ng@input@extra@region@files Iterate through list of extra region files to allow other packages to define new regions.

```

\def\@tracklang@input@extra@region@files{%
  \@tracklang@for\@tracklang@currfile:=\@tracklang@extra@region@filelist\do
  {%
    \@tracklang@inputfile{\@tracklang@currfile}%
  }%
}

```

input@extra@script@filelist

```

\def\@tracklang@extra@script@filelist{}

```

`\TrackLangAddExtraScriptFile` Add the given file name to the list of files that should be automatically loaded by `tracklang-scripts.tex`

```

\def\TrackLangAddExtraScriptFile#1{%
  \ifx\TrackLangScriptMap\undefined
  \else
tracklang-scripts.tex has already been loaded so input the file now.
    \@tracklang@inputfile{#1}%
  \fi
  \@tracklang@add{#1}{\@tracklang@extra@script@filelist}%
}

```

`\tracklang@input@extra@script@files` Iterate through list of extra script files to allow other packages to define new scripts.

```

\def\@tracklang@input@extra@script@files{%
  \@tracklang@for\@tracklang@currfile:=\@tracklang@extra@script@filelist\do
  {%
    \@tracklang@inputfile{\@tracklang@currfile}%
  }%
}

```

`\GetTrackedDialectFromLanguageTag{<tag>}{<cs>}`

`\GetTrackedDialectFromLanguageTag`

Find the tracked dialect that matches the given language tag and stores the dialect label in `<cs>`. If no match found, `<cs>` will be empty. Just tests the root language, script, variant, sub-language and region. Doesn't check the additional information. As from v1.3.6, this sets `\TrackedDialectClosestSubMatch` to the closest sub-match.

```

\def\GetTrackedDialectFromLanguageTag#1#2{%

```

Initialise default values (in case of no match).

```

  \def#2{%
  \def\TrackedDialectClosestSubMatch{%
  \@tracklang@parselangtag{#1}%
  \edef\@tracklang@dialect{%
    \@TrackLangEnvLang
    \@TrackLangEnvSubLang
    \@TrackLangEnvScript
    \@TrackLangEnvTerritory
    \@TrackLangEnvModifier
    \@TrackLangEnvVariant}%

```

Has this dialect label been tracked?

```

  \IfTrackedDialect{\@tracklang@dialect}%
  {%

```

Found it. All done.

```

    \let#2\@tracklang@dialect
  }%
  {%

```

Get the root language label.

```
\edef\@tracklang@lang{\TrackLangGetKnownLangFromIso\@TrackLangEnvLang}%
```

Get the default script for this language.

```
\edef\@tracklang@defscript{\TrackLangGetDefaultScript\@tracklang@lang}%
```

Keep track of best match.

```
\def\@tracklang@bestmatch{0}%
```

Get the list of tracked dialects for this language.

```
\edef\@tracklang@dialects{\TrackedDialectsFromLanguage\@tracklang@lang}%
```

For each dialect in this list, check if it matches.

```
\@tracklang@for\@tracklang@dialect:=\@tracklang@dialects\do{%
```

Does the script match? (Initialise to no.)

```
\def\@tracklang@currentmatch{0}%
```

```
\edef\@tracklang@tmp{%
```

```
\GetTrackedDialectScript{\@tracklang@dialect}}%
```

```
\ifx\@tracklang@tmp\@TrackLangEnvScript
```

Script matches.

```
\def\@tracklang@currentmatch{1}%
```

```
\else
```

Script doesn't match. If no script has been provided, does this dialect's script match the default for this language?

```
\ifx\@TrackLangEnvScript\empty
```

```
\ifx\@tracklang@tmp\@tracklang@defscript
```

Default script matches.

```
\def\@tracklang@currentmatch{1}%
```

```
\fi
```

```
\fi
```

```
\fi
```

Does the sub-language match?

```
\edef\@tracklang@tmp{%
```

```
\GetTrackedDialectSubLang{\@tracklang@dialect}}%
```

```
\ifx\@tracklang@tmp\@TrackLangEnvSubLang
```

Sub-language matches.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 1}%
```

```
\else
```

Sub-language doesn't match.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 0}%
```

```
\fi
```

Does the variant match?

```
\edef\@tracklang@tmp{%
```

```
\GetTrackedDialectVariant{\@tracklang@dialect}}%
```

```
\ifx\@tracklang@tmp\@TrackLangEnvVariant
```

Variant matches.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 1}%  
\else
```

Variant doesn't match.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 0}%  
\fi
```

Does the region match?

```
\edef\@tracklang@tmp{%  
\TrackedIsoCodeFromLanguage{3166-1}{\@tracklang@dialect}}%  
\ifx\@tracklang@tmp\@TrackLangEnvTerritory
```

Region matches.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 1}%  
\else
```

Region doesn't match.

```
\edef\@tracklang@currentmatch{\@tracklang@currentmatch 0}%  
\fi
```

Do all four match?

```
\ifx\@tracklang@currentmatch\@tracklang@fullmatch
```

Found it.

```
\let#2\@tracklang@dialect  
\else
```

Not a complete match. Is this the best match so far?

```
\ifnum\@tracklang@currentmatch>\@tracklang@bestmatch\relax  
\let\TrackedDialectClosestSubMatch\@tracklang@dialect  
\let\@tracklang@bestmatch\@tracklang@currentmatch  
\fi  
\fi  
}%  
}%  
}
```

`\@tracklang@fullmatch` (Used to identify a full match for script, sub-language, variant and region.)

```
\def\@tracklang@fullmatch{1111}
```

`\TrackLangFromEnv` This command performs the following steps: query environment variable (if `\TrackLangEnv` not already set), parse `\TrackLangEnv` (if it has been set), and add the dialect (if recognised).

Note that this works slightly differently from just using `\TrackLangQueryEnv` followed by `\TrackLangParseFromEnv` and `\TrackPredefinedDialect`.

```
\def\TrackLangFromEnv{%
```

Initialise.

```
\def\TrackLangEnvLang{}%  
\def\TrackLangEnvTerritory{}%  
\def\TrackLangEnvCodeSet{}%  
\def\TrackLangEnvModifier{}%
```

If `\TrackQueryEnv` is empty, assume `\TrackQueryEnv` has already been attempted but failed, so don't bother retrying.

```
\ifx\TrackLangEnv\undefined
  \TrackLangQueryEnv
\fi
\ifx\TrackLangEnv\empty
  \@tracklang@warn{\string\TrackLangFromEnv\space
    non-operational as \string\TrackLangEnv\space is empty}%
\else
```

At this point `\TrackLangEnv` shouldn't be undefined (if `\TrackLangQueryEnv` fails it should define `\TrackLangEnv` to be empty), but check in case something unexpected has happened.

```
\ifx\TrackLangEnv\undefined
  \@tracklang@warn{\string\TrackLangFromEnv\space
    non-operational as \string\TrackLangEnv\space hasn't been
    defined}%
\else
```

Parse and track.

```
\@tracklang@parse@track@locale{\TrackLangEnv}%
\let\TrackLangEnvLang\@TrackLangEnvLang
\let\TrackLangEnvTerritory\@TrackLangEnvTerritory
\let\TrackLangEnvCodeSet\@TrackLangEnvCodeSet
\let\TrackLangEnvModifier\@TrackLangEnvModifier
\fi
\fi
}
```

```
\TrackLocale{<locale>}
```

`\TrackLocale`

Track the dialect identified by the given locale. The argument may either be a predefined language/dialect or in the same format as `\TrackLangEnv`.

```
\def\TrackLocale#1{%
```

Is the argument a recognised dialect?

```
\@tracklang@ifundef{\@tracklang@add@#1}%
{%
  \@tracklang@parse@track@locale{#1}%
}%
{%
  \@tracklang@nameuse{\@tracklang@add@#1}%
}%
}
```

`\@tracklang@parse@track@locale` Parse localisation format and track.

```
\def\@tracklang@parse@track@locale#1{%
  \@tracklang@parse@locale{#1}%
```

```

    \@tracklang@track@locale
  }

\@tracklang@track@locale
\def\@tracklang@track@locale{%
Is the language code known?
\TrackLangIfKnownLangFromIso{\@TrackLangEnvLang}
{%
  \edef\@tracklang@lang{\TrackLangGetKnownLangFromIso\@TrackLangEnvLang}%
  \let\@tracklang@dialect\@TrackLangEnvLang
  \ifx\@TrackLangEnvSubLang\empty
  \else
    \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvSubLang}%
  \fi
  \ifx\@TrackLangEnvScript\empty
  \else
    \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvScript}%
  \fi
  \ifx\@TrackLangEnvTerritory\empty
  \else
    \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvTerritory}%
  \fi
  \ifx\@TrackLangEnvModifier\empty
  \else
    \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvModifier}%
  \fi
  \ifx\@TrackLangEnvVariant\empty
  \else
    \edef\@tracklang@dialect{\@tracklang@dialect-\@TrackLangEnvVariant}%
  \fi
Language code is recognised. Is the dialect label recognised?
\@tracklang@ifundef{\@tracklang@add@\@tracklang@dialect}%
{%
Not a recognised dialect. Form new dialect name (without hyphen).
  \edef\@tracklang@dialect{%
    \@TrackLangEnvLang
    \@TrackLangEnvSubLang
    \@TrackLangEnvScript
    \@TrackLangEnvTerritory
    \@TrackLangEnvModifier
    \@TrackLangEnvVariant}%
Add this new dialect.
  \AddTrackedDialect{\@tracklang@dialect}{\@tracklang@lang}%
  \AddTrackedLanguageIsoCodes{\@tracklang@lang}%
Is there a sub-language tag?
  \ifx\@TrackLangEnvFirstSubLang\empty
  \else

```

```

        \expandafter\AddTrackedIsoLanguage
        \expandafter\ThreeLetterExtIsoLanguageCode
        \expandafter{\@TrackLangEnvFirstSubLang}%
        {\@tracklang@dialect}%
    \fi
}%
{%
```

Dialect is recognised.

```

        \csname @tracklang@add@\@tracklang@dialect\endcsname
    }%
}%
{%
```

Unknown language code.

```

\@tracklang@warn{Unknown language code ‘\@TrackLangEnvLang’}%
\edef\@tracklang@dialect{%
    \@TrackLangEnvLang
    \@TrackLangEnvSubLang
    \@TrackLangEnvScript
    \@TrackLangEnvTerritory
    \@TrackLangEnvModifier
    \@TrackLangEnvVariant}%
\AddTrackedDialect{\@tracklang@dialect}{\@TrackLangEnvLang}%

```

Determine if the language code is a two or three letter code.

```

\expandafter\@tracklang@hasthirdchar
    \@TrackLangEnvLang\relax\relax\relax\@end@tracklang@hasthirdchar
}%
{%
```

639-2 code. Track it.

```

    \AddTrackedIsoLanguage{639-2}{\@TrackLangEnvLang}{undetermined}%
}%
{%
```

639-1 code. Track it.

```

    \AddTrackedIsoLanguage{639-1}{\@TrackLangEnvLang}{undetermined}%
}%
}%

```

Add the territory if provided. (The territory may not have been defined by the dialect option.)

```

    \ifx\@TrackLangEnvTerritory\empty
    \else
        \expandafter\AddTrackedRegion\expandafter
        {\@TrackLangEnvTerritory}%
        {\@tracklang@dialect}%
    \fi

```

If a modifier was provided, add that.

```

    \ifx\@TrackLangEnvModifier\empty
    \else

```

```

        \SetTrackedDialectModifier{\@tracklang@dialect}{\@TrackLangEnvModifier}%
    \fi
If a variant was provided, add that.
    \ifx\@TrackLangEnvVariant\empty
    \else
        \SetTrackedDialectVariant{\@tracklang@dialect}{\@TrackLangEnvVariant}%
    \fi
If a script was provided, add that.
    \ifx\@TrackLangEnvScript\empty
    \else
        \SetTrackedDialectScript{\@tracklang@dialect}{\@TrackLangEnvScript}%
    \fi
If a language extension was provided, add that.
    \ifx\@TrackLangEnvSubLang\empty
    \else
        \SetTrackedDialectSubLang{\@tracklang@dialect}{\@TrackLangEnvSubLang}%
    \fi
If additional information was provided, add that.
    \ifx\@TrackLangEnvAdditional\empty
    \else
        \SetTrackedDialectAdditional{\@tracklang@dialect}{\@TrackLangEnvAdditional}%
    \fi
}

```

4.5 Predefined Root Languages

The ISO 639-1 and 639-2 codes are used to map the root language name to the ISO language code. The 3166-1 codes are used to map the dialect/variant to the ISO country code. The country code is omitted if ambiguous (for example, the language is spoken in multiple countries). Languages that have a country code may be spoken as a minority language in another region. In this case, `\TrackLocale` should be used instead to set the country code as appropriate. Some “dialects” are just synonyms for a language name, such as “francais” or “frenchb”. These are defined in §4.6. Some of the languages have two ISO 639-2 codes designated as “B” (bibliographic) or “T” (terminology). In these cases the terminology code is used as the primary 639-2 code. The extra “B” and “T” codes are only provided if they are different.

`\@tracklang@declareoption` Provide a hook to declare a predefined setting as a package option. This is defined by `tracklang.sty` before loading `tracklang.tex` but if this file isn’t loaded through `tracklang.sty` provide a definition that ignores its argument if not already defined.

```

\ifx\@tracklang@declareoption\undefined
\def\@tracklang@declareoption#1{}
\fi

```


`\TrackLangProvidePredefinedLanguage` Set up a language label for use with `\TrackPredefinedDialect`. Note that this doesn't check if already defined.

```
\def\TrackLangProvidePredefinedLanguage#1{%
  \@tracklang@namedef{@tracklang@add@#1}{%
    \AddTrackedLanguage{#1}%
    \AddTrackedLanguageIsoCodes{#1}%
    \AddTrackedCountryIsoCode{#1}%
  }%
}
```

```
\TrackLangDeclareLanguageOption{<language name>}{<639-1
code>}{<639-2 (T)>}{<639-2 (B)>}{<639-3>}{<3166-1>}{<default
script>}
```

`\TrackLangDeclareLanguageOption`

Define a new root language that's declared as an option. The language name must be expanded before use. The default script is the ISO 15924 alpha script code. (Some languages may be written in multiple scripts. Leave empty if not obvious default.)

```
\def\TrackLangDeclareLanguageOption#1#2#3#4#5#6#7{%
  \@tracklang@ifundef{@tracklang@add@#1}%
  {%
    \TrackLangNewLanguage{#1}{#2}{#3}{#4}{#5}{#6}{#7}%
    \TrackLangProvidePredefinedLanguage{#1}%
    \@tracklang@declareoption{#1}%
  }%
  {%
    \@tracklang@err{language option '#1' has already been defined}{}%
  }%
}
```

`\@tracklang@add@abkhaz`

```
\TrackLangDeclareLanguageOption{abkhaz}{ab}{abk}{}{}{Cyr1}
```

`\@tracklang@add@afar`

```
\TrackLangDeclareLanguageOption{afar}{aa}{aar}{}{}{Latn}
```

`\@tracklang@add@afrikaans`

```
\TrackLangDeclareLanguageOption{afrikaans}{af}{afz}{}{}{Latn}
```

`\@tracklang@add@akan`

```
\TrackLangDeclareLanguageOption{akan}{ak}{aka}{}{}{Latn}
```

`\@tracklang@add@albanian`

```
\TrackLangDeclareLanguageOption{albanian}{sq}{sqi}{alb}{}{}{Latn}
```

`\@tracklang@add@amharic`

```
\TrackLangDeclareLanguageOption{amharic}{am}{amh}{}{}{ET}{Ethi}
```

```

\@tracklang@add@anglosaxon
    \TrackLangDeclareLanguageOption{anglosaxon}{ang}{}{}{Runr}

\@tracklang@add@apache
    \TrackLangDeclareLanguageOption{apache}{apa}{}{}{Latn}

\@tracklang@add@arabic
    \TrackLangDeclareLanguageOption{arabic}{ar}{ara}{}{}{Arab}

\@tracklang@add@aragonese
    \TrackLangDeclareLanguageOption{aragonese}{an}{arg}{}{}{ES}{Latn}

\@tracklang@add@armenian
    \TrackLangDeclareLanguageOption{armenian}{hy}{hye}{arm}{}{}{Armn}

\@tracklang@add@assamese
    \TrackLangDeclareLanguageOption{assamese}{as}{asm}{}{}{}{Beng}

\@tracklang@add@asturian
    \TrackLangDeclareLanguageOption{asturian}{}{ast}{}{}{}{Latn}

\@tracklang@add@avaric
    \TrackLangDeclareLanguageOption{avaric}{av}{ava}{}{}{}{Cyr1}

\@tracklang@add@avestan
    \TrackLangDeclareLanguageOption{avestan}{ae}{ave}{}{}{}{Avst}

\@tracklang@add@aymara
    \TrackLangDeclareLanguageOption{aymara}{ay}{aym}{}{}{}{Latn}

\@tracklang@add@azerbaijani The default script is dependent on the region, but this is a regionless definition
    so using Latin as the default here as Azerbaijani alphabet is a Latin alphabet.
    Other countries may be using a different script, such as Cyrillic in Russia.
    \TrackLangDeclareLanguageOption{azerbaijani}{az}{aze}{}{}{}{Latn}

\@tracklang@add@bahasai
    \TrackLangDeclareLanguageOption{bahasai}{id}{ind}{}{}{IN}{Latn}

\@tracklang@add@bahasam
    \TrackLangDeclareLanguageOption{bahasam}{ms}{msa}{may}{}{MY}{Latn}

\@tracklang@add@bambara
    \TrackLangDeclareLanguageOption{bambara}{bm}{bam}{}{}{ML}{Latn}

\@tracklang@add@bashkir
    \TrackLangDeclareLanguageOption{bashkir}{ba}{bak}{}{}{}{Cyr1}

```

`\@tracklang@add@basque`
`\TrackLangDeclareLanguageOption{basque}{eu}{eus}{baq}{}{}{Latn}`

`\@tracklang@add@belarusian`
`\TrackLangDeclareLanguageOption{belarusian}{be}{bel}{}{}{Cyr1}`

`\@tracklang@add@bengali`
`\TrackLangDeclareLanguageOption{bengali}{bn}{ben}{}{}{Beng}`

`\@tracklang@add@berber` No default. Could be Tifinagh, Latin or Arabic.
`\TrackLangDeclareLanguageOption{berber}{}{ber}{}{}{}`

`\@tracklang@add@bihari` No clear default.
`\TrackLangDeclareLanguageOption{bihari}{bh}{bih}{}{}{}`

`\@tracklang@add@bislama`
`\TrackLangDeclareLanguageOption{bislama}{bi}{bis}{}{}{VU}{Latn}`

`\@tracklang@add@bokmal`
`\TrackLangDeclareLanguageOption{bokmal}{nb}{nob}{}{}{NO}{Latn}`

`\@tracklang@add@bosnian`
`\TrackLangDeclareLanguageOption{bosnian}{bs}{bos}{}{}{Latn}`

`\@tracklang@add@breton`
`\TrackLangDeclareLanguageOption{breton}{br}{bre}{}{}{FR}{Latn}`

`\@tracklang@add@bulgarian`
`\TrackLangDeclareLanguageOption{bulgarian}{bg}{bul}{}{}{Cyr1}`

`\@tracklang@add@burmese`
`\TrackLangDeclareLanguageOption{burmese}{my}{mya}{bur}{}{}{Mymr}`

`\@tracklang@add@catalan`
`\TrackLangDeclareLanguageOption{catalan}{ca}{cat}{}{}{Latn}`

`\@tracklang@add@chamorro`
`\TrackLangDeclareLanguageOption{chamorro}{ch}{cha}{}{}{Latn}`

`\@tracklang@add@chechen`
`\TrackLangDeclareLanguageOption{chechen}{ce}{che}{}{}{Cyr1}`

`\@tracklang@add@chichewa`
`\TrackLangDeclareLanguageOption{chichewa}{ny}{nya}{}{}{Latn}`

`\@tracklang@add@chinese`
`\TrackLangDeclareLanguageOption{chinese}{zh}{zho}{chi}{}{}{Hans}`

```

\tracklang@add@churchslavonic
\TrackLangDeclareLanguageOption{churchslavonic}{cu}{chu}{}{}{Glag}

\@tracklang@add@chuvash
\TrackLangDeclareLanguageOption{chuvash}{cv}{chv}{}{}{RU}{Cyr1}

\@tracklang@add@coptic
\TrackLangDeclareLanguageOption{coptic}{}{cop}{}{}{Copt}

\@tracklang@add@cornish
\TrackLangDeclareLanguageOption{cornish}{kw}{cor}{}{}{GB}{Latn}

\@tracklang@add@corsican
\TrackLangDeclareLanguageOption{corsican}{co}{cos}{}{}{Latn}

\@tracklang@add@cree
\TrackLangDeclareLanguageOption{cree}{cr}{cre}{}{}{Cans}

\@tracklang@add@croatian
\TrackLangDeclareLanguageOption{croatian}{hr}{hrv}{}{}{Latn}

\@tracklang@add@czech
\TrackLangDeclareLanguageOption{czech}{cs}{ces}{cze}{}{}{Latn}

\@tracklang@add@danish
\TrackLangDeclareLanguageOption{danish}{da}{dan}{}{}{Latn}

\@tracklang@add@divehi
\TrackLangDeclareLanguageOption{divehi}{dv}{div}{}{}{MV}{Thaa}

\@tracklang@add@dutch
\TrackLangDeclareLanguageOption{dutch}{nl}{nld}{dut}{}{}{Latn}

\@tracklang@add@dzongkha
\TrackLangDeclareLanguageOption{dzongkha}{dz}{dzo}{}{}{BT}{Tibt}

\tracklang@add@easternpunjabi
\TrackLangDeclareLanguageOption{easternpunjabi}{pa}{pan}{}{}{IN}{Guru}

\@tracklang@add@english
\TrackLangDeclareLanguageOption{english}{en}{eng}{}{}{Latn}

\@tracklang@add@esperanto
\TrackLangDeclareLanguageOption{esperanto}{eo}{epo}{}{}{Latn}

\@tracklang@add@estonian
\TrackLangDeclareLanguageOption{estonian}{et}{est}{}{}{Latn}

```

```

\@tracklang@add@ewe
\TrackLangDeclareLanguageOption{ewe}{ee}{ewe}{}{}{Latn}

\@tracklang@add@faroese
\TrackLangDeclareLanguageOption{faroese}{fo}{fao}{}{}{Latn}

\@tracklang@add@farsi
\TrackLangDeclareLanguageOption{farsi}{fa}{fas}{per}{}{}{Arab}

\@tracklang@add@fijian
\TrackLangDeclareLanguageOption{fijian}{fj}{fij}{}{}{FJ}{Latn}

\@tracklang@add@finnish
\TrackLangDeclareLanguageOption{finnish}{fi}{fin}{}{}{Latn}

\@tracklang@add@french
\TrackLangDeclareLanguageOption{french}{fr}{fra}{fre}{}{}{Latn}

\@tracklang@add@friulan
\TrackLangDeclareLanguageOption{friulan}{}{fur}{}{}{IT}{Latn}

\@tracklang@add@fula No default. Could be Latin or Arabic.
\TrackLangDeclareLanguageOption{fula}{ff}{ful}{}{}{}

\@tracklang@add@galician
\TrackLangDeclareLanguageOption{galician}{gl}{glg}{}{}{Latn}

\@tracklang@add@ganda
\TrackLangDeclareLanguageOption{ganda}{lg}{lug}{}{}{UG}{Latn}

\@tracklang@add@georgian
\TrackLangDeclareLanguageOption{georgian}{ka}{kat}{geo}{}{}{Geor}

\@tracklang@add@german
\TrackLangDeclareLanguageOption{german}{de}{deu}{ger}{}{}{Latn}

\@tracklang@add@greek
\TrackLangDeclareLanguageOption{greek}{el}{ell}{gre}{}{}{Grek}

\@tracklang@add@guarani
\TrackLangDeclareLanguageOption{guarani}{gn}{grn}{}{}{Latn}

\@tracklang@add@gujarati
\TrackLangDeclareLanguageOption{gujarati}{gu}{guj}{}{}{Gujr}

\@tracklang@add@haitian
\TrackLangDeclareLanguageOption{haitian}{ht}{hat}{}{}{HT}{Latn}

```

```

\@tracklang@add@hausa
\TrackLangDeclareLanguageOption{hausa}{ha}{hau}{}{}{Latn}

\@tracklang@add@hebrew
\TrackLangDeclareLanguageOption{hebrew}{he}{heb}{}{}{Hebr}

\@tracklang@add@herero
\TrackLangDeclareLanguageOption{herero}{hz}{her}{}{}{Latn}

\@tracklang@add@hindi
\TrackLangDeclareLanguageOption{hindi}{hi}{hin}{}{}{Deva}

\@tracklang@add@hirimotu
\TrackLangDeclareLanguageOption{hirimotu}{ho}{hmo}{}{}{PG}{Latn}

\@tracklang@add@icelandic
\TrackLangDeclareLanguageOption{icelandic}{is}{isl}{ice}{}{IS}{Latn}

\@tracklang@add@ido
\TrackLangDeclareLanguageOption{ido}{io}{ido}{}{}{Latn}

\@tracklang@add@igbo
\TrackLangDeclareLanguageOption{igbo}{ig}{ibo}{}{}{Latn}

\@tracklang@add@interlingua
\TrackLangDeclareLanguageOption{interlingua}{ia}{ina}{}{}{Latn}

\@tracklang@add@interlingue
\TrackLangDeclareLanguageOption{interlingue}{ie}{ile}{}{}{Latn}

\@tracklang@add@inuktitut
\TrackLangDeclareLanguageOption{inuktitut}{iu}{iku}{}{}{Cans}

\@tracklang@add@inupiaq
\TrackLangDeclareLanguageOption{inupiaq}{ik}{ipk}{}{}{Latn}

\@tracklang@add@irish
\TrackLangDeclareLanguageOption{irish}{ga}{gle}{}{}{Latn}

\@tracklang@add@italian
\TrackLangDeclareLanguageOption{italian}{it}{ita}{}{}{Latn}

\@tracklang@add@japanese
\TrackLangDeclareLanguageOption{japanese}{ja}{jpn}{}{}{Hani}

\@tracklang@add@javanese
\TrackLangDeclareLanguageOption{javanese}{jv}{jav}{}{}{Latn}

```

`\@tracklang@add@kalaallisut`
`\TrackLangDeclareLanguageOption{kalaallisut}{kl}{kal}{-}{-}{Latn}`

`\@tracklang@add@kannada`
`\TrackLangDeclareLanguageOption{kannada}{kn}{kan}{-}{-}{IN}{Knda}`

`\@tracklang@add@kanuri`
`\TrackLangDeclareLanguageOption{kanuri}{kr}{kau}{-}{-}{Latn}`

`\@tracklang@add@kashmiri` No default script. Could be Arabic or Devanagari.
`\TrackLangDeclareLanguageOption{kashmiri}{ks}{kas}{-}{-}{IN}{-}`

`\@tracklang@add@kazakh` Default script varies according to region.
`\TrackLangDeclareLanguageOption{kazakh}{kk}{kaz}{-}{-}{-}{-}`

`\@tracklang@add@khmer`
`\TrackLangDeclareLanguageOption{khmer}{km}{khm}{-}{-}{Khmr}`

`\@tracklang@add@kikuyu`
`\TrackLangDeclareLanguageOption{kikuyu}{ki}{kik}{-}{-}{Latn}`

`\@tracklang@add@kinyarwanda`
`\TrackLangDeclareLanguageOption{kinyarwanda}{rw}{kin}{-}{-}{Latn}`

`\@tracklang@add@kirundi`
`\TrackLangDeclareLanguageOption{kirundi}{rn}{run}{-}{-}{Latn}`

`\@tracklang@add@komi`
`\TrackLangDeclareLanguageOption{komi}{kv}{kom}{-}{-}{RU}{Cyr1}`

`\@tracklang@add@kongo`
`\TrackLangDeclareLanguageOption{kongo}{kg}{kon}{-}{-}{Latn}`

`\@tracklang@add@korean`
`\TrackLangDeclareLanguageOption{korean}{ko}{kor}{-}{-}{Hang}`

`\@tracklang@add@kurdish` Script varies according to region.
`\TrackLangDeclareLanguageOption{kurdish}{ku}{kur}{-}{-}{-}{-}`

`\@tracklang@add@kwanyama`
`\TrackLangDeclareLanguageOption{kwanyama}{kj}{kua}{-}{-}{Latn}`

`\@tracklang@add@kyrgyz`
`\TrackLangDeclareLanguageOption{kyrgyz}{ky}{kir}{-}{-}{Cyr1}`

`\@tracklang@add@lao`
`\TrackLangDeclareLanguageOption{lao}{lo}{lao}{-}{-}{Lao}`

\@tracklang@add@latin
\TrackLangDeclareLanguageOption{latin}{la}{lat}{}{}{Latn}

\@tracklang@add@latvian
\TrackLangDeclareLanguageOption{latvian}{lv}{lav}{}{}{Latn}

\@tracklang@add@limburgish
\TrackLangDeclareLanguageOption{limburgish}{li}{lim}{}{}{Latn}

\@tracklang@add@lingala
\TrackLangDeclareLanguageOption{lingala}{ln}{lin}{}{}{Latn}

\@tracklang@add@lithuanian
\TrackLangDeclareLanguageOption{lithuanian}{lt}{lit}{}{}{Latn}

\@tracklang@add@lsorbian
\TrackLangDeclareLanguageOption{lsorbian}{}{dsb}{}{}{DE}{Latn}

\@tracklang@add@lubakatanga
\TrackLangDeclareLanguageOption{lubakatanga}{lu}{lub}{}{}{CD}{Latn}

\@tracklang@add@luxembourgish
\TrackLangDeclareLanguageOption{luxembourgish}{lb}{ltz}{}{}{Latn}

\@tracklang@add@macedonian
\TrackLangDeclareLanguageOption{macedonian}{mk}{mkd}{mac}{}{}{Cyr1}

\@tracklang@add@magyar
\TrackLangDeclareLanguageOption{magyar}{hu}{hun}{}{}{Latn}

\@tracklang@add@malagasy
\TrackLangDeclareLanguageOption{malagasy}{mg}{mlg}{}{}{Latn}

\@tracklang@add@malayalam
\TrackLangDeclareLanguageOption{malayalam}{ml}{mal}{}{}{IN}{Mlym}

\@tracklang@add@maltese
\TrackLangDeclareLanguageOption{maltese}{mt}{mlt}{}{}{Latn}

\@tracklang@add@manx
\TrackLangDeclareLanguageOption{manx}{gv}{glv}{}{}{IM}{Latn}

\@tracklang@add@maori
\TrackLangDeclareLanguageOption{maori}{mi}{mri}{mao}{}{NZ}{Latn}

\@tracklang@add@marathi
\TrackLangDeclareLanguageOption{marathi}{mr}{mar}{}{}{IN}{Deva}


```

\@tracklang@add@marshallese
    \TrackLangDeclareLanguageOption{marshallese}{mh}{mah}{}{}{MH}{Latn}

\@tracklang@add@mongolian
    \TrackLangDeclareLanguageOption{mongolian}{mn}{mon}{}{}{Mong}

\@tracklang@add@nauruan
    \TrackLangDeclareLanguageOption{nauruan}{na}{nau}{}{}{NR}{Latn}

\@tracklang@add@navajo
    \TrackLangDeclareLanguageOption{navajo}{nv}{nav}{}{}{US}{Latn}

\@tracklang@add@ndonga
    \TrackLangDeclareLanguageOption{ndonga}{ng}{ndo}{}{}{Latn}

\@tracklang@add@nepali
    \TrackLangDeclareLanguageOption{nepali}{ne}{nep}{}{}{Deva}

    \@tracklang@add@nko
    \TrackLangDeclareLanguageOption{nko}{}{nqo}{}{}{Nkoo}

\@tracklang@add@northernndebele
    \TrackLangDeclareLanguageOption{northernndebele}{nd}{nde}{}{}{Latn}

\@tracklang@add@nynorsk
    \TrackLangDeclareLanguageOption{nynorsk}{nn}{nno}{}{}{NO}{Latn}

\@tracklang@add@norsk
    \TrackLangDeclareLanguageOption{norsk}{no}{nor}{}{}{Latn}

\@tracklang@add@northernsotho
    \TrackLangDeclareLanguageOption{northernsotho}{}{nso}{}{}{Latn}

\@tracklang@add@nuosu
    \TrackLangDeclareLanguageOption{nuosu}{ii}{iii}{}{}{CN}{Yiii}

\@tracklang@add@occitan
    \TrackLangDeclareLanguageOption{occitan}{oc}{oci}{}{}{Latn}

\@tracklang@add@ojibwe
    \TrackLangDeclareLanguageOption{ojibwe}{oj}{oji}{}{}{Latn}

\@tracklang@add@oromo
    \TrackLangDeclareLanguageOption{oromo}{om}{orm}{}{}{Latn}

\@tracklang@add@oriya
    \TrackLangDeclareLanguageOption{oriya}{or}{ori}{}{}{Orya}

```

```

\@tracklang@add@ossetian
    \TrackLangDeclareLanguageOption{ossetian}{os}{oss}{}{}{}{Cyr1}

\@tracklang@add@pali
    \TrackLangDeclareLanguageOption{pali}{pi}{pli}{}{}{}{Brah}

\@tracklang@add@pashto
    \TrackLangDeclareLanguageOption{pashto}{ps}{pus}{}{}{}{Arab}

\@tracklang@add@piedmontese
    \TrackLangDeclareLanguageOption{piedmontese}{}{}{}{pms}{IT}{Latn}

\@tracklang@add@polish
    \TrackLangDeclareLanguageOption{polish}{pl}{pol}{}{}{}{Latn}

\@tracklang@add@portuges
    \TrackLangDeclareLanguageOption{portuges}{pt}{por}{}{}{}{Latn}

\@tracklang@add@quechua
    \TrackLangDeclareLanguageOption{quechua}{qu}{que}{}{}{}{Latn}

\@tracklang@add@romanian
    \TrackLangDeclareLanguageOption{romanian}{ro}{ron}{rum}{}{}{}{Latn}

\@tracklang@add@romansh
    \TrackLangDeclareLanguageOption{romansh}{rm}{roh}{}{}{}{CH}{Latn}

\@tracklang@add@russian
    \TrackLangDeclareLanguageOption{russian}{ru}{rus}{}{}{}{Cyr1}

\@tracklang@add@samin
    \TrackLangDeclareLanguageOption{samin}{se}{sme}{}{}{}{Latn}

\@tracklang@add@sanskrit
    \TrackLangDeclareLanguageOption{sanskrit}{sa}{san}{}{}{}{}

\@tracklang@add@samoan
    \TrackLangDeclareLanguageOption{samoan}{sm}{smo}{}{}{}{Latn}

\@tracklang@add@sango
    \TrackLangDeclareLanguageOption{sango}{sg}{sag}{}{}{}{Latn}

\@tracklang@add@sardinian
    \TrackLangDeclareLanguageOption{sardinian}{sc}{srd}{}{}{}{IT}{Latn}

\@tracklang@add@scots Scots. Also spoken in Northern Ireland, so no region. There's no ISO 639-1
language code for this language.
    \TrackLangDeclareLanguageOption{scots}{}{sco}{}{}{}{Latn}

```

\@tracklang@add@scottish Scottish Gaelic. Also spoken in Canada, so no region.
\TrackLangDeclareLanguageOption{scottish}{gd}{gla}{}{}{Latn}

\@tracklang@add@serbian
\TrackLangDeclareLanguageOption{serbian}{sr}{srp}{}{}{Cyr1}

\@tracklang@add@shona
\TrackLangDeclareLanguageOption{shona}{sn}{sna}{}{}{Latn}

\@tracklang@add@sindhi
\TrackLangDeclareLanguageOption{sindhi}{sd}{snd}{}{}{Sind}

\@tracklang@add@sinhalese
\TrackLangDeclareLanguageOption{sinhalese}{si}{sin}{}{}{LK}{Sinh}

\@tracklang@add@slovak
\TrackLangDeclareLanguageOption{slovak}{sk}{slk}{slo}{}{}{Latn}

\@tracklang@add@slovene
\TrackLangDeclareLanguageOption{slovene}{sl}{slv}{}{}{Latn}

\@tracklang@add@somali
\TrackLangDeclareLanguageOption{somali}{so}{som}{}{}{Latn}

\@tracklang@add@southernndebele
\TrackLangDeclareLanguageOption{southernndebele}{nr}{nbl}{}{}{ZA}{Latn}

\@tracklang@add@southernsotho
\TrackLangDeclareLanguageOption{southernsotho}{st}{sot}{}{}{Latn}

\@tracklang@add@spanish
\TrackLangDeclareLanguageOption{spanish}{es}{spa}{}{}{Latn}

\@tracklang@add@sudanese
\TrackLangDeclareLanguageOption{sudanese}{su}{sun}{}{}{Sund}

\@tracklang@add@swahili
\TrackLangDeclareLanguageOption{swahili}{sw}{swa}{}{}{}

\@tracklang@add@swati
\TrackLangDeclareLanguageOption{swati}{ss}{ssw}{}{}{Latn}

\@tracklang@add@swedish
\TrackLangDeclareLanguageOption{swedish}{sv}{swe}{}{}{Latn}

\@tracklang@add@syriac
\TrackLangDeclareLanguageOption{syriac}{}{syr}{}{}{Syrc}

```

\@tracklang@add@tagalog
\TrackLangDeclareLanguageOption{tagalog}{tl}{tgl}{}{}{PH}{Latn}

\@tracklang@add@tahitian
\TrackLangDeclareLanguageOption{tahitian}{ty}{tah}{}{}{PF}{Latn}

\@tracklang@add@tai
\TrackLangDeclareLanguageOption{tai}{}{tai}{}{}{}{}

\@tracklang@add@tajik
\TrackLangDeclareLanguageOption{tajik}{tg}{tgk}{}{}{}{Cyr1}

\@tracklang@add@tamil
\TrackLangDeclareLanguageOption{tamil}{ta}{tam}{}{}{}{Taml}

\@tracklang@add@tatar
\TrackLangDeclareLanguageOption{tatar}{tt}{tat}{}{}{}{Cyr1}

\@tracklang@add@telugu
\TrackLangDeclareLanguageOption{telugu}{te}{tel}{}{}{}{IN}{Telu}

\@tracklang@add@thai
\TrackLangDeclareLanguageOption{thai}{th}{tha}{}{}{}{TH}{Thai}

\@tracklang@add@tibetan
\TrackLangDeclareLanguageOption{tibetan}{bo}{bod}{tib}{}{}{}{Tibt}

\@tracklang@add@tigrinya
\TrackLangDeclareLanguageOption{tigrinya}{ti}{tir}{}{}{}{Ethi}

\@tracklang@add@tonga
\TrackLangDeclareLanguageOption{tonga}{to}{ton}{}{}{}{TO}{Latn}

\@tracklang@add@tsonga
\TrackLangDeclareLanguageOption{tsonga}{ts}{tso}{}{}{}{Latn}

\@tracklang@add@tswana
\TrackLangDeclareLanguageOption{tswana}{tn}{tsn}{}{}{}{Latn}

\@tracklang@add@turkish
\TrackLangDeclareLanguageOption{turkish}{tr}{tur}{}{}{}{Latn}

\@tracklang@add@turkmen
\TrackLangDeclareLanguageOption{turkmen}{tk}{tuk}{}{}{}{Latn}

\@tracklang@add@twi
\TrackLangDeclareLanguageOption{twi}{tw}{twi}{}{}{}{GH}{Latn}

```

```

\@tracklang@add@ukrainian
    \TrackLangDeclareLanguageOption{ukrainian}{uk}{ukr}{}{}{UA}{Cyr1}

\@tracklang@add@undetermined Undetermined language (ISO 636-2 code 'und') for unknown languages. There's
no ISO 639-1 language code for this language.
    \TrackLangDeclareLanguageOption{undetermined}{}{und}{}{}{}{Latn}

    \@tracklang@add@urdu
        \TrackLangDeclareLanguageOption{urdu}{ur}{urd}{}{}{}{Arab}

\@tracklang@add@usorbian
    \TrackLangDeclareLanguageOption{usorbian}{}{hsb}{}{}{}{DE}{Latn}

\@tracklang@add@uyghur
    \TrackLangDeclareLanguageOption{uyghur}{ug}{uig}{}{}{}{CN}{Arab}

\@tracklang@add@uzbek
    \TrackLangDeclareLanguageOption{uzbek}{uz}{uzb}{}{}{}{Latn}

\@tracklang@add@venda
    \TrackLangDeclareLanguageOption{venda}{ve}{ven}{}{}{}{ZA}{Latn}

\@tracklang@add@vietnamese
    \TrackLangDeclareLanguageOption{vietnamese}{vi}{vie}{}{}{}{Latn}

\@tracklang@add@volapuk
    \TrackLangDeclareLanguageOption{volapuk}{vo}{vol}{}{}{}{Latn}

\@tracklang@add@walloon No country code as Walloon is spoken in multiple regions (Wallonia in Belgium,
some villages in Northern France and north-east of Wisconsin.) Not the same
as Belgian French.
    \TrackLangDeclareLanguageOption{walloon}{wa}{wln}{}{}{}{Latn}

\@tracklang@add@welsh Also spoken in Argentina, so no region.
    \TrackLangDeclareLanguageOption{welsh}{cy}{cym}{wel}{}{}{Latn}

\@tracklang@add@westernfrisian
    \TrackLangDeclareLanguageOption{westernfrisian}{fy}{fry}{}{}{}{NL}{Latn}

\@tracklang@add@wolof
    \TrackLangDeclareLanguageOption{wolof}{wo}{wol}{}{}{}{Latn}

\@tracklang@add@xhosa
    \TrackLangDeclareLanguageOption{xhosa}{xh}{xho}{}{}{}{Latn}

\@tracklang@add@yiddish
    \TrackLangDeclareLanguageOption{yiddish}{yi}{yid}{}{}{}{Hebr}

```

```

\@tracklang@add@yoruba
    \TrackLangDeclareLanguageOption{yoruba}{yo}{yor}{}{}{Latn}

\@tracklang@add@zhuang
    \TrackLangDeclareLanguageOption{zhuang}{za}{zha}{}{}{CN}{Hani}

\@tracklang@add@zulu
    \TrackLangDeclareLanguageOption{zulu}{zu}{zul}{}{}{Latn}

```

4.6 Predefined Dialects

Provide some predefined dialects.

```

\TrackLangProvidePredefinedDialect{<dialect>}{<root
language>}{<3166-1
code>}{<modifier>}{<variant>}{<map>}{<script>}

```

\TrackLangProvidePredefinedDialect

This defines a predefined dialect label that can be used by `\TrackPredefinedDialect`. The arguments must be expanded before use. The final argument `<map>` is the mapping from `<dialect>` to the closest babel dialect label.

```

\def\TrackLangProvidePredefinedDialect#1#2#3#4#5#6#7{
    \ifx\relax#3\relax

```

No region.

```

        \ifx\relax#4\relax

```

No modifier.

```

            \ifx\relax#5\relax

```

No variant.

```

                \@tracklang@namedef{@tracklang@add@#1}{%
                    \AddTrackedDialect{#1}{#2}%
                    \AddTrackedLanguageIsoCodes{#2}%

```

Make it easier for the parser to pick up the dialect label. Note that this should be the same as `\TrackLangLastTrackedDialect` but the parser references `\@tracklang@dialect`.

```

                    \def\@tracklang@dialect{#1}%
                }%
            \else

```

Has variant but no modifier.

```

                \@tracklang@namedef{@tracklang@add@#1}{%
                    \AddTrackedDialect{#1}{#2}%
                    \AddTrackedLanguageIsoCodes{#2}%
                    \SetTrackedDialectVariant{#1}{#5}%
                    \def\@tracklang@dialect{#1}%
                }%
            \fi
        \else

```

Has modifier.

```
\ifx\relax#5\relax
```

No variant.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \SetTrackedDialectModifier{#1}{#4}%  
  \def\@tracklang@dialect{#1}%  
}%  
\else
```

Variant and modifier.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \SetTrackedDialectModifier{#1}{#4}%  
  \SetTrackedDialectVariant{#1}{#5}%  
  \def\@tracklang@dialect{#1}%  
}%  
\fi  
\fi  
\else
```

Has a region.

```
\ifx\relax#4\relax
```

No modifier.

```
\ifx\relax#5\relax
```

No variant.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \AddTrackedRegion{#3}{#1}%  
  \def\@tracklang@dialect{#1}%  
}%  
\else
```

Variant no modifier.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \AddTrackedRegion{#3}{#1}%  
  \SetTrackedDialectVariant{#1}{#5}%  
  \def\@tracklang@dialect{#1}%  
}%  
\fi  
\else
```

Has modifier.

```
\ifx\relax#5\relax
```

No variant.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \AddTrackedRegion{#3}{#1}%  
  \SetTrackedDialectModifier{#1}{#4}%  
  \def\@tracklang@dialect{#1}%  
}%  
\else
```

Variant and modifier.

```
\@tracklang@namedef{@tracklang@add@#1}{%  
  \AddTrackedDialect{#1}{#2}%  
  \AddTrackedLanguageIsoCodes{#2}%  
  \AddTrackedRegion{#3}{#1}%  
  \SetTrackedDialectModifier{#1}{#4}%  
  \SetTrackedDialectVariant{#1}{#5}%  
  \def\@tracklang@dialect{#1}%  
}%  
\fi  
\fi  
\fi
```

Add the mapping if provided.

```
\ifx\relax#6\relax  
\else  
  \expandafter  
  \let\expandafter\@tracklang@tmp\csname @tracklang@add@#1\endcsname  
  \expandafter\def\csname @tracklang@add@#1\expandafter\endcsname  
  \expandafter{\@tracklang@tmp\SetTrackedDialectLabelMap{#1}{#6}}%  
\fi
```

Add the script if provided.

```
\ifx\relax#7\relax  
\else  
  \expandafter  
  \let\expandafter\@tracklang@tmp\csname @tracklang@add@#1\endcsname  
  \expandafter\def\csname @tracklang@add@#1\expandafter\endcsname  
  \expandafter{\@tracklang@tmp\SetTrackedDialectScript{#1}{#7}}%  
\fi  
}
```

```
\TrackLangDeclareDialectOption{<dialect>}{<root  
language>}{<3166-1  
code>}{<modifier>}{<variant>}{<map>}{<script>}
```

\TrackLangDeclareDialectOption

The option name is the same as the dialect name. The arguments must be expanded before use. The final argument *<map>* is the mapping from *<dialect>* to the closest babel dialect label. May be empty if no relevant mapping.


```

\tracklang@add@istriacountyitalian
\TrackLangDeclareDialectOption{istriacountyitalian}{italian}{HR}{}{}{}

\@tracklang@add@netherlands
\TrackLangDeclareDialectOption{netherlands}{dutch}{NL}{}{}{}

\@tracklang@add@persian
\TrackLangDeclareDialectOption{persian}{farsi}{}{}{}{}

\@tracklang@add@flemish
\TrackLangDeclareDialectOption{flemish}{dutch}{BE}{}{}{}

\@tracklang@add@français
\TrackLangDeclareDialectOption{français}{french}{}{}{}{}

\@tracklang@add@frenchb
\TrackLangDeclareDialectOption{frenchb}{french}{}{}{}{}

\@tracklang@add@france
\TrackLangDeclareDialectOption{france}{french}{FR}{}{}{}

\@tracklang@add@belgique
\TrackLangDeclareDialectOption{belgique}{french}{BE}{}{}{}

\@tracklang@add@belgiangerman
\TrackLangDeclareDialectOption{belgiangerman}{german}{BE}{}{}{}

\@tracklang@add@nbelgiangerman
\TrackLangDeclareDialectOption{nbelgiangerman}{german}{BE}{new}{1996}{ngerman}{}

\@tracklang@add@friulian
\TrackLangDeclareDialectOption{friulian}{friulan}{IT}{}{}{}

\@tracklang@add@friulano
\TrackLangDeclareDialectOption{friulano}{friulan}{IT}{}{}{}

\@tracklang@add@furlan Added since it's a babel alias for friulan.
\TrackLangDeclareDialectOption{furlan}{friulan}{IT}{}{}{}

\@tracklang@add@kurmanji Added since it's a babel label.
\TrackLangDeclareDialectOption{kurmanji}{kurdish}{}{}{}{}

\@tracklang@add@galicien
\TrackLangDeclareDialectOption{galicien}{galician}{}{}{}{}

\@tracklang@add@deutsch
\TrackLangDeclareDialectOption{deutsch}{german}{}{}{}{}

```

```

\@tracklang@add@ngerman
\TrackLangDeclareDialectOption{ngerman}{german}{new}{1996}{}{}

\@tracklang@add@ngermanb
\TrackLangDeclareDialectOption{ngermanb}{german}{new}{1996}{ngerman}{}

\@tracklang@add@germanb
\TrackLangDeclareDialectOption{germanb}{german}{}{}{}{}

\@tracklang@add@ngermanDE
\TrackLangDeclareDialectOption{ngermanDE}{german}{DE}{new}{1996}{ngerman}{}

\@tracklang@add@germanDE
\TrackLangDeclareDialectOption{germanDE}{german}{DE}{}{}{}{}

\@tracklang@add@hungarian
\TrackLangDeclareDialectOption{hungarian}{magyar}{HU}{}{}{}{}

\@tracklang@add@indon
\TrackLangDeclareDialectOption{indon}{bahasai}{IN}{}{}{}{}

\@tracklang@add@indonesian
\TrackLangDeclareDialectOption{indonesian}{bahasai}{IN}{}{}{}{}

\@tracklang@add@gaeilge
\TrackLangDeclareDialectOption{gaeilge}{irish}{}{}{}{}{}

\@tracklang@add@IEirish Irish spoken in Republic of Ireland
\TrackLangDeclareDialectOption{IEirish}{irish}{IE}{}{}{}{}

\@tracklang@add@GBirish Irish spoken in the United Kingdom of Great Britain and Northern Ireland
\TrackLangDeclareDialectOption{GBirish}{irish}{GB}{}{}{}{}

\@tracklang@add@IEenglish English spoken in the Republic of Ireland.
\TrackLangDeclareDialectOption{IEenglish}{english}{IE}{}{}{british}{}

\@tracklang@add@italy
\TrackLangDeclareDialectOption{italy}{italian}{IT}{}{}{}{}

\@tracklang@add@vatican
\TrackLangDeclareDialectOption{vatican}{italian}{VA}{}{}{}{}

\@tracklang@add@sanmarino
\TrackLangDeclareDialectOption{sanmarino}{italian}{SM}{}{}{}{}

ng@add@sloveneistriaitalian
\TrackLangDeclareDialectOption{sloveneistriaitalian}{italian}{SI}{}{}{}{}

```

`\tracklang@add@jerseyenglish` Allow it to hook to pick up `\captionsbritish` as well as `\captionsenglish` since the date format closely matches `british`.
`\TrackLangDeclareDialectOption{jerseyenglish}{english}{JE}{}{}{british}{}`

`\tracklang@add@jerseyfrench`
`\TrackLangDeclareDialectOption{jerseyfrench}{french}{JE}{}{}{}{}`

`\tracklang@add@guernseyenglish` Allow it to hook to pick up `\captionsbritish` as well as `\captionsenglish` since the date format closely matches `british`.
`\TrackLangDeclareDialectOption{guernseyenglish}{english}{GG}{}{}{british}{}`

`\tracklang@add@guernseyfrench`
`\TrackLangDeclareDialectOption{guernseyfrench}{french}{GG}{}{}{}{}`

`\@tracklang@add@latein`
`\TrackLangDeclareDialectOption{latein}{latin}{}{}{}{}{}{}`

`\@tracklang@add@lowersorbian`
`\TrackLangDeclareDialectOption{lowersorbian}{lsorbian}{DE}{}{}{}{}{}{}`

`\@tracklang@add@malay`
`\TrackLangDeclareDialectOption{malay}{bahasam}{MY}{}{}{}{}{}{}`

`\@tracklang@add@meyalu`
`\TrackLangDeclareDialectOption{meyalu}{bahasam}{MY}{}{}{}{}{}{}`

`\@tracklang@add@maltamaltese`
`\TrackLangDeclareDialectOption{maltamaltese}{maltese}{MT}{}{}{}{}{}{}`

`\@tracklang@add@maltaenglish` Allow it to hook to pick up `\captionsbritish` as well as `\captionsenglish` since the date format closely matches `british`.
`\TrackLangDeclareDialectOption{maltaenglish}{english}{MT}{}{}{}{british}{}{}`

`\@tracklang@add@newzealand`
`\TrackLangDeclareDialectOption{newzealand}{english}{NZ}{}{}{}{}{}{}`

`\tracklang@add@isleofmanenglish` Allow it to hook to pick up `\captionsbritish` as well as `\captionsenglish` since the date format closely matches `british`.
`\TrackLangDeclareDialectOption{isleofmanenglish}{english}{IM}{}{}{}{british}{}{}`

`\@tracklang@add@norwegian`
`\TrackLangDeclareDialectOption{norwegian}{norsk}{NO}{}{}{}{}{}{}`

`\@tracklang@add@piemonteis`
`\TrackLangDeclareDialectOption{piemonteis}{piedmontese}{IT}{}{}{}{}{}{}`

`\tracklang@add@polutonikogreek`
`\TrackLangDeclareDialectOption{polutonikogreek}{greek}{}{polyton}{}{}{}{}{}{}`

```

\@tracklang@add@polutoniko
    \TrackLangDeclareDialectOption{polutoniko}{greek}{}{polyton}{}{}{}
\@tracklang@add@portuguese
    \TrackLangDeclareDialectOption{portuguese}{portuges}{}{}{}{}
\@tracklang@add@portugal
    \TrackLangDeclareDialectOption{portugal}{portuges}{PT}{}{}{}
\@tracklang@add@romansch
    \TrackLangDeclareDialectOption{romansch}{romansh}{}{}{}{}
\@tracklang@add@rumantsch
    \TrackLangDeclareDialectOption{rumantsch}{romansh}{}{}{}{}
\@tracklang@add@romanche
    \TrackLangDeclareDialectOption{romanche}{romansh}{}{}{}{}
\@tracklang@add@russianb
    \TrackLangDeclareDialectOption{russianb}{russian}{}{}{}{}
\@tracklang@add@gaelic Scottish Gaelic. Note that this is not the same as Scots.
    \TrackLangDeclareDialectOption{gaelic}{scottish}{}{}{}{}
\@tracklang@add@GBscottish
    \TrackLangDeclareDialectOption{GBscottish}{scottish}{GB}{}{}{}
\@tracklang@add@serbianc
    \TrackLangDeclareDialectOption{serbianc}{serbian}{}{}{}{Cyr1}
\@tracklang@add@serbianl
    \TrackLangDeclareDialectOption{serbianl}{serbian}{}{}{}{Latn}
\@tracklang@add@slovenian
    \TrackLangDeclareDialectOption{slovenian}{slovene}{}{}{}{}
\@tracklang@add@slovenia
    \TrackLangDeclareDialectOption{slovenia}{slovene}{SI}{}{}{slovenian}{}
\@add@sloveneistriasslovenian
    \TrackLangDeclareDialectOption{sloveneistriasslovenian}{slovene}{SI}{}{}{slovenian}{}
\@tracklang@add@spainspanish
    \TrackLangDeclareDialectOption{spainspanish}{spanish}{ES}{}{}{}
\@tracklang@add@argentinespanish
    \TrackLangDeclareDialectOption{argentinespanish}{spanish}{AR}{}{}{}

```

tracklang@add@bolivianspanish
 \TrackLangDeclareDialectOption{bolivianspanish}{spanish}{BO}{}{}{}{}

tracklang@add@chilianspanish
 \TrackLangDeclareDialectOption{chilianspanish}{spanish}{CL}{}{}{}{}

tracklang@add@columbianspanish
 \TrackLangDeclareDialectOption{columbianspanish}{spanish}{CO}{}{}{}{}

tracklang@add@costaricanspanish
 \TrackLangDeclareDialectOption{costaricanspanish}{spanish}{CR}{}{}{}{}

@tracklang@add@cubanspanish
 \TrackLangDeclareDialectOption{cubanspanish}{spanish}{CU}{}{}{}{}

tracklang@add@dominicanspanish
 \TrackLangDeclareDialectOption{dominicanspanish}{spanish}{DO}{}{}{}{}

tracklang@add@ecudorianspanish
 \TrackLangDeclareDialectOption{ecudorianspanish}{spanish}{EC}{}{}{}{}

tracklang@add@elsalvadorspanish
 \TrackLangDeclareDialectOption{elsalvadorspanish}{spanish}{SV}{}{}{}{}

tracklang@add@guatemalanspanish
 \TrackLangDeclareDialectOption{guatemalanspanish}{spanish}{GT}{}{}{}{}

tracklang@add@honduranspanish
 \TrackLangDeclareDialectOption{honduranspanish}{spanish}{HN}{}{}{}{}

tracklang@add@mexicanspanish
 \TrackLangDeclareDialectOption{mexicanspanish}{spanish}{MX}{}{}{}{}

tracklang@add@nicaraguanspanish
 \TrackLangDeclareDialectOption{nicaraguanspanish}{spanish}{NI}{}{}{}{}

@tracklang@add@panamaspanish
 \TrackLangDeclareDialectOption{panamaspanish}{spanish}{PA}{}{}{}{}

tracklang@add@paraguayspanish
 \TrackLangDeclareDialectOption{paraguayspanish}{spanish}{PY}{}{}{}{}

tracklang@add@peruvianspanish
 \TrackLangDeclareDialectOption{peruvianspanish}{spanish}{PE}{}{}{}{}

tracklang@add@puertoricospansish
 \TrackLangDeclareDialectOption{puertoricospansish}{spanish}{PR}{}{}{}{}

```

\tracklang@add@uruguayspanish
\TrackLangDeclareDialectOption{uruguayspanish}{spanish}{UY}{}{}{}

\tracklang@add@venezuelanspanish
\TrackLangDeclareDialectOption{venezuelanspanish}{spanish}{VE}{}{}{}

\@tracklang@add@swissgerman
\TrackLangDeclareDialectOption{swissgerman}{german}{CH}{}{}{}

\@tracklang@add@nswissgerman
\TrackLangDeclareDialectOption{nswissgerman}{german}{CH}{new}{1996}{ngerman}{}

\@tracklang@add@swissfrench
\TrackLangDeclareDialectOption{swissfrench}{french}{CH}{}{}{}

\@tracklang@add@swissitalian
\TrackLangDeclareDialectOption{swissitalian}{italian}{CH}{}{}{}

\@tracklang@add@swissromansh
\TrackLangDeclareDialectOption{swissromansh}{romansh}{CH}{}{}{}

\@tracklang@add@UKenglish
\TrackLangDeclareDialectOption{UKenglish}{english}{GB}{}{}{}

\@tracklang@add@ukraineb
\TrackLangDeclareDialectOption{ukraineb}{ukrainian}{UA}{}{}{}

\@tracklang@add@ukraine
\TrackLangDeclareDialectOption{ukraine}{ukrainian}{UA}{}{}{}

\@tracklang@add@uppersorbian
\TrackLangDeclareDialectOption{uppersorbian}{usorbian}{DE}{}{}{}

\@tracklang@add@USenglish
\TrackLangDeclareDialectOption{USenglish}{english}{US}{}{}{}

\@tracklang@add@valencian
\TrackLangDeclareDialectOption{valencian}{catalan}{}{}{}{}

\@tracklang@add@valencien
\TrackLangDeclareDialectOption{valencien}{catalan}{}{}{}{}

\@tracklang@add@cymraeg
\TrackLangDeclareDialectOption{cymraeg}{welsh}{}{}{}{}

\@tracklang@add@GBwelsh
\TrackLangDeclareDialectOption{GBwelsh}{welsh}{GB}{}{}{}

\@tracklang@add@nil Add babel's nil as a dialect of undetermined language.
\TrackLangDeclareDialectOption{nil}{undetermined}{}{}{}{}

```

4.7 Dialect Option Synonyms

Add some dialect synonyms:

```
\LetTrackLangSynonym
  \def\LetTrackLangSynonym#1#2{%
    \expandafter\let\csname @tracklang@add@#1\expandafter\endcsname
      \csname @tracklang@add@#2\endcsname
  }

\LetTrackLangOption
  \def\LetTrackLangOption#1#2{%
    \LetTrackLangSynonym{#1}{#2}%
    \@tracklang@declareoption{#1}%
  }

\@tracklang@add@en-US
  \LetTrackLangOption{en-US}{american}

\@tracklang@add@en-GB
  \LetTrackLangOption{en-GB}{british}

\@tracklang@add@en-AU
  \LetTrackLangOption{en-AU}{australian}

\@tracklang@add@en-NZ
  \LetTrackLangOption{en-NZ}{newzealand}

\@tracklang@add@en-CA
  \LetTrackLangOption{en-CA}{canadian}

\@tracklang@add@fr-CA
  \LetTrackLangOption{fr-CA}{canadien}

\@tracklang@add@fr-BE
  \LetTrackLangOption{fr-BE}{belgique}

\@tracklang@add@pt-BR
  \LetTrackLangOption{pt-BR}{brazilian}

\@tracklang@add@it-HR
  \LetTrackLangOption{it-HR}{istriacountyitalian}

\@tracklang@add@nl-BE
  \LetTrackLangOption{nl-BE}{flemish}

\@tracklang@add@fr-FR
  \LetTrackLangOption{fr-FR}{france}
```


\@tracklang@add@de-DE
\LetTrackLangOption{de-DE}{germanDE}

\@tracklang@add@de-BE
\LetTrackLangOption{de-BE}{belgiangerman}

\@tracklang@add@en-GG
\LetTrackLangOption{en-GG}{guernseyenglish}

\@tracklang@add@fr-GG
\LetTrackLangOption{fr-GG}{guernseyfrench}

\@tracklang@add@it-IT
\LetTrackLangOption{it-IT}{italy}

\@tracklang@add@mt-MT
\LetTrackLangOption{mt-MT}{maltamaltese}

\@tracklang@add@en-MT
\LetTrackLangOption{en-MT}{maltaenglish}

\@tracklang@add@en-IM
\LetTrackLangOption{en-IM}{isleofmanenglish}

\@tracklang@add@en-JE
\LetTrackLangOption{en-JE}{jerseyenglish}

\@tracklang@add@fr-JE
\LetTrackLangOption{fr-JE}{jerseyfrench}

\@tracklang@add@nl-NL
\LetTrackLangOption{nl-NL}{netherlands}

\@tracklang@add@pt-PT
\LetTrackLangOption{pt-PT}{portugal}

\@tracklang@add@it-SM
\LetTrackLangOption{it-SM}{sanmarino}

\@tracklang@add@sl-SI
\LetTrackLangOption{sl-SI}{slovenia}

\@tracklang@add@it-SI
\LetTrackLangOption{it-SI}{sloveneistriaitalian}

\@tracklang@add@es-ES
\LetTrackLangOption{es-ES}{spainspanish}

\@tracklang@add@es-AR
\LetTrackLangOption{es-AR}{argentinaspanish}

\@tracklang@add@es-BO
\LetTrackLangOption{es-BO}{boliviaspanish}

\@tracklang@add@es-CL
\LetTrackLangOption{es-CL}{chilespanish}

\@tracklang@add@es-CO
\LetTrackLangOption{es-CO}{colombiaspanish}

\@tracklang@add@es-CR
\LetTrackLangOption{es-CR}{costaricaspanish}

\@tracklang@add@es-CU
\LetTrackLangOption{es-CU}{cubaspanish}

\@tracklang@add@es-DO
\LetTrackLangOption{es-DO}{dominicaspanish}

\@tracklang@add@es-EC
\LetTrackLangOption{es-EC}{ecuatoriaspanish}

\@tracklang@add@es-SV
\LetTrackLangOption{es-SV}{elsalvadorspanish}

\@tracklang@add@es-GT
\LetTrackLangOption{es-GT}{guatemalaspanish}

\@tracklang@add@es-HN
\LetTrackLangOption{es-HN}{hondurasspanish}

\@tracklang@add@es-MX
\LetTrackLangOption{es-MX}{mexicospanish}

\@tracklang@add@es-NI
\LetTrackLangOption{es-NI}{nicaraguaspanish}

\@tracklang@add@es-PA
\LetTrackLangOption{es-PA}{panamaspanish}

\@tracklang@add@es-PY
\LetTrackLangOption{es-PY}{paraguayspanish}

\@tracklang@add@es-PE
\LetTrackLangOption{es-PE}{peruspanish}

\@tracklang@add@es-PR
\LetTrackLangOption{es-PR}{puertoricospanish}

\@tracklang@add@es-UY
\LetTrackLangOption{es-UY}{uruguayspanish}

\@tracklang@add@es-VE
\LetTrackLangOption{es-VE}{venezuelanspanish}

\@tracklang@add@de-CH
\LetTrackLangOption{de-CH}{swissgerman}

\@tracklang@add@fr-CH
\LetTrackLangOption{fr-CH}{swissfrench}

\@tracklang@add@it-CH
\LetTrackLangOption{it-CH}{swissitalian}

\@tracklang@add@rm-CH
\LetTrackLangOption{rm-CH}{swissromansh}

\@tracklang@add@it-VA
\LetTrackLangOption{it-VA}{vatican}

\@tracklang@add@ga-IE Irish Gaelic in Republic of Ireland.
\LetTrackLangOption{ga-IE}{IEIrish}

\@tracklang@add@ga-GB Irish Gaelic in Northern Ireland.
\LetTrackLangOption{ga-GB}{GBIrish}

\@tracklang@add@en-IE English spoken in Republic of Ireland.
\LetTrackLangOption{en-IE}{IEEnglish}

\@tracklang@add@de-AT-1996
\LetTrackLangOption{de-AT-1996}{naustrian}

\@tracklang@add@de-AT
\LetTrackLangOption{de-AT}{austrian}

\@tracklang@add@id-IN
\LetTrackLangOption{id-IN}{bahasa}

\@tracklang@add@ms-MY
\LetTrackLangOption{ms-MY}{malay}

\@tracklang@add@hr-HR
\LetTrackLangOption{hr-HR}{croatia}

```
\@tracklang@add@de-DE-1996
```

```
\LetTrackLangOption{de-DE-1996}{ngermanDE}
```

```
\@tracklang@add@de-CH-1996
```

```
\LetTrackLangOption{de-CH-1996}{nswissgerman}
```

```
\@tracklang@add@hu-HU
```

```
\LetTrackLangOption{hu-HU}{hungarian}
```

```
\@tracklang@add@gd-GB
```

```
\LetTrackLangOption{gd-GB}{GBscottish}
```

```
\@tracklang@add@cy-GB
```

```
\LetTrackLangOption{cy-GB}{GBwelsh}
```

4.8 Conditionals and Loops

```
\IfTrackedLanguage{<language>}{<true part>}{<>false part>}
```

```
\IfTrackedLanguage
```

```
\long\def\IfTrackedLanguage#1#2#3{%
```

First find out if the language name is empty.

```
\edef\@tracklang@element{#1}%
\ifx\@tracklang@element\empty
```

Language is empty, so do false part.

```
#3%
\else
\expandafter\@tracklang@ifinlist\expandafter{\@tracklang@element}%
\@tracklang@languages
{%
```

In list, so do true part.

```
#2%
}%
{%
```

Not in list, so do false part.

```
#3%
}%
\fi
}
```

```
\IfTrackedDialect{<dialect>}{<true part>}{<>false part>}
```

```
\IfTrackedDialect
```

```
\long\def\IfTrackedDialect#1#2#3{%
  \@tracklang@ifundef{\@tracklang@fromdialect@#1}{#3}{#2}%
}
```

```
\IfTrackedIsoCode{<code type>}{<code>}{<true part>}{<false
part>}
```

\IfTrackedIsoCode

```
\long\def\IfTrackedIsoCode#1#2#3#4{%
  \@tracklang@ifundef{\@tracklang@#1@isotolang@#2}{#4}{#3}%
}
```

```
\IfTrackedLanguageHasIsoCode{<code type>}{<language>}{<true
part>}{<false
part>}
```

\IfTrackedLanguageHasIsoCode

```
\long\def\IfTrackedLanguageHasIsoCode#1#2#3#4{%
  \@tracklang@ifundef{\@tracklang@#1@isofromlang@#2}{#4}{#3}%
}
```

```
\ForEachTrackedLanguage{<cs>}{<body>}
```

\ForEachTrackedLanguage

Iterates through the list of tracked languages. On each iteration *<cs>* is set to the language tag and *<body>* is performed.

```
\long\def\ForEachTrackedLanguage#1#2{%
  \@tracklang@for#1:=\@tracklang@languages\do{#2}%
}
```

```
\ForEachTrackedDialect{<cs>}{<body>}
```

\ForEachTrackedDialect

Iterates through the list of tracked dialects. On each iteration *<cs>* is set to the dialect tag and *<body>* is performed.

```
\long\def\ForEachTrackedDialect#1#2{%
  \@tracklang@for#1:=\@tracklang@dialects\do{#2}%
}
```

\AnyTrackedRegions

```
\long\def\AnyTrackedRegions#1#2{%
  \ifx\@tracklang@regions\empty
  #2%
  \else
  #1%
  \fi
}
```

```
\ForEachTrackedRegion{<cs>}{<body>}
```

\ForEachTrackedRegion

Iterates through the list of tracked regions. On each iteration *<cs>* is set to the region tag and *<body>* is performed.

```
\long\def\ForEachTrackedRegion#1#2{%
  \@tracklang@for#1:=\@tracklang@regions\do{#2}%
}
```

\AnyTrackedLanguages

```
\long\def\AnyTrackedLanguages#1#2{%
  \ifx\@tracklang@languages\empty
    #2%
  \else
    #1%
  \fi
}
```

```
\IfTrackedLanguageFileExists{<dialect>}{<prefix>}{<suffix>}
{<true
part>}{<false part>}
```

\IfTrackedLanguageFileExists

Determines if the file *<prefix><tag><suffix>* exists, where *<tag>* is an ISO code or ISO codes or label identifying the language. If *<dialect>* hasn't been identified as a tracked dialect, this just does *<false part>*, otherwise this tries various different combinations for *<tag>*. If the file *<prefix><tag><suffix>* exists, `\CurrentTrackedTag` is set to *<tag>* and *<true part>* is performed, otherwise *<false part>* is performed. The order of priority has changed with version 1.4 and now includes a check for variations that include the script. If the original ordering is specifically required, the old behaviour can be obtained with `\IfTrackedLanguageFileExists@orig`.

```
\long\def\IfTrackedLanguageFileExists#1#2#3#4#5{%
  \@tracklang@verbose{Finding file for dialect '#1'}%
```

Initialise.

```
\def\@tracklang@test@if@file@exists@for@dialect{%
  \@tracklang@test@if@file@exists@for@dialect
}%
\def\@tracklang@test@if@file@exists@for@region{%
  \@tracklang@test@if@file@exists@for@region
}%
\def\CurrentTrackedTag{%
```

Select this dialect.

```
\SetCurrentTrackedDialect{#1}%
\IfTrackedDialect{#1}%
{%
```

Save the three types of language codes to for reference.

```
\edef\CurrentTrackedIsoCodeI{\TrackedIsoCodeFromLanguage
{639-1}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeII{\TrackedIsoCodeFromLanguage
{639-2}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeIII{\TrackedIsoCodeFromLanguage
{639-3}{\CurrentTrackedLanguage}}%
```

Earlier versions of this had too many nested conditionals, which was confusing and hard to follow. This is a rewrite that removes the nesting and adds extra checks for dialect scripts.

```
\@tracklang@test@if@file@exists@for@tag{#1}{#2}{#3}%
\@tracklang@if@file@exists{#4}{#5}%
}%
{#5}% unknown dialect
}
```

```
\IfTrackedLanguageFileExistsOmitOnlyRegion{<dialect>}
{<prefix>}{<suffix>}{<true
part>}{<false part>}
```

ageFileExistsOmitOnlyRegion

As above but skips check for only region.

```
\long\def\IfTrackedLanguageFileExistsOmitOnlyRegion#1#2#3#4#5{%
\@tracklang@verbose{Finding file for dialect ‘#1’}%
```

Initialise.

```
\def\@@tracklang@test@if@file@exists@for@dialect{%
\@tracklang@test@if@file@exists@for@dialect
}%
\def\@@tracklang@test@if@file@exists@for@region{%
\@tracklang@test@if@file@exists@for@notregiononly
}%
\def\CurrentTrackedTag{}}%
```

Select this dialect.

```
\SetCurrentTrackedDialect{#1}%
\IfTrackedDialect{#1}%
{%
```

Save the three types of language codes to for reference.

```
\edef\CurrentTrackedIsoCodeI{\TrackedIsoCodeFromLanguage
{639-1}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeII{\TrackedIsoCodeFromLanguage
{639-2}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeIII{\TrackedIsoCodeFromLanguage
{639-3}{\CurrentTrackedLanguage}}%
```

Earlier versions of this had too many nested conditionals, which was confusing and hard to follow. This is a rewrite that removes the nesting and adds extra checks for dialect scripts.

```

        \@tracklang@test@if@file@exists@for@tag{#1}{#2}{#3}%
        \@tracklang@if@file@exists{#4}{#5}%
    }%
    {#5}% unknown dialect
}

```

```

\IfTrackedLanguageFileExistsOmitDialectLabelOnlyRegion
{<dialect>}{<prefix>}{<suffix>}{<true
part>}{<false part>}

```

tDialectLabelOmitOnlyRegion

As above but skips check for dialect label and only region. Note that if the dialect label happens to also be the root label, it will still be checked but right at the end instead of near the start.

```

\long\def\IfTrackedLanguageFileExistsOmitDialectLabelOmitOnlyRegion#1#2#3#4#5{%
    \@tracklang@verbose{Finding file for dialect ‘#1’}%

```

Initialise.

```

    \def\@tracklang@test@if@file@exists@for@dialect{%
        \@tracklang@test@if@file@exists@for@skipdialectlabel
    }%
    \def\@tracklang@test@if@file@exists@for@region{%
        \@tracklang@test@if@file@exists@for@notregiononly
    }%
    \def\CurrentTrackedTag{}%

```

Select this dialect.

```

    \SetCurrentTrackedDialect{#1}%
    \IfTrackedDialect{#1}%
    {%

```

Save the three types of language codes to for reference.

```

    \edef\CurrentTrackedIsoCodeI{\TrackedIsoCodeFromLanguage
        {639-1}{\CurrentTrackedLanguage}}%
    \edef\CurrentTrackedIsoCodeII{\TrackedIsoCodeFromLanguage
        {639-2}{\CurrentTrackedLanguage}}%
    \edef\CurrentTrackedIsoCodeIII{\TrackedIsoCodeFromLanguage
        {639-3}{\CurrentTrackedLanguage}}%

```

Earlier versions of this had too many nested conditionals, which was confusing and hard to follow. This is a rewrite that removes the nesting and adds extra checks for dialect scripts.

```

        \@tracklang@test@if@file@exists@for@tag{#1}{#2}{#3}%
        \@tracklang@if@file@exists{#4}{#5}%
    }%
    {#5}% unknown dialect
}

```



```
\IfTrackedLanguageFileExistsOmitDialectLabel{<dialect>}
  {<prefix>}{<suffix>}{<true
  part>}{<false part>}
```

FileExistsOmitDialectLabel

As above but skips check for dialect label. Note that if the dialect label happens to also be the root label, it will still be checked but right at the end instead of near the start.

```
\long\def\IfTrackedLanguageFileExistsOmitDialectLabel#1#2#3#4#5{%
  \@tracklang@verbose{Finding file for dialect ‘#1’}%
```

Initialise.

```
\def\@tracklang@test@if@file@exists@for@dialect{%
  \@tracklang@test@if@file@exists@for@skipdialectlabel
}%
\def\@tracklang@test@if@file@exists@for@region{%
  \@tracklang@test@if@file@exists@for@region
}%
\def\CurrentTrackedTag{}
```

Select this dialect.

```
\SetCurrentTrackedDialect{#1}%
\IfTrackedDialect{#1}%
{%
```

Save the three types of language codes to for reference.

```
\edef\CurrentTrackedIsoCodeI{\TrackedIsoCodeFromLanguage
  {639-1}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeII{\TrackedIsoCodeFromLanguage
  {639-2}{\CurrentTrackedLanguage}}%
\edef\CurrentTrackedIsoCodeIII{\TrackedIsoCodeFromLanguage
  {639-3}{\CurrentTrackedLanguage}}%
```

Earlier versions of this had too many nested conditionals, which was confusing and hard to follow. This is a rewrite that removes the nesting and adds extra checks for dialect scripts.

```
\@tracklang@test@if@file@exists@for@tag{#1}{#2}{#3}%
  \@tracklang@if@file@exists{#4}{#5}%
}%
{#5}% unknown dialect
}
```

ng@test@if@file@exists@noop

```
\def\@tracklang@test@if@file@exists@noop#1#2#3{}
```

t@test@if@file@exists@for@tag

```
\def\@tracklang@test@if@file@exists@for@tag#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedLanguageTag
  \@tracklang@verbose{Testing tag (exact) ‘\CurrentTrackedTag’}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
```

```

    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
      \let\@tracklang@if@file@exists\@tracklang@secondoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@dialect
    }%
    \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
  }

```

Allow dialect label test to be skipped.

```
\if@file@exists@for@dialect
```

```

\def\@tracklang@test@if@file@exists@for@dialect{%
  \@tracklang@test@if@file@exists@for@dialect
}

```

```
\if@file@exists@for@dialect
```

```

\def\@tracklang@test@if@file@exists@for@dialect#1#2#3{%
  \edef\CurrentTrackedTag{#1}%
  \@tracklang@verbose{Testing tag (dialect) ‘\CurrentTrackedTag’}%
  \@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \IfTrackedLanguageHasIsoCode{639-1}{\CurrentTrackedLanguage}%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscriptregion
    }%
    {%
      \IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptregion
      }%
      {%
        \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
        {%
          \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptregion
        }%
        {%
          \let\CurrentTrackedIsoCode\empty
          \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
        }%
      }%
    }%
  }%
}
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%

```

```

}

@exists@for@notdialectlabel Allow dialect label test to be skipped.
\def\@tracklang@test@if@file@exists@for@skipdialectlabel#1#2#3{%
  \IfTrackedLanguageHasIsoCode{639-1}{\CurrentTrackedLanguage}%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscriptregion
  }%
  {%
    \IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptregion
    }%
    {%
      \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptregion
      }%
      {%
        \let\CurrentTrackedIsoCode\empty
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
      }%
    }%
  }%
}
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

@exists@for@langIscriptregion Test <639-1>-<sublang>-<script>-<region> combination.
\def\@tracklang@test@if@file@exists@for@langIscriptregion#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeI
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \ifx\CurrentTrackedDialectScript\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
  \fi
  \ifx\CurrentTrackedRegion\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
  \fi
  \@tracklang@verbose{Testing tag (639-1 [sublang] [script] [region]) ‘\CurrentTrackedTag’}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%

```

```

\ifx\CurrentTrackedRegion\empty
\ifx\CurrentTrackedDialectScript\empty

```

No script or region set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langII
\else
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-1 [no script region]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langII
}%
\fi
\else

```

No region set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscript
\else
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-1 script [no region]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscr
}%
\fi
\fi
\else
\ifx\CurrentTrackedDialectScript\empty

```

Region is set but no script. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipregion
\else
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-1 [no script] region) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop

```

```

    }%
    {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipreg
    }%
    \fi
\else

```

Region and script set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscript
\else
    \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript
        -\CurrentTrackedRegion}%
    \@tracklang@verbose{Testing tag (639-1 [omit sublang] script region)
        '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
        \let\@tracklang@if@file@exists\@tracklang@firstoftwo
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscr
    }%
    \fi
\fi
\fi
}
\fi
}
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

ists@for@langIIscriptregion Test (639-2)-<sublang>-<script>-<region> combination.

```

\def\@tracklang@test@if@file@exists@for@langIIscriptregion#1#2#3{%
    \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \ifx\CurrentTrackedDialectSubLang\empty
    \else
        \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
    \fi
    \ifx\CurrentTrackedDialectScript\empty
    \else
        \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
    \fi
    \ifx\CurrentTrackedRegion\empty
    \else
        \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
    \fi
    \@tracklang@verbose{Testing tag (639-2 [sublang] [script] [region])
        '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%

```

```

\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%

```

```

\ifx\CurrentTrackedRegion\empty
\ifx\CurrentTrackedDialectScript\empty

```

No script or region set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII
\else
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-2 [omit sublang] [no script region])
'\CurrentTrackedTag'}%
\@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII
}%
\fi
\else

```

No region set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskripscrip
\else
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-2 [omit sublang] script [no region])
'\CurrentTrackedTag'}%
\@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskripscrip
}%
\fi
\fi
\else
\ifx\CurrentTrackedDialectScript\empty

```

Region is set but no script. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIiskipregio
\else

```

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-2 [omit sublang] [no script] region)
‘\CurrentTrackedTag’}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipre
}%
\fi
\else

```

Both region and script are set. If there’s a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipscrip
\else
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript
-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-2 [omit sublang] script region)
‘\CurrentTrackedTag’}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipsc
}%
\fi
\fi
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

sts@for@langIIIscripregion Test (639-3)-(sublang)-(script)-(region) combination.

```

\def\@tracklang@test@if@file@exists@for@langIIIscripregion#1#2#3{%
\let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\ifx\CurrentTrackedDialectScript\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
\fi

```

```

\ifx\CurrentTrackedRegion\empty
\else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
\fi
\@tracklang@verbose{Testing tag (639-3 [sublang] [script] [region])
  '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedRegion\empty
    \ifx\CurrentTrackedDialectScript\empty

```

No script or region set. If there's a sub-language code then try again without it.

```

  \ifx\CurrentTrackedDialectSubLang\empty
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
  \else
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \@tracklang@verbose{Testing tag (639-3 [omit sublang] [no script region])
      '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
  \fi
\else

```

No region set. If there's a sub-language code then try again without it.

```

  \ifx\CurrentTrackedDialectSubLang\empty
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscr
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
    \@tracklang@verbose{Testing tag (639-3 [omit sublang] script [no region])
      '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskips
    }%
  \fi
\fi

```



```

\else
\ifx\CurrentTrackedDialectScript\empty

```

Region is set but no script. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipreg
\else
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang] [no script] region)
'\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipreg
}%
\fi
\else

```

Both region and script are set. If there's a sub-language code then try again without it.

```

\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscr
\else
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript
-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang] script region)
'\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscr
}%
\fi
\fi
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

@exists@for@langIskipscript No region. Has a script but already tested with 639-1 and script. Just test language code alone.

```

\def\@tracklang@test@if@file@exists@for@langIskipscript#1#2#3{%
\let\CurrentTrackedTag\CurrentTrackedIsoCode

```

```

\ifx\CurrentTrackedDialectSubLang\empty
\else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\@tracklang@verbose{Testing tag (639-1 [sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscript
  }%
  {%
    \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscript
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
  }%
  \else

```

Try without sub-language code.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-1 [omit sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscript
  }%
  {%
    \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscript
    }%
  }%
  {%

```

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
  }%
}
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

file@exists@for@langIIscript No region but has a script.

```

\def\@tracklang@test@if@file@exists@for@langIIscript#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-2 [sublang] script) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipscript
    \else

```

Try without sub-language.

```

    \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
    \@tracklang@verbose{Testing tag (639-2 [omit sublang] script)
      '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipscript
    }%
  \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIIskipscript No region. Has a script but already checked.

```

\def\@tracklang@test@if@file@exists@for@langIIskipscript#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty

```

```

\else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\@tracklang@verbose{Testing tag (639-1 [sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
    \IfTrackedLanguageHasIsoCode
      {639-3}{\CurrentTrackedLanguage}
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscrip
      }%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
      }%
    \else

```

Try without sub-language.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-2 [omit sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscrip
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
  }%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

le@exists@for@langIIIscrip No region but has a script.

```

\def\@tracklang@test@if@file@exists@for@langIIIscrip#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else

```

```

\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-3 [sublang] script) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscript
\else

```

Try without sub-language.

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscript
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIIIskipscript No region. Has a script but already checked.

```

\def\@tracklang@test@if@file@exists@for@langIIIskipscript#1#2#3{%
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\@tracklang@verbose{Testing tag (639-3 [sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedDialectSubLang\empty
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
\else

```

Try without sub-language.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode

```

```

\@tracklang@verbose{Testing tag (639-3 [omit sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

~~@exists@for@lang~~Iskipregion No script. Has a region but already tested with 639-1 and script. Just test language code alone.

```

\def\@tracklang@test@if@file@exists@for@langIskipregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \@tracklang@verbose{Testing tag (639-1 [sublang]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
    \IfTrackedLanguageHasIsoCode
    {639-2}{\CurrentTrackedLanguage}
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIregion
    }%
    {%
      \IfTrackedLanguageHasIsoCode
      {639-3}{\CurrentTrackedLanguage}
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIregion
      }%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
      }%
    }%
  }%
  \else

```

Try without sub-language code.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-1 [omit sublang]) '\CurrentTrackedTag'}%

```

```

\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIregion
  }%
  {%
    \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIregion
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
  }%
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

file@exists@for@langIIregion No script but has a region.

```

\def\@tracklang@test@if@file@exists@for@langIIregion#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectRegion}%
  \@tracklang@verbose{Testing tag (639-2 [sublang] region) '\CurrentTrackedTag'}%
  \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipregion
    \else

```

Try without sub-language.

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectRegion}%
\@tracklang@verbose{Testing tag (639-2 [omit sublang] region)

```

```

        '\CurrentTrackedTag'}%
\tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipregion
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIIskipregion No script. Has a region but already tested with 639-2 and region. Just test language code alone.

```

\def\@tracklang@test@if@file@exists@for@langIIskipregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \@tracklang@verbose{Testing tag (639-2 [sublang]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
    \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIregion
    }%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    }%
    \else

```

Try without sub-language code.

```

  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \@tracklang@verbose{Testing tag (639-2 [omit sublang]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \IfTrackedLanguageHasIsoCode

```



```

        {639-3}{\CurrentTrackedLanguage}
        {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIregion
        }%
        {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
        }%
        }%
    \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

file@exists@for@langIIregion No script but has a region.

```

\def\@tracklang@test@if@file@exists@for@langIIregion#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectRegion}%
  \@tracklang@verbose{Testing tag (639-2 [sublang] region) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
  \ifx\CurrentTrackedDialectSubLang\empty
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipregion
  \else

```

Try without sub-language.

```

  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectRegion}%
  \@tracklang@verbose{Testing tag (639-2 [omit sublang] region)
  '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipregion
  }%
  \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

exists@for@langIIIskipregion No script. Has a region but already tested with 639-3 and region. Just test language code alone.

```
\def\@tracklang@test@if@file@exists@for@langIIIskipregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \@tracklang@verbose{Testing tag (639-2 [sublang]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
    \else
```

Try without sub-language code.

```
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-2 [omit sublang])
  '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}
```

le@exists@for@langIIIregion No script but has a region.

```
\def\@tracklang@test@if@file@exists@for@langIIIregion#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectRegion}%
  \@tracklang@verbose{Testing tag (639-3 [sublang] region) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
```

```

}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipregion
  \else

```

Try without sub-language.

```

  \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectRegion}%
  \@tracklang@verbose{Testing tag (639-3 [omit sublang] region)
    '\CurrentTrackedTag'}%
  \@tracklang@if@file@exists@next{\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipregion
  }%
  \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

s@for@langIskipscriptregion Already tested script and region. Test without script if the script is the default then without region.

```

\def\@tracklang@test@if@file@exists@for@langIskipscriptregion#1#2#3{%

```

Is the script the default for this dialect?

```

  \@tracklang@ifcseqcsname\CurrentTrackedDialectScript
    {\@tracklang@knowniso@script@\CurrentTrackedLanguage}%
  {%

```

Try just language code and region.

```

  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
  \@tracklang@verbose{Testing tag (639-1 [sublang] region) '\CurrentTrackedTag'}%
  \@tracklang@if@file@exists@next{\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty

```

Try just language code and script.

```

  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscripiskipr
  \else

```

Try without sub-language.

```
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-1 [omit sublang] region)
  '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscripiski
}%
\fi
}%
}%
{%
```

Script isn't the default.

```
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscripiski
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}
```

s@for@langIscripiski Test with script and without region.

```
\def\@tracklang@test@if@file@exists@for@langIscripiski#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-1 [sublang] script) '\CurrentTrackedTag'}%
  \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
```

Try just language code.

```
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIscripiski
\else
```

Try without sub-language.

```
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-1 [omit sublang] script)
  '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
```

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIskipscripts
    }%
    \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

or@langIskipscriptskipregion Test without script and without region.

```

\def\@tracklang@test@if@file@exists@for@langIskipscriptskipregion#1#2#3{%
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \ifx\CurrentTrackedDialectSubLang\empty
    \else
        \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
    \fi
    \@tracklang@verbose{Testing tag (639-1 [sublang]) ‘\CurrentTrackedTag’}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
        \let\@tracklang@if@file@exists\@tracklang@firstoftwo
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
        \ifx\CurrentTrackedDialectSubLang\empty

```

Try other language codes with script and region.

```

    \IfTrackedLanguageHasIsoCode
    {639-2}{\CurrentTrackedLanguage}
    {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptregio
    }%
    {%
        \IfTrackedLanguageHasIsoCode
        {639-3}{\CurrentTrackedLanguage}
        {%
            \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
            \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscript
        }%
        {%

```

No other language codes. Try just the region.

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
    }%
    \else

```

Try just language code.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-1 [omit sublang]) ‘\CurrentTrackedTag’}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%

```

```

{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%

```

Try other language codes with script and region.

```

\IfTrackedLanguageHasIsoCode
{639-2}{\CurrentTrackedLanguage}
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptregi
}%
{%
\IfTrackedLanguageHasIsoCode
{639-3}{\CurrentTrackedLanguage}
{%
\let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscript
}%
{%

```

No other language codes. Try just the region.

```

\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
}%
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

`\@for@langIIskipscriptregion` Already tested script and region. Test without script if the script is the default then without region.

```

\def\@tracklang@test@if@file@exists@for@langIIskipscriptregion#1#2#3{%

```

Is the script the default for this dialect?

```

\@tracklang@ifcseqcsname\CurrentTrackedDialectScript
{\@tracklang@knowniso@script@\CurrentTrackedLanguage}%
{%

```

Try just language code and region.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-2 [sublang] region) '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo

```

```

\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedDialectSubLang\empty

```

Try just language code and script.

```

\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptskip
\else

```

Try without sub-language.

```

\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-2 [omit sublang] region)
'\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptsk
}%
\fi
}%
}%
{%

```

Script isn't the default.

```

\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIscriptskipregi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

@for@langIIscriptskipregion Test with script and without region.

```

\def\@tracklang@test@if@file@exists@for@langIIscriptskipregion#1#2#3{%
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-2 [sublang] script) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedDialectSubLang\empty

```

Try just language code.

```

\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipscripstk
\else

```

Try without sub-language.

```
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-2 [omit sublang] script)
  '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIskipscripts
}%
\fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}
```

@langIIskipscriptsregion Test without script and without region.

```
\def\@tracklang@test@if@file@exists@for@langIIskipscriptsregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \@tracklang@verbose{Testing tag (639-2 [sublang]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
```

Try other language code with script and region.

```
\IfTrackedLanguageHasIsoCode
{639-3}{\CurrentTrackedLanguage}
{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptreg
}%
{%
```

No other language codes. Try just the region.

```
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
}%
\else
```

Try just language code.

```
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag (639-2 [omit sublang]) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
```



```

    {%
      \let\@tracklang@if@file@exists\@tracklang@firstoftwo
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%

```

Try other language codes with script and region.

```

    \IfTrackedLanguageHasIsoCode
    {639-3}{\CurrentTrackedLanguage}
    {%
      \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptreg
    }%
    {%

```

No other language codes. Try just the region.

```

      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
    }%
  }%
  \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

for@langIIIscriptregion Already tested script and region. Test without script if the script is the default then without region.

```

\def\@tracklang@test@if@file@exists@for@langIIIscriptregion#1#2#3{%
Is the script the default for this dialect?
\@tracklang@ifcseqcsname\CurrentTrackedDialectScript
{\@tracklang@knowniso@script@\CurrentTrackedLanguage}%
{%

```

Try just language code and region.

```

\let\CurrentTrackedTag\CurrentTrackedIsoCode
\ifx\CurrentTrackedDialectSubLang\empty
\else
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-3 [sublang] region) '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\ifx\CurrentTrackedDialectSubLang\empty

```

Try just language code and script.

```

\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscriptski
\else

```

Try without sub-language.

```
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang] region)
  '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscripsts
}%
\fi
}%
}%
{%
```

Script isn't the default.

```
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIscripsts@skipreg
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}
```

for@langIIIscripsts@skipregion Test with script and without region.

```
\def\@tracklang@test@if@file@exists@for@langIIIscripsts@skipregion#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectScript}%
  \@tracklang@verbose{Testing tag (639-3 [sublang] script) '\CurrentTrackedTag'}%
  \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
```

Try just language code.

```
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscripsts
\else
```

Try without sub-language.

```
\edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectScript}%
\@tracklang@verbose{Testing tag (639-3 [omit sublang] script)
  '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
```

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIskipscript
    }%
    \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

langIIIskipscriptskipregion Test without script and without region.

```

\def\@tracklang@test@if@file@exists@for@langIIIskipscriptskipregion#1#2#3{%
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \ifx\CurrentTrackedDialectSubLang\empty
    \else
        \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
    \fi
    \@tracklang@verbose{Testing tag (639-3 [sublang]) ‘\CurrentTrackedTag’}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
        \let\@tracklang@if@file@exists\@tracklang@firstoftwo
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%
        \ifx\CurrentTrackedDialectSubLang\empty

```

No other language codes. Try just the region.

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
    \else

```

Try just language code.

```

        \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \@tracklang@verbose{Testing tag (639-3 [omit sublang])
        ‘\CurrentTrackedTag’}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {%
        \let\@tracklang@if@file@exists\@tracklang@firstoftwo
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
    }%
    {%

```

No other language codes. Try just the region.

```

        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@region
    }%
    \fi
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

t@if@file@exists@for@langII No region or script.

```

\def\@tracklang@test@if@file@exists@for@langII#1#2#3{%

```

```

\IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
  \ifx\CurrentTrackedDialectSubLang\empty
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectSubLang}%
  \fi
  \@tracklang@verbose{Testing tag (639-2 [sublang]) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \ifx\CurrentTrackedDialectSubLang\empty
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII
    \else
      \let\CurrentTrackedTag\CurrentTrackedIsoCode
      \@tracklang@verbose{Testing tag (639-2 [omit sublang])
        '\CurrentTrackedTag'}%
      \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
      {%
        \let\@tracklang@if@file@exists\@tracklang@firstoftwo
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
      }%
      {%
        \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII
      }%
    \fi
  }%
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIII
  }%
  \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

\@if@file@exists@for@langIII No region or script.

```

\def\@tracklang@test@if@file@exists@for@langIII#1#2#3{%
  \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
  {%
    \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
    \ifx\CurrentTrackedDialectSubLang\empty
      \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \else
      \edef\CurrentTrackedTag{\CurrentTrackedIsoCode-\CurrentTrackedDialectSubLang}%
    \fi
    \@tracklang@verbose{Testing tag (639-3 [sublang]) '\CurrentTrackedTag'}%
  }%
}

```

```

\@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
{%
  \let\@tracklang@if@file@exists\@tracklang@firstoftwo
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
  \ifx\CurrentTrackedDialectSubLang\empty
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
  \else
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \@tracklang@verbose{Testing tag (639-3 [omit sublang])
    '\CurrentTrackedTag'}%
  \@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
  }%
  \fi
}%
}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

Allow region test to be skipped.

st@if@file@exists@for@region

```

\def\@tracklang@test@if@file@exists@for@region{%
  \@tracklang@test@if@file@exists@for@region
}

```

st@if@file@exists@for@region Test just the region.

```

\def\@tracklang@test@if@file@exists@for@region#1#2#3{%
  \let\CurrentTrackedTag\CurrentTrackedRegion
  \@tracklang@verbose{Testing tag (region) '\CurrentTrackedTag'}%
  \@tracklang@if@file@exists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langvariant
  }%
  \@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

le@exists@for@notregiononly Test just the region.

```
\def\@tracklang@test@if@file@exists@for@notregiononly#1#2#3{%  
  \@tracklang@test@if@file@exists@for@langvariant{#1}{#2}{#3}%  
}
```

file@exists@for@langvariant Test language code and variant

```
\def\@tracklang@test@if@file@exists@for@langvariant#1#2#3{%  
  \ifx\CurrentTrackedDialectVariant\empty  
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang  
  \else  
    \IfTrackedLanguageHasIsoCode{639-1}{\CurrentTrackedLanguage}%  
    {%  
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIvariant  
    }%  
    {%  
      \IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%  
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIvariant  
    }%  
    {%  
      \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%  
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIvariant  
    }%  
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang  
  }%  
}%  
\fi  
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%  
}
```

file@exists@for@langIvariant Test 639-1 code and variant

```
\def\@tracklang@test@if@file@exists@for@langIvariant#1#2#3{%  
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeI  
  \let\CurrentTrackedTag\CurrentTrackedIsoCode  
  \ifx\CurrentTrackedDialectSubLang\empty  
  \else  
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%  
  \fi  
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectVariant}%  
  \@tracklang@verbose{Testing tag (639-1 [sublang] variant) '\CurrentTrackedTag'}%  
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%  
  {%  
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo  
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop  
  }%  
  {%  
  }
```

```

\IfTrackedLanguageHasIsoCode{639-2}{\CurrentTrackedLanguage}%
{%
  \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIvariant
}
{%
  \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIvariant
  }
  {%
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang
  }%
}%
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

le@exists@for@langIIvariant Test 639-2 code and variant

```

\def\@tracklang@test@if@file@exists@for@langIIvariant#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else
    \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
  \fi
  \edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectVariant}%
  \@tracklang@verbose{Testing tag (639-2 [sublang] variant) '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {%
    \let\@tracklang@if@file@exists\@tracklang@firstoftwo
    \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
  }%
  {%
    \IfTrackedLanguageHasIsoCode{639-3}{\CurrentTrackedLanguage}%
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@langIIIvariant
    }
    {%
      \let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang
    }%
  }%
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

e@exists@for@langIIIvariant Test 639-3 code and variant

```

\def\@tracklang@test@if@file@exists@for@langIIIvariant#1#2#3{%
  \let\CurrentTrackedIsoCode\CurrentTrackedIsoCodeIII
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \ifx\CurrentTrackedDialectSubLang\empty
  \else

```

```

\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectSubLang}%
\fi
\edef\CurrentTrackedTag{\CurrentTrackedTag-\CurrentTrackedDialectVariant}%
\@tracklang@verbose{Testing tag (639-3 [sublang] variant) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@noop
}%
{%
\let\@tracklang@test@if@file@exists@next\@tracklang@test@if@file@exists@for@rootlang
}%
\@tracklang@test@if@file@exists@next{#1}{#2}{#3}%
}

```

\@tracklang@if@file@exists@for@rootlang Test the root language label. (Final test.)

```

\def\@tracklang@test@if@file@exists@for@rootlang#1#2#3{%
\let\CurrentTrackedTag\CurrentTrackedLanguage
\@tracklang@verbose{Testing tag (root) '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{%
\let\@tracklang@if@file@exists\@tracklang@firstoftwo
}%
{}}%
}

```

\CurrentTrackedLanguageFileExists@orig The new definition of \IfTrackedLanguageFileExists has a different order of priority. If the original behaviour is specifically required, this has the pre version 1.4 definition.

```

\long\def\IfTrackedLanguageFileExists@orig#1#2#3#4#5{%
\@tracklang@verbose{Finding file for dialect '#1' (pre-v1.4)}%
\def\CurrentTrackedTag{}%
\SetCurrentTrackedDialect{#1}%
\IfTrackedDialect{#1}%
{%
\edef\CurrentTrackedTag{#1}%
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{#4}%
{%
\IfTrackedLanguageHasIsoCode
{639-1}{\CurrentTrackedLanguage}
{%
\edef\CurrentTrackedIsoCode{%
\TrackedIsoCodeFromLanguage
{639-1}{\CurrentTrackedLanguage}}%
\ifx\CurrentTrackedRegion\empty
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
}
}
}
}
}

```



```

\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{#4}
{%
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \edef\CurrentTrackedIsoCode{%
      \TrackedIsoCodeFromLanguage
      {639-2}{\CurrentTrackedLanguage}}%
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
    {#4}%
    {%
      \let\CurrentTrackedTag\CurrentTrackedLanguage
      \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
      \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
    }%
  }%
  {%
    \let\CurrentTrackedTag\CurrentTrackedLanguage
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
  }%
}%
\else
\edef\CurrentTrackedTag{%
  \CurrentTrackedIsoCode-\CurrentTrackedRegion}%
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
{#4}
{%
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \let\org@currenttrackedisocode\CurrentTrackedIsoCode
    \edef\CurrentTrackedIsoCode{%
      \TrackedIsoCodeFromLanguage
      {639-2}{\CurrentTrackedLanguage}}%
    \edef\CurrentTrackedTag{%
      \CurrentTrackedIsoCode-\CurrentTrackedRegion}%
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
    {#4}%
    {%
      \let\CurrentTrackedTag\org@currenttrackedisocode
      \let\org@currenttrackedisocode\CurrentTrackedIsoCode
      \let\CurrentTrackedIsoCode\CurrentTrackedTag
      \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
      \@tracklang@ifFileExists{#2\CurrentTrackedTag#3}%
    }%
  }%
}

```

```

{#4}
{%
  \let\CurrentTrackedIsoCode\org@currenttrackedisocode
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {#4}%
  {%
    \let\CurrentTrackedTag\CurrentTrackedRegion
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {#4}%
    {%
      \let\CurrentTrackedTag\CurrentTrackedLanguage
      \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
      \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
    }%
  }%
}%
}%
}%
}%
\let\CurrentTrackedTag\CurrentTrackedIsoCode
\@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
\@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
{#4}%
{%
  \let\CurrentTrackedTag\CurrentTrackedRegion
  \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {#4}%
  {%
    \let\CurrentTrackedTag\CurrentTrackedLanguage
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
  }%
}%
}%
}%
\fi
}%
{%
  \IfTrackedLanguageHasIsoCode
  {639-2}{\CurrentTrackedLanguage}
  {%
    \edef\CurrentTrackedIsoCode{%
      \TrackedIsoCodeFromLanguage
      {639-2}{\CurrentTrackedLanguage}}%
  }%
  {%

```

```

\IfTrackedLanguageHasIsoCode
  {639-3}{\CurrentTrackedLanguage}
  {%
    \edef\CurrentTrackedIsoCode{%
      \TrackedIsoCodeFromLanguage
        {639-3}{\CurrentTrackedLanguage}}%
  }%
  {%
    \let\CurrentTrackedIsoCode\empty
  }%
}%
\ifx\CurrentTrackedIsoCode\empty
\ifx\CurrentTrackedRegion\empty
  \let\CurrentTrackedTag\CurrentTrackedLanguage
  \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
\else
  \let\CurrentTrackedTag\CurrentTrackedRegion
  \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {#4}%
  {%
    \let\CurrentTrackedTag\CurrentTrackedLanguage
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
  }%
\fi
\else
\ifx\CurrentTrackedRegion\empty
  \let\CurrentTrackedTag\CurrentTrackedIsoCode
  \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {#4}%
  {%
    \let\CurrentTrackedTag\CurrentTrackedLanguage
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}{#4}{#5}%
  }%
\else
  \edef\CurrentTrackedTag{%
    \CurrentTrackedIsoCode-\CurrentTrackedRegion}%
  \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
  \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
  {#4}%
  {%
    \let\CurrentTrackedTag\CurrentTrackedIsoCode
    \@tracklang@verbose{Testing tag '\CurrentTrackedTag'}%
    \@tracklang@IfFileExists{#2\CurrentTrackedTag#3}%
    {#4}%
  }%

```



```

    }
  \else
    \expandafter\xdef\csname ver@\TrackLangRequireDialectPrefix
      -#1.1df\endcsname{%
      {%
        \newlinechar='\^^J
        \def\MessageBreak{^^J}%
        \message{^^JFile: \TrackLangRequireDialectPrefix-#1.1df^^J}%
      }%
      \long\def\@tracklang@next{#2}%
    \fi
    \@tracklang@next
  }
\def\@tracklang@providesresource#1[#2]{%
\expandafter\xdef\csname ver@#1\endcsname{#2}%
{%
  \newlinechar='\^^J
  \def\MessageBreak{^^J}%
  \message{^^JFile: #1 #2^^J}%
}%
}
\else

```

LaTeX code can simply use \ProvidesFile.

```

\def\TrackLangProvidesResource#1{%
  \ifx\TrackLangRequireDialectPrefix\undefined
    \@tracklang@err{Resources files using
      \string\TrackLangProvidesResource\space
      must be loaded with \string\TrackLangRequireDialect}%
  \fi
  \expandafter\ProvidesFile\expandafter
    {\TrackLangRequireDialectPrefix-#1.1df}%
}
\fi

```

```
\TrackLangAddToHook{<code>}{<type>}
```

\TrackLangAddToHook

Within the resource files, a check is required for the language hook, where the hook type is given by *<type>*. For example, if *<type>* is `captions`, the for `babel`, this is `\captions<dialect>` (dialect obtained through `\CurrentTrackedDialect`) and for `polyglossia`, this is `\captions<language>` (language obtained through `\CurrentTrackedLanguage`). This command is not permitted outside resource files.

```
\def\TrackLangAddToHook{\noop@TrackLangAddToHook}
```

\noop@TrackLangAddToHook

```

\def\noop@TrackLangAddToHook#1#2{%
  \@tracklang@err{\string\TrackLangAddToHook\space

```

```

    only permitted within resource files}
  }

\@TrackLangAddToHook
  \def\@TrackLangAddToHook#1#2{%
babel check first.
  \@tracklang@ifundef{#2\CurrentTrackedDialect}%
  {%
Does the dialect label have a mapping?
  \IfTrackedDialectHasMapping{\CurrentTrackedDialect}%
  {%
Try the mapping label next.
  \edef\@tracklang@tmp{%
    \csname @tracklang@dialectmap@tohook@\CurrentTrackedDialect\endcsname}%
  \@tracklang@ifundef{#2\@tracklang@tmp}%
  {%
No captions hook. Try polyglossia.
  \@tracklang@ifundef{#2\CurrentTrackedLanguage}%
  {%
No captions hook. Do nothing (it's possible no language package has been
loaded).
  \@tracklang@verbose{no hook found for \CurrentTrackedDialect}%
  }%
  {%
  \@tracklang@addtohook{#2}{\CurrentTrackedLanguage}{#1}%
  }%
  }%
  {%
  \@tracklang@addtohook{#2}{\@tracklang@tmp}{#1}%
  }%
  }%
  {%
polyglossia check next.
  \@tracklang@ifundef{#2\CurrentTrackedLanguage}%
  {%
No captions hook.
  \@tracklang@verbose{no hook found for \CurrentTrackedDialect}%
  }%
  {%
  \@tracklang@addtohook{#2}{\CurrentTrackedLanguage}{#1}%
  }%
  }%
  }%
  {%
  \@tracklang@addtohook{#2}{\CurrentTrackedDialect}{#1}%
  }%

```

Do the code now. (This is needed for cases such as the `ngerman` which defines `\captionsngerman` but calls it immediately rather than at the start of the document.)

```
#1%
}
```

```
\@tracklang@addtohook{<type>}{<label>}{<code>}
```

`\@tracklang@addtohook`

```
\def\@tracklang@addtohook#1#2#3{%
\expandafter\let\expandafter\@tracklang@hook\csname #1#2\endcsname
\expandafter
\gdef\csname#1#2\expandafter\endcsname\expandafter{\@tracklang@hook#3}%
}
```

Since the captions hook is the most common, provide a shortcut.

```
\TrackLangAddToCaptions{<code>}
```

`\TrackLangAddToCaptions`

```
\def\TrackLangAddToCaptions#1{\TrackLangAddToHook{#1}{captions}}
```

```
\TrackLangRedefHook{<code>}{<type>}
```

`\TrackLangRedefHook`

Similar to `\TrackLangAddToHook` but redefines the hook rather than appending to it. This command is not permitted outside resource files.

```
\def\TrackLangRedefHook{\noop@TrackLangRedefHook}
```

`\noop@TrackLangRedefHook`

```
\def\noop@TrackLangRedefHook#1#2{%
\@tracklang@err{\string\TrackLangRedefHook\space
only permitted within resource files}
}
```

`\@TrackLangRedefHook`

```
\def\@TrackLangRedefHook#1#2{%
babel check first.
\@tracklang@ifundef{#2\CurrentTrackedDialect}%
{%
Does the dialect label have a mapping?
\IfTrackedDialectHasMapping{\CurrentTrackedDialect}%
{%
```

Try the mapping label next.

```
\edef\@tracklang@tmp{%
  \csname @tracklang@dialectmap@tohook@\CurrentTrackedDialect\endcsname}%
\@tracklang@ifundef{#2\@tracklang@tmp}%
{%
```

No captions hook. Try polyglossia.

```
\@tracklang@ifundef{#2\CurrentTrackedLanguage}%
{%
```

No captions hook. Do nothing (it's possible no language package has been loaded).

```
\@tracklang@verbose{no hook found for \CurrentTrackedDialect}%
}%
{%

\@tracklang@verbose{found '#2' hook '\CurrentTrackedLanguage' for
dialect \CurrentTrackedDialect}%
\@tracklang@redefhook{#2}{\CurrentTrackedLanguage}{#1}%
}%
}%
{%

\@tracklang@verbose{found '#2' hook '\@tracklang@tmp' for
dialect \CurrentTrackedDialect}%
\@tracklang@redefhook{#2}{\@tracklang@tmp}{#1}%
}%
}%
{%
```

polyglossia check next.

```
\@tracklang@ifundef{#2\CurrentTrackedLanguage}%
{%
```

No captions hook.

```
\@tracklang@verbose{no hook found for \CurrentTrackedDialect}%
}%
{%

\@tracklang@verbose{found '#2' hook '\CurrentTrackedLanguage' for
dialect \CurrentTrackedDialect}%
\@tracklang@redefhook{#2}{\CurrentTrackedLanguage}{#1}%
}%
}%
{%

\@tracklang@verbose{found '#2' hook '\CurrentTrackedDialect' for
dialect \CurrentTrackedDialect}%
\@tracklang@redefhook{#2}{\CurrentTrackedDialect}{#1}%
}%
```


Do the code now in case the hook has already been used.

```
#1%
}
```

\@tracklang@redefhook

```
\@tracklang@redefhook{<type>}{<label>}{<code>}
```

```
\def\@tracklang@redefhook#1#2#3{%
\expandafter\gdef\csname#1#2\endcsname{#3}%
}
```

\SetTrackedDialectLabelMap

```
\SetTrackedDialectLabelMap{<tracklang-label>}{<hook-label>}
```

Define a mapping between a tracklang dialect label and the corresponding label used by the language hook. For example, `ngermanDE` is a recognised tracklang dialect label, but the closest babel equivalent is `ngerman`, so `ngermanDE` would need to be mapped to `ngerman` for the language hooks. The arguments are `<tracklang-label>` (the tracklang dialect label) and `<hook-label>` (the babel, polyglossia etc label).

```
\def\SetTrackedDialectLabelMap#1#2{%
```

Store the mapping that can obtain the hook label from the tracklang label (tracklang to hook).

```
\@tracklang@enamedef{\@tracklang@dialectmap@tohook@#1}{#2}%
```

Store the mapping that can obtain the tracklang label from the hook label.

```
\@tracklang@enamedef{\@tracklang@dialectmap@fromhook@#2}{#1}%
}
```

\IfTrackedDialectHasMapping

```
\IfTrackedDialectHasMapping{<tracklang label>}{<true>}
{<false>}
```

Test if the tracklang dialect label has been assigned a mapping to a language hook.

```
\def\IfTrackedDialectHasMapping#1#2#3{%
\@tracklang@ifundef{\@tracklang@dialectmap@tohook@#1}{#3}{#2}%
}
```

\HasMappingFromTrackedDialect

```
\IfHookHasMappingFromTrackedDialect{<hook label>}{<true>}
{<false>}
```

Tests if the language hook label has been assigned a mapping from a tracklang dialect label.

```
\def\IfHookHasMappingFromTrackedDialect#1#2#3{%
  \@tracklang@ifundef{@tracklang@dialectmap@fromhook@#1}{#3}{#2}%
}
```

```
\GetTrackedDialectToMapping{<tracklang label>}
```

\GetTrackedDialectToMapping

Gets the mapping for the given tracklang dialect label to a language hook label or the *<label>* itself if no mapping has been defined.

```
\def\GetTrackedDialectToMapping#1{%
  \@tracklang@ifundef{@tracklang@dialectmap@tohook@#1}{#1}%
  {\csname @tracklang@dialectmap@tohook@#1\endcsname}%
}
```

```
\GetTrackedDialectFromMapping{<language hook>}
```

\GetTrackedDialectFromMapping

Gets the reverse mapping from the given language hook to the tracklang label.

```
\def\GetTrackedDialectFromMapping#1{%
  \@tracklang@ifundef{@tracklang@dialectmap@fromhook@#1}{#1}%
  {\csname @tracklang@dialectmap@fromhook@#1\endcsname}%
}
```

```
\TrackLangRequireResource{<tag>}
```

\TrackLangRequireResource

```
\def\TrackLangRequireResource{\noop@TrackLangRequireResource}
```

\noop@TrackLangRequireResource

Default behaviour outside of resources files: generate an error and ignore arguments.

```
\def\noop@TrackLangRequireResource#1{%
  \@tracklang@err{\string\TrackLangRequireResource\space
  only permitted within resource files}
}
```

\@TrackLangRequireResource

Actual behaviour.

```
\def\@TrackLangRequireResource#1{%
  \@tracklang@ifundef{ver@TrackLangRequireDialectPrefix-#1.ldf}%
  {%
    \@tracklang@iffileexists{\TrackLangRequireDialectPrefix-#1.ldf}%
    {%
      \@tracklang@inputfile{\TrackLangRequireDialectPrefix-#1.ldf}%
    }%
    {%
      \@tracklang@warn{No ‘\TrackLangRequireDialectPrefix’ support for
      language/region ‘#1’\MessageBreak
      (resource file ‘\TrackLangRequireDialectPrefix-#1.ldf’ not found)}%
    }%
  }%
}
```

```

    }%
  }%
  {}%
}

```

```

\TrackLangRequireResourceOrDo{<tag>}{<resource
loaded code>}{<resource already loaded code>}

```

\TrackLangRequireResourceOrDo

Like \TrackLangRequireResource but also does *<resource loaded code>* if the resource file is loaded or *<resource already loaded code>* if the resource file has already been loaded.

```

\def\TrackLangRequireResourceOrDo{%
  \noop@TrackLangRequireResourceOrDo
}

```

\TrackLangRequireResourceOrDo

Default behaviour outside of resources files: generate an error and ignore arguments.

```

\def\noop@TrackLangRequireResourceOrDo#1#2#3{%
  \@tracklang@err{\string\TrackLangRequireResourceOrDo\space
  only permitted within resource files}
}

```

\TrackLangRequireResourceOrDo

Actual behaviour.

```

\def\@TrackLangRequireResourceOrDo#1#2#3{%
  \@tracklang@ifundef{ver@\TrackLangRequireDialectPrefix-#1.ldf}%
  {%
    \@tracklang@ifFileExists{\TrackLangRequireDialectPrefix-#1.ldf}%
    {%
      \@tracklang@inputfile{\TrackLangRequireDialectPrefix-#1.ldf}%
      #2%
    }%
    {%
      \@tracklang@warn{No ‘\TrackLangRequireDialectPrefix’ support for
      language/region ‘#1’\MessageBreak
      (resource file ‘\TrackLangRequireDialectPrefix-#1.ldf’ not found)}%
    }%
  }%
  {#3}%
}

```

```

\TrackLangRequestResource{<tag>}{<not found code>}

```

\TrackLangRequestResource

Like \TrackLangRequireResource but does *<not found code>* if the file doesn't exist.

```

\def\TrackLangRequestResource{\noop@TrackLangRequestResource}

```

`\noop@TrackLangRequestResource` Default behaviour outside of resources files: generate an error and ignore arguments.

```
\def\noop@TrackLangRequestResource#1#2{%
  \@tracklang@err{\string\TrackLangRequestResource\space
  only permitted within resource files}
}
```

`\@TrackLangRequestResource` Actual behaviour.

```
\def\@TrackLangRequestResource#1#2{%
  \@tracklang@ifundef{ver@\TrackLangRequireDialectPrefix-#1.ldf}%
  {%
    \@tracklang@ifFileExists{\TrackLangRequireDialectPrefix-#1.ldf}%
    {%
      \@tracklang@inputfile{\TrackLangRequireDialectPrefix-#1.ldf}%
    }%
  }%
  {#2}%
}%
{}}%
```

`\TrackLangRequireDialect` [*load code*] {*pkgname*} {*dialect*}

```
\def\TrackLangRequireDialect{\@TrackLangRequireDialect}
```

`\noop@TrackLangRequireDialect` No-op code.

```
\def\noop@TrackLangRequireDialect#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@noop@TrackLangRequireDialect[]}%
  \else
    \def\@tracklang@next{\@noop@TrackLangRequireDialect[] {#1}}%
  \fi
  \@tracklang@next
}
\def\@noop@TrackLangRequireDialect[#1]#2#3{%
  \@tracklang@err{\string\TrackLangRequireDialect...\space
  only permitted within resource files}
}
```

`\@TrackLangRequireDialect` Actual code.

```
\def\@TrackLangRequireDialect#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@TrackLangRequireDialect[]}%
  \else
    \def\@tracklang@next{%
      \@TrackLangRequireDialect
      [\TrackLangRequireResource{\CurrentTrackedTag}] {#1}}%
  \fi
}
```

```

    \@tracklang@next
  }
\def\@@TrackLangRequireDialect[#1]#2#3{%
  \def\TrackLangRequireDialectPrefix{#2}%
  \IfTrackedLanguageFileExists{#3}%
  {#2-}% prefix
  {.ldf}% suffix
  {%
    \@TrackLang@RequireDialect{#1}%
  }%
  {%
    \@tracklang@warn{No '#2' support for dialect '#3'
    \ifTrackLangShowWarnings
    \else
      (switch on tracklang's verbose mode for search attempts)
    \fi
  }%
  }%
}

```

\@@TrackLang@RequireDialect

```
\def\@@TrackLang@RequireDialect#1{%
```

Enable \TrackLangRequireResource etc so that they can only be used in resource files.

```

\let\TrackLangRequireResource\@TrackLangRequireResource
\let\TrackLangRequireResourceOrDo\@TrackLangRequireResourceOrDo
\let\TrackLangRequestResource\@TrackLangRequestResource

```

Disable \TrackLangRequireDialect etc so that they can't be used in resource files.

```

\let\TrackLangRequireDialect\noop@TrackLangRequireDialect
\let\TrackLangRequireDialectOmitDialectLabel\noop@TrackLangRequireDialect
\let\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
  \noop@TrackLangRequireDialect
\let\TrackLangRequireDialectOmitOnlyRegion\noop@TrackLangRequireDialect

```

Enable \TrackLangAddToHook.

```
\let\TrackLangAddToHook\@TrackLangAddToHook
```

Load resource file using the code provided in the first argument.

```
#1%
```

Disable \TrackLangRequireResource etc.

```

\let\TrackLangRequireResource\noop@TrackLangRequireResource
\let\TrackLangRequireResourceOrDo\noop@TrackLangRequireResourceOrDo
\let\TrackLangRequestResource\noop@TrackLangRequestResource

```

Enable \TrackLangRequireDialect etc.

```

\let\TrackLangRequireDialect\@TrackLangRequireDialect
\let\TrackLangRequireDialectOmitDialectLabel
  \@TrackLangRequireDialectOmitDialectLabel

```

```

\let\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
  \@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
\let\TrackLangRequireDialectOmitOnlyRegion
  \@TrackLangRequireDialectOmitOnlyRegion
Disable \TrackLangAddToHook.
\let\TrackLangAddToHook\noop@TrackLangAddToHook
}

```

```

\TrackLangRequireDialectOmitDialectLabel[⟨load code⟩]
{⟨pkgname⟩}{⟨dialect⟩}

```

quireDialectOmitDialectLabel

```

\def\TrackLangRequireDialectOmitDialectLabel{%
  \@TrackLangRequireDialectOmitDialectLabel}

```

quireDialectOmitDialectLabel Actual code.

```

\def\@TrackLangRequireDialectOmitDialectLabel#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@TrackLangRequireDialectOmitDialectLabel[]%
  \else
    \def\@tracklang@next{%
      \@TrackLangRequireDialectOmitDialectLabel
        [\TrackLangRequireResource{\CurrentTrackedTag}]{#1}}%
    \fi
    \@tracklang@next
  }
\def\@@TrackLangRequireDialectOmitDialectLabel[#1]#2#3{%
  \def\TrackLangRequireDialectPrefix{#2}%
  \IfTrackedLanguageFileExistsOmitDialectLabel{#3}%
  {#2-}% prefix
  {.ldf}% suffix
  {%
    \@TrackLang@RequireDialect{#1}%
  }%
  {%
    \@tracklang@warn{No ‘#2’ support for dialect ‘#3’
    \ifTrackLangShowWarnings
    \else
      (switch on tracklang’s verbose mode for search attempts)
    \fi
  }%
  }%
}

```

```

\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion[⟨load
code⟩]{⟨pkgname⟩}{⟨dialect⟩}

```

lectOmitLabelOmitOnlyRegion

```

\def\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion{%
  \@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion}

```

tDialectLabelOmitOnlyRegion Actual code.

```

\def\@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion[]}%
  \else
    \def\@tracklang@next{%
      \@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion
        [\TrackLangRequireResource{\CurrentTrackedTag}]{#1}}%
    \fi
  \@tracklang@next
}
\def\@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion[#1]#2#3{%
  \def\TrackLangRequireDialectPrefix{#2}%
  \IfTrackedLanguageFileExistsOmitDialectLabelOmitOnlyRegion{#3}%
  {#2-}% prefix
  {.ldf}% suffix
  {%
    \@TrackLang@RequireDialect{#1}%
  }%
  {%
    \@tracklang@warn{No '#2' support for dialect '#3'
      \ifTrackLangShowWarnings
        \else
          (switch on tracklang's verbose mode for search attempts)
        \fi
    }%
  }%
}

```

```

\TrackLangRequireDialectOmitOnlyRegion[<load code>]
  {<pkgname>}{<dialect>}

```

RequireDialectOmitOnlyRegion

```

\def\TrackLangRequireDialectOmitOnlyRegion{%
  \@TrackLangRequireDialectOmitOnlyRegion}

```

RequireDialectOmitOnlyRegion Actual code.

```

\def\@TrackLangRequireDialectOmitOnlyRegion#1{%
  \ifx[#1\relax
    \def\@tracklang@next{\@TrackLangRequireDialectOmitOnlyRegion[]}%
  \else
    \def\@tracklang@next{%
      \@TrackLangRequireDialectOmitOnlyRegion
        [\TrackLangRequireResource{\CurrentTrackedTag}]{#1}}%
    \fi
  \@tracklang@next
}

```

```

}
\def\@@TrackLangRequireDialectOmitOnlyRegion[#1]#2#3{%
  \def\TrackLangRequireDialectPrefix{#2}%
  \IfTrackedLanguageFileExistsOmitOnlyRegion{#3}%
  {#2-}% prefix
  {.ldf}% suffix
  {%
    \@@TrackLang@RequireDialect{#1}%
  }%
  {%
    \@tracklang@warn{No '#2' support for dialect '#3'
    \ifTrackLangShowWarnings
    \else
      (switch on tracklang's verbose mode for search attempts)
    \fi
  }%
}%
}

```

Restore category code for @ if necessary.

```
\@tracklang@restore@at
```

5 Regions Generic Code (tracklang-region-codes.tex)

This is only loaded if a mapping is required between numeric and alphabetic region codes. (It would slow down the package loading to automatically load if not required.) Since this is loaded on the fly, we need to be careful about spurious spaces.

```

\ifnum\catcode'\@=11\relax
  \def\@tracklang@regions@restore@at{%
\else
  \expandafter\edef\csname @tracklang@regions@restore@at\endcsname{%
    \noexpand\catcode'\noexpand\@=\number\catcode'\@ \relax
  }%
  \catcode'\@=11\relax
\fi

```

Check if this file has already been loaded:

```

\ifx\TrackLangRegionMap\undefined
\else
  \@tracklang@regions@restore@at
  \expandafter\endinput
\fi

```

Version info.

```

\expandafter\def\csname ver@tracklang-region-codes.tex\endcsname{%
  2025/03/04 v1.6.5 (NLCT) Track Languages Regions}%

```


\TrackLangRegionMap

```
\TrackLangRegionMap{<numeric code>}{<alpha-2 code>}{<alpha-3 code>}
```

Define mapping.

```
\def\TrackLangRegionMap#1#2#3{%
  \@tracklang@enamedef{@tracklang@region@numtoalphaii@#1}{#2}%
  \@tracklang@enamedef{@tracklang@region@numtoalphaiii@#1}{#3}%
  \@tracklang@enamedef{@tracklang@region@alphaiitonum@#2}{#1}%
  \@tracklang@enamedef{@tracklang@region@alphaiiitonum@#3}{#1}%
  \@tracklang@enamedef{@tracklang@region@alphaiiitoalphaiii@#2}{#3}%
  \@tracklang@enamedef{@tracklang@region@alphaiiitoalphaii@#3}{#2}%
}%
```

\TrackLangAlphaIIToNumericRegion

```
\TrackLangAlphaIIToNumericRegion{<alpha-2 code>}
```

```
\def\TrackLangAlphaIIToNumericRegion#1{%
  \@tracklang@nameuse{@tracklang@region@alphaiitonum@#1}%
}%
```

\TrackLangNumericToAlphaIIRegion

```
\TrackLangNumericToAlphaIIRegion{<numeric code>}
```

```
\def\TrackLangNumericToAlphaIIRegion#1{%
  \@tracklang@nameuse{@tracklang@region@numtoalphaii@#1}%
}%
```

\TrackLangIfKnownAlphaIIRegion

```
\TrackLangIfKnownAlphaIIRegion{<alpha-2 code>}{<true>}{<false>}
```

```
\def\TrackLangIfKnownAlphaIIRegion#1#2#3{%
  \@tracklang@ifundef{@tracklang@region@alphaiitonum@#1}%
  {#3}%
  {#2}%
}%
```

\TrackLangIfKnownNumericRegion

```
\TrackLangIfKnownNumericRegion{<numeric code>}{<true>}{<false>}
```

```

\def\TrackLangIfKnownNumericRegion#1#2#3{%
  \@tracklang@ifundef{@tracklang@region@numtoalphaii@#1}%
  {#3}%
  {#2}%
}%

```

\TrackLangAlphaIIIToNumericRegion{*alpha-3 code*}

\TrackLangAlphaIIIToNumericRegion

```

\def\TrackLangAlphaIIIToNumericRegion#1{%
  \@tracklang@nameuse{@tracklang@region@alphaiiitonum@#1}%
}%

```

\TrackLangNumericToAlphaIIIRRegion{*numeric code*}

\TrackLangNumericToAlphaIIIRRegion

```

\def\TrackLangNumericToAlphaIIIRRegion#1{%
  \@tracklang@nameuse{@tracklang@region@numtoalphaii@#1}%
}%

```

\TrackLangIfKnownAlphaIIIRRegion{*alpha-3 code*}{*true*}{*false*}

\TrackLangIfKnownAlphaIIIRRegion

```

\def\TrackLangIfKnownAlphaIIIRRegion#1#2#3{%
  \@tracklang@ifundef{@tracklang@region@alphaiiitonum@#1}%
  {#3}%
  {#2}%
}%

```

Define mappings.

```

\TrackLangRegionMap{004}{AF}{AFG}%
\TrackLangRegionMap{248}{AX}{ALA}%
\TrackLangRegionMap{008}{AL}{ALB}%
\TrackLangRegionMap{012}{DZ}{DZA}%
\TrackLangRegionMap{016}{AS}{ASM}%
\TrackLangRegionMap{020}{AD}{AND}%
\TrackLangRegionMap{024}{AO}{AGO}%
\TrackLangRegionMap{660}{AI}{AIA}%
\TrackLangRegionMap{010}{AQ}{ATA}%
\TrackLangRegionMap{028}{AG}{ATG}%
\TrackLangRegionMap{032}{AR}{ARG}%
\TrackLangRegionMap{051}{AM}{ARM}%
\TrackLangRegionMap{533}{AW}{ABW}%

```

\\TrackLangRegionMap{036}{AU}{AUS}%
\\TrackLangRegionMap{040}{AT}{AUT}%
\\TrackLangRegionMap{031}{AZ}{AZE}%
\\TrackLangRegionMap{044}{BS}{BHS}%
\\TrackLangRegionMap{048}{BH}{BHR}%
\\TrackLangRegionMap{050}{BD}{BGD}%
\\TrackLangRegionMap{052}{BB}{BRB}%
\\TrackLangRegionMap{112}{BY}{BLR}%
\\TrackLangRegionMap{056}{BE}{BEL}%
\\TrackLangRegionMap{084}{BZ}{BLZ}%
\\TrackLangRegionMap{204}{BJ}{BEN}%
\\TrackLangRegionMap{060}{BM}{BMU}%
\\TrackLangRegionMap{064}{BT}{BTN}%
\\TrackLangRegionMap{068}{BO}{BOL}%
\\TrackLangRegionMap{535}{BQ}{BES}%
\\TrackLangRegionMap{070}{BA}{BIH}%
\\TrackLangRegionMap{072}{BW}{BWA}%
\\TrackLangRegionMap{074}{BV}{BVT}%
\\TrackLangRegionMap{076}{BR}{BRA}%
\\TrackLangRegionMap{086}{IO}{IOT}%
\\TrackLangRegionMap{096}{BN}{BRN}%
\\TrackLangRegionMap{100}{BG}{BGR}%
\\TrackLangRegionMap{854}{BF}{BFA}%
\\TrackLangRegionMap{108}{BI}{BDI}%
\\TrackLangRegionMap{132}{CV}{CPV}%
\\TrackLangRegionMap{116}{KH}{KHM}%
\\TrackLangRegionMap{120}{CM}{CMR}%
\\TrackLangRegionMap{124}{CA}{CAN}%
\\TrackLangRegionMap{136}{KY}{CYM}%
\\TrackLangRegionMap{140}{CF}{CAF}%
\\TrackLangRegionMap{148}{TD}{TCD}%
\\TrackLangRegionMap{152}{CL}{CHL}%
\\TrackLangRegionMap{156}{CN}{CHN}%
\\TrackLangRegionMap{162}{CX}{CXR}%
\\TrackLangRegionMap{166}{CC}{CCK}%
\\TrackLangRegionMap{170}{CO}{COL}%
\\TrackLangRegionMap{174}{KM}{COM}%
\\TrackLangRegionMap{180}{CD}{COD}%
\\TrackLangRegionMap{178}{CG}{COG}%
\\TrackLangRegionMap{184}{CK}{COK}%
\\TrackLangRegionMap{188}{CR}{CRI}%
\\TrackLangRegionMap{384}{CI}{CIV}%
\\TrackLangRegionMap{191}{HR}{HRV}%
\\TrackLangRegionMap{192}{CU}{CUB}%
\\TrackLangRegionMap{531}{CW}{CUW}%
\\TrackLangRegionMap{196}{CY}{CYP}%
\\TrackLangRegionMap{203}{CZ}{CZE}%
\\TrackLangRegionMap{208}{DK}{DNK}%
\\TrackLangRegionMap{262}{DJ}{DJI}%
\\TrackLangRegionMap{212}{DM}{DMA}%

\TrackLangRegionMap{214}{DO}{DOM}%
\TrackLangRegionMap{218}{EC}{ECU}%
\TrackLangRegionMap{818}{EG}{EGY}%
\TrackLangRegionMap{222}{SV}{SLV}%
\TrackLangRegionMap{226}{GQ}{GNQ}%
\TrackLangRegionMap{232}{ER}{ERI}%
\TrackLangRegionMap{233}{EE}{EST}%
\TrackLangRegionMap{231}{ET}{ETH}%
\TrackLangRegionMap{238}{FK}{FLK}%
\TrackLangRegionMap{234}{FO}{FRO}%
\TrackLangRegionMap{242}{FJ}{FJI}%
\TrackLangRegionMap{246}{FI}{FIN}%
\TrackLangRegionMap{250}{FR}{FRA}%
\TrackLangRegionMap{254}{GF}{GUF}%
\TrackLangRegionMap{258}{PF}{PYF}%
\TrackLangRegionMap{260}{TF}{ATF}%
\TrackLangRegionMap{266}{GA}{GAB}%
\TrackLangRegionMap{270}{GM}{GMB}%
\TrackLangRegionMap{268}{GE}{GEO}%
\TrackLangRegionMap{276}{DE}{DEU}%
\TrackLangRegionMap{288}{GH}{GHA}%
\TrackLangRegionMap{292}{GI}{GIB}%
\TrackLangRegionMap{300}{GR}{GRC}%
\TrackLangRegionMap{304}{GL}{GRL}%
\TrackLangRegionMap{308}{GD}{GRD}%
\TrackLangRegionMap{312}{GP}{GLP}%
\TrackLangRegionMap{316}{GU}{GUM}%
\TrackLangRegionMap{320}{GT}{GTM}%
\TrackLangRegionMap{831}{GG}{GGY}%
\TrackLangRegionMap{324}{GN}{GIN}%
\TrackLangRegionMap{624}{GW}{GNB}%
\TrackLangRegionMap{328}{GY}{GUY}%
\TrackLangRegionMap{332}{HT}{HTI}%
\TrackLangRegionMap{334}{HM}{HMD}%
\TrackLangRegionMap{336}{VA}{VAT}%
\TrackLangRegionMap{340}{HN}{HND}%
\TrackLangRegionMap{344}{HK}{HKG}%
\TrackLangRegionMap{348}{HU}{HUN}%
\TrackLangRegionMap{352}{IS}{ISL}%
\TrackLangRegionMap{356}{IN}{IND}%
\TrackLangRegionMap{360}{ID}{IDN}%
\TrackLangRegionMap{364}{IR}{IRN}%
\TrackLangRegionMap{368}{IQ}{IRQ}%
\TrackLangRegionMap{372}{IE}{IRL}%
\TrackLangRegionMap{833}{IM}{IMN}%
\TrackLangRegionMap{376}{IL}{ISR}%
\TrackLangRegionMap{380}{IT}{ITA}%
\TrackLangRegionMap{388}{JM}{JAM}%
\TrackLangRegionMap{392}{JP}{JPN}%
\TrackLangRegionMap{832}{JE}{JEY}%

\TrackLangRegionMap{400}{JO}{JOR}%
\TrackLangRegionMap{398}{KZ}{KAZ}%
\TrackLangRegionMap{404}{KE}{KEN}%
\TrackLangRegionMap{296}{KI}{KIR}%
\TrackLangRegionMap{408}{KP}{PRK}%
\TrackLangRegionMap{410}{KR}{KOR}%
\TrackLangRegionMap{414}{KW}{KWT}%
\TrackLangRegionMap{417}{KG}{KGZ}%
\TrackLangRegionMap{418}{LA}{LAO}%
\TrackLangRegionMap{428}{LV}{LVA}%
\TrackLangRegionMap{422}{LB}{LBN}%
\TrackLangRegionMap{426}{LS}{LSO}%
\TrackLangRegionMap{430}{LR}{LBR}%
\TrackLangRegionMap{434}{LY}{LBY}%
\TrackLangRegionMap{438}{LI}{LIE}%
\TrackLangRegionMap{440}{LT}{LTU}%
\TrackLangRegionMap{442}{LU}{LUX}%
\TrackLangRegionMap{446}{MO}{MAC}%
\TrackLangRegionMap{807}{MK}{MKD}%
\TrackLangRegionMap{450}{MG}{MDG}%
\TrackLangRegionMap{454}{MW}{MWI}%
\TrackLangRegionMap{458}{MY}{MYS}%
\TrackLangRegionMap{462}{MV}{MDV}%
\TrackLangRegionMap{466}{ML}{MLI}%
\TrackLangRegionMap{470}{MT}{MLT}%
\TrackLangRegionMap{584}{MH}{MHL}%
\TrackLangRegionMap{474}{MQ}{MTQ}%
\TrackLangRegionMap{478}{MR}{MRT}%
\TrackLangRegionMap{480}{MU}{MUS}%
\TrackLangRegionMap{175}{YT}{MYT}%
\TrackLangRegionMap{484}{MX}{MEX}%
\TrackLangRegionMap{583}{FM}{FSM}%
\TrackLangRegionMap{498}{MD}{MDA}%
\TrackLangRegionMap{492}{MC}{MCO}%
\TrackLangRegionMap{496}{MN}{MNG}%
\TrackLangRegionMap{499}{ME}{MNE}%
\TrackLangRegionMap{500}{MS}{MSR}%
\TrackLangRegionMap{504}{MA}{MAR}%
\TrackLangRegionMap{508}{MZ}{MOZ}%
\TrackLangRegionMap{104}{MM}{MMR}%
\TrackLangRegionMap{516}{NA}{NAM}%
\TrackLangRegionMap{520}{NR}{NRU}%
\TrackLangRegionMap{524}{NP}{NPL}%
\TrackLangRegionMap{528}{NL}{NLD}%
\TrackLangRegionMap{540}{NC}{NCL}%
\TrackLangRegionMap{554}{NZ}{NZL}%
\TrackLangRegionMap{558}{NI}{NIC}%
\TrackLangRegionMap{562}{NE}{NER}%
\TrackLangRegionMap{566}{NG}{NGA}%
\TrackLangRegionMap{570}{NU}{NIU}%

\\TrackLangRegionMap{574}{NF}{NFK}%
\\TrackLangRegionMap{580}{MP}{MNP}%
\\TrackLangRegionMap{578}{NO}{NOR}%
\\TrackLangRegionMap{512}{OM}{OMN}%
\\TrackLangRegionMap{586}{PK}{PAK}%
\\TrackLangRegionMap{585}{PW}{PLW}%
\\TrackLangRegionMap{275}{PS}{PSE}%
\\TrackLangRegionMap{591}{PA}{PAN}%
\\TrackLangRegionMap{598}{PG}{PNG}%
\\TrackLangRegionMap{600}{PY}{PRY}%
\\TrackLangRegionMap{604}{PE}{PER}%
\\TrackLangRegionMap{608}{PH}{PHL}%
\\TrackLangRegionMap{612}{PN}{PCN}%
\\TrackLangRegionMap{616}{PL}{POL}%
\\TrackLangRegionMap{620}{PT}{PRT}%
\\TrackLangRegionMap{630}{PR}{PRI}%
\\TrackLangRegionMap{634}{QA}{QAT}%
\\TrackLangRegionMap{638}{RE}{REU}%
\\TrackLangRegionMap{642}{RO}{ROU}%
\\TrackLangRegionMap{643}{RU}{RUS}%
\\TrackLangRegionMap{646}{RW}{RWA}%
\\TrackLangRegionMap{652}{BL}{BLM}%
\\TrackLangRegionMap{654}{SH}{SHN}%
\\TrackLangRegionMap{659}{KN}{KNA}%
\\TrackLangRegionMap{662}{LC}{LCA}%
\\TrackLangRegionMap{663}{MF}{MAF}%
\\TrackLangRegionMap{666}{PM}{SPM}%
\\TrackLangRegionMap{670}{VC}{VCT}%
\\TrackLangRegionMap{882}{WS}{WSM}%
\\TrackLangRegionMap{674}{SM}{SMR}%
\\TrackLangRegionMap{678}{ST}{STP}%
\\TrackLangRegionMap{682}{SA}{SAU}%
\\TrackLangRegionMap{686}{SN}{SEN}%
\\TrackLangRegionMap{688}{RS}{SRB}%
\\TrackLangRegionMap{690}{SC}{SYC}%
\\TrackLangRegionMap{694}{SL}{SLE}%
\\TrackLangRegionMap{702}{SG}{SGP}%
\\TrackLangRegionMap{534}{SX}{SXM}%
\\TrackLangRegionMap{703}{SK}{SVK}%
\\TrackLangRegionMap{705}{SI}{SVN}%
\\TrackLangRegionMap{090}{SB}{SLB}%
\\TrackLangRegionMap{706}{SO}{SOM}%
\\TrackLangRegionMap{710}{ZA}{ZAF}%
\\TrackLangRegionMap{239}{GS}{SGS}%
\\TrackLangRegionMap{728}{SS}{SSD}%
\\TrackLangRegionMap{724}{ES}{ESP}%
\\TrackLangRegionMap{144}{LK}{LKA}%
\\TrackLangRegionMap{729}{SD}{SDN}%
\\TrackLangRegionMap{740}{SR}{SUR}%
\\TrackLangRegionMap{744}{SJ}{SJM}%

```

\TrackLangRegionMap{748}{SZ}{SWZ}%
\TrackLangRegionMap{752}{SE}{SWE}%
\TrackLangRegionMap{756}{CH}{CHE}%
\TrackLangRegionMap{760}{SY}{SYR}%
\TrackLangRegionMap{158}{TW}{TWN}%
\TrackLangRegionMap{762}{TJ}{TJK}%
\TrackLangRegionMap{834}{TZ}{TZA}%
\TrackLangRegionMap{764}{TH}{THA}%
\TrackLangRegionMap{626}{TL}{TLS}%
\TrackLangRegionMap{768}{TG}{TGO}%
\TrackLangRegionMap{772}{TK}{TKL}%
\TrackLangRegionMap{776}{TO}{TON}%
\TrackLangRegionMap{780}{TT}{TTO}%
\TrackLangRegionMap{788}{TN}{TUN}%
\TrackLangRegionMap{792}{TR}{TUR}%
\TrackLangRegionMap{795}{TM}{TKM}%
\TrackLangRegionMap{796}{TC}{TCA}%
\TrackLangRegionMap{798}{TV}{TUV}%
\TrackLangRegionMap{800}{UG}{UGA}%
\TrackLangRegionMap{804}{UA}{UKR}%
\TrackLangRegionMap{784}{AE}{ARE}%
\TrackLangRegionMap{826}{GB}{GBR}%
\TrackLangRegionMap{581}{UM}{UMI}%
\TrackLangRegionMap{840}{US}{USA}%
\TrackLangRegionMap{858}{UY}{URY}%
\TrackLangRegionMap{860}{UZ}{UZB}%
\TrackLangRegionMap{548}{VU}{VUT}%
\TrackLangRegionMap{862}{VE}{VEN}%
\TrackLangRegionMap{704}{VN}{VNM}%
\TrackLangRegionMap{092}{VG}{VGB}%
\TrackLangRegionMap{850}{VI}{VIR}%
\TrackLangRegionMap{876}{WF}{WLF}%
\TrackLangRegionMap{732}{EH}{ESH}%
\TrackLangRegionMap{887}{YE}{YEM}%
\TrackLangRegionMap{894}{ZM}{ZMB}%
\TrackLangRegionMap{716}{ZW}{ZWE}%

\@tracklang@input@extra@region@files
  Restore category code of @.
\@tracklang@regions@restore@at

```

6 ISO 15924 Scripts L^AT_EX Package (tracklang-scripts.sty)

This is just a L^AT_EX package wrapper for the generic code in tracklang-scripts.tex.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{tracklang-scripts}[2025/03/04 v1.6.5 (NLCT) Track
Language Scripts (LaTeX)]

```

```
\RequirePackage{tracklang}
\input{tracklang-scripts}
```

7 ISO 15924 Scripts Generic Code (tracklang-scripts.tex)

Provides information about ISO 15924 scripts. Not automatically loaded.

```
\ifnum\catcode'\@=11\relax
  \def\@tracklang@scripts@restore@at{ }%
\else
  \expandafter\edef\csname @tracklang@scripts@restore@at\endcsname{%
    \noexpand\catcode'\noexpand\@=\number\catcode'\@ \relax
  }%
  \catcode'\@=11\relax
\fi
```

Check if this file has already been loaded:

```
\ifx\TrackLangScriptMap\undefined
\else
  \@tracklang@scripts@restore@at
  \expandafter\endinput
\fi
```

Version info.

```
\expandafter\def\csname ver@tracklang-scripts.tex\endcsname{%
  2025/03/04 v1.6.5 (NLCT) Track Languages Scripts (Generic)}%
```

```
\TrackLangScriptMap{<letter
code>}{<number>}{<name>}{<direction>}{<parent>}
```

\TrackLangScriptMap

Define mapping. To avoid problems with encodings, only use ASCII characters in the arguments. The first argument is the four-letter ISO 15924 code. The second argument is the numeric code. The third argument is just intended for informational purposes. The fourth argument indicates the direction. This may be LR (left-to-right), RL (right-to-left), TB (top-to-bottom), *varies* or *inherited*. The *<parent>* argument is for the parent writing system, which may be left blank. (Currently, this is blank for all the mappings provided here, but the syntax has five arguments in case of future development.)

```
\def\TrackLangScriptMap#1#2#3#4#5{%
```

This user command is provided to make it easier to test the script using \ifx.

```
\@tracklang@enamedef{TrackLangScript#1}{#1}%
\@tracklang@enamedef{@tracklang@script@numtoalpha@#2}{#1}%
\@tracklang@enamedef{@tracklang@script@alphatonum@#1}{#2}%
\@tracklang@enamedef{@tracklang@script@alphatname@#1}{#3}%
\@tracklang@enamedef{@tracklang@script@alphatodir@#1}{#4}%
\ifx\relax#5\relax
\else
```



```

        \@tracklang@enamedef{@tracklang@script@parent@#1}{#5}%
    \fi
}

```

\TrackLangScriptAlphaToNumeric

```
\TrackLangScriptAlphaToNumeric{<alpha code>}
```

```

\def\TrackLangScriptAlphaToNumeric#1{%
    \@tracklang@nameuse{@tracklang@script@alphanum@#1}%
}%

```

\TrackLangScriptIfKnownAlpha

```
\TrackLangScriptIfKnownAlpha{<alpha
code>}{<true>}{<false>}
```

```

\def\TrackLangScriptIfKnownAlpha#1#2#3{%
    \@tracklang@ifundef{@tracklang@script@alphanum@#1}%
    {#3}%
    {#2}%
}%

```

\TrackLangScriptNumericToAlpha

```
\TrackLangScriptNumericToAlpha{<numeric code>}
```

```

\def\TrackLangScriptNumericToAlpha#1{%
    \@tracklang@nameuse{@tracklang@script@numtoalpha@#1}%
}%

```

\TrackLangScriptIfKnownNumeric

```
\TrackLangScriptIfKnownNumeric{<numeric
code>}{<true>}{<false>}
```

```

\def\TrackLangScriptIfKnownNumeric#1#2#3{%
    \@tracklang@ifundef{@tracklang@script@numtoalpha@#1}%
    {#3}%
    {#2}%
}%

```

\TrackLangScriptAlphaToName

```
\TrackLangScriptAlphaToName{<alpha code>}
```

```
\def\TrackLangScriptAlphaToName#1{%
  \@tracklang@nameuse{@tracklang@script@alphaname@#1}%
}%
```

```
\TrackLangScriptAlphaToDir{<alpha code>}
```

\TrackLangScriptAlphaToDir

```
\def\TrackLangScriptAlphaToDir#1{%
  \@tracklang@nameuse{@tracklang@script@alphatodir@#1}%
}%
```

I wasn't sure whether or not to implement a parent, but it's here if required. Unlike the other elements above, there's also a command to set this field.

```
\TrackLangScriptSetParent{<alpha code>}{<parent alpha
code>}
```

\TrackLangScriptSetParent

```
\def\TrackLangScriptSetParent#1#2{%
  \@tracklang@namedef{@tracklang@script@parent@#1}{#2}%
}%
```

```
\TrackLangScriptGetParent{<alpha code>}
```

\TrackLangScriptGetParent

```
\def\TrackLangScriptGetParent#1{%
  \@tracklang@nameuse{@tracklang@script@parent@#1}%
}%
```

```
\TrackLangScriptIfHasParent{<alpha
code>}{<true>}{<false>}
```

\TrackLangScriptIfHasParent

```
\def\TrackLangScriptIfHasParent#1#2#3{%
  \@tracklang@ifundef{@tracklang@script@parent@#1}%
  {#3}%
  {#2}%
}%
```

Define mappings. The parent information is currently missing.

```
\TrackLangScriptMap{Adlm}{166}{Adlam}{RL}{}%
\TrackLangScriptMap{Afak}{439}{Afaka}{varies}{}%
\TrackLangScriptMap{Aghb}{239}{Caucasian Albanian}{LR}{}%
```

```

\TrackLangScriptMap{Ahom}{338}{Ahom, Tai Ahom}{LR}{}%
\TrackLangScriptMap{Arab}{160}{Arabic}{RL}{}%
\TrackLangScriptMap{Aran}{161}{Arabic (Nastaliq variant)}{RL}{}%
\TrackLangScriptMap{Armi}{124}{Imperial Aramaic}{RL}{}%
\TrackLangScriptMap{Armn}{230}{Armenian}{LR}{}%
\TrackLangScriptMap{Avst}{134}{Avestan}{RL}{}%
\TrackLangScriptMap{Bali}{360}{Balinese}{LR}{}%
\TrackLangScriptMap{Bamu}{435}{Bamum}{LR}{}%
\TrackLangScriptMap{Bass}{259}{Bassa Vah}{LR}{}%
\TrackLangScriptMap{Batk}{365}{Batak}{LR}{}%
\TrackLangScriptMap{Beng}{334}{Bhaiksuki}{LR}{}%
\TrackLangScriptMap{Blis}{550}{Blissymbols}{varies}{}%
\TrackLangScriptMap{Bopo}{285}{Bopomofo}{LR}{}%
\TrackLangScriptMap{Brah}{300}{Brahmi}{LR}{}%
\TrackLangScriptMap{Brai}{570}{Braille}{LR}{}%
\TrackLangScriptMap{Bugi}{367}{Buginese}{LR}{}%
\TrackLangScriptMap{Buhd}{372}{Buhid}{LR}{}%
\TrackLangScriptMap{Cakm}{349}{Chakma}{LR}{}%
\TrackLangScriptMap{Cans}{440}{Unified Canadian Aboriginal Syllabics}{LR}{}%
\TrackLangScriptMap{Cari}{201}{Carian}{LR}{}%
\TrackLangScriptMap{Cham}{358}{Cham}{LR}{}%
\TrackLangScriptMap{Cher}{445}{Cherokee}{LR}{}%
\TrackLangScriptMap{Cirt}{291}{Cirth}{varies}{}%
\TrackLangScriptMap{Copt}{204}{Coptic}{LR}{}%
\TrackLangScriptMap{Cprt}{403}{Cypriot}{RL}{}%
\TrackLangScriptMap{Cyrl}{220}{Cyrillic}{LR}{}%
\TrackLangScriptMap{CyrS}{221}{Cyrillic (Old Church Slavonic variant)}{varies}{}%
\TrackLangScriptMap{Deva}{315}{Devanagari (Nagari)}{LR}{}%
\TrackLangScriptMap{Dsrt}{250}{Deseret (Mormon)}{LR}{}%
\TrackLangScriptMap{Dupl}{755}{Duployan shorthand, Duployan stenography}{LR}{}%
\TrackLangScriptMap{Egyd}{070}{Egyptian demotic}{RL}{}%
\TrackLangScriptMap{Egyh}{060}{Egyptian hieratic}{RL}{}%
\TrackLangScriptMap{Egyp}{050}{Egyptian hieroglyphs}{LR}{}%
\TrackLangScriptMap{Elba}{226}{Elbasan}{LR}{}%
\TrackLangScriptMap{Ethi}{430}{Ethiopic (Ge'ez)}{LR}{}%
\TrackLangScriptMap{Geok}{241}{Khutsuri (Asomtavruli and Nuskhuri)}{LR}{}%
\TrackLangScriptMap{Geor}{240}{Georgian (Mkhedruli)}{LR}{}%
\TrackLangScriptMap{Glag}{225}{Glagolitic}{LR}{}%
\TrackLangScriptMap{Goth}{206}{Gothic}{LR}{}%
\TrackLangScriptMap{Gran}{343}{Grantha}{LR}{}%
\TrackLangScriptMap{Grek}{200}{Greek}{LR}{}%
\TrackLangScriptMap{Gujr}{320}{Gujarati}{LR}{}%
\TrackLangScriptMap{Guru}{310}{Gurmukhi}{LR}{}%
\TrackLangScriptMap{Hanb}{503}{Han with Bopomofo (alias for Han + Bopomofo)}{LR}{}%
\TrackLangScriptMap{Hang}{286}{Hangul}{LR}{}%
\TrackLangScriptMap{Hani}{500}{Han (Hanzi, Kanji, Hanja)}{LR}{}%
\TrackLangScriptMap{Hano}{371}{Hanunoo}{LR}{}%
\TrackLangScriptMap{Hans}{501}{Han (Simplified variant)}{varies}{}%
\TrackLangScriptMap{Hant}{502}{Han (Traditional variant)}{varies}{}%
\TrackLangScriptMap{Hatr}{127}{Hatran}{RL}{}%

```

```

\TrackLangScriptMap{Hebr}{125}{Hebrew}{RL}{}%
\TrackLangScriptMap{Hira}{410}{Hiragana}{LR}{}%
\TrackLangScriptMap{Hluw}{080}{Anatolian Hieroglyphs (Luwian Hieroglyphs, Hittite Hieroglyphs)}{LR}{}%
\TrackLangScriptMap{Hmng}{450}{Pahawh Hmong}{LR}{}%
\TrackLangScriptMap{Hrkt}{412}{Japanese syllabaries (alias for Hiragana + Katakana)}{varies}{}%
\TrackLangScriptMap{Hung}{176}{Old Hungarian (Hungarian Runic)}{RL}{}%
\TrackLangScriptMap{Inds}{610}{Indus (Harappan)}{RL}{}%
\TrackLangScriptMap{Ital}{210}{Old Italic (Etruscan, Oscan, etc.)}{LR}{}%
\TrackLangScriptMap{Jamo}{284}{Jamo (alias for Jamo subset of Hangul)}{LR}{}%
\TrackLangScriptMap{Java}{361}{Javanese}{LR}{}%
\TrackLangScriptMap{Jpan}{413}{Japanese (alias for Han + Hiragana + Katakana)}{varies}{}%
\TrackLangScriptMap{Jurc}{510}{Jurchen}{LR}{}%
\TrackLangScriptMap{Kali}{357}{Kayah Li}{LR}{}%
\TrackLangScriptMap{Kana}{411}{Katakana}{LR}{}%
\TrackLangScriptMap{Khar}{305}{Kharoshthi}{RL}{}%
\TrackLangScriptMap{Khmr}{355}{Khmer}{LR}{}%
\TrackLangScriptMap{Khoj}{322}{Khojki}{LR}{}%
\TrackLangScriptMap{Kitl}{505}{Khitan large script}{LR}{}%
\TrackLangScriptMap{Kits}{288}{Khitan small script}{TB}{}%
\TrackLangScriptMap{Knda}{345}{Kannada}{LR}{}%
\TrackLangScriptMap{Kore}{287}{Korean (alias for Hangul + Han)}{LR}{}%
\TrackLangScriptMap{Kpel}{436}{Kpelle}{LR}{}%
\TrackLangScriptMap{Kthi}{317}{Kaithi}{LR}{}%
\TrackLangScriptMap{Lana}{351}{Tai Tham (Lanna)}{LR}{}%
\TrackLangScriptMap{Laoo}{356}{Lao}{LR}{}%
\TrackLangScriptMap{Latf}{217}{Latin (Fraktur variant)}{varies}{}%
\TrackLangScriptMap{Latg}{216}{Latin (Gaelic variant)}{LR}{}%
\TrackLangScriptMap{Latn}{215}{Latin}{LR}{}%
\TrackLangScriptMap{Leke}{364}{Leke}{LR}{}%
\TrackLangScriptMap{Lepc}{335}{Lepcha}{LR}{}%
\TrackLangScriptMap{Limb}{336}{Limbu}{LR}{}%
\TrackLangScriptMap{Lina}{400}{Linear A}{LR}{}%
\TrackLangScriptMap{Linb}{401}{Linear B}{LR}{}%
\TrackLangScriptMap{Lisu}{399}{Lisu (Fraser)}{LR}{}%
\TrackLangScriptMap{Loma}{437}{Loma}{LR}{}%
\TrackLangScriptMap{Lyci}{202}{Lycian}{LR}{}%
\TrackLangScriptMap{Lydi}{116}{Lydian}{RL}{}%
\TrackLangScriptMap{Mahj}{314}{Mahajani}{LR}{}%
\TrackLangScriptMap{Mand}{140}{Mandaic, Mandaean}{RL}{}%
\TrackLangScriptMap{Mani}{139}{Manichaeon}{RL}{}%
\TrackLangScriptMap{Marc}{332}{Marchen}{LR}{}%
\TrackLangScriptMap{Maya}{090}{Mayan hieroglyphs}{varies}{}%
\TrackLangScriptMap{Mend}{438}{Mende Kikakui}{RL}{}%
\TrackLangScriptMap{Merc}{101}{Meroitic Cursive}{RL}{}%
\TrackLangScriptMap{Mero}{100}{Meroitic Hieroglyphs}{RL}{}%
\TrackLangScriptMap{Mlym}{347}{Malayalam}{LR}{}%
\TrackLangScriptMap{Modi}{324}{Modi}{LR}{}%
\TrackLangScriptMap{Mong}{145}{Mongolian}{TB}{}%
\TrackLangScriptMap{Moon}{218}{Moon code, Moon script, Moon type)}{varies}{}%
\TrackLangScriptMap{Mroo}{199}{Mro, Mru}{LR}{}%

```

```

\TrackLangScriptMap{Mtei}{337}{Meitei Mayek (Meithei, Meetei)}{LR}{}%
\TrackLangScriptMap{Mult}{323}{Multani}{LR}{}%
\TrackLangScriptMap{Mymr}{350}{Myanmar (Burmese)}{LR}{}%
\TrackLangScriptMap{Narb}{106}{Old North Arabian (Ancient North Arabian)}{RL}{}%
\TrackLangScriptMap{Nbat}{159}{Nabataean}{RL}{}%
\TrackLangScriptMap{Newa}{333}{Newa, Newar, Newari}{LR}{}%
\TrackLangScriptMap{Nkgb}{420}{Nakhi Geba}{LR}{}%
\TrackLangScriptMap{Nkoo}{165}{N'Ko}{RL}{}%
\TrackLangScriptMap{Nshu}{499}{Nushu}{LR}{}%
\TrackLangScriptMap{Ogam}{212}{Ogham}{varies}{}%
\TrackLangScriptMap{Olck}{261}{Ol Chiki}{LR}{}%
\TrackLangScriptMap{Orkh}{175}{Old Turkic, Orkhon Runic}{RL}{}%
\TrackLangScriptMap{Orya}{327}{Oriya}{LR}{}%
\TrackLangScriptMap{Osge}{219}{Osage}{LR}{}%
\TrackLangScriptMap{Osma}{260}{Osmanya}{LR}{}%
\TrackLangScriptMap{Palm}{126}{Palmyrene}{RL}{}%
\TrackLangScriptMap{Pauc}{263}{Pau Cin Hau}{LR}{}%
\TrackLangScriptMap{Perm}{227}{Old Permic}{LR}{}%
\TrackLangScriptMap{Phag}{331}{Phags-pa}{TB}{}%
\TrackLangScriptMap{Phli}{131}{Inscriptional Pahlavi}{RL}{}%
\TrackLangScriptMap{Phlp}{132}{Psalter Pahlavi}{RL}{}%
\TrackLangScriptMap{Phlv}{133}{Book Pahlavi}{RL}{}%
\TrackLangScriptMap{Phnx}{115}{Phoenician}{RL}{}%
\TrackLangScriptMap{Piqd}{293}{Klingon (KLI plqAD)}{LR}{}%
\TrackLangScriptMap{Plrd}{282}{Miao (Pollard)}{LR}{}%
\TrackLangScriptMap{Prti}{130}{Inscriptional Parthian}{RL}{}%
\TrackLangScriptMap{Qaaa}{900}{Reserved for private use (start)}{varies}{}%
\TrackLangScriptMap{Qaai}{908}{Private use}{varies}{}%
\TrackLangScriptMap{Qabx}{949}{Reserved for private use (end)}{varies}{}%
\TrackLangScriptMap{Rjng}{363}{Rejang (Redjang, Kaganga)}{LR}{}%
\TrackLangScriptMap{Roro}{620}{Rongorongo}{varies}{}%
\TrackLangScriptMap{Runr}{211}{Runic}{LR}{}%
\TrackLangScriptMap{Samr}{123}{Samaritan}{RL}{}%
\TrackLangScriptMap{Sara}{292}{Sarati}{varies}{}%
\TrackLangScriptMap{Sarb}{105}{Old South Arabian}{RL}{}%
\TrackLangScriptMap{Saur}{344}{Saurashtra}{LR}{}%
\TrackLangScriptMap{Sgnw}{095}{SignWriting}{TB}{}%
\TrackLangScriptMap{Shaw}{281}{Shavian (Shaw)}{LR}{}%
\TrackLangScriptMap{Shrd}{319}{Sharada}{LR}{}%
\TrackLangScriptMap{Sidd}{302}{Siddham}{LR}{}%
\TrackLangScriptMap{Sind}{318}{Khudawadi, Sindhi}{LR}{}%
\TrackLangScriptMap{Sinh}{348}{Sinhala}{LR}{}%
\TrackLangScriptMap{Sora}{398}{Sora Sompeng}{LR}{}%
\TrackLangScriptMap{Sund}{362}{Sundanese}{LR}{}%
\TrackLangScriptMap{Sylo}{316}{Syloti Nagri}{LR}{}%
\TrackLangScriptMap{Sycr}{135}{Syriac}{RL}{}%
\TrackLangScriptMap{Syre}{138}{Syriac (Estrangelo variant)}{RL}{}%
\TrackLangScriptMap{Syri}{137}{Syriac (Western variant)}{RL}{}%
\TrackLangScriptMap{Syrn}{136}{Syriac (Eastern variant)}{RL}{}%
\TrackLangScriptMap{Tagb}{373}{Tagbanwa}{LR}{}%

```

```

\TrackLangScriptMap{Takr}{321}{Takri}{LR}{}%
\TrackLangScriptMap{Tale}{353}{Tai Le}{LR}{}%
\TrackLangScriptMap{Talu}{354}{New Tai Lue}{LR}{}%
\TrackLangScriptMap{Taml}{346}{Tamil}{LR}{}%
\TrackLangScriptMap{Tang}{520}{Tangut}{LR}{}%
\TrackLangScriptMap{Tavt}{359}{Tai Viet}{LR}{}%
\TrackLangScriptMap{Telu}{340}{Telugu}{LR}{}%
\TrackLangScriptMap{Teng}{290}{Tengwar}{LR}{}%
\TrackLangScriptMap{Tfng}{120}{Tifinagh (Berber)}{LR}{}%
\TrackLangScriptMap{Tglg}{370}{Tagalog (Baybayin, Alibata)}{LR}{}%
\TrackLangScriptMap{Thaa}{170}{Thaana}{RL}{}%
\TrackLangScriptMap{Thai}{352}{Thai}{LR}{}%
\TrackLangScriptMap{Tibt}{330}{Tibetan}{LR}{}%
\TrackLangScriptMap{Tirh}{326}{Tirhuta}{LR}{}%
\TrackLangScriptMap{Ugar}{040}{Ugaritic}{LR}{}%
\TrackLangScriptMap{Vaii}{470}{Vai}{LR}{}%
\TrackLangScriptMap{Visp}{280}{Visible Speech}{LR}{}%
\TrackLangScriptMap{Wara}{262}{Warang Citi (Varang Kshiti)}{LR}{}%
\TrackLangScriptMap{Wole}{480}{Woleai}{RL}{}%
\TrackLangScriptMap{Xpeo}{030}{Old Persian}{LR}{}%
\TrackLangScriptMap{Xsux}{020}{Cuneiform, Sumeru-Akkadian}{LR}{}%
\TrackLangScriptMap{Yiii}{460}{Yi}{LR}{}%
\TrackLangScriptMap{Zinh}{994}{Inherited script}{inherited}{}%
\TrackLangScriptMap{Zmth}{995}{Mathematical notation}{LR}{}%
\TrackLangScriptMap{Zsym}{996}{Symbols}{varies}{}%
\TrackLangScriptMap{Zsye}{993}{Symbols (emoji variant)}{varies}{}%
\TrackLangScriptMap{Zxxx}{997}{Unwritten documents}{varies}{}%
\TrackLangScriptMap{Zyyy}{998}{Undetermined script}{varies}{}%
\TrackLangScriptMap{Zzzz}{999}{Uncoded script}{varies}{}%

```

Load additional script files.

```

\@tracklang@input@extra@script@files
  Restore category code of @.
\@tracklang@scripts@restore@at

```

Change History

1.0 – 2014-09-29	
General: Initial release	2
1.1 – 2014-11-21	
\@tracklang@add@argentinespanish:	
new	77
\@tracklang@add@bolivianspanish:	
new	78
\@tracklang@add@chilianspanish:	
new	78
\@tracklang@add@columbianspanish:	
new	78
\@tracklang@add@costaricanspanish:	
new	78
\@tracklang@add@cubanspanish:	
new	78
\@tracklang@add@de-BE: new	81
\@tracklang@add@de-CH: new	83
\@tracklang@add@de-DE: new	81
\@tracklang@add@dominicanspanish:	
new	78
\@tracklang@add@ecudorianspanish:	
new	78
\@tracklang@add@elsalvadorspanish:	
new	78
\@tracklang@add@en-AU: new	80
\@tracklang@add@en-CA: new	80
\@tracklang@add@en-GB: new	80
\@tracklang@add@en-GG: new	81
\@tracklang@add@en-IM: new	81
\@tracklang@add@en-JE: new	81
\@tracklang@add@en-MT: new	81
\@tracklang@add@en-NZ: new	80
\@tracklang@add@en-US: new	80
\@tracklang@add@es-AR: new	82
\@tracklang@add@es-BO: new	82
\@tracklang@add@es-CL: new	82
\@tracklang@add@es-CO: new	82
\@tracklang@add@es-CR: new	82
\@tracklang@add@es-CU: new	82
\@tracklang@add@es-DO: new	82
\@tracklang@add@es-EC: new	82
\@tracklang@add@es-ES: new	81
\@tracklang@add@es-GT: new	82
\@tracklang@add@es-HN: new	82
\@tracklang@add@es-MX: new	82
\@tracklang@add@es-NI: new	82
\@tracklang@add@es-PA: new	82
\@tracklang@add@es-PE: new	82
\@tracklang@add@es-PR: new	83
\@tracklang@add@es-PY: new	82
\@tracklang@add@es-SV: new	82
\@tracklang@add@es-UY: new	83
\@tracklang@add@es-VE: new	83
\@tracklang@add@fr-BE: new	80
\@tracklang@add@fr-CA: new	80
\@tracklang@add@fr-CH: new	83
\@tracklang@add@fr-FR: new	80
\@tracklang@add@fr-GG: new	81
\@tracklang@add@fr-JE: new	81
\@tracklang@add@france: new	74
\@tracklang@add@guatemalanspanish:	
new	78
\@tracklang@add@guernseyenglish:	
new	76
\@tracklang@add@guernseyfrench:	
new	76
\@tracklang@add@honduranspanish:	
new	78
\@tracklang@add@isleofmanenglish:	
new	76
\@tracklang@add@it-CH: new	83
\@tracklang@add@it-HR: new	80
\@tracklang@add@it-IT: new	81
\@tracklang@add@it-SI: new	81
\@tracklang@add@it-SM: new	81
\@tracklang@add@it-VA: new	83
\@tracklang@add@jerseyenglish:	
new	76
\@tracklang@add@jerseyfrench:	
new	76
\@tracklang@add@maltaenglish:	
new	76
\@tracklang@add@maltamaltese:	
new	76
\@tracklang@add@maltese: new	64
\@tracklang@add@manx: new	64
\@tracklang@add@mexicanspanish:	
new	78
\@tracklang@add@mt-MT: new	81
\@tracklang@add@netherlands:	
new	74
\@tracklang@add@ngermanDE:	
new	75

\@tracklang@add@nicaraguanspanish:	removed hard-coded
new	polyglossia language list 3
\@tracklang@add@nl-BE: new	. 80
\@tracklang@add@nl-NL: new	. 81
\@tracklang@add@panamaspanish:	
new	. 78
\@tracklang@add@paraguayspanish:	
new	. 78
\@tracklang@add@peruvianspanish:	
new	. 78
\@tracklang@add@portugal: new	77
\@tracklang@add@pt-BR: new	. 80
\@tracklang@add@pt-PT: new	. 81
\@tracklang@add@puertoricospanish:	
new	. 78
\@tracklang@add@rm-CH: new	. 83
\@tracklang@add@sl-SI: new	. 81
\@tracklang@add@spainspanish:	
new	. 77
\@tracklang@add@swissfrench:	
new	. 79
\@tracklang@add@swissgerman:	
new	. 79
\@tracklang@add@swissitalian:	
new	. 79
\@tracklang@add@swissromansh:	
new	. 79
\@tracklang@add@uruguayspanish:	
new	. 79
\@tracklang@add@venezuelanspanish:	
new	. 79
\@tracklang@declareoption:	
new	. 56
\LetTrackLangOption: new	. . . 80
1.2 – 2015-03-23	
\@tracklang@add@GBirish: new	75
\@tracklang@add@IEenglish:	
new	. 75
\@tracklang@add@IEirish: new	75
\@tracklang@add@en-IE: new	. 83
\@tracklang@add@ga-GB: new	. 83
\@tracklang@add@ga-IE: new	. 83
1.3 – 2016-10-07	
General: added check for @	
category code 8
added test for german.sty 3
added	
tracklang-region-codes.tex	. 136
added tracklang-scripts.sty	. . 143
added tracklang-scripts.tex	. . 144
\@TrackLangRequestResource:	
new 132
\@TrackLangRequireDialect:	
new 132
\@TrackLangRequireResource:	
new 130
\@TrackLangRequireResourceOrDo:	
new 131
\@tracklang@add@GBscottish:	
new 77
\@tracklang@add@GBwelsh: new	79
\@tracklang@add@abkhaz: new	. 57
\@tracklang@add@afar: new	. . 57
\@tracklang@add@akan: new	. . 57
\@tracklang@add@aragonese:	
new 58
\@tracklang@add@assamese: new	58
\@tracklang@add@avaric: new	. 58
\@tracklang@add@avestan: new	58
\@tracklang@add@aymara: new	. 58
\@tracklang@add@azerbaijani:	
new 58
\@tracklang@add@bambara: new	58
\@tracklang@add@bashkir: new	58
\@tracklang@add@belarusian:	
new 59
\@tracklang@add@berber: new	. 59
\@tracklang@add@bihari: new	. 59
\@tracklang@add@bislama: new	59
\@tracklang@add@bokmal: new	. 59
\@tracklang@add@bosnian: new	59
\@tracklang@add@burmese: new	59
\@tracklang@add@chamorro: new	59
\@tracklang@add@chechen: new	59
\@tracklang@add@chichewa: new	59
\@tracklang@add@chinese: new	59
\@tracklang@add@churchslavonic:	
new 60
\@tracklang@add@chuvash: new	60
\@tracklang@add@cornish: new	60
\@tracklang@add@corsican: new	60
\@tracklang@add@cree: new	. . 60
\@tracklang@add@cy-GB: new	. 84
\@tracklang@add@de-AT: new	. 83
\@tracklang@add@de-AT-1996:	
new 83

\@tracklang@add@de-CH-1996:		\@tracklang@add@limburgish:	
new	84	new	64
\@tracklang@add@de-DE-1996:		\@tracklang@add@lingala: new	64
new	84	\@tracklang@add@lubakatanga:	
\@tracklang@add@dzongkha: new	60	new	64
\@tracklang@add@easternpunjabi:		\@tracklang@add@luxembourgish:	
new	60	new	64
\@tracklang@add@ewe: new	61	\@tracklang@add@macedonian:	
\@tracklang@add@faroeese: new	61	new	64
\@tracklang@add@fijian: new	61	\@tracklang@add@malagasy: new	64
\@tracklang@add@fula: new	61	\@tracklang@add@maori: new	64
\@tracklang@add@ganda: new	61	\@tracklang@add@marshallese:	
\@tracklang@add@gd-GB: new	84	new	65
\@tracklang@add@georgian: new	61	\@tracklang@add@mongolian:	
\@tracklang@add@germanDE: new	75	new	65
\@tracklang@add@germanb: new	75	\@tracklang@add@ms-MY: new	83
\@tracklang@add@guarani: new	61	\@tracklang@add@nauruan: new	65
\@tracklang@add@gujarati: new	61	\@tracklang@add@naustrian:	
\@tracklang@add@haitian: new	61	added modifier	73
\@tracklang@add@hausa: new	62	\@tracklang@add@navajo: new	65
\@tracklang@add@herero: new	62	\@tracklang@add@nbelgiangerman:	
\@tracklang@add@hirimotu: new	62	new	74
\@tracklang@add@hr-HR: new	83	\@tracklang@add@ndonga: new	65
\@tracklang@add@hu-HU: new	84	\@tracklang@add@nepali: new	65
\@tracklang@add@id-IN: new	83	\@tracklang@add@ngerman:	
\@tracklang@add@ido: new	62	added modifier	75
\@tracklang@add@igbo: new	62	\@tracklang@add@ngermanDE:	
\@tracklang@add@interlingue:		added modifier	75
new	62	\@tracklang@add@ngermanb: new	75
\@tracklang@add@inuktitut:		\@tracklang@add@northernndebele:	
new	62	new	65
\@tracklang@add@inupiaq: new	62	\@tracklang@add@northernsotho:	
\@tracklang@add@japanese: new	62	new	65
\@tracklang@add@javanese: new	62	\@tracklang@add@nswissgerman:	
\@tracklang@add@kalaallisut:		new	79
new	63	\@tracklang@add@nuosu: new	65
\@tracklang@add@kanuri: new	63	\@tracklang@add@ojibwe: new	65
\@tracklang@add@kashmiri: new	63	\@tracklang@add@oriya: new	65
\@tracklang@add@kazakh: new	63	\@tracklang@add@oromo: new	65
\@tracklang@add@khmer: new	63	\@tracklang@add@ossetian: new	66
\@tracklang@add@kikuyu: new	63	\@tracklang@add@pali: new	66
\@tracklang@add@kinyarwanda:		\@tracklang@add@pashto: new	66
new	63	\@tracklang@add@polutoniko:	
\@tracklang@add@kirundi: new	63	added modifier	77
\@tracklang@add@komi: new	63	\@tracklang@add@polutonikogreek:	
\@tracklang@add@kongo: new	63	added modifier	76
\@tracklang@add@korean: new	63	\@tracklang@add@quechua: new	66
\@tracklang@add@kurdish: new	63	\@tracklang@add@samoan: new	66
\@tracklang@add@kwanyama: new	63	\@tracklang@add@sango: new	66
\@tracklang@add@kyrgyz: new	63		

\@tracklang@add@sardinian:	\@tracklang@hasthirdchar: new	38
new	\@tracklang@ifalldigits: new	40
\@tracklang@add@serbianc: new	\@tracklang@ifalpha: new	39
\@tracklang@add@serbianl: new	\@tracklang@ifalphanumeric:	
\@tracklang@add@shona: new	new	40
\@tracklang@add@sindhi: new	\@tracklang@ifdigit: new	39
\@tracklang@add@sinhalese:	\@tracklang@iflanguage@ii@tag:	
new	new	41
\@tracklang@add@sloveneistriasslovenian	\@tracklang@iflanguage@iii@tag:	
fixed root language name	new	41
\@tracklang@add@somali: new	\@tracklang@ifregion@ii@tag:	
\@tracklang@add@southernndebele:	new	43
new	\@tracklang@ifregion@iii@tag:	
\@tracklang@add@southernsotho:	new	43
new	\@tracklang@ifscripttag: new	44
\@tracklang@add@sudanese: new	\@tracklang@ifundef: added	
\@tracklang@add@swahili: new	check for \ifc\$name	8
\@tracklang@add@swati: new	\@tracklang@ifvariant@iv@tag:	
\@tracklang@add@tagalog: new	new	45
\@tracklang@add@tahitian: new	\@tracklang@info: new	12
\@tracklang@add@tajik: new	\@tracklang@known@langs: new	24
\@tracklang@add@tatar: new	\@tracklang@locale@c: new	14
\@tracklang@add@tigrinya: new	\@tracklang@locale@posix: new	14
\@tracklang@add@tonga: new	\@tracklang@nameuse: added	
\@tracklang@add@tsonga: new	check for undef	10
\@tracklang@add@tswana: new	\@tracklang@parse@langtag:	
\@tracklang@add@twi: new	new	47
\@tracklang@add@usorbian:	\@tracklang@parse@locale: new	19
corrected ISO 639-1 code	\@tracklang@parse@track@locale:	
\@tracklang@add@uyghur: new	new	53
\@tracklang@add@uzbek: new	\@tracklang@parseenv: new	21
\@tracklang@add@venda: new	\@tracklang@sanitize: new	11
\@tracklang@add@volapuk: new	\@tracklang@secondoftwo: new	11
\@tracklang@add@westernfrisian:	\@tracklang@split@hyphen: new	21
new	\@tracklang@split@otherunderscore:	
\@tracklang@add@wolof: new	new	21
\@tracklang@add@xhosa: new	\@tracklang@split@underscore:	
\@tracklang@add@yiddish: new	new	20
\@tracklang@add@yoruba: new	\@tracklang@split@underscoreorhyp:	
\@tracklang@add@zhuang: new	new	20
\@tracklang@add@zulu: new	\@tracklang@track@locale: new	54
\@tracklang@addtohook: new	\@tracklang@warn: new	12
\@tracklang@enamedef: new	\AddTrackedCountryIsoCode:	
\@tracklang@firstoftwo: new	new	37
\@tracklang@hasfifthchar: new	\AddTrackedLanguageIsoCodes:	
\@tracklang@hasfourthchar:	new	36
new	\GetTrackedDialectAdditional:	
\@tracklang@hasninthchar: new	new	32
\@tracklang@hassecondchar:	\GetTrackedDialectFromLanguageTag:	
new	new	50

\GetTrackedDialectFromMapping:		\ThreeLetterExtIsoLanguageCode:	
new	130	new	29
\GetTrackedDialectModifier:		\TrackLangAddToCaptions: new	127
new	30	\TrackLangAddToHook: new	125
\GetTrackedDialectScript: new	30	\TrackLangAlphaIIIToNumericRegion:	
\GetTrackedDialectSubLang:		new	138
new	32	\TrackLangAlphaIIToNumericRegion:	
\GetTrackedDialectToMapping:		new	137
new	130	\TrackLangDeclareDialectOption:	
\GetTrackedDialectVariant:		new	72
new	31	\TrackLangDeclareLanguageOption:	
\GetTrackedLanguageTag: new	33	new	57
\IfHasTrackedDialectAdditional:		\TrackLangFromEnv: new	52
new	33	\TrackLangGetDefaultScript:	
\IfHasTrackedDialectModifier:		new	28
new	30	\TrackLangGetKnownCountry:	
\IfHasTrackedDialectScript:		new	27
new	30	\TrackLangGetKnownIsoThreeLetterLang:	
\IfHasTrackedDialectSubLang:		new	26
new	32	\TrackLangGetKnownIsoThreeLetterLangB:	
\IfHasTrackedDialectVariant:		new	27
new	31	\TrackLangGetKnownIsoTwoLetterLang:	
\IfTrackedDialectHasMapping:		new	26
new	129	\TrackLangGetKnownLangFromIso:	
\IfTrackedDialectIsScriptCs:		new	27
new	30	\TrackLangIfAlphaNumericChar:	
\ifTrackLangShowInfo: new	12	new	40
\ifTrackLangShowWarnings: new	11	\TrackLangIfHasDefaultScript:	
\LetTrackLangSynonym: new	80	new	28
\noop@TrackLangRequestResource:		\TrackLangIfHasKnownCountry:	
new	132	new	27
\noop@TrackLangRequireDialect:		\TrackLangIfKnownAlphaIIRegion:	
new	132	new	138
\noop@TrackLangRequireResource:		\TrackLangIfKnownAlphaIRegion:	
new	130	new	137
\noop@TrackLangRequireResourceOrDo:		\TrackLangIfKnownIsoThreeLetterLang:	
new	131	new	26
\SetCurrentTrackedDialect:		\TrackLangIfKnownIsoThreeLetterLangB:	
new	33	new	26
\SetTrackedDialectAdditional:		\TrackLangIfKnownIsoTwoLetterLang:	
new	32	new	25
\SetTrackedDialectLabelMap:		\TrackLangIfKnownLang: new	25
new	129	\TrackLangIfKnownLangFromIso:	
\SetTrackedDialectModifier:		new	27
new	29	\TrackLangIfKnownNumericRegion:	
\SetTrackedDialectScript: new	30	new	137
\SetTrackedDialectSubLang:		\TrackLangIfLanguageTag: new	41
new	32	\TrackLangIfRegionTag: new	42
\SetTrackedDialectVariant:		\TrackLangIfScriptTag: new	43
new	31	\TrackLangIfVariantTag: new	44

\TrackLangNewLanguage: new .	24	\TrackLangProvidePredefinedDialect:	
\TrackLangNumericToAlphaIIRegion:		fixed mapping order	72
new	138	1.3.4 – 2017-03-25	
\TrackLangNumericToAlphaIIRegion:		\@tracklang@add@furlan: new .	74
new	137	\@tracklang@add@kurmanji: new	74
\TrackLangParseFromEnv: new .	18	\@tracklang@err: fixed typo in	
\TrackLangProvidesResource:		\errhelp command name . .	11
new	124	\@tracklang@pkgwarn: new . . .	11
\TrackLangQueryEnv: new . .	15, 17	1.3.5 – 2018-02-21	
\TrackLangQueryOtherEnv:		General: check for \xpg@loaded .	3
new	16, 17	1.3.6 – 2018-05-13	
\TrackLangRegionMap: new . . .	136	\@tracklang@fullmatch: new .	52
\TrackLangRequestResource:		\GetTrackedDialectFromLanguageTag:	
new	131	added	
\TrackLangRequireDialect:		\TrackedDialectClosestSubMatch	
new	132	50
\TrackLangRequireResource:		1.3.7 – 2019-08-31	
new	130	General: corrected misspelt	
\TrackLangRequireResourceOrDo:		command	4, 7
new	131	1.3.8 – 2019-10-06	
\TrackLangScriptAlphaToDir:		\@tracklang@add@nil: new . . .	79
new	146	\@tracklang@add@undetermined:	
\TrackLangScriptAlphaToName:		new	69
new	145	\@tracklang@prelangpkgcheck@hook:	
\TrackLangScriptAlphaToNumeric:		new	2
new	145	1.3.9 – 2019-11-11	
\TrackLangScriptGetParent:		\@TrackIfKnownLanguage: new .	47
new	146	\TrackIfKnownLanguage: new .	47
\TrackLangScriptIfHasParent:		1.4 – 2019-11-30	
new	146	General: input extra regions if	
\TrackLangScriptIfKnownAlpha:		provided	143
new	145	new	150
\TrackLangScriptIfKnownNumeric:		removed some spurious empty	
new	145	braces and commented out	
\TrackLangScriptMap: new . . .	144	EOL	146
\TrackLangScriptNumericToAlpha:		\@tracklang@firstoftwo: made	
new	145	long	11
\TrackLangScriptSetParent:		\@tracklang@ifcseqcsname: new	10
new	146	\@tracklang@input@extra@region@filelist:	
\TrackLanguageTag: new	46	new	49
\TrackLocale: new	53	\@tracklang@input@extra@region@files:	
1.3.2 – 2016-10-11		new	49
\@tracklang@tryshellescape:		\@tracklang@input@extra@script@filelist:	
added check if \shellescape		new	49
has been set to \relax	14	\@tracklang@input@extra@script@files:	
1.3.3 – 2016-11-03		new	50
\IfHookHasMappingFromTrackedDialect:		\@tracklang@redefhook: new .	129
new	129	\@tracklang@secondoftwo: made	
\SetCurrentTrackedDialect:		long	11
fixed mapping	34		

\@tracklang@test@if@file@exists@for@dialect@tracklang@test@if@file@exists@for@langIskipscriptregion:	new	90	new	107
\@tracklang@test@if@file@exists@for@langIskipscriptskipregion:	new	115	new	109
\@tracklang@test@if@file@exists@for@langIvariant:	new	116	new	118
\@tracklang@test@if@file@exists@for@langIvariant:	new	106	new	118
\@tracklang@test@if@file@exists@for@langIvariant@notregiononly:	new	100	new	118
\@tracklang@test@if@file@exists@for@langIvariant@region:	new	95	new	117
\@tracklang@test@if@file@exists@for@langIvariant@rootlang:	new	114	new	120
\@tracklang@test@if@file@exists@for@langIvariant@tag:	new	105	new	89
\@tracklang@test@if@file@exists@for@langIvariant@noop:	new	101	new	89
\@tracklang@test@if@file@exists@for@langIvariant@new	new	113	new	12
\@tracklang@test@if@file@exists@for@langIvariant@check for scripts	new	115	\IfTrackedLanguageFileExists:	87
\@tracklang@test@if@file@exists@for@langIvariant@orig:	new	119	\IfTrackedLanguageFileExists@orig:	120
\@tracklang@test@if@file@exists@for@langIvariant@omitDialectLabel:	new	103, 105	\IfTrackedLanguageFileExistsOmitDialectLabel:	89
\@tracklang@test@if@file@exists@for@langIvariant@omitOnlyRegion:	new	99	\IfTrackedLanguageFileExistsOmitOnlyRegion:	88
\@tracklang@test@if@file@exists@for@langIvariant@region: scripts	new	93	\ifTrackLangShowVerbose: new	12
\@tracklang@test@if@file@exists@for@langIvariant@regionFile:	new	111	new	49
\@tracklang@test@if@file@exists@for@langIvariant@extraScriptFile:	new	104	new	50
\@tracklang@test@if@file@exists@for@langIvariant@providePredefinedDialect:	new	99	new	70
\@tracklang@test@if@file@exists@for@langIvariant@providePredefinedLanguage:	new	110	new	57
\@tracklang@test@if@file@exists@for@langIvariant@skipregion:	new	112	1.5 – 2020-06-30	127
\@tracklang@test@if@file@exists@for@langIvariant@AddToHook:	new	119	removed redundant code and added	
\@tracklang@test@if@file@exists@for@langIvariant@scriptregion:	new	91	\@TrackLangRedefHook: removed	126
\@tracklang@test@if@file@exists@for@langIvariant@skipregion and added	new	108	verbose message	128
\@tracklang@test@if@file@exists@for@langIvariant@langII:	new	102	removed spurious code block	116
\@tracklang@test@if@file@exists@for@langIvariant@IfTrackedLanguageFileExists@orig:	new	97	added verbose messages	120

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

Symbols	
\-	21
\@	8, 22, 136, 144
\@@	9, 10
\@TrackLang@RequireDialect	133, <u>133</u> , 134–136
\@@TrackLangRequireDialect	132, 133
\@@TrackLangRequireDialectOmitDialectLabel	133, 134, <u>134</u>
\@@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion	134, 135, <u>135</u>
\@@TrackLangRequireDialectOmitOnlyRegion	134, 135, <u>135</u>
\@input	9
\@tracklang@checklocale	13, <u>13</u>
\@tracklang@ifalldigits	40, <u>40</u>
\@tracklang@split@hyphen	21
\@tracklang@split@otherunderscore	21
\@tracklang@split@underscore	20
\@tracklang@test@if@file@exists@for@dialect	86–90, <u>90</u>
\@tracklang@test@if@file@exists@for@region	86–91, 109, 110, 112, 113, 115, <u>117</u>
\TrackIfKnownLanguage	47, <u>47</u>
\TrackLangAddToHook	<u>126</u> , 133
\TrackLangEnvAdditional	19, 47, 49, 56
\TrackLangEnvCodeSet	19, 21, 47, 53
\TrackLangEnvFirstSubLang	19, 45, 47, 54, 55
\TrackLangEnvLang	19, 20, 47, 48, 50, 51, 53–55
\TrackLangEnvModifier	19, 47, 50, 53–56
\TrackLangEnvScript	19, 47, 48, 50, 51, 54–56
\TrackLangEnvSubLang	19, 45, 47, 50, 51, 54–56
\TrackLangEnvTerritory	19, 20, 47–50, 52–55
\@TrackLangEnvVariant	19, 45, 47, 50, 51, 54–56
\@TrackLangRedefHook	<u>127</u>
\@TrackLangRequestResource	<u>132</u> , 133
\@TrackLangRequireDialect	132, <u>132</u> , 133
\@TrackLangRequireDialectOmitDialectLabel	133, 134, <u>134</u>
\@TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion	134, 135, <u>135</u>
\@TrackLangRequireDialectOmitOnlyRegion	134, 135, <u>135</u>
\@TrackLangRequireResource	<u>130</u> , 133
\@TrackLangRequireResourceOrDo	<u>131</u> , 133
\TrackLanguageTag	46, <u>46</u>
\@after	22, 23
\@before	22
\@declaredoptions	2
\@empty	3, 7
\@end@tracklang@hasfifthchar	38, 43, 44
\@end@tracklang@hasfourthchar	38, 41–44
\@end@tracklang@hasninthchar	39, 44
\@end@tracklang@hassecondchar	38, 40–42
\@end@tracklang@hasthirdchar	38, 41, 42, 48, 55
\@filef@und	12
\@for	4–6, 9, 10
\@fortmp	9
\@gobble	2
\@ifpackageloaded	3, 5
\@ifundefined	3–7
\@namedef	5, 6, 10
\@nameuse	4–7
\@nil	9, 23
\@nnil	9
\@noop@TrackLangRequireDialect	132
\@onelevel@sanitize	11
\@org@tracklang@add@latex	4, 5

\@tracklang@ifFileExists	\@tracklang@add@Serbian	6
.....	<u>12, 89–124, 130–132</u>	\@tracklang@add@Slovak	6
\@tracklang@add	\@tracklang@add@Slovene	6
.....	<u>23, 23, 24, 25, 28, 49, 50</u>	\@tracklang@add@Spanish	6
\@tracklang@add@Acadian	\@tracklang@add@Swedish	6
\@tracklang@add@Afrikaans	\@tracklang@add@Turkish	6
\@tracklang@add@AmericanEnglish	\@tracklang@add@UKenglish	<u>79</u>
\@tracklang@add@Austrian	\@tracklang@add@USenglish	<u>79</u>
\@tracklang@add@Bahasa	\@tracklang@add@Ukrainian	6
\@tracklang@add@Basque	\@tracklang@add@UpperSorbian	...	6
\@tracklang@add@Brazilian	\@tracklang@add@Welsh	6
\@tracklang@add@Breton	\@tracklang@add@abkhaz	<u>57</u>
\@tracklang@add@BritishEnglish	\@tracklang@add@acadian	<u>5, 73</u>
\@tracklang@add@Bulgarian	\@tracklang@add@afar	<u>57</u>
\@tracklang@add@Canadian	\@tracklang@add@afrikaans	<u>5, 57</u>
\@tracklang@add@Canadien	\@tracklang@add@akan	<u>57</u>
\@tracklang@add@Catalan	\@tracklang@add@albanian	<u>57</u>
\@tracklang@add@Croatian	\@tracklang@add@american	<u>5, 73</u>
\@tracklang@add@Czech	\@tracklang@add@amharic	<u>57</u>
\@tracklang@add@Danish	\@tracklang@add@anglosaxon	<u>58</u>
\@tracklang@add@Dutch	\@tracklang@add@apache	<u>58</u>
\@tracklang@add@English	\@tracklang@add@arabic	<u>58</u>
\@tracklang@add@Esperanto	\@tracklang@add@aragonese	<u>58</u>
\@tracklang@add@Estonian	\@tracklang@add@argentinespanish	<u>77</u>
\@tracklang@add@Finnish	<u>77</u>
\@tracklang@add@French	\@tracklang@add@armenian	<u>58</u>
\@tracklang@add@GBirish	\@tracklang@add@cassamese	<u>58</u>
\@tracklang@add@GBscottish	\@tracklang@add@asturian	<u>58</u>
\@tracklang@add@GBwelsh	\@tracklang@add@australian	<u>73</u>
\@tracklang@add@Galician	\@tracklang@add@austrian	<u>5, 73</u>
\@tracklang@add@German	\@tracklang@add@avaric	<u>58</u>
\@tracklang@add@Greek	\@tracklang@add@avestan	<u>58</u>
\@tracklang@add@Hebrew	\@tracklang@add@aymara	<u>58</u>
\@tracklang@add@Hungarian	\@tracklang@add@azerbaijani	...	<u>58</u>
\@tracklang@add@IEenglish	\@tracklang@add@bahasa	<u>5, 73</u>
\@tracklang@add@IEirish	\@tracklang@add@bahasai	<u>58</u>
\@tracklang@add@Icelandic	\@tracklang@add@bahasam	<u>58</u>
\@tracklang@add@Irish	\@tracklang@add@bambara	<u>58</u>
\@tracklang@add@Italian	\@tracklang@add@bashkir	<u>58</u>
\@tracklang@add@Latin	\@tracklang@add@basque	<u>5, 59</u>
\@tracklang@add@LowerSorbian	...	\@tracklang@add@belarusian	...	<u>59</u>
\@tracklang@add@Magyar	\@tracklang@add@belgiangerman	...	<u>74</u>
\@tracklang@add@Norsk	\@tracklang@add@belgique	<u>74</u>
\@tracklang@add@Nynorsk	\@tracklang@add@bengali	<u>59</u>
\@tracklang@add@Polish	\@tracklang@add@berber	<u>59</u>
\@tracklang@add@Polutoniko	\@tracklang@add@bihari	<u>59</u>
\@tracklang@add@Portuguese	...	\@tracklang@add@bislama	<u>59</u>
\@tracklang@add@Romanian	\@tracklang@add@bokmal	<u>59</u>
\@tracklang@add@Russian	\@tracklang@add@bolivianspanish	<u>78</u>
\@tracklang@add@Scottish	\@tracklang@add@bosnian	<u>59</u>

\@tracklang@add@brazil	5, 73	\@tracklang@add@en-CA	80
\@tracklang@add@brazilian	73	\@tracklang@add@en-GB	80
\@tracklang@add@breton	5, 59	\@tracklang@add@en-GG	81
\@tracklang@add@british	5, 73	\@tracklang@add@en-IE	83
\@tracklang@add@bulgarian	5, 59	\@tracklang@add@en-IM	81
\@tracklang@add@burmese	59	\@tracklang@add@en-JE	81
\@tracklang@add@canadian	5, 73	\@tracklang@add@en-MT	81
\@tracklang@add@canadien	5, 73	\@tracklang@add@en-NZ	80
\@tracklang@add@catalan	6, 59	\@tracklang@add@en-US	80
\@tracklang@add@chamorro	59	\@tracklang@add@english	6, 60
\@tracklang@add@chechen	59	\@tracklang@add@es-AR	82
\@tracklang@add@chichewa	59	\@tracklang@add@es-BO	82
\@tracklang@add@chilianspanish	78	\@tracklang@add@es-CL	82
\@tracklang@add@chinese	59	\@tracklang@add@es-CO	82
\@tracklang@add@churchslavonic	60	\@tracklang@add@es-CR	82
\@tracklang@add@chuvash	60	\@tracklang@add@es-CU	82
\@tracklang@add@columbianspanish	78	\@tracklang@add@es-DO	82
\@tracklang@add@coptic	60	\@tracklang@add@es-EC	82
\@tracklang@add@cornish	60	\@tracklang@add@es-ES	81
\@tracklang@add@corsican	60	\@tracklang@add@es-GT	82
\@tracklang@add@costaricanspanish	78	\@tracklang@add@es-HN	82
\@tracklang@add@cree	60	\@tracklang@add@es-MX	82
\@tracklang@add@croatia	73	\@tracklang@add@es-NI	82
\@tracklang@add@croatian	6, 60	\@tracklang@add@es-PA	82
\@tracklang@add@cubanspanish	78	\@tracklang@add@es-PE	82
\@tracklang@add@cy-GB	84	\@tracklang@add@es-PR	83
\@tracklang@add@cymraeg	79	\@tracklang@add@es-PY	82
\@tracklang@add@czech	6, 60	\@tracklang@add@es-SV	82
\@tracklang@add@danish	6, 60	\@tracklang@add@es-UY	83
\@tracklang@add@de-AT	83	\@tracklang@add@es-VE	83
\@tracklang@add@de-AT-1996	83	\@tracklang@add@esperanto	6, 60
\@tracklang@add@de-BE	81	\@tracklang@add@estonian	6, 60
\@tracklang@add@de-CH	83	\@tracklang@add@ewe	61
\@tracklang@add@de-CH-1996	84	\@tracklang@add@faroese	61
\@tracklang@add@de-DE	81	\@tracklang@add@farsi	61
\@tracklang@add@de-DE-1996	84	\@tracklang@add@fijian	61
\@tracklang@add@deutsch	74	\@tracklang@add@finnish	6, 61
\@tracklang@add@divehi	60	\@tracklang@add@flemish	74
\@tracklang@add@dominicanspanish	78	\@tracklang@add@fr-BE	80
\@tracklang@add@dutch	5, 6, 60	\@tracklang@add@fr-CA	80
\@tracklang@add@dzongkha	60	\@tracklang@add@fr-CH	83
\@tracklang@add@easternpunjabi	60	\@tracklang@add@fr-FR	80
\@tracklang@add@ecudorianspanish	78	\@tracklang@add@fr-GG	81
\@tracklang@add@elsalvadorspanish	78	\@tracklang@add@fr-JE	81
\@tracklang@add@en-AU	80	\@tracklang@add@francais	74
		\@tracklang@add@france	74
		\@tracklang@add@french	5, 6, 61
		\@tracklang@add@frenchb	74
		\@tracklang@add@friulan	61
		\@tracklang@add@friulano	74

<code>\@tracklang@add@friulian</code>	74	<code>\@tracklang@add@it-HR</code>	80
<code>\@tracklang@add@fula</code>	61	<code>\@tracklang@add@it-IT</code>	81
<code>\@tracklang@add@furlan</code>	74	<code>\@tracklang@add@it-SI</code>	81
<code>\@tracklang@add@ga-GB</code>	83	<code>\@tracklang@add@it-SM</code>	81
<code>\@tracklang@add@ga-IE</code>	83	<code>\@tracklang@add@it-VA</code>	83
<code>\@tracklang@add@gaeilge</code>	75	<code>\@tracklang@add@italian</code>	6, 62
<code>\@tracklang@add@gaelic</code>	77	<code>\@tracklang@add@italy</code>	75
<code>\@tracklang@add@galician</code>	6, 61	<code>\@tracklang@add@japanese</code>	62
<code>\@tracklang@add@galicien</code>	74	<code>\@tracklang@add@javanese</code>	62
<code>\@tracklang@add@ganda</code>	61	<code>\@tracklang@add@jerseyenglish</code>	76
<code>\@tracklang@add@gd-GB</code>	84	<code>\@tracklang@add@jerseyfrench</code>	76
<code>\@tracklang@add@georgian</code>	61	<code>\@tracklang@add@kalaallisut</code>	63
<code>\@tracklang@add@german</code>	3, 6, 61	<code>\@tracklang@add@kannada</code>	63
<code>\@tracklang@add@germanDE</code>	75	<code>\@tracklang@add@kanuri</code>	63
<code>\@tracklang@add@germanb</code>	75	<code>\@tracklang@add@kashmiri</code>	63
<code>\@tracklang@add@greek</code>	6, 61	<code>\@tracklang@add@kazakh</code>	63
<code>\@tracklang@add@guarani</code>	61	<code>\@tracklang@add@khmer</code>	63
<code>\@tracklang@add@guatemalanspanish</code>	78	<code>\@tracklang@add@kikuyu</code>	63
<code>\@tracklang@add@guernseyenglish</code>	76	<code>\@tracklang@add@kinyarwanda</code>	63
<code>\@tracklang@add@guernseyfrench</code>	76	<code>\@tracklang@add@kirundi</code>	63
<code>\@tracklang@add@gujarati</code>	61	<code>\@tracklang@add@komi</code>	63
<code>\@tracklang@add@haitian</code>	61	<code>\@tracklang@add@kongo</code>	63
<code>\@tracklang@add@hausa</code>	62	<code>\@tracklang@add@korean</code>	63
<code>\@tracklang@add@hebrew</code>	6, 62	<code>\@tracklang@add@kurdish</code>	63
<code>\@tracklang@add@herero</code>	62	<code>\@tracklang@add@kurmanji</code>	74
<code>\@tracklang@add@hindi</code>	62	<code>\@tracklang@add@kwanyama</code>	63
<code>\@tracklang@add@hirimotu</code>	62	<code>\@tracklang@add@kyrgyz</code>	63
<code>\@tracklang@add@honduranspanish</code>	78	<code>\@tracklang@add@lao</code>	63
<code>\@tracklang@add@hr-HR</code>	83	<code>\@tracklang@add@latein</code>	76
<code>\@tracklang@add@hu-HU</code>	84	<code>\@tracklang@add@latex</code>	4, 5
<code>\@tracklang@add@hungarian</code>	6, 75	<code>\@tracklang@add@latin</code>	6, 64
<code>\@tracklang@add@icelandic</code>	6, 62	<code>\@tracklang@add@latvian</code>	64
<code>\@tracklang@add@id-IN</code>	83	<code>\@tracklang@add@limburgish</code>	64
<code>\@tracklang@add@ido</code>	62	<code>\@tracklang@add@lingala</code>	64
<code>\@tracklang@add@igbo</code>	62	<code>\@tracklang@add@lithuanian</code>	64
<code>\@tracklang@add@indon</code>	75	<code>\@tracklang@add@lowersorbian</code>	6, 76
<code>\@tracklang@add@indonesian</code>	75	<code>\@tracklang@add@lsorbian</code>	64
<code>\@tracklang@add@interlingua</code>	62	<code>\@tracklang@add@lubakatanga</code>	64
<code>\@tracklang@add@interlingue</code>	62	<code>\@tracklang@add@luxembourgish</code>	64
<code>\@tracklang@add@inuktitut</code>	62	<code>\@tracklang@add@macedonian</code>	64
<code>\@tracklang@add@inupiaq</code>	62	<code>\@tracklang@add@magyar</code>	6, 64
<code>\@tracklang@add@irish</code>	6, 62	<code>\@tracklang@add@malagasy</code>	64
<code>\@tracklang@add@isleofmanenglish</code>	76	<code>\@tracklang@add@malay</code>	76
<code>\@tracklang@add@istriacountycroatian</code>	73	<code>\@tracklang@add@malayalam</code>	64
<code>\@tracklang@add@istriacountyitalian</code>	74	<code>\@tracklang@add@maltenglish</code>	76
<code>\@tracklang@add@it-CH</code>	83	<code>\@tracklang@add@maltamaltese</code>	76
		<code>\@tracklang@add@maltese</code>	64
		<code>\@tracklang@add@manx</code>	64
		<code>\@tracklang@add@maori</code>	64
		<code>\@tracklang@add@marathi</code>	64

\@tracklang@add@marshallese . . .	65	\@tracklang@add@pt-PT	81
\@tracklang@add@mexicanspanish	78	\@tracklang@add@puertoricospanish	
\@tracklang@add@meyalu	76		78
\@tracklang@add@mongolian	65	\@tracklang@add@quechua	66
\@tracklang@add@ms-MY	83	\@tracklang@add@erm-CH	83
\@tracklang@add@mt-MT	81	\@tracklang@add@romanche	77
\@tracklang@add@nauruan	65	\@tracklang@add@romanian	6, 66
\@tracklang@add@naustrian	5, 73	\@tracklang@add@romansch	77
\@tracklang@add@navajo	65	\@tracklang@add@romansh	66
\@tracklang@add@belgiangerman	74	\@tracklang@add@rumantsch	77
\@tracklang@add@ndonga	65	\@tracklang@add@russian	6, 66
\@tracklang@add@nepali	65	\@tracklang@add@russianb	77
\@tracklang@add@netherlands	74	\@tracklang@add@samin	66
\@tracklang@add@newzealand	76	\@tracklang@add@samoan	66
\@tracklang@add@ngerman	3, 6, 75	\@tracklang@add@sango	66
\@tracklang@add@ngermanDE	75	\@tracklang@add@sanmarino	75
\@tracklang@add@ngermanb	75	\@tracklang@add@sanskrit	66
\@tracklang@add@nicaraguanspanish		\@tracklang@add@sardinian	66
	78	\@tracklang@add@scots	66
\@tracklang@add@nil	79	\@tracklang@add@scottish	6, 67
\@tracklang@add@nko	65	\@tracklang@add@serbian	6, 67
\@tracklang@add@nl-BE	80	\@tracklang@add@serbianc	77
\@tracklang@add@nl-NL	81	\@tracklang@add@serbianl	77
\@tracklang@add@norsk	6, 65	\@tracklang@add@shona	67
\@tracklang@add@northernndebele	65	\@tracklang@add@sindhi	67
\@tracklang@add@northernsotho	65	\@tracklang@add@sinhalese	67
\@tracklang@add@norwegian	76	\@tracklang@add@sl-SI	81
\@tracklang@add@nswissgerman	79	\@tracklang@add@slovak	6, 67
\@tracklang@add@nuosu	65	\@tracklang@add@slovene	6, 67
\@tracklang@add@nynorsk	6, 65	\@tracklang@add@sloveneistriaitalian	
\@tracklang@add@occitan	65		75
\@tracklang@add@ojibwe	65	\@tracklang@add@sloveneistriaslovenian	
\@tracklang@add@oriya	65		77
\@tracklang@add@oromo	65	\@tracklang@add@slovenia	77
\@tracklang@add@ossetian	66	\@tracklang@add@slovenian	77
\@tracklang@add@pali	66	\@tracklang@add@somali	67
\@tracklang@add@panamaspanish	78	\@tracklang@add@southernndebele	67
\@tracklang@add@paraguayspanish	78	\@tracklang@add@southernsotho	67
\@tracklang@add@pashto	66	\@tracklang@add@spainspanish	77
\@tracklang@add@persian	74	\@tracklang@add@spanish	6, 67
\@tracklang@add@peruvianspanish	78	\@tracklang@add@sudanese	67
\@tracklang@add@piedmontese	66	\@tracklang@add@swahili	67
\@tracklang@add@piemonteis	76	\@tracklang@add@swati	67
\@tracklang@add@polish	6, 66	\@tracklang@add@swedish	6, 67
\@tracklang@add@polutoniko	6, 77	\@tracklang@add@swissfrench	79
\@tracklang@add@polutonikogreek	76	\@tracklang@add@swissgerman	79
\@tracklang@add@portugal	77	\@tracklang@add@swissitalian	79
\@tracklang@add@portuges	66	\@tracklang@add@swissromansh	79
\@tracklang@add@portuguese	5, 6, 77	\@tracklang@add@syriac	67
\@tracklang@add@pt-BR	80	\@tracklang@add>tagalog	68

<code>\@tracklang@add@tahitian</code>	68	<code>\@tracklang@defscript</code>	51
<code>\@tracklang@add@tai</code>	68	<code>\@tracklang@dialect</code>	
<code>\@tracklang@add@tajik</code>	68	34, 50–52, 54–56, 70–72
<code>\@tracklang@add@tamil</code>	68	<code>\@tracklang@dialects</code>	
<code>\@tracklang@add@tatar</code>	68	22, 23, 34, 51, 85
<code>\@tracklang@add@telugu</code>	68	<code>\@tracklang@doifinlist</code>	22, 23
<code>\@tracklang@add@thai</code>	68	<code>\@tracklang@element</code>	23, 84
<code>\@tracklang@add@tibetan</code>	68	<code>\@tracklang@enamedef</code>	10,
<code>\@tracklang@add@tigrinya</code>	68	24, 25, 28–32, 129, 137, 144–146
<code>\@tracklang@add@tonga</code>	68	<code>\@tracklang@end@parseenv</code>	19, 21
<code>\@tracklang@add@tsonga</code>	68	<code>\@tracklang@end@split@hyphen</code>	21
<code>\@tracklang@add@tswana</code>	68	<code>\@tracklang@end@split@underscore</code>	20, 21
<code>\@tracklang@add@turkish</code>	6, 68	<code>\@tracklang@err</code>	11,
<code>\@tracklang@add@turkmen</code>	68	38, 57, 73, 124, 125, 127, 130–132
<code>\@tracklang@add@twi</code>	68	<code>\@tracklang@extra@region@filelist</code>	49
<code>\@tracklang@add@ukraine</code>	79	49, 50
<code>\@tracklang@add@ukraineb</code>	79	<code>\@tracklang@extra@script@filelist</code>	49, 50
<code>\@tracklang@add@ukrainian</code>	6, 69	<code>\@tracklang@firstoftwo</code>	
<code>\@tracklang@add@undetermined</code>	69	11, 39, 40, 90–120
<code>\@tracklang@add@uppersorbian</code>	6, 79	<code>\@tracklang@for</code>	9, 34, 49–51, 85, 86
<code>\@tracklang@add@urdu</code>	69	<code>\@tracklang@forloop</code>	9
<code>\@tracklang@add@uruguayspanish</code>	79	<code>\@tracklang@fornoop</code>	10
<code>\@tracklang@add@usorbian</code>	69	<code>\@tracklang@fullmatch</code>	52, 52
<code>\@tracklang@add@uyghur</code>	69	<code>\@tracklang@hasfifthchar</code>	38, 43, 44
<code>\@tracklang@add@uzbek</code>	69	<code>\@tracklang@hasfourthchar</code>	38, 41–44
<code>\@tracklang@add@valencian</code>	79	<code>\@tracklang@hasninthchar</code>	38, 44
<code>\@tracklang@add@valencien</code>	79	<code>\@tracklang@hassecondchar</code>	38, 40–42
<code>\@tracklang@add@vatican</code>	75	<code>\@tracklang@hasthirdchar</code>	38, 41, 42, 48, 55
<code>\@tracklang@add@venda</code>	69	<code>\@tracklang@hook</code>	127
<code>\@tracklang@add@venezuelanspanish</code>	79	<code>\@tracklang@if@file@exists</code>	87–120
<code>\@tracklang@add@vietnamese</code>	69	<code>\@tracklang@ifalldigits</code>	40, 42
<code>\@tracklang@add@volapuk</code>	69	<code>\@tracklang@ifalpha</code>	39, 40
<code>\@tracklang@add@walloon</code>	69	<code>\@tracklang@ifalphanumeric</code>	40, 40
<code>\@tracklang@add@welsh</code>	6, 69	<code>\@tracklang@ifcseqcsname</code>	
<code>\@tracklang@add@westernfrisian</code>	69	10, 107, 110, 113
<code>\@tracklang@add@wolof</code>	69	<code>\@tracklang@ifdigit</code>	39, 40, 45
<code>\@tracklang@add@xhosa</code>	69	<code>\@tracklang@ifinlist</code>	22, 23, 25, 84
<code>\@tracklang@add@yiddish</code>	69	<code>\@tracklang@iflanguage@ii@tag</code>	41, 41
<code>\@tracklang@add@yoruba</code>	70	<code>\@tracklang@iflanguage@iii@tag</code>	41, 41
<code>\@tracklang@add@zhuang</code>	70	<code>\@tracklang@ifforloop</code>	9, 10
<code>\@tracklang@add@zulu</code>	70	<code>\@tracklang@ifregion@ii@tag</code>	42, 43
<code>\@tracklang@addtohook</code>	126, 127	<code>\@tracklang@ifregion@iii@tag</code>	43
<code>\@tracklang@bestmatch</code>	51, 52	<code>\@tracklang@ifscripttag</code>	43, 44
<code>\@tracklang@checklocale</code>	13, 15, 16	<code>\@tracklang@ifundef</code>	7,
<code>\@tracklang@currentmatch</code>	51, 52	8, 10, 24, 26–28, 30, 32, 33,
<code>\@tracklang@currfile</code>	49, 50		
<code>\@tracklang@declaredoptions</code>	2, 4, 5		
<code>\@tracklang@declareoption</code>	2, 2, 56, 57, 73, 80		

\@tracklang@test@if@file@exists@for@lang@fr@skip@warn	12, 14, 16–19, 36, .. 94, 95, 103, 104, <u>104</u> , 105–107	46, 49, 53, 55, 130, 131, 133–136
\@tracklang@test@if@file@exists@for@lang@fr@skip@opt	15, 16	
.....	94, 99, <u>99</u>	\~ 11, 12, 125
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@region	20, 21	
.....	95, <u>110</u>	
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	111, 112, <u>112</u>	\AddTrackedCountryIsoCode ... 37, 57
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	118, 119, <u>119</u>	\AddTrackedDialect
.....	23, 24, 54, 55, 70–72	
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	24, 28, 37, 55	\AddTrackedIsoLanguage
.....	90, 91, <u>91</u>	24, 28, 37, 55
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	4, 7, <u>24</u> , 57	\AddTrackedLanguage
.....	107, 108, <u>108</u>	4, 7, <u>24</u> , 57
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	36, 54, 57, 70–72	\AddTrackedLanguageIsoCodes ...
.....	92, 93, <u>102</u>	36, 54, 57, 70–72
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	24, 37, 55, 71, 72	\AddTrackedRegion .
.....	92, 97	24, 37, 55, 71, 72
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	86	\AnyTrackedLanguages
.....	92, 97	86
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	85	\AnyTrackedRegions
.....	93, <u>107</u>	85
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	5, 6	\bhl@loaded
.....	108, 109, <u>109</u>	\begin@group
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	15, 16	15, 16
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	118, <u>118</u>	C
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	7	\caption@serbian
.....	96, 98–106, 117, 118, <u>118</u>	7
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	8, 20–22, 136, 144	\catcode
.....	91	8, 20–22, 136, 144
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	12	\close@set
.....	91	12
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	3, 8, 10, 22, 24, 28, 31, 33,	\csname
.....	37, 55, 72, 80, 125–130, 136, 144	3, 8, 10, 22, 24, 28, 31, 33,
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	87, 88, <u>118</u>	37, 55, 72, 80, 125–130, 136, 144
.....	87, 88, <u>118</u>	\CurrentTrackedDialect
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	34–36, 126–128	87, 88, <u>118</u>
.....	86, 89, <u>117</u> , <u>117</u>	34–36, 126–128
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	35, 36	\CurrentTrackedDialectAdditional
.....	118–120, <u>120</u>	35, 36
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	35, 36	\CurrentTrackedDialectModifier
.....	88, 89, <u>91</u>	35, 36
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	103, 105–107	\CurrentTrackedDialectRegion ..
.....	87–89, <u>89</u>	103, 105–107
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	35, 36,	\CurrentTrackedDialectScript ..
.....	90–120	35, 36,
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	91–97, 99, 101, 107, 108, 110–114	91–97, 99, 101, 107, 108, 110–114
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	35, 36, 91–120	\CurrentTrackedDialectSubLang .
.....	89, 90–120	35, 36, 91–120
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	35, 36, 118–120	\CurrentTrackedDialectVariant .
.....	7,	35, 36, 118–120
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	35, 36, 90–123	7,
.....	46, 47, 54, <u>54</u>	12, 13, 25, 51, 52, 72, 126, 128
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	87–89, 91, 118	46, 47, 54, <u>54</u>
.....	3, 7, <u>12</u> , 34–36, 86–124, 126, 128	87–89, 91, 118
\@tracklang@test@if@file@exists@for@lang@fr@skip@script@skip@region	87–89, 93, 99, 103, 105, 116, 119	3, 7, <u>12</u> , 34–36, 86–124, 126, 128
.....	87–89, 93, 99, 103, 105, 116, 119	87–89, 93, 99, 103, 105, 116, 119

	85 , 90 , 91 , 98 , 100 , 102–104 , 109 , 110 , 112 , 113 , 116 , 118–123	<code>\org@currenttrackedisocode</code> 121 , 122
<code>\ifTrackLangShowInfo</code>	12 , 12	
<code>\ifTrackLangShowVerbose</code>	12 , 12	
<code>\ifTrackLangShowWarnings</code>	11 , 11 , 133–136	
<code>\ifx</code>	3 , 7–21 , 23 , 25 , 31 , 38– 40 , 45–56 , 70–72 , 84–86 , 91– 120 , 123–125 , 132 , 134–136 , 144	
<code>\input</code>	2 , 9 , 144	
<code>\inputencodingname</code>	13	
<code>\inputlineno</code>	11 , 12	
		P
		<code>\PackageError</code> 11
		<code>\PackageInfo</code> 4 , 5 , 12
		<code>\PackageWarning</code> 4 , 7 , 11
		<code>\pdfshellescape</code> 14 , 15
		<code>\ProcessOptions</code> 2
		<code>\providecommand</code> 2
		<code>\ProvidesFile</code> 124 , 125
		<code>\ProvidesPackage</code> 2 , 143
		R
		<code>\relax</code> 8–10 , 12–16 , 19–23 , 38–44 , 48 , 52 , 55 , 70–72 , 124 , 132 , 134–136 , 144
		<code>\RequirePackage</code> 144
		S
		<code>\SetCurrentTrackedDialect</code> 33 , 86–89 , 120
		<code>\SetTrackedDialectAdditional</code> 32 , 56
		<code>\SetTrackedDialectLabelMap</code> 7 , 72 , 129
		<code>\SetTrackedDialectModifier</code> 29 , 56 , 71 , 72
		<code>\SetTrackedDialectScript</code> 7 , 30 , 56 , 72
		<code>\SetTrackedDialectSubLang</code> . . . 32 , 56
		<code>\SetTrackedDialectVariant</code> 31 , 56 , 70–72
		<code>\shellescape</code> 14 , 15
		<code>\space</code> 3–5 , 7 , 14 , 19 , 53 , 124 , 125 , 127 , 130–132
		<code>\string</code> 3–5 , 7 , 14 , 16–19 , 36 , 46 , 53 , 124 , 125 , 127 , 130–132
		T
		<code>\TeXOSQueryLocale</code> 16–18
		<code>\the</code> 11 , 12
		<code>\this@language</code> 4–7
		<code>\ThreeLetterExtIsoLanguageCode</code> 29 , 37 , 55
		<code>\ThreeLetterIsoLanguageCode</code> . 29 , 37
		<code>\TrackedDialectClosestSubMatch</code> 50 , 52
		<code>\TrackedDialectsFromLanguage</code> 29 , 34 , 51
		<code>\TrackedIsoCodeFromLanguage</code> 29 , 33 , 35 , 36 , 52 , 87–89 , 120–123
L		
<code>\language</code>	36	
<code>\lccode</code>	39 , 41 , 42 , 44	
<code>\let</code>	2 , 4–6 , 9–11 , 13 , 19 , 20 , 22 , 23 , 34 , 40 , 45 , 48–50 , 52– 54 , 72 , 80 , 89–124 , 127 , 133 , 134	
<code>\LetTrackLangOption</code> . . .	80 , 80 , 81–84	
<code>\LetTrackLangSynonym</code>	80 , 80	
<code>\LocaleForEach</code>	3 , 7	
<code>\long</code>	8–12 , 84–89 , 120 , 124 , 125	
M		
<code>\mainbabelname</code>	4 , 5	
<code>\meaning</code>	11	
<code>\message</code>	11 , 12 , 125	
<code>\MessageBreak</code> 11 , 12 , 36 , 125 , 130 , 131		
N		
<code>\NeedsTeXFormat</code>	2 , 143	
<code>\newif</code>	11 , 12	
<code>\newlinechar</code>	11 , 12 , 125	
<code>\noexpand</code>	8 , 15 , 16 , 136 , 144	
<code>\noop@TrackLangAddToHook</code> 125 , 125 , 134		
<code>\noop@TrackLangRedefHook</code> . .	127 , 127	
<code>\noop@TrackLangRequestResource</code> 131 , 132 , 133		
<code>\noop@TrackLangRequireDialect</code> 132 , 133		
<code>\noop@TrackLangRequireResource</code> 130 , 130 , 133		
<code>\noop@TrackLangRequireResourceOrDo</code> 131 , 131 , 133		
<code>\number</code>	8 , 136 , 144	
O		
<code>\openin</code>	12	

<code>\TrackedLanguageFromDialect</code>	<code>\TrackLangIfKnownLangFromIso</code>
. 29 , 31 , 33 , 35 27 , 47 , 54
<code>\TrackedLanguageFromIsoCode</code>	<code>\TrackLangIfKnownNumericRegion</code>
. 28 48 , 137
<code>\TrackIfKnownLanguage</code>	<code>\TrackLangIfLanguageTag</code>
. 47 41 , 45
<code>\tracklang@propresult</code>	<code>\TrackLangIfRegionTag</code>
. 7 42 , 48
<code>\TrackLangAddExtraRegionFile</code>	<code>\TrackLangIfScriptTag</code>
. 49 43 , 48
<code>\TrackLangAddExtraScriptFile</code>	<code>\TrackLangIfVariantTag</code>
. 50 44 , 45
<code>\TrackLangAddToCaptions</code>	<code>\TrackLangLastTrackedDialect</code>
. 127 7 , 24
<code>\TrackLangAddToHook</code>	<code>\TrackLangNewLanguage</code>
. 125 , 125 , 127 , 133 , 134 24 , 57
<code>\TrackLangAlphaIIIToNumericRegion</code>	<code>\TrackLangNumericToAlphaIIRegion</code>
. 138 138
<code>\TrackLangAlphaIIToNumericRegion</code>	<code>\TrackLangNumericToAlphaIRegion</code>
. 137 48 , 137
<code>\TrackLangDeclareDialectOption</code>	<code>\tracklangparseenvatmod</code>
. 72 , 73 – 79 22
<code>\TrackLangDeclareLanguageOption</code>	<code>\TrackLangParseFromEnv</code>
. 57 , 57 , 58 – 70 18
<code>\TrackLangEncodingName</code>	<code>\tracklangparsemod</code>
. 13 21 , 22
<code>\tracklangendparseenvatmod</code>	<code>\TrackLangProvidePredefinedDialect</code>
. 22 70 , 73
<code>\TrackLangEnv</code>	<code>\TrackLangProvidePredefinedLanguage</code>
. 13 – 19 , 53 57 , 57
<code>\TrackLangEnvCodeSet</code>	<code>\TrackLangProvidesResource</code>
. 19 , 52 , 53 124
<code>\TrackLangEnvLang</code>	<code>\TrackLangQueryEnv</code>
. 19 , 52 , 53 14 , 15 , 17 , 53
<code>\TrackLangEnvModifier</code>	<code>\TrackLangQueryOtherEnv</code>
. 19 , 52 , 53 14 , 16 , 17
<code>\TrackLangEnvTerritory</code>	<code>\TrackLangRedefHook</code>
. 19 , 52 , 53 127 , 127
<code>\TrackLangFromEnv</code>	<code>\TrackLangRegionMap</code>
. 52 49 , 136 , 136 , 138 – 143
<code>\TrackLangGetDefaultScript</code>	<code>\TrackLangRequestResource</code>
. 28 , 35 , 51 131 , 132 , 133
<code>\TrackLangGetKnownCountry</code>	<code>\TrackLangRequireDialect</code>
. 27 124 , 125 , 132 , 132 , 133
<code>\TrackLangGetKnownIsoThreeLetterLang</code>	<code>\TrackLangRequireDialectOmitDialectLabel</code>
. 26 133 , 134
<code>\TrackLangGetKnownIsoThreeLetterLangB</code>	<code>\TrackLangRequireDialectOmitDialectLabelOmitOnlyRegion</code>
. 27 133 – 135
<code>\TrackLangGetKnownIsoTwoLetterLang</code>	<code>\TrackLangRequireDialectOmitLabelOmitOnlyRegion</code>
. 26 134
<code>\TrackLangGetKnownLangFromIso</code>	<code>\TrackLangRequireDialectOmitOnlyRegion</code>
. 27 , 51 , 54 133 , 134 , 135
<code>\TrackLangIfAlphaNumericChar</code>	<code>\TrackLangRequireDialectPrefix</code>
. 40 124 , 125 , 130 – 136
<code>\TrackLangIfHasDefaultScript</code>	<code>\TrackLangRequireResource</code>
. 28 , 31 130 , 130 , 132 – 135
<code>\TrackLangIfHasKnownCountry</code>	<code>\TrackLangRequireResourceOrDo</code>
. 27 131 , 131 , 133
<code>\TrackLangIfKnownAlphaIIRegion</code>	<code>\TrackLangScriptAlphaToDir</code>
. 138 146
<code>\TrackLangIfKnownAlphaIRegion</code>	<code>\TrackLangScriptAlphaToName</code>
. 137 145
<code>\TrackLangIfKnownIsoThreeLetterLang</code>	<code>\TrackLangScriptAlphaToNumeric</code>
. 26 145
<code>\TrackLangIfKnownIsoThreeLetterLangB</code>	<code>\TrackLangScriptGetParent</code>
. 26 146
<code>\TrackLangIfKnownIsoTwoLetterLang</code>	
. 25	
<code>\TrackLangIfKnownLang</code>	
. 25	

